

Specifications	FAS2750 10GBASE-T Single Chassis HA Pair	FAS2750 UTA2 Single Chassis HA Pair	FAS2820 Single Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Storage Limits			
Max Number of Drives (Total)	144	144	144
Internal Drives count	Max: 24 per Chassis;	Max: 24 per Chassis;	Max: 12 per Chassis;
Max number of NL-SAS Drives	Max: 144 per HA Pair;	Max: 144 per HA Pair;	Max: 144 per HA Pair;
Max number of NVMe SSD Drives	N/A	N/A	N/A
Max number of SAS Drives	Max: 144 per HA Pair;	Max: 144 per HA Pair;	Max: 144 per HA Pair;
Max number of SSD Drives	Max: 144 per HA Pair;	Max: 144 per HA Pair;	Max: 138 per HA Pair;
Max number of DS212C shelves	9 external	9 external	1 internal + 9 external OR 0 internal + 10 external
Max number of DS224C shelves	1 internal + 5 external OR 0 internal + 6 external	1 internal + 5 external OR 0 internal + 6 external	6 external
Max number of DS460C shelves	2 external	2 external	2 external
Max number of NS224 shelves	N/A	N/A	N/A
Max number of NS224 w/ NSM100B shelves	N/A	N/A	N/A
Capacity Limits			
Marketing Maximum Raw Capacity (GB)			
Node	2,923,200	2,923,200	3,456,000
HA Pair	2,923,200	2,923,200	3,456,000
Core Cluster Limits			
Maximum number of storage virtual machines (SVMs) - NAS			
Cluster	512	512	512
Maximum number of LIFs - NAS			
Node	512	512	512
HA Pair	512	512	512
Cluster	4,096	4,096	4,096
Maximum number of connections - NAS/S3			
Node	100,000	100,000	100,000
HA Pair (Non-Scalable)	100,000	100,000	100,000
Maximum Number of VLANs			
Node	512	512	512
Maximum number of flexible volumes - NAS			
Node	1,000	1,000	1,000
HA Pair	2,000	2,000	2,000
Cluster	24,000	24,000	24,000
Maximum number of lock manager locked objects (CIFS and NFS combined)			
Node	1,200,000	1,200,000	1,200,000
HA Pair	1,200,000	1,200,000	1,200,000
Cluster	12,288,000	12,288,000	12,288,000
Maximum number of Intercluster LIFs			
Node	8	8	8
Minimum Root Aggregate (MiB)			
Node	191,488	191,488	191,488
Minimum Root Volume (GiB)			
Node	150	150	150
Maximum IPsec Policies			
SVM	256	256	256
Cluster	1,500	1,500	1,500
Maximum Number of IPspaces			
Cluster	512	512	512

Specifications	FAS2750 10GBASE-T Single Chassis HA Pair	FAS2750 UTA2 Single Chassis HA Pair	FAS2820 Single Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum IPsec Policies (If not using HW Offload)			
SVM	N/A	N/A	N/A
Cluster	N/A	N/A	N/A
Maximum IPsec Policies (If using HW Offload)			
SVM	N/A	N/A	N/A
Cluster	N/A	N/A	N/A
Maximum Number of Auditing-Enabled SVMs			
Cluster	400	400	400
Max Flash Cache (no Flash Pool) (TiB)			
HA Pair	2	2	2
Max Total Cache (Flash Cache + Flash Pool) (TiB)			
HA Pair	144	144	144
Maximum Composite Aggregate Size (TiB)			
HA Pair	8,400	8,400	8,400
Max Flash Pool (no Flash Cache) (TiB)			
HA Pair	144	144	144
Default Flash Cache (TiB)			
HA Pair	2	2	2
System Maximums and Limits			
Max Nodes per Cluster (NAS / SAN)	24 / 12	24 / 12	24 / 12
Max FabricPool Size	8400 TiB	8400 TiB	8400 TiB
Max Infinite Volume Data Constituent Size	Not Supported	Not Supported	Not Supported
Max FlexGroup Data Constituent Size	300 TiB	300 TiB	300 TiB
Min Root Volume Size	150 GiB ^[1]	150 GiB ^[1]	150 GiB ^[1]
NetApp Volume Encryption	NVE	NVE	NVE
Processor			
Processor Model	64-bit 12-core 1.50 Ghz	64-bit 12-core 1.50 Ghz	64-bit 8-core 2.20 Ghz
Processor Architecture	64 bit	64 bit	64 bit
Processor Speed	1.50 Ghz	1.50 Ghz	2.20 Ghz
Processor Count (Per Node)	1	1	1
Processor Count (Per Config)	2	2	2
Processor Cores (Per CPU)	12	12	8
Processor Cores (Per Node)	12	12	8
Processor Cores (Per Config)	24	24	16
Memory			
NVME (Per Node)	1024 GB	1024 GB	1024 GB
NVME (Per Config)	2048 GB	2048 GB	2048 GB
NVMEM (Per Node)	4 GB	4 GB	4 GB
NVMEM (Per Config)	8 GB	8 GB	8 GB
NVRAM (Per Node)	N/A	N/A	N/A
NVRAM (Per Config)	N/A	N/A	N/A
RAM (Per Node)	32 GB	32 GB	64 GB
RAM (Per Config)	64 GB	64 GB	128 GB
Onboard Ports			
Ethernet Ports	8 x RJ45 (10Gb) 4 x SFP+ (10Gb)	4 x SFP+ (10Gb)	-
Fibre Channel Ports	-	-	-
UTA2 Ports	Not Supported	8 x SFP+ (10Gb/16Gb)	Not Supported
Expansion Slots			2 x PCIe3 (per System)
SAS Ports	4 x MiniSAS HD (12Gb)	4 x MiniSAS HD (12Gb)	4 x MiniSAS HD (12Gb)
Physical Characteristics			
Rack Units	2	2	2

	FAS2750 10GBASE-T Single Chassis HA Pair	FAS2750 UTA2 Single Chassis HA Pair	FAS2820 Single Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Chassis Height	3.35" (8.5 cm)	3.35" (8.5 cm)	3.42" (8.69 cm)
Chassis Width with Mounting Flanges	18.9" (48 cm)	18.9" (48 cm)	18.9" (48 cm)
Chassis Width without Mounting Flanges	17.6" (44.7 cm)	17.6" (44.7 cm)	17.6" (44.7 cm)
Chassis Depth with Cable Mgmt	24.13" (61.3 cm)	24.13" (61.3 cm)	25.12" (63.8 cm)
Chassis Depth without Cable Mgmt	19.02" (48.3 cm)	19.02" (48.3 cm)	20" (50.8 cm)
Chassis Weight			
System Clearance Dimensions			
Front Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)	6.03" (15.3 cm)
Front Clearance (Maintenance)	24.03" (61 cm)	24.03" (61 cm)	24.03" (61 cm)
Rear Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)	6.03" (15.3 cm)
Rear Clearance (Maintenance)	13" (33 cm)	13" (33 cm)	13" (33 cm)
Environmental Requirements			
Operating Temperature Range	41 to 113 deg F 5 to 45 deg C	41 to 113 deg F 5 to 45 deg C	50 to 95 deg F 10 to 35 deg C
Storage Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Transit Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Operating Relative Humidity	8 to 90 %	8 to 90 %	8 to 80 %
Storage Relative Humidity	10 to 95 %	10 to 95 %	10 to 95 %
Transit Relative Humidity	10 to 95 %	10 to 95 %	10 to 95 %
Operating Altitude Range	Up to 10000.0 ft Up to 3048.0 m	Up to 10000.0 ft Up to 3048.0 m	Up to 10000.0 ft Up to 3048.0 m
Storage Altitude Range	Up to 40000.0 ft Up to 12192.0 m	Up to 40000.0 ft Up to 12192.0 m	Up to 40000.0 ft Up to 12192.0 m
Transit Altitude Range	Up to 39989.8 ft Up to 12192 m	Up to 39989.8 ft Up to 12192 m	Up to 39989.8 ft Up to 12192 m
Acoustic Noise - Sound Power	6.9 Bels	6.9 Bels	7.8 Bels
Acoustic Noise - Sound Pressure	51 dBA	51 dBA	68.4 dBA
Input Power Voltage	100 to 120; 200 to 240;	100 to 120; 200 to 240;	100 to 120; 200 to 240;
Storage OS Requirements (for selected major version)			
Recommended Version	9.19.1, 9.19.1P2	9.19.1, 9.19.1P2	9.19.1, 9.19.1P2
Minimum OS	9.19.1RC1	9.19.1RC1	9.19.1RC1
Maximum OS	9.19.1P2	9.19.1P2	9.19.1P2
Software and Firmware * indicates that firmware is bundled with Storage OS Version			
BIOS	11.25*	11.25*	19.9*
BMC	11.13*	11.13*	17.5P1*
Product Standards Compliance			
Certifications EMC/EMI	AMCA, FCC, ICES, KC, Morocco, VCCI	AMCA, FCC, ICES, KC, Morocco, VCCI	AMCA, FCC, ICES, KC, Morocco, VCCI
Certifications safety	BIS, CB, CSA, G_K_U-SoR, IRAM, NOM, NRCS, SONCAP, TBS	BIS, CB, CSA, G_K_U-SoR, IRAM, NOM, NRCS, SONCAP, TBS	BIS, CB, CSA, G_K_U-SoR, IRAM, NOM, NRCS, SONCAP, TBS
Certifications Safety/EMC/EMI	EAC, UKRSEPRO	EAC, UKRSEPRO	EAC, UKRSEPRO
Certifications Safety/EMC/EMI/RoHS	BSMI, CE DoC, UKCA DoC	BSMI, CE DoC, UKCA DoC	BSMI, CE DoC, UKCA DoC
Standards EMC/EMI	BS-EN-55024, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835	BS-EN-55024, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835	BS-EN-55024, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835

Specifications	FAS2750 10GBASE-T Single Chassis HA Pair	FAS2750 UTA2 Single Chassis HA Pair	FAS2820 Single Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Standards Safety	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 14336, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 14336, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 14336, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)
System Availability & Support			
Release Date	May 2018	May 2018	May 2023
End of Availability (EOA)	-	-	-
End of Support (EOS)	-	-	-
NFS Cluster Limits			
Maximum Number of NFS over TLS Connections			
Node	10,000	10,000	10,000
Maximum number of Export Policies			
Cluster	24,000	24,000	24,000
Maximum number of Export Rules			
Cluster	200,000	200,000	200,000
Maximum NFSv4 Access Control Entries			
ACL (Access List)	1,024	1,024	1,024
Maximum number of client objects			
Node	10,000	10,000	10,000
HA Pair	10,000	10,000	10,000
Maximum Number of NFSv4 ByteLock Objects			
Node	1,000,000	1,000,000	1,000,000
Maximum Number of NFSv4 Client Objects			
Node	100,000	100,000	100,000
Maximum Number of NFSv4 Copy State Objects			
Node	10,000	10,000	10,000
Maximum Number of NFSv4 Deleg Objects			
Node	1,000,000	1,000,000	1,000,000
Maximum Number of NFSv4 Deleg State Objects			
Node	1,000,000	1,000,000	1,000,000
Maximum Number of NFSv4 Layout Objects			
Node	1,000,000	1,000,000	1,000,000
Maximum Number of NFSv4 Layout State Objects			
Node	1,000,000	1,000,000	1,000,000
Maximum Number of NFSv4 LayoutLock Objects			
Node	1,000,000	1,000,000	1,000,000
Maximum Number of NFSv4 Lock State Objects			
Node	2,000,000	2,000,000	4,000,000
Maximum Number of NFSv4 Open Objects			
Node	1,000,000	1,000,000	1,000,000
Maximum Number of NFSv4 Open State Objects			
Node	1,000,000	1,000,000	1,000,000
Maximum Number of NFSv4 Owner Objects			
Node	1,000,000	1,000,000	1,000,000
Maximum Number of NFSv4 Sessions			
Node	100,000	100,000	100,000
Maximum Number of NFSv4 String Objects			

Specifications	FAS2750 10GBASE-T Single Chassis HA Pair	FAS2750 UTA2 Single Chassis HA Pair	FAS2820 Single Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Node	1,000,000	1,000,000	1,000,000
WAFL Cluster Limits			
Maximum Size of a 64-bit Aggregate (TiB)			
Aggregate	800	800	800
Maximum Size of a 64-bit Volume (TiB)			
Volume	300	300	300
Maximum file size in a 64-bit Volume (TiB)			
File	128	128	128
Maximum number of Volume Snapshot Copies			
Volume	1,023	1,023	1,023
Node	1,023,000	1,023,000	1,023,000
HA Pair	2,046,000	2,046,000	2,046,000
Maximum character length for Snapshot copy names			
Snapshot	255	255	255
Maximum number of hard links			
File	100,000	100,000	100,000
Maximum number of inodes/files			
Volume	2,000,000,000	2,000,000,000	2,000,000,000
Maximum number of qtrees			
Volume	4,995	4,995	4,995
Node	100,000	100,000	100,000
HA Pair	200,000	200,000	200,000
Cluster	400,000	400,000	400,000
Maximum number of qtrees with Extended Performance Monitoring			
Cluster	50,000	50,000	50,000
Maximum number of concurrent DataMotion for Volumes (vol move) operations			
Node	16	16	16
HA Pair (Non-Scalable)	16	16	16
Maximum Depth of Clones			
Volume	999	999	999
Maximum Number of First Origin Clones			
Volume	999	999	999
Quality of Service Cluster Limits			
Maximum number of Policy Groups			
Cluster	12,000	12,000	12,000
Maximum number of QoS user workloads			
Cluster	40,000	40,000	40,000
SAN Cluster Limits			
Maximum number of storage virtual machines (SVMs) - SAN			
Cluster	1,000	1,000	1,000
Maximum number of flexible volumes - SAN			
Node	1,000	1,000	1,000
HA Pair	2,000	2,000	2,000
Cluster	12,000	12,000	12,000
Maximum number of LUNs			
Volume	1,024	1,024	1,024
Node	8,192	8,192	8,192
HA Pair	16,384	16,384	16,384
Cluster	65,536	65,536	65,536

Specifications	FAS2750 10GBASE-T Single Chassis HA Pair	FAS2750 UTA2 Single Chassis HA Pair	FAS2820 Single Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum number of LUN mappings			
igroup	4,096	4,096	4,096
Node	8,192	8,192	8,192
HA Pair	16,384	16,384	16,384
Cluster	65,536	65,536	65,536
Maximum LUN size (TiB)			
LUN	128	128	128
Maximum FC queue depth available			
Port	2,048	2,048	2,048
Maximum Number of SAN Hosts (ITNs)			
Port	512	512	512
Node	4,096	4,096	4,096
HA Pair	8,192	8,192	8,192
Cluster	32,768	32,768	32,768
Maximum number of LIFS - iSCSI			
Port	32	32	32
Portset	32	32	32
SVM	256	256	256
Node	512	512	512
HA Pair	1,024	1,024	1,024
Cluster	4,096	4,096	4,096
Maximum number of LIFS - FCP			
Port	32	32	32
Portset	32	32	32
SVM	256	256	256
Node	512	512	512
HA Pair	1,024	1,024	1,024
Cluster	4,096	4,096	4,096
Maximum number of igroups			
Node	2,048	2,048	2,048
HA Pair	4,096	4,096	4,096
Cluster	16,384	16,384	16,384
Maximum number of initiators			
igroup	256	256	256
Node	2,048	2,048	2,048
HA Pair	4,096	4,096	4,096
Cluster	16,384	16,384	16,384
Maximum number of portsets			
Node	2,048	2,048	2,048
HA Pair	4,096	4,096	4,096
Cluster	16,384	16,384	16,384
Maximum number of iSCSI sessions			
Node	4,096	4,096	4,096
HA Pair	8,192	8,192	8,192
Cluster	32,768	32,768	32,768
CIFS Cluster Limits			
Maximum number of connected shares			
Node	800,000	800,000	800,000
HA Pair	800,000	800,000	800,000
Maximum number of regular shares			
Cluster	60,000	60,000	60,000
Maximum number of open files			
Connection	65,536	65,536	65,536
Node	600,000	600,000	600,000
HA Pair	600,000	600,000	600,000
Maximum number of local users			

Specifications	FAS2750 10GBASE-T Single Chassis HA Pair	FAS2750 UTA2 Single Chassis HA Pair	FAS2820 Single Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Cluster	5,000	5,000	5,000
Maximum number of local groups			
Cluster	10,000	10,000	10,000
Maximum number of local group members			
Cluster	30,000	30,000	30,000
Data Protection Cluster Limits			
Maximum number of NDMP sessions			
Node	36	36	36
HA Pair (Non-Scalable)	36	36	36
Maximum number of data protection (DP) mirrors and/or SnapVault relationships			
Volume	1	1	1
Node	1,000	1,000	1,000
HA Pair	2,000	2,000	2,000
Cluster	15,000	15,000	15,000
Maximum number of load sharing (LS) mirrors			
NAS SVM	2	2	2
Maximum number of concurrent Snap Mirror or SnapVault transfers			
Node	100	100	100
Maximum fan-out from source for DP mirror			
Volume	8	8	8
Maximum fan-out from source for LS mirror			
NAS SVM	2	2	2
Maximum number of clusters that can be peered			
Cluster	400	400	400
Maximum Number of constituent volumes in a SnapMirror relationship			
FlexGroup	200	200	200
FlexGroup/Node	50	50	50
HA Pair	1,000	1,000	1,000
Cluster	6,000	6,000	6,000
Maximum number of SnapMirror Synchronous relationships			
Volume	1	1	1
Node	80	80	80
HA Pair	80	80	80
Maximum Number of Flexible Volumes in SVM DR			
SVM	300	300	300
HA Pair	1,000	1,000	1,000
Maximum Number of storage virtual machine disaster recovery (SVM DR) relationship			
Cluster	128	128	128
Maximum Number of Concurrent SVM Migration			
Cluster	1	1	1
Maximum Number of Volumes with SVM Migration			
SVM	80	80	80

Specifications	FAS2750 10GBASE-T Single Chassis HA Pair	FAS2750 UTA2 Single Chassis HA Pair	FAS2820 Single Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum Size of Cluster for SVM Migration			
Cluster	24	24	24
Maximum Number of FlexGroups and/or Consistency Groups supported in (SVM DR) relationship			
Cluster	32	32	32
Maximum Number of FlexGroups Constituents Volumes supported in (SVM DR) relationship			
FlexGroup	200	200	200
Maximum Number of Concurrent SnapDiff Sessions			
Node	64	64	64
HA Pair	128	128	128
NVMe/oF Cluster Limits			
Maximum number of storage virtual machines (SVMs) - NVMe/oF			
Cluster	32	32	32
Maximum number of flexible volumes - NVMe/oF			
Node	1,000	1,000	1,000
HA Pair	2,000	2,000	2,000
Cluster	12,000	12,000	12,000
Maximum number of namespaces			
Volume	1,024	1,024	1,024
Node	8,192	8,192	8,192
HA Pair	16,384	16,384	16,384
Cluster	65,536	65,536	65,536
Maximum number of subsystems			
SVM	8,192	8,192	8,192
Cluster	8,192	8,192	8,192
Maximum number of namespace mappings			
Subsystem	1,024	1,024	1,024
Node	8,192	8,192	8,192
HA Pair	16,384	16,384	16,384
Cluster	65,536	65,536	65,536
Maximum namespace size			
Namespace	128	128	128
Maximum I/O queue depth available - NVMe/FC			
Regular Priority Queue	N/A	N/A	N/A
High Priority Queue	N/A	N/A	N/A
Maximum I/O queue count available - NVMe/FC			
Regular Priority Controller	N/A	N/A	N/A
High Priority Controller	N/A	N/A	N/A
Maximum number of hosts			
Subsystem	64	64	64
Maximum number of LIFS - NVMe/oF			
Port	16	16	16
SVM	24	24	24
Node	32	32	32
HA Pair	32	32	32
Cluster	96	96	96
Node/SVM	2	2	2
Maximum number of controllers - NVMe/FC			

Specifications	FAS2750 10GBASE-T Single Chassis HA Pair	FAS2750 UTA2 Single Chassis HA Pair	FAS2820 Single Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Port	N/A	N/A	N/A
Maximum I/O queue count available - NVMe/TCP			
Regular Priority Controller	2	2	2
High Priority Controller	4	4	4
Maximum I/O queue depth available - NVMe/TCP			
Regular Priority Queue	128	128	128
High Priority Queue	128	128	128
Maximum number of controllers - NVMe/TCP			
Node	64	64	128
FlexCache Cluster Limits			
Max caches from/of an origin volume (degree of fan-out)			
Origin	100	100	100
Max origin volumes			
Node	400	400	400
HA Pair	800	800	800
Max cache constituent volumes			
Node	800	800	800
HA Pair	1,600	1,600	1,600
Max cache volumes			
Node	400	400	400
HA Pair	800	800	800
Max origin constituent volumes			
Node	800	800	800
HA Pair	1,600	1,600	1,600
S3 Cluster Limits			
Maximum Number of Buckets			
FlexGroup Volume	1,000	1,000	1,000
Cluster	12,000	12,000	12,000
Maximum Number of Objects			
Bucket	400,000,000,000	400,000,000,000	400,000,000,000
Maximum Number of Users			
Object Store/StorageVM	4,000	4,000	4,000
Cluster	96,000	96,000	96,000
Maximum Size of the Bucket (PB)			
Vserver	60	60	60
Consistency Groups			
Maximum Number of CG Constituents Volumes supported in (SVM DR) relationship			
Consistency group	80	80	80
Maximum Number of Consistency Groups			
Cluster	15,000	15,000	15,000
Maximum Number of Consistency Groups and Parent Consistency Groups			
Cluster	15,000	15,000	15,000
Maximum Number of Parent Consistency Groups			
Cluster	15,000	15,000	15,000
Maximum Number of Child Consistency Groups in a Parent Consistency Group			
Parent consistency group	5	5	5

	FAS2750 10GBASE-T Single Chassis HA Pair	FAS2750 UTA2 Single Chassis HA Pair	FAS2820 Single Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum Number of Flexible Volumes in a Consistency Group			
Consistency group	80	80	80
Maximum Flexible Volumes across all the Child Consistency Groups under a Parent Consistency Group			
Parent consistency group	80	80	80
Maximum Number of Flexible Volumes in a Child Consistency Group			
Child consistency group	80	80	80
FlexGroup Rebalancing Limits			
Maximum Concurrent File Move at Destination Node			
Node	1,500	1,500	1,500
Maximum Number of Concurrent File Move Operations			
FlexGroup Constituent	1,500	1,500	1,500
Foreign LUN Import			
Maximum Block Size			
Bytes	512	512	512
Maximum Number of Concurrent Foreign LUN Imports			
Node	8	8	8
Maximum Number of FLI Initiators			
Intercluster LIF	1	1	1
Maximum Number of Sessions			
Intercluster LIF	16	16	16
Node	32	32	32
Maximum Size of Imported LUN (TB)			
LUN	4	4	4

Specifications	FAS50 Single Chassis HA Pair	FAS70 Dual Chassis HA Pair	FAS90 Dual Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Storage Limits			
Max Number of Drives (Total)	480	1440	1440
Internal Drives count	Max: 22 per Chassis;	N/A	N/A
Max number of NL-SAS Drives	Max: 480 per HA Pair;	Max: 1440 per HA Pair;	Max: 1440 per HA Pair;
Max number of NVMe SSD Drives	Max: 22 per HA Pair;	Max: 240 per HA Pair;	Max: 240 per HA Pair;
Max number of SAS Drives	Max: 480 per HA Pair;	Max: 1440 per HA Pair;	Max: 1440 per HA Pair;
Max number of SSD Drives	Max: 96 per HA Pair;	Max: 480 per HA Pair;	Max: 480 per HA Pair;
Max number of DS212C shelves	40 external	80 external	80 external
Max number of DS224C shelves	20 external	60 external	60 external
Max number of DS460C shelves	8 external	24 external	24 external
Max number of NS224 shelves	1 internal	10 external	10 external
Max number of NS224 w/ NSM100B shelves	N/A	10 external	10 external
Capacity Limits			
Marketing Maximum Raw Capacity (GB)			
Node	11,520,000	15,000,000	15,000,000
HA Pair	11,520,000	15,000,000	15,000,000
Core Cluster Limits			
Maximum number of storage virtual machines (SVMs) - NAS			
Cluster	1,024	1,024	1,024
Maximum number of LIFs - NAS			
Node	1,024	1,024	1,024
HA Pair	1,024	1,024	1,024
Cluster	4,096	4,096	4,096
Maximum number of connections - NAS/S3			
Node	100,000	100,000	100,000
HA Pair (Non-Scalable)	100,000	100,000	100,000
Maximum Number of VLANs			
Node	512	512	512
Maximum number of flexible volumes - NAS			
Node	1,000	1,000	2,500
HA Pair	2,000	2,000	5,000
Cluster	8,000	24,000	30,000
Maximum number of lock manager locked objects (CIFS and NFS combined)			
Node	3,000,000	3,000,000	3,000,000
HA Pair	3,000,000	3,000,000	3,000,000
Cluster	12,288,000	12,288,000	12,288,000
Maximum number of Intercluster LIFs			
Node	8	8	8
Minimum Root Aggregate (MiB)			
Node	191,488	191,488	191,488
Minimum Root Volume (GiB)			
Node	150	150	150
Maximum IPsec Policies			
SVM	N/A	256	256
Cluster	N/A	1,500	1,500
Maximum Number of IPspaces			
Cluster	512	512	512

Specifications	FAS50 Single Chassis HA Pair	FAS70 Dual Chassis HA Pair	FAS90 Dual Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum IPsec Policies (If not using HW Offload)			
SVM	256	N/A	N/A
Cluster	1,500	N/A	N/A
Maximum IPsec Policies (If using HW Offload)			
SVM	40	N/A	N/A
Cluster	40	N/A	N/A
Maximum Number of Auditing-Enabled SVMs			
Cluster	400	400	400
Max Flash Cache (no Flash Pool) (TiB)			
HA Pair	4	8	16
Max Total Cache (Flash Cache + Flash Pool) (TiB)			
HA Pair	144	144	144
Maximum Composite Aggregate Size (TiB)			
HA Pair	16,800	16,800	16,800
Max Flash Pool (no Flash Cache) (TiB)			
HA Pair	144	144	144
Default Flash Cache (TiB)			
HA Pair	4	4	8
System Maximums and Limits			
Max Nodes per Cluster (NAS / SAN)	8 / 8	24 / 12	24 / 12
Max FabricPool Size	16800 TiB	16800 TiB	16800 TiB
Max Infinite Volume Data Constituent Size	Not Supported	Not Supported	Not Supported
Max FlexGroup Data Constituent Size	300 TiB	300 TiB	300 TiB
Min Root Volume Size	150 GiB	150 GiB	150 GiB
NetApp Volume Encryption	NVE	NVE	NVE
Processor			
Processor Model	64-bit 16-core 2.0 GHz	64-bit 16-Core 2.0GHz	64-bit 32-Core 2.0GHz
Processor Architecture	64 bit	64 bit	64 bit
Processor Speed	2.00 Ghz	2.00 Ghz	2.00 Ghz
Processor Count (Per Node)	1	2	2
Processor Count (Per Config)	2	4	4
Processor Cores (Per CPU)	16	16	32
Processor Cores (Per Node)	16	32	64
Processor Cores (Per Config)	32	64	128
Memory			
NVME (Per Node)	N/A	N/A	N/A
NVME (Per Config)	N/A	N/A	N/A
NVMEM (Per Node)	8 GB	N/A	N/A
NVMEM (Per Config)	16 GB	N/A	N/A
NVRAM (Per Node)	N/A	32 GB	64 GB
NVRAM (Per Config)	N/A	64 GB	128 GB
RAM (Per Node)	64 GB	128 GB	512 GB
RAM (Per Config)	128 GB	256 GB	1024 GB
Onboard Ports			
Ethernet Ports	-	-	-
Fibre Channel Ports	-	-	-
UTA2 Ports	Not Supported	Not Supported	Not Supported
Expansion Slots	8 x IO Module (per System) 4 x U.2 PCIe (per System)	9 x IO Module (per Chassis) 18 x IO Module (per System)	9 x IO Module (per Chassis) 18 x IO Module (per System)
SAS Ports	-	-	-
Physical Characteristics			
Rack Units	2	4	4

Specifications	FAS50 Single Chassis HA Pair	FAS70 Dual Chassis HA Pair	FAS90 Dual Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Chassis Height	3.43" (8.7 cm)	3.5" (8.89 cm)	3.5" (8.89 cm)
Chassis Width with Mounting Flanges	19.02" (48.3 cm)	19.02" (48.3 cm)	19.02" (48.3 cm)
Chassis Width without Mounting Flanges	17.6" (44.7 cm)	17.68" (44.9 cm)	17.68" (44.9 cm)
Chassis Depth with Cable Mgmt	-	35.24" (89.5 cm)	35.24" (89.5 cm)
Chassis Depth without Cable Mgmt	22.05" (56 cm)	30.04" (76.3 cm)	30.04" (76.3 cm)
Chassis Weight			
System Clearance Dimensions			
Front Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)	6.03" (15.3 cm)
Front Clearance (Maintenance)	24.03" (61 cm)	31.99" (81.2 cm)	31.99" (81.2 cm)
Rear Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)	6.03" (15.3 cm)
Rear Clearance (Maintenance)	16.94" (43 cm)	11.03" (28 cm)	11.03" (28 cm)
Environmental Requirements			
Operating Temperature Range	50 to 95 deg F 10 to 35 deg C	50 to 95 deg F 10 to 35 deg C	50 to 95 deg F 10 to 35 deg C
Storage Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Transit Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Operating Relative Humidity	8 to 80 %	8 to 80 %	8 to 80 %
Storage Relative Humidity	10 to 95 %	10 to 95 %	10 to 95 %
Transit Relative Humidity	10 to 95 %	10 to 95 %	10 to 95 %
Operating Altitude Range	Up to 10000.0 ft Up to 3048.0 m	Up to 10000.0 ft Up to 3048.0 m	Up to 10000.0 ft Up to 3048.0 m
Storage Altitude Range	Up to 40000.0 ft Up to 12192.0 m	Up to 40000.0 ft Up to 12192.0 m	Up to 40000.0 ft Up to 12192.0 m
Transit Altitude Range	Up to 39989.8 ft Up to 12192 m	Up to 39989.8 ft Up to 12192 m	Up to 39989.8 ft Up to 12192 m
Acoustic Noise - Sound Power	8 Bels	8.5 Bels	8.5 Bels
Acoustic Noise - Sound Pressure	70.5 dBA	67.7 dBA	67.7 dBA
Input Power Voltage	40 to 48; 200 to 240;	40 to 48; 100 to 120; 200 to 240;	40 to 48; 200 to 240;
Storage OS Requirements (for selected major version)			
Recommended Version	9.19.1, 9.19.1P2	9.19.1, 9.19.1P2	9.19.1, 9.19.1P2
Minimum OS	9.19.1RC1	9.19.1RC1	9.19.1RC1
Maximum OS	9.19.1P2	9.19.1P2	9.19.1P2
Software and Firmware * indicates that firmware is bundled with Storage OS Version			
BIOS	21.4.1, 21.3*	20.8*	20.8*
BMC	19.4*	18.6*	18.6*
Product Standards Compliance			
Certifications EMC/EMI	AMCA, FCC, ICES, KC, Morocco, VCCI	AMCA, FCC, ICES, KC, Morocco, VCCI	AMCA, FCC, ICES, KC, Morocco, VCCI
Certifications safety	BIS, CB, CSA, G_K_U-SoR, IRAM, NOM, NRCS, SONCAP, TBS	BIS, CB, CSA, G_K_U-SoR, IRAM, NOM, NRCS, SONCAP, TBS	BIS, CB, CSA, G_K_U-SoR, IRAM, NOM, NRCS, SONCAP, TBS
Certifications Safety/EMC/EMI	EAC, UKRSEPRO	EAC, UKRSEPRO	EAC, UKRSEPRO
Certifications Safety/EMC/EMI/RoHS	BSMI, CE DoC, UKCA DoC	BSMI, CE DoC, UKCA DoC	BSMI, CE DoC, UKCA DoC
Standards EMC/EMI	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835

Specifications	FAS50 Single Chassis HA Pair	FAS70 Dual Chassis HA Pair	FAS90 Dual Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Standards Safety	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)
System Availability & Support			
Release Date	Feb 2025	Sep 2024	Sep 2024
End of Availability (EOA)	-	-	-
End of Support (EOS)	-	-	-
NFS Cluster Limits			
Maximum Number of NFS over TLS Connections			
Node	10,000	10,000	10,000
Maximum number of Export Policies			
Cluster	24,000	24,000	24,000
Maximum number of Export Rules			
Cluster	200,000	200,000	200,000
Maximum NFSv4 Access Control Entries			
ACL (Access List)	1,024	1,024	1,024
Maximum number of client objects			
Node	100,000	100,000	100,000
HA Pair	100,000	100,000	100,000
Maximum Number of NFSv4 ByteLock Objects			
Node	1,000,000	1,000,000	13,312,000
Maximum Number of NFSv4 Client Objects			
Node	100,000	100,000	409,600
Maximum Number of NFSv4 Copy State Objects			
Node	10,000	10,000	4,096,000
Maximum Number of NFSv4 Deleg Objects			
Node	1,000,000	1,000,000	8,192,000
Maximum Number of NFSv4 Deleg State Objects			
Node	1,000,000	1,000,000	8,192,000
Maximum Number of NFSv4 Layout Objects			
Node	1,000,000	1,000,000	4,096,000
Maximum Number of NFSv4 Layout State Objects			
Node	1,000,000	1,000,000	4,096,000
Maximum Number of NFSv4 LayoutLock Objects			
Node	1,000,000	1,000,000	4,096,000
Maximum Number of NFSv4 Lock State Objects			
Node	4,000,000	1,000,000	8,192,000
Maximum Number of NFSv4 Open Objects			
Node	1,000,000	1,000,000	12,288,000
Maximum Number of NFSv4 Open State Objects			
Node	1,000,000	1,000,000	12,288,000
Maximum Number of NFSv4 Owner Objects			
Node	1,000,000	1,000,000	2,457,600
Maximum Number of NFSv4 Sessions			
Node	100,000	100,000	409,600
Maximum Number of NFSv4 String Objects			

Specifications	FAS50 Single Chassis HA Pair	FAS70 Dual Chassis HA Pair	FAS90 Dual Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Node	1,000,000	1,000,000	4,096,000
WAFL Cluster Limits			
Maximum Size of a 64-bit Aggregate (TiB)			
Aggregate	800	800	800
Maximum Size of a 64-bit Volume (TiB)			
Volume	300	300	300
Maximum file size in a 64-bit Volume (TiB)			
File	128	128	128
Maximum number of Volume Snapshot Copies			
Volume	1,023	1,023	1,023
Node	1,023,000	1,023,000	1,023,000
HA Pair	2,046,000	2,046,000	2,046,000
Maximum character length for Snapshot copy names			
Snapshot	255	255	255
Maximum number of hard links			
File	100,000	100,000	100,000
Maximum number of inodes/files			
Volume	2,000,000,000	2,000,000,000	2,000,000,000
Maximum number of qtrees			
Volume	4,995	4,995	4,995
Node	100,000	100,000	100,000
HA Pair	200,000	200,000	200,000
Cluster	2,400,000	2,400,000	2,400,000
Maximum number of qtrees with Extended Performance Monitoring			
Cluster	50,000	50,000	50,000
Maximum number of concurrent DataMotion for Volumes (vol move) operations			
Node	16	16	16
HA Pair (Non-Scalable)	16	16	16
Maximum Depth of Clones			
Volume	999	999	1,000
Maximum Number of First Origin Clones			
Volume	999	999	1,023
Quality of Service Cluster Limits			
Maximum number of Policy Groups			
Cluster	12,000	12,000	12,000
Maximum number of QoS user workloads			
Cluster	40,000	40,000	40,000
SAN Cluster Limits			
Maximum number of storage virtual machines (SVMs) - SAN			
Cluster	1,000	1,000	1,000
Maximum number of flexible volumes - SAN			
Node	1,000	1,000	1,000
HA Pair	2,000	2,000	2,000
Cluster	8,000	12,000	12,000
Maximum number of LUNs			
Volume	1,024	1,024	1,024
Node	8,192	12,288	12,288
HA Pair	16,384	24,576	24,576
Cluster	65,536	98,304	98,304

Specifications	FAS50 Single Chassis HA Pair	FAS70 Dual Chassis HA Pair	FAS90 Dual Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum number of LUN mappings			
igroup	4,096	4,096	4,096
Node	8,192	12,288	12,288
HA Pair	16,384	24,576	24,576
Cluster	65,536	98,304	98,304
Maximum LUN size (TiB)			
LUN	128	128	128
Maximum FC queue depth available			
Port	2,048	2,048	2,048
Maximum Number of SAN Hosts (ITNs)			
Port	512	512	512
Node	4,096	8,192	8,192
HA Pair	8,192	16,384	16,384
Cluster	32,768	65,536	65,536
Maximum number of LIFS - iSCSI			
Port	32	32	32
Portset	32	32	32
SVM	256	256	256
Node	512	512	512
HA Pair	1,024	1,024	1,024
Cluster	4,096	4,096	4,096
Maximum number of LIFS - FCP			
Port	32	32	32
Portset	32	32	32
SVM	256	256	256
Node	512	512	512
HA Pair	1,024	1,024	1,024
Cluster	4,096	4,096	4,096
Maximum number of igroups			
Node	2,048	4,096	4,096
HA Pair	4,096	8,192	8,192
Cluster	16,384	32,768	32,768
Maximum number of initiators			
igroup	256	256	256
Node	2,048	4,096	4,096
HA Pair	4,096	8,192	8,192
Cluster	16,384	32,768	32,768
Maximum number of portsets			
Node	2,048	4,096	4,096
HA Pair	4,096	8,192	8,192
Cluster	16,384	32,768	32,768
Maximum number of iSCSI sessions			
Node	4,096	8,192	8,192
HA Pair	8,192	16,384	16,384
Cluster	32,768	65,536	65,536
CIFS Cluster Limits			
Maximum number of connected shares			
Node	1,000,000	1,000,000	1,000,000
HA Pair	1,000,000	1,000,000	1,000,000
Maximum number of regular shares			
Cluster	300,000	300,000	300,000
Maximum number of open files			
Connection	65,536	65,536	65,536
Node	1,500,000	1,500,000	1,500,000
HA Pair	1,500,000	1,500,000	1,500,000
Maximum number of local users			

	FAS50 Single Chassis HA Pair	FAS70 Dual Chassis HA Pair	FAS90 Dual Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
	Cluster 35,000	Cluster 35,000	Cluster 35,000
Maximum number of local groups			
Cluster	320,000	320,000	320,000
Maximum number of local group members			
Cluster	640,000	640,000	640,000
Data Protection Cluster Limits			
Maximum number of NDMP sessions			
Node	36	36	36
HA Pair (Non-Scalable)	36	36	36
Maximum number of data protection (DP) mirrors and/or SnapVault relationships			
Volume	1	1	1
Node	1,000	1,000	1,000
HA Pair	2,000	2,000	2,000
Cluster	8,000	15,000	15,000
Maximum number of load sharing (LS) mirrors			
NAS SVM	2	2	2
Maximum number of concurrent Snap Mirror or SnapVault transfers			
Node	250	250	250
Maximum fan-out from source for DP mirror			
Volume	8	8	8
Maximum fan-out from source for LS mirror			
NAS SVM	2	2	2
Maximum number of clusters that can be peered			
Cluster	400	400	400
Maximum Number of constituent volumes in a SnapMirror relationship			
FlexGroup	200	200	200
FlexGroup/Node	50	50	50
HA Pair	1,000	1,000	1,000
Cluster	6,000	6,000	6,000
Maximum number of SnapMirror Synchronous relationships			
Volume	1	1	1
Node	80	80	80
HA Pair	80	80	80
Maximum Number of Flexible Volumes in SVM DR			
SVM	300	300	300
HA Pair	1,000	1,000	1,000
Maximum Number of storage virtual machine disaster recovery (SVM DR) relationship			
Cluster	128	128	128
Maximum Number of Concurrent SVM Migration			
Cluster	1	1	1
Maximum Number of Volumes with SVM Migration			
SVM	80	80	80

	FAS50 Single Chassis HA Pair	FAS70 Dual Chassis HA Pair	FAS90 Dual Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum Size of Cluster for SVM Migration			
Cluster	24	24	24
Maximum Number of FlexGroups and/or Consistency Groups supported in (SVM DR) relationship			
Cluster	32	32	32
Maximum Number of FlexGroups Constituents Volumes supported in (SVM DR) relationship			
FlexGroup	200	200	200
Maximum Number of Concurrent SnapDiff Sessions			
Node	64	64	64
HA Pair	128	128	128
NVMe/oF Cluster Limits			
Maximum number of storage virtual machines (SVMs) - NVMe/oF			
Cluster	32	32	32
Maximum number of flexible volumes - NVMe/oF			
Node	1,000	1,000	1,000
HA Pair	2,000	2,000	2,000
Cluster	8,000	12,000	12,000
Maximum number of namespaces			
Volume	1,024	1,024	1,024
Node	8,192	12,288	12,288
HA Pair	16,384	24,576	24,576
Cluster	65,536	98,304	98,304
Maximum number of subsystems			
SVM	8,192	8,192	8,192
Cluster	8,192	8,192	8,192
Maximum number of namespace mappings			
Subsystem	1,024	1,024	1,024
Node	8,192	12,288	12,288
HA Pair	16,384	24,576	24,576
Cluster	65,536	98,304	98,304
Maximum namespace size			
Namespace	128	128	128
Maximum I/O queue depth available - NVMe/FC			
Regular Priority Queue	32	32	32
High Priority Queue	32	32	64
Maximum I/O queue count available - NVMe/FC			
Regular Priority Controller	4	4	4
High Priority Controller	6	6	8
Maximum number of hosts			
Subsystem	64	64	64
Maximum number of LIFS - NVMe/oF			
Port	16	16	16
SVM	24	24	24
Node	32	32	32
HA Pair	32	32	32
Cluster	96	96	96
Node/SVM	2	2	2
Maximum number of controllers - NVMe/FC			

	FAS50 Single Chassis HA Pair	FAS70 Dual Chassis HA Pair	FAS90 Dual Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
	Port 256	256	256
Maximum I/O queue count available - NVMe/TCP			
Regular Priority Controller	2	2	2
High Priority Controller	4	4	8
Maximum I/O queue depth available - NVMe/TCP			
Regular Priority Queue	128	128	128
High Priority Queue	128	128	128
Maximum number of controllers - NVMe/TCP			
Node	128	512	2,048
FlexCache Cluster Limits			
Max caches from/of an origin volume (degree of fan-out)			
Origin	100	100	100
Max origin volumes			
Node	400	400	400
HA Pair	800	800	800
Max cache constituent volumes			
Node	800	800	800
HA Pair	1,600	1,600	1,600
Max cache volumes			
Node	400	400	400
HA Pair	800	800	800
Max origin constituent volumes			
Node	800	800	800
HA Pair	1,600	1,600	1,600
S3 Cluster Limits			
Maximum Number of Buckets			
FlexGroup Volume	1,000	1,000	1,000
Cluster	12,000	12,000	12,000
Maximum Number of Objects			
Bucket	400,000,000,000	400,000,000,000	400,000,000,000
Maximum Number of Users			
Object Store/StorageVM	4,000	4,000	4,000
Cluster	96,000	96,000	96,000
Maximum Size of the Bucket (PB)			
Vserver	60	60	60
Consistency Groups			
Maximum Number of CG Constituents Volumes supported in (SVM DR) relationship			
Consistency group	80	80	80
Maximum Number of Consistency Groups			
Cluster	15,000	15,000	15,000
Maximum Number of Consistency Groups and Parent Consistency Groups			
Cluster	15,000	15,000	15,000
Maximum Number of Parent Consistency Groups			
Cluster	15,000	15,000	15,000
Maximum Number of Child Consistency Groups in a Parent Consistency Group			
Parent consistency group	5	5	5

	FAS50 Single Chassis HA Pair	FAS70 Dual Chassis HA Pair	FAS90 Dual Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum Number of Flexible Volumes in a Consistency Group			
Consistency group	80	80	80
Maximum Flexible Volumes across all the Child Consistency Groups under a Parent Consistency Group			
Parent consistency group	80	80	80
Maximum Number of Flexible Volumes in a Child Consistency Group			
Child consistency group	80	80	80
FlexGroup Rebalancing Limits			
Maximum Concurrent File Move at Destination Node			
Node	1,500	1,500	1,500
Maximum Number of Concurrent File Move Operations			
FlexGroup Constituent	1,500	1,500	1,500
Foreign LUN Import			
Maximum Block Size			
Bytes	512	512	512
Maximum Number of Concurrent Foreign LUN Imports			
Node	8	8	8
Maximum Number of FLI Initiators			
Intercluster LIF	1	1	1
Maximum Number of Sessions			
Intercluster LIF	16	16	16
Node	32	32	32
Maximum Size of Imported LUN (TB)			
LUN	4	4	4

Notes ID	Notes Description
1	The root volume and aggregate on this system are significantly smaller than on previous generation systems. Core dump files that used to be written to the root volume are now written to the controller's boot media, instead.