

CSS Selector Cheat Sheet - `findElement(By.cssSelector("here"));`

Attribute Selector

HTML: `<input name="email" value="" />`
CSS: `[name='email']`

HTML: `<input type="radio" name="point" value="1" />`
`<input type="radio" name="point" value="2" />`
`<input type="radio" name="point" value="3" />`

Selecting second radio button by matching two attributes
CSS: `[name='point'][value='2']`

Element Selector

Same class name with different elements
HTML: `<div class="username">johndoe</div>`
`<span class="username">johndoe</span>`

Shorthand for `div[class='username']`
CSS: `div.username`

ID Selector

HTML: `<input id="email" value="" />`

Shorthand for `[id='email']`
CSS: `#email`

Class Name Selector

HTML: `<div class="class-name">...</div>`

Shorthand for `[class='class-name']`
CSS: `.class-name`

Multiple classes
HTML: `<div class="some-class another-class">...</div>`

Match multiple classes by chaining them
CSS: `.some-class.another-class`

Ordering Selector

HTML: `<ul class="colors">`
`<li>Red</li>`
`<li>Purple</li>`
`<li>Black</li>`
`</ul>`

Select second item from the list
CSS: `.colors li:nth-of-type(2)`

Hierarchy Selector

Label elements in different classes
HTML: `<div class="name">`
`<label>Doe</label>`
`</div>`
`<div class="email">`
`<label>test@email.com</label>`
`</div>`

Select parent (class) first and then select child (label)
CSS: `.name label`

Nested element
HTML: `<div id="feedback">`
`<div class="comments">`
`<textarea></textarea>`
`</div>`
`</div>`

Select id (feedback), class (comments), and textarea
CSS: `#feedback .comments textarea`

Multiple hierarchy
HTML: `<div class="comments">`
`<textarea></textarea>`
`</div>`
`<div class="comments">`
`<div class="something">`
`<textarea></textarea>`
`</div>`
`</div>`

Angle bracket (>) to select the direct child
CSS: `.comments > textarea`

CSS Operators

`^=` Match at the beginning of the attribute
`$=` Match at the end of the attribute
`*=` Match anywhere in the attribute

Dynamic ID part (xo)
HTML: `<a href="#" id="u_0_5_xo">...</a>`

Match only the beginning
CSS: `[id^='u_0_5']`

Dynamic user ID
HTML: `<a href="/user/32578/edit/">Edit Profile</a>`

Matching the beginning and the end
CSS: `a[href^='/user/'][href$='/edit/']`

Dynamic session ID
HTML: `<a href="https://example.com/dashboard/?session=7845263">Dashboard</a>`

Match anywhere in the URL
`a[href*='/dashboard/']`