

English: john likes mary

$$\begin{array}{ccccc} \text{john} & & \text{likes} & & \text{mary} \\ \hline \text{NP} & & (\text{S/NP})/\text{NP} & & \text{NP} \\ \hline & & \text{S/NP} & & \\ \hline & & \text{S} & & \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \\ \longrightarrow \end{array}$$

Turkish: ucte dus tu (no semantics)

every	spy	sg	chase	3p	past	a	dog	sg
$((S/(S \setminus N_2))/N)$	N_0	NIL	$((S_- \setminus N_2)/N_2)$	$((S \setminus N_{2,sg})(S \setminus N_2))$	$((S_+ \setminus N_2) \setminus (S_- \setminus N_2))$	$((S \setminus (S/N_2))/N)$	N_0	NIL
	$\xrightarrow{N_{0,sg} <}$			$\xrightarrow{((S_+ \setminus N_{2,sg}) \setminus (S \setminus N_2)) <^B}$			$\xrightarrow{N_{0,sg} <}$	
$\xrightarrow{(S/(S \setminus N_{2,sg}))}$				$\xrightarrow{((S_+ \setminus N_{2,sg})/N_2) <^B}$		$\xrightarrow{(S \setminus (S/N_2))}$		
			$\xrightarrow{(S/N_2) >^B}$					
S								
<								

Turkish: ucte dus tu (with semantics)

every	spy	sg	chase	3p	pa
NIL	NIL	NIL	NIL	NIL	NIL
$: \lambda p. \lambda q. \lambda e. \forall x. p x \rightarrow q x e$	$: spy' : \lambda x. x$	$: \lambda x. \lambda y. \lambda e. chase' e \wedge agent' ey \wedge patient' ex$	$: \lambda x. x$	$: \lambda x. x$	$: \lambda x. x$
	$\overline{N_{0,sg} : spy'}^<$			$\overline{((S_+ \setminus N_{2,sg}) \setminus (S \setminus N_2))}^<$	
$\overline{(S / (S \setminus N_{2,sg})) : \lambda q. \lambda e. \forall x. spy' x \rightarrow q x e}^>$			$\overline{((S_+ \setminus N_{2,sg}) / N_2) : \lambda x. \lambda y. \lambda e. chase' e \wedge agent' ey \wedge patient' ex}^>$		$\overline{(S \setminus N_2) : \lambda y. \lambda e. \exists x. dog' x \wedge chase' ex}^>$
			$S : \lambda e. \forall x. spy' x \rightarrow \exists x_0. dog' x_0 \wedge chase' e \wedge agent' ex$		
every	spy	sg	chase	3p	pa
$((S / (S \setminus N_2)) / N)$	N_0	NIL	$((S \setminus N_2) / N_2)$	$((S \setminus N_{2,sg}) \setminus (S \setminus N_2))$	
$: \lambda p. \lambda q. \lambda e. \forall x. p x \rightarrow q x e$	$: spy' : \lambda x. x$	$: \lambda x. \lambda y. \lambda e. chase' e \wedge agent' ey \wedge patient' ex$	$: \lambda x. \lambda y. \lambda e. chase' e \wedge agent' ey \wedge patient' ex$	$: \lambda x. x$	
	$\overline{N_{0,sg} : spy'}^<$			$\overline{((S_+ \setminus N_{2,sg}))}^<$	
$\overline{(S / (S \setminus N_{2,sg})) : \lambda q. \lambda e. \forall x. spy' x \rightarrow q x e}^>$			$\overline{((S_+ \setminus N_{2,sg}) / N_2) : \lambda x. \lambda y. \lambda e. chase' e \wedge agent' ey \wedge patient' ex}^>$		
			$(S / N_2) : \lambda x. \lambda e. \forall x_0. spy' x_0 \rightarrow chase' e \wedge agent' ex_0 \wedge patient' ex$		
			$S : \lambda e. \exists x. dog' x \wedge \forall x_0. spy' x_0 \rightarrow chase' e \wedge agent' ex_0 \wedge patient' ex$		