

Discussion 12: More SQL, Final Review

disc12.pdf (disc12.pdf)

This is an online worksheet that you can work on during discussions. Your work is not graded and you do not need to submit anything.

SQL

You can refer back to Discussion 11 (/disc/disc11/) for an overview of SQL, including joins and aggregation.

(Adapted from Fall 2019) The scoring table has three columns, a player column of strings, a points column of integers, and a quarter column of integers. The players table has two columns, a name column of strings and a team column of strings. Complete the SQL statements below so that they would compute the correct result even if the rows in these tables were different than those shown.

Important: You may write anything in the blanks including keywords such as WHERE or ORDER BY. Use the following tables for the questions below:

```
CREATE TABLE scoring AS
  SELECT "Donald Stewart" AS player, 7 AS points, 1 AS quarter UNION
  SELECT "Christopher Brown Jr.", 7, 1 UNION
  SELECT "Ryan Sanborn", 3, 2 UNION
  SELECT "Greg Thomas", 3, 2 UNION
  SELECT "Cameron Scarlett", 7, 3 UNION
  SELECT "Nikko Remigio", 7, 4 UNION
  SELECT "Ryan Sanborn", 3, 4 UNION
  SELECT "Chase Garbers", 7, 4;
```

```
CREATE TABLE players AS
  SELECT "Ryan Sanborn" AS name, "Stanford" AS team UNION
  SELECT "Donald Stewart", "Stanford" UNION
  SELECT "Cameron Scarlett", "Stanford" UNION
  SELECT "Christopher Brown Jr.", "Cal" UNION
  SELECT "Greg Thomas", "Cal" UNION
  SELECT "Nikko Remigio", "Cal" UNION
  SELECT "Chase Garbers", "Cal";
```

Q1: Big Quarters

Write a SQL statement to select a one-column table of quarters in which more than 10 total points were scored.

Solution: `SELECT quarter FROM scoring GROUP BY quarter HAVING SUM(points) > 10;`

Q2: Score

Write a SQL statement to select a two-column table where the first column is the team name and the second column is the total points scored by that team. Assume that no two players have the same name.

Solution: `SELECT team, SUM(points) FROM scoring, players WHERE player=name GROUP BY team;`

Final Review

The following worksheet is final review! It covers various topics that have been seen throughout the semester.

Your TA will not be able to get to all of the problems on this worksheet so feel free to work through the remaining problems on your own. Bring any questions you have to office hours or post them on piazza.

Good luck on the final and congratulations on making it to the last discussion of CS61A!

Recursion

Q3: Maximum Subsequence

A subsequence of a number is a series of (not necessarily contiguous) digits of the number. For example, 12345 has subsequences that include 123, 234, 124, 245, etc. Your task is to get the maximum subsequence below a certain length.

Your Answer

```

1  def max_subseq(n, t):
2      """
3          Return the maximum subsequence of length at most t that can be found in the given nu
4          For example, for n = 2012 and t = 2, we have that the subsequences are
5              2
6              0
7              1
8              2
9              20
10             21
11             22
12             01
13             02
14             12
15             and of these, the maxumum number is 22, so our answer is 22.
16
17             >>> max_subseq(2012, 2)
18             22
19             >>> max_subseq(20125, 3)
20             225
21             >>> max_subseq(20125, 5)
22             20125
23             >>> max_subseq(20125, 6) # note that 20125 == 020125
24             20125
25             >>> max_subseq(12345, 3)
26             345

```

```
26      345
27      >>> max_subseq(12345, 0) # 0 is of length 0
28      0
29      >>> max_subseq(12345, 1)
30      5
31      >>> from construct_check import check
32      >>> # ban usage of str
33      >>> check(LAB_SOURCE_FILE, 'max_subseq', ['Str', 'Slice'])
34      True
35      ""
36      "*** YOUR CODE HERE ***"
37
38
```

Solution

```
def max_subseq(n, t):
    """
    Return the maximum subsequence of length at most t that can be found in the given
    For example, for n = 2012 and t = 2, we have that the subsequences are
        2
        0
        1
        2
        20
        21
        22
        01
        02
        12
    and of these, the maximum number is 22, so our answer is 22.

    >>> max_subseq(2012, 2)
    22
    >>> max_subseq(20125, 3)
    225
    >>> max_subseq(20125, 5)
    20125
    >>> max_subseq(20125, 6) # note that 20125 == 020125
    20125
    >>> max_subseq(12345, 3)
    345
    >>> max_subseq(12345, 0) # 0 is of length 0
    0
    >>> max_subseq(12345, 1)
    5
    >>> from construct_check import check
    >>> # ban usage of str
    >>> check(LAB_SOURCE_FILE, 'max_subseq', ['Str', 'Slice'])
    True
    """
    if n == 0 or t == 0:
        return 0
    with_last = max_subseq(n // 10, t - 1) * 10 + n % 10
    without_last = max_subseq(n // 10, t)
    return max(with_last, without_last)
```

Mutation

Q4: Reverse

Write a function that reverses the given list. Be sure to mutate the original list. This is practice, so don't use the built-in `reverse` function!

Your Answer

```
1  def reverse(lst):
2      """Reverses lst using mutation.
3
4      >>> original_list = [5, -1, 29, 0]
5      >>> reverse(original_list)
6      >>> original_list
7      [0, 29, -1, 5]
8      >>> odd_list = [42, 72, -8]
9      >>> reverse(odd_list)
10     >>> odd_list
11     [-8, 72, 42]
12     """
13     "*** YOUR CODE HERE ***"
14
15
```

Solution

```
def reverse(lst):
    """Reverses lst using mutation.

    >>> original_list = [5, -1, 29, 0]
    >>> reverse(original_list)
    >>> original_list
    [0, 29, -1, 5]
    >>> odd_list = [42, 72, -8]
    >>> reverse(odd_list)
    >>> odd_list
    [-8, 72, 42]
    """

    # iterative solution
    midpoint = len(lst) // 2
    last = len(lst) - 1
    for i in range(midpoint):
        lst[i], lst[last - i] = lst[last - i], lst[i]
```

Efficiency

Q5: The First Order...of Growth

What is the efficiency of `rey` ?

```
def rey(finn):  
    poe = 0  
    while finn >= 2:  
        poe += finn  
        finn = finn / 2  
    return
```

Logarithmic, because our while loop iterates at most $\log(\text{finn})$ times, due to `finn` being halved in every iteration. This is commonly known as $\Theta(\log(\text{finn}))$ runtime. Another way of looking at this if you duplicate the input, we only add a single iteration to the time, which also indicates logarithmic.

What is the efficiency of `mod_7` ?

```
def mod_7(n):  
    if n % 7 == 0:  
        return 0  
    else:  
        return 1 + mod_7(n - 1)
```

Constant, since at worst it will require 6 recursive calls to reach the base case. This is commonly known as a $\Theta(1)$ runtime.

Trees

Q6: Level Mutation

As a reminder, the depth of a node is how far away the node is from the root. We define this as the number of edges between the root to the node. As there are no edges between the root and itself, the root has depth 0.

Given a tree `t` and a list of one-argument functions `funcs`, write a function that will mutate the labels of `t` using the function from `funcs` at the corresponding depth. For example, the label at the root node (with a depth of 0) will be mutated using the function at index 0, or `funcs[0]`. Assume all of the functions in `funcs` will be able to take in a label value and return a valid label value.

If `t` is a leaf and there are more than 1 functions in `funcs`, all of the remaining functions should be applied in order to the label of `t`. (See the doctests for an example.) If `funcs` is empty, the tree should remain unmodified.

Your Answer

```

1  def level_mutation(t, funcs):
2      """Mutates t using the functions in the list funcs.
3
4      >>> t = Tree(1, [Tree(2, [Tree(3)])])
5      >>> funcs = [lambda x: x + 1, lambda y: y * 5, lambda z: z ** 2]
6      >>> level_mutation(t, funcs)
7      >>> t                                     # funcs[0] was applied to the label 1, funcs[1]
8      Tree(2, [Tree(10, [Tree(9)])])
9      >>> t2 = Tree(1, [Tree(2), Tree(3, [Tree(4)])])
10     >>> level_mutation(t2, funcs)
11     >>> t2                                     # (2 * 5) ** 2 = 100
12     Tree(2, [Tree(100), Tree(15, [Tree(16)])])
13     >>> t3 = Tree(1, [Tree(2)])
14     >>> level_mutation(t3, funcs)
15     >>> t3
16     Tree(2, [Tree(100)])
17     """
18     if _____:
19         return
20     t.label = _____
21     remaining = _____
22     if _____ and remaining:
23         for _____:
24             _____
25     for b in t.branches:
26         _____
27
28
```


Solution

```

def level_mutation(t, funcs):
    """Mutates t using the functions in the list funcs.

    >>> t = Tree(1, [Tree(2, [Tree(3)])])
    >>> funcs = [lambda x: x + 1, lambda y: y * 5, lambda z: z ** 2]
    >>> level_mutation(t, funcs)
    >>> t
    # funcs[0] was applied to the label 1, funcs[1] was applied to the label 2, and
    Tree(2, [Tree(10, [Tree(9)])])
    >>> t2 = Tree(1, [Tree(2), Tree(3, [Tree(4)])])
    >>> level_mutation(t2, funcs)
    >>> t2
    # (2 * 5) ** 2 = 100
    Tree(2, [Tree(100), Tree(15, [Tree(16)])])
    >>> t3 = Tree(1, [Tree(2)])
    >>> level_mutation(t3, funcs)
    >>> t3
    Tree(2, [Tree(100)])
    """
    if not funcs:
        return
    t.label = funcs[0](t.label)
    remaining = funcs[1:]
    if t.is_leaf() and remaining:
        for f in remaining:
            t.label = f(t.label)
    for b in t.branches:
        level_mutation(b, remaining)

```

As an extra challenge, try implementing `level_mutation_link`, which has the same behavior as `level_mutation` except it will take in a Linked List of functions `funcs` (rather than a Python list of functions).

Your Answer

```

1  def level_mutation_link(t, funcs):
2      if _____:
3          return
4      t.label = _____
5      remaining = _____
6      if _____ and _____:
7          while _____:
8              _____
9              remaining = remaining.rest
10     for b in t.branches:
11         _____
12
13
```

Solution

```

def level_mutation_link(t, funcs):
    if funcs is Link.empty:
        return
    t.label = funcs.first(t.label)
    remaining = funcs.rest
    if t.is_leaf() and remaining is not Link.empty:
        while remaining is not Link.empty:
            t.label = remaining.first(t.label)
            remaining = remaining.rest
    for b in t.branches:
        level_mutation(b, remaining)

```

Linked Lists

Q7: Multiply Links

Write a function that takes in a Python list of linked lists and multiplies them element-wise. It should return a new linked list.

If not all of the `Link` objects are of equal length, return a linked list whose length is that of the shortest linked list given. You may assume the `Link` objects are shallow linked lists, and that `lst_of_lns` contains at least one linked list.

Your Answer

```

1  def multiply_lns(lst_of_lns):
2      """
3      >>> a = Link(2, Link(3, Link(5)))
4      >>> b = Link(6, Link(4, Link(2)))
5      >>> c = Link(4, Link(1, Link(0, Link(2))))
6      >>> p = multiply_lns([a, b, c])
7      >>> p.first
8      48
9      >>> p.rest.first
10     12
11     >>> p.rest.rest.rest is Link.empty
12     True
13     """
14     # Implementation Note: you might not need all lines in this skeleton code
15     _____ = _____
16     for _____:
17         if _____:
18             _____
19             _____
20     _____
21     _____
22
23
```

Solution

```
def multiply_links(lst_of_links):
    """
    >>> a = Link(2, Link(3, Link(5)))
    >>> b = Link(6, Link(4, Link(2)))
    >>> c = Link(4, Link(1, Link(0, Link(2))))
    >>> p = multiply_links([a, b, c])
    >>> p.first
    48
    >>> p.rest.first
    12
    >>> p.rest.rest.rest is Link.empty
    True
    """
    # Implementation Note: you might not need all lines in this skeleton code
    product = 1
    for lnk in lst_of_links:
        if lnk is Link.empty:
            return Link.empty
        product *= lnk.first
    lst_of_links_rests = [lnk.rest for lnk in lst_of_links]
    return Link(product, multiply_links(lst_of_links_rests))
```

For our base case, if we detect that any of the lists in the list of `Link`s is empty, we can return the empty linked list as we're not going to multiply anything.

Otherwise, we compute the product of all the firsts in our list of `Link`s. Then, the subproblem we use here is the rest of all the linked lists in our list of `Links`. Remember that the result of calling `multiply_links` will be a linked list! We'll use the product we've built so far as the first item in the returned `Link`, and then the result of the recursive call as the rest of that `Link`.

Next, we have the iterative solution:

```

def multiply_links(lst_of_links):
    """
    >>> a = Link(2, Link(3, Link(5)))
    >>> b = Link(6, Link(4, Link(2)))
    >>> c = Link(4, Link(1, Link(0, Link(2))))
    >>> p = multiply_links([a, b, c])
    >>> p.first
    48
    >>> p.rest.first
    12
    >>> p.rest.rest.rest is Link.empty
    True
    """
    # Alternate iterative approach
    import operator
    from functools import reduce
    def prod(factors):
        return reduce(operator.mul, factors, 1)

    head = Link.empty
    tail = head
    while Link.empty not in lst_of_links:
        all_prod = prod([l.first for l in lst_of_links])
        if head is Link.empty:
            head = Link(all_prod)
            tail = head
        else:
            tail.rest = Link(all_prod)
            tail = tail.rest
        lst_of_links = [l.rest for l in lst_of_links]
    return head

```

The iterative solution is a bit more involved than the recursive solution. Instead of building the list **backwards** as in the recursive solution (because of the order that the recursive calls result in, the last item in our list will be finished first), we'll build the resulting linked list as we go along.

We use `head` and `tail` to track the front and end of the new linked list we're creating. Our stopping condition for the loop is if any of the `Link`s in our list of `Link`s runs out of items.

Finally, there's some special handling for the first item. We need to update both `head` and `tail` in that case. Otherwise, we just append to the end of our list using `tail`, and update `tail`.

Scheme

Q8: List Insert

Write a Scheme function that, when given an element, a list, and an index, inserts the element into the list at that index. You can assume that the index is in bounds for the list.

Your Answer

```
1 (define (insert element lst index)
2   'YOUR-CODE-HERE
3 )
4
5 (expect (insert 2 '(1 7 9) 2) (1 7 2 9))
6 (expect (insert 'a '(b c) 0) (a b c))
7
```

Solution

```
(define (insert element lst index)
  (if (= index 0)
      (cons element lst)
      (cons (car lst) (insert element (cdr lst) (- index 1))))
)

(expect (insert 2 '(1 7 9) 2) (1 7 2 9))
(expect (insert 'a '(b c) 0) (a b c))
```

Q9: Group by Non-Decreasing

Define a function `nondecreaselist`, which takes in a scheme list of numbers and outputs a list of lists, which overall has the same numbers in the same order, but grouped into lists that are non-decreasing.

For example, if the input is a stream containing elements

```
(1 2 3 4 1 2 3 4 1 1 1 2 1 1 0 4 3 2 1)
```

the output should contain elements

```
((1 2 3 4) (1 2 3 4) (1 1 1 2) (1 1) (0 4) (3) (2) (1))
```

Note: The skeleton code is just a suggestion; feel free to use your own structure if you prefer.

Your Answer

```

1  (define (nondecreaselist s)
2
3      (if _____
4          _____
5          (let ((rest _____))
6              (if _____
7                  (cons _____ rest)
8                  (cons _____ (cdr rest)))
9              )
10         )
11     )
12 )
13
14 (expect (nondecreaselist '(1 2 3 1 2 3)) ((1 2 3) (1 2 3)))
15
16 (expect (nondecreaselist '(1 2 3 4 1 2 3 4 1 1 1 2 1 1 0 4 3 2 1))
17         ((1 2 3 4) (1 2 3 4) (1 1 1 2) (1 1) (0 4) (3) (2) (1)))
18
```

Solution

```
(define (nondecreaselist s)

  (if (null? s)
      nil
      (let ((rest (nondecreaselist (cdr s))) )
          (if (or (null? (cdr s)) (> (car s) (car (cdr s))))
              (cons (list (car s)) rest)
              (cons (cons (car s) (car rest)) (cdr rest)))
          )
      )
  )

(expect (nondecreaselist '(1 2 3 1 2 3)) ((1 2 3) (1 2 3)))

(expect (nondecreaselist '(1 2 3 4 1 2 3 4 1 1 1 2 1 1 0 4 3 2 1))
        ((1 2 3 4) (1 2 3 4) (1 1 1 2) (1 1) (0 4) (3) (2) (1)))
```


Regex

Q10: Greetings

Let's say hello to our fellow bears! We've received messages from our new friends at Berkeley, and we want to determine whether or not these messages are *greetings*. In this problem, there are two types of greetings - salutations and valedictions. The first are messages that start with "hi", "hello", or "hey", where the first letter of these words can be either capitalized or lowercase. The second are messages that end with the word "bye" (capitalized or lowercase), followed by either an exclamation point, a period, or no punctuation. Write a regular expression that determines whether a given message is a greeting.

Your Answer

```
1  import re
2
3  def greetings(message):
4      """
5      Returns whether a string is a greeting. Greetings begin with either Hi, Hello, or
6      Hey (first letter either capitalized or lowercase), and/or end with Bye (first letter
7      either capitalized or lowercase) optionally followed by an exclamation point or period.
8
9      >>> greetings("Hi! Let's talk about our favorite submissions to the Scheme Art Contest")
10     True
11     >>> greetings("Hey I love Taco Bell")
12     True
13     >>> greetings("I'm going to watch the sun set from the top of the Campanile! Bye!")
14     True
15     >>> greetings("Bye Bye Birdie is one of my favorite musicals.")
16     False
17     >>> greetings("High in the hills of Berkeley lived a legendary creature. His name was")
18     False
19     >>> greetings('Hi!')
20     True
21     >>> greetings("bye")
22     True
23     """
24     return bool(re.search(_____, message))
25
26
```

Solution

```
import re

def greetings(message):
    """
    Returns whether a string is a greeting. Greetings begin with either Hi, Hello, or
    Hey (first letter either capitalized or lowercase), and/or end with Bye (first l
    either capitalized or lowercase) optionally followed by an exclamation point or ;

    >>> greetings("Hi! Let's talk about our favorite submissions to the Scheme Art Co
    True
    >>> greetings("Hey I love Taco Bell")
    True
    >>> greetings("I'm going to watch the sun set from the top of the Campanile! Bye
    True
    >>> greetings("Bye Bye Birdie is one of my favorite musicals.")
    False
    >>> greetings("High in the hills of Berkeley lived a legendary creature. His name
    False
    >>> greetings('Hi!')
    True
    >>> greetings("bye")
    True
    """
    return bool(re.search(r"^(?([Hh](ey|i|ello)\b))|(\b[bB]ye[!\.]?$)", message))
```

