BASIX	COMMITMENTS
CERTIFICATE NO. A235418_C	02
FIXTU	RES AND SYSTEMS
LIGHTING	MIN 40% OF NEW OR ALTERED LIGHT FIXTURES TO BE FITTED WITH FLUORESCENT, COMPACT FLUORESCENT OR LIGHT-EMITTING-DIODE (LED) LAMPS
WET AREAS: NEW OR ALTERED	SHOWER HEADS 3 STAR RATED TOILETS 3 STAR RATED TAPS 3 STAR RATED
INSUL	ATION REQUIREMENTS
FLOOR ABOVE EXISTING DWELLING OR BUILDING	NIL
EXTERNAL WALL: BRICK VENEER	RI.I6 (or RI.70 INCLUDING CONSTRUCTION)
EXTERNAL WALL: CAVITY BRICK	NIL
EXTERNAL WALL: FRAMED (WEATHERBOARD, FIBRO, METAL CLAD)	R1.30 (or R1.70 INCLUDING CONSTRUCTION)
FLAT CEILING, PITCHED ROOF	CEILING: R 2.50 (UP) ROOF: FOIL/ SARKING DARK (SOLAR ABSORPTANCE >0.70)
GLAZI	NG REQUIREMENTS
WINDOWS	
WI W2, W3, W4, W5, W6, W7, W8, \$ WIO,	STANDARD ALUMINIUM, SINGLE PYROLYTIC LOW-E, (OR U-VALUE: 5.7, SHGC:0.47)
SHAD	ING DEVICES
WINDOWS	
WI, W2, W3, W4, W5 \$ W6,	EAVE / VERANDAH / PERGOLA / BALCONY >= 450MM
W8	PROJECTION /HEIGHT ABOVE SILL RATIO >= 0.36
W7	EAVE / VERANDAH / PERGOLA / BALCONY >= 750MM
WIO	EAVE / VERANDAH / PERGOLA / BALCONY >= 900MM

EXTERNAL	PAINT	SCHEDULE

EXTERNAL FAMILY CONTEDUCE						
ITEM	BRAND eg. WATTYL	CODE	COLOUR			
Fascia Board			Deep Ocean			
Soffit Lining			Off White			
Wall Cladding			Viking Grey			
Gable Cladding			Viking Grey			
Cover Battens			Deep Ocean			
Wall Cladding - Bump Out			Viking Grey			


FINAL CONSTRUCTION.


SPFCI	FICATION SUMMARY	SPECIAL NOTES						
STRUCTURAL TIMBER - All to ASA 1 684.2			PROVIDE TWO (2) SMOKE DETECTORS AS SHOWN REUSE EXISTING SMOKE DETECTOR IF POSSIBLE - ELECTRICIAN TO CHECK					
WALLS: F5 SOFTWOOD 90 X 35 EXT. STUDS @ 70 X 35 INT. STUDS @	ROOF: ROOF TRUSSES .600 CTS TO MANUFACTURERS .600 CTS DETAILS @ .600 CTS	REUSE EXISTING SMOKE DETECTOR IF POSSIBLE - ELECTRICIAN TO CHECK FOR COMPLIANCE WITH THE BUILDING CODE OF AUSTRALIA (NCC). AS PER THE NCC - ALL WET AREA WINDOWS TO HAVE TOUGHENED GLASS. REMOVE THE EXISTING HOT WATER UNIT FROM ROOF SPACE. CONNECT/INSTALL THIRTY THREE (33) DOWNLIGHT FITTINGS, TWO (2) 3-IN-I FAN/LIGHT/HEATER UNITS & THREE (3) CEILING SWEEP FANS (AS SUPPLIED BY THE OWNER). PROVIDE A GAS BAYONET TO THE GROUND FLOOR LIVING ROOM						
FLOOR: Refer to Structu	ral Layouts. WIND LOAD W 28 N							
FINISHES		•	NSTALL OWNER SUPPLIED SHAVING CA THE FIRST FLOOR ENSUITE & BATHROO	BINETS & HEATE				
BRICKWORK	COMMON BRICKWORK TO PARTY WALL \$ COMMON BRICKWORK FOR RENDER AND PAINT FINISH ELSEWHERE.	'						
FLOORING	19MM STRUCTURAL PARTICLEBOARD							
CLADDING	CLADDING FIXED TO 20mm BATTENS OVER POLASTIC INSULATION BLANKET. 200mm WEATHERTEX "SMOOTH" CLADDING TO EXTERNAL WALLS ON NORTH ELEVATION BUMP OUT. FC SHEET WITH Ex. I 00x23 DAR TIMBER COVER BATTENS TO GABLE END.							
WINDOWS - STEGBAR KEYED LOCKS (TERRAIN: 3)	FRAME: PREFINISHED ALUMINIUM							
INSECT SCREENS: TO ALL NEW OPERABLE WINDOW SASHES	FRAME: PREFINISHED ALUMINIUM MESH: FIBREGLASS	WORKS BY OWNER REMOVAL \$ INSTALLATION OF T.V ANTENNA AS REQUIRED \$ CONNECTION TO NEW AND EXISTING TV POINTS.						
ROOF COVERING	TERRA COTTA ROOF TILES TO MATCH EXISTING AS CLOSE AS POSSIBLE, REUSE EXISTING TILES WHERE SHOWN.	PROVISION OF CUPBOARD TO LOBBY AREA AS SHOWN. PHONE AND/OR DATA CABLING IF REQUIRED. SUPPLY THIRTY THREE (33) DOWNLIGHT FITTINGS, TWO (2) 3-IN-I						
ROOF SARKING	FLAME RETARDANT DOUBLE SIDED ALUMINIUM FOIL	FAN/LIGHT/HEATER UNITS & THREE (3) CEILING SWEEP FANS. SUPPLY OF SHAVING CABINETS & HEATED TOWEL RAILS TO FIRST FEMALITE & BATTEROAM FOR INSTALLATION BY BUILDED.				FLOOR		
INSULATION (FIBREGLASS)	R3.0 BATTS TO FIRST FLOOR ADDITION CEILING AREA R2.0 BATTS TO FIRST FLOOR EXTERNAL WALL FRAMES R2.0 ACCOUSTIC BATTS TO BEDROOM INTERNAL WALLS I 2mm POLASTIC INSULATION BLANKET TO BED 2 'BUMP OUT' WALLS.	RELOCATION OF TV SATELITE DISH IF REQUIRED INCLUDING CONNECTION NEW & EXISTING T.V. POINTS. SUPPLY DECKING BOARDS FOR NEW STEP ADJACENT BIFOLD DOOR UIPPROVISION OF STORMWATER SYSTEM CONNECTED TO NEW & EXISTING						
INTERNAL FIXINGS	DAR: FINGER JOINTED PINE SKIRTING: Ex. I 50x25 "HALF SPLAYED" ARCHITRAVE: Ex. I 00x25 "SQUARE DRESSED"	ָ 	DOWNPIPES.					
INTERNAL DOORS	PRIMED HARDBOARD HOLLOW CORE 'FLUSH' TO LINEN \$ PRIMED HARDBOARD SOLID CORE "FLUSH" ELSEWHERE.	1	FINAL CONSTRUCTION		5.C.	17-03-16		
STAIRCASE MAPLE TREADS \$	TYPE: OPEN RISER	Н	TO CONTRACTS		S.C.	18-02-16		
STRINGERS	WIDTH: I OOOmm	G	CHECK PLAN		B.P.	09-02-16		
	RISE: 18 @ 182mm	F	AMENDED FOR COUNCIL		N.E.	11-12-15		
	GOING: 240mm (260mm TREAD)	E	BASIX ADDED \$ TO COUNCIL		N.E.	23-11-15		
FASCIA & BARGE	MATERIAL: DAR TIMBER	D	POV 17255		5.C.	03-11-15		
BOARDS BARGE TO PARTY WALL	MATERIAL: PREFINISHED ZINCALUME	С	TO CLIENT		N.L.	09-10-15		
DANGE TO FAIRTI WALL	COLOUR: DEEP OCEAN	В	POV 17002 \$ 17004 \$ SURVEY AD)UEU	-	28-09-15		
GUTTERS \$ DOWNPIPES	TYPE: OGEE	A No.	TECHNICAL ISSUE		A.M.	08-09-15		
	MATERIAL: PREFINISHED ALUMINIUM GUTTER COLOUR: DEEP OCEAN DOWNPIPE COLOUR: DEEP OCEAN		IGN CONSULTANT: DAREK SZYMANSKI		DRAWN	DATE		
HOT WATER UNIT	CONNECT TO EXISTING	PR	OPOSED ADDITIONS & ALTE	RATIONS				
PAINTING - REFER TO SPECIFICATION FOR THE EXTENT OF WORK	FIRST FLOOR EXTERNAL: BY CAPE COD FIRST FLOOR INTERNAL: BY CAPE COD	FO	R MR R & MRS N SEKE	L				
	PAINTING TO ALTERATION AND RENOVATION WORK TO BE BY THE OWNER	AT 4 GARRETT STREET MAROUBRA NSW 2035						
FINISHED GROUND LEVE CONDITIONS.	LS SHOWN ON PLAN ARE SUBJECT TO SITE	COL	JNCIL: RANDWICK					
DO NOT SCALE OFF DRA	WINGS.			A.B.N. 54 000	0 605 40	7		
ALL DIMENSIONS SHOW MEASURE DURING CONS	N ARE THEORETICAL ONLY AND ARE SUBJECT TO SITE STRUCTION.	(Cape Cod	SUITE 41, 410 NORTH PARRAI PHONE: (02) 9	MATTA 21	51		
	EN MADE FOR SHRINKAGE OR MILLING. GN AND PRINT IS THE PROPERTY OF CAPE COD AND IS		AUSTRALIA	BUILDERS LICE				

SHEET: 1 OF 8

JOB NO: 769 1/15

COPYRIGHT THIS DESIGN AND PRINT IS THE PROPERTY OF CAPE COD AND IS ISSUED FOR THE SOLE PURPOSE OF ENTERING INTO A BUILDING CONTRACT WITH THE COMPANY. IT MUST NOT BE USED OR REPRODUCED IN WHOLE OR IN PART WITHOUT WRITTEN PERMISSION FROM THE COMPANY.





Site Plan


No. : 4 Lot. : A

FOR: MR R & MRS N SEKEL


DP : 410431

AREA: 309.8m² (By Title) : 3 | 1.4m² (By Calc) HOLMES STREET

Legend











Ground Floor Plan

(4) Note: Existing ground floor eastern, northern \$ western external wall of kitchen/meals room to have smooth texture polymer render.









FOR: MR R & MRS N SEKEL

WINDOW SCHEDL	JLE (BASIX A2354	118 02)		CLIENT:		ALUMINIUM (STEGBAR) WIN	NDOWS:				
STANDARD NOTES:						STANDARD ALUMINIUM CC	LOURS: ANODISED CLEAR, AP STONE BEIGE, SURFMIST, WHI	O GREY, CUSTOM BLACK, TE BIRCH, WOODLAND			
	RE DRAWN AS VIEWED FROM	OUTSIDE		CLIENT:		GREY.	orone beioe, con mor, win	TE BIKGH, WOODE KID			
 ALL WINDOWS COME WIT WINDOW OPENINGS NOTI 	'H "KEYED ALIKE" LOCKS ED "R" HAVE RESTRICTED OPEN	IINGS TO COMPLY WITI	H THE	BUII DFR:	DATE:	CUSTOM COLOURS AVAILA	ABLE: DEEP OCEAN, HAMERSLE	Y BROWN, NOTRE DAME,			
NCC 3.9.2.5						POTTERY.			TERRAIN: 3 W	IND LOAD: W 28 N	
	(WI) ADH 1326	COLOUR	GLAZING		SPECIAL NOTES		WIO BDF 2122		GLAZING	SPECIAL NOTES	
		PEARL WHITE	SINGLE PYR LOW-E, (U-\		RESTRICT BOTTOM SASH OPENINGS TO 125mm TO COMPLY WITH NCC.				BINGLE PYROLYTIC OW-E, (U-VALUE:		
	N ELEVATION / BEDROOM I	INSECT SCREEN	5.7, SHGC:				W ELEVATION / LIVING		5.7, SHGC:0.47)		
	ALUMINIUM	ALUMINIUM FIBREGLASS MESH	DEL/EAL		RESTRICT TOP SASHES TO OPEN NO LOWER THAN 1700mm ABOVE FLOOR LEVEL.		ALUMINIUM	BY OWNER	E) (EA)		
	DOUBLE HUNG OPEN / FIXED / OPEN	PEARL WHITE	REVEAL I 40mm		-		BIFOLD OPEN / OPEN / OPEN		EVEAL 70mm		
		COLOUR	GLAZING		SPECIAL NOTES						
	(W2) AAW 0614	PEARL WHITE	SINGLE PYR		TRANSLUCENT FILM APPLIED BY BUILDER.						
	N ELEVATION / ENSUITE	INSECT SCREEN	LOW-E, (U-\ 5.7, SHGC:								
	ALUMINIUM	ALUMINIUM		,							
	AWNING	FIBREGLASS MESH PEARL WHITE	REVEAL								
	OPEN / OPEN		I 40mm								
	(W3) ADH 1308	COLOUR PEARL WHITE	GLAZING	ONEIG	SPECIAL NOTES RESTRICT TOP # BOTTOM SASH OPENING TO						
	N ELEVATION / BEDROOM 2	T LAKE WITH	SINGLE PYR LOW-E, (U-\	/ALUE:	125mm TO COMPLY WITH NCC.			_			
	ALUMINIUM	INSECT SCREEN	5.7, SHGC:	:0.47)							
	DOUBLE HUNG	ALUMINIUM FIBREGLASS MESH	REVEAL		-			-			
	OPEN OPEN	PEARL WHITE	I 40mm		-						
	(W4) ADH 1318	COLOUR	GLAZING		SPECIAL NOTES						
	(W4) ADH 1318	PEARL WHITE	SINGLE PYR		RESTRICT BOTTOM SASH OPENINGS TO 125mm TO COMPLY WITH NCC.						
	E ELEVATION / BEDROOM 2	INSECT SCREEN	LOW-E, (U-\ 5.7, SHGC:		12311111 TO COMILET WITH NCC.						
	ALUMINIUM	ALUMINIUM			RESTRICT TOP SASHES TO OPEN NO LOWER THAN 1700mm ABOVE FLOOR LEVEL.						
	DOUBLE HUNG OPEN / OPEN	FIBREGLASS MESH PEARL WHITE	REVEAL I 40mm		THAN 1700HIII ADOVE LEGGIC LEVEL.						
	OI EN / OI EN	COLOUR	GLAZING		SPECIAL NOTES						
	(W5) AAW 0608	PEARL WHITE	SINGLE PYR	OLYTIC	RESTRICT BOTTOM SASH OPENINGS TO	-					
	E ELEVATION / BATHROOM		LOW-E, (U-\	/ALUE:	I 25mm TO COMPLY WITH NCC.						
	ALUMINIUM	INSECT SCREEN ALUMINIUM	5.7, SHGC:	:0.47)	RESTRICT TOP SASHES TO OPEN NO LOWER						
	AWNING	FIBREGLASS MESH	REVEAL		THAN 1700mm ABOVE FLOOR LEVEL.						
	OPEN	PEARL WHITE	I 40mm								
	(W6) ADH 1318	COLOUR PEARL WHITE	GLAZING		SPECIAL NOTES						
	\bigcirc	- FLARL WIIIL	SINGLE PYR LOW-E, (U-\								
X	E ELEVATION / BEDROOM 3 ALUMINIUM	INSECT SCREEN	5.7, SHGC:								
	DOUBLE HUNG	ALUMINIUM FIBREGLASS MESH	REVEAL					\dashv \vdash			
	OPEN / OPEN	PEARL WHITE	I 40mm								
	(W7) AFW 2000	COLOUR	GLAZING		SPECIAL NOTES						
	(W7) AFW 2008	PEARL WHITE	SINGLE PYR LOW-E, (U-\								
	W ELEVATION / LOBBY	INSECT SCREEN	5.7, SHGC:								
	ALUMINIUM	N/A	T								
	FIXED		REVEAL I 40mm		-					_	
		COLOUR	GLAZING		SPECIAL NOTES						
	(W8) ADH 1315	PEARL WHITE	SINGLE PYR	OLYTIC	OF EGINE NOTES						
	W ELEVATION / LOBBY	INSECT SCREEN	LOW-E, (U-\ 5.7, SHGC:								
X	ALUMINIUM	ALUMINIUM	3.7, 51100.	.017)							
	DOUBLE HUNG	FIBREGLASS MESH PEARL WHITE	REVEAL								
	OPEN / OPEN	LINCE WITTE	I 40mm								
	(W9) DELETED				SPECIAL NOTES						
			_								
		1			†			1			
FOR: MRR & MRS	N SEKFI			AT: 4	GARRETT STREET MAROUBRA N	ISW 2035		SCALE. I. NITS	FET. 8 OF 8	OB NO: 7691/15 1	CapaCod