| BASIX | COMMITMENTS |
|---|--|
| CERTIFICATE NO. A256625_C | 03 |
| FIXTU | RES AND SYSTEMS |
| LIGHTING | MIN 40% OF NEW OR ALTERED LIGHT FIXTURES TO BE FITTED WITH FLUORESCENT, COMPACT FLUORESCENT OR LIGHT-EMITTING-DIODE (LED) LAMPS |
| WET AREAS: NEW OR ALTERED | SHOWER HEADS 3 STAR RATED TOILETS 3 STAR RATED TAPS 3 STAR RATED |
| INSUL | ATION REQUIREMENTS |
| FLOOR ABOVE EXISTING DWELLING OR BUILDING | NIL |
| EXTERNAL WALL: BRICK VENEER | R1.16 (or R1.70 INCLUDING CONSTRUCTION) |
| EXTERNAL WALL: EXTERNAL INSULATED FACADE SYSTEM (EIFS)(FACADE PANEL:75mm) | NIL |
| FLAT CEILING, PITCHED ROOF | CEILING: R 2.50 (UP) ROOF: FOIL/ SARKING DARK (SOLAR ABSORPTANCE >0.70) |
| GLAZI | NG REQUIREMENTS |
| WINDOWS | |
| W7, \$ W8 | STANDARD ALUMINIUM, SINGLE CLEAR, (OR U-VALUE: 7.63, SHGC: 0.75) |
| W3, W4, W6, \$ W9 | STANDARD ALUMINIUM, SINGLE PYROLYTIC LOW-E, (OR U-VALUE: 5.7, SHGC:0.47) |
| SHAD | ING DEVICES |
| WINDOWS | |
| W9 | PROJECTION /HEIGHT ABOVE SILL RATIO >= 0.23 |
| W3, W4, W6, W7, \$ W8 | EAVE / VERANDAH / PERGOLA / BALCONY >= 450MM |
| | |

FINAL CONS

| | FLOOR: 190x45mm MIN. FLOOR JOISTS WIND LOAD W 33 N | | | AS3700 AS SITE IS WITHIN 1KM OF OCEAN. CONNECT/INSTALL TWENTY TWO (22) DOWNLIGHT FITTINGS, ONE (1) HEATED TOWEL RAIL & ONE (1) 3-IN-1 FAN/LIGHT/HEATER UNIT (AS SUPPLIED BY THE OWNER). PROVIDE B/HEADS ONLY TO FIRST FLOOR ROBES. | | | | |
|------------|--|---|--|--|------------|----------|--|--|
| | FINISHES | | | | | | | |
| | BRICKWORK | COMMON BRICKWORK TO PARTY WALL (LAID AS FACE ABOVE NEIGHBOURS ROOF LINE) | PROVIDE CONTROL COCK TO MIXER TYPE TAPS. | | | | | |
| | FLOORING | I 9MM STRUCTURAL PARTICLEBOARD | | | | | | |
| | CLADDING | 75mm POLYSTYRENE WALL SHEETING OVER POLYSTYRENE CORE WALL INSULATION WITH APPLIED TEXTURE PAINT FINISH TO FIRST FLOOR \$ TIMBER WEATHERBOARD CLADDING TO NEW ADDITION GABLE | | | | | | |
| | WINDOWS - STEGBAR KEYED LOCKS (TERRAIN: 3) | FRAME: PREFINISHED ALUMINIUM | | | | | | |
| | INSECT SCREENS: TO ALL NEW OPERABLE WINDOW SASHES | FRAME: PREFINISHED ALUMINIUM MESH: FIBREGLASS | WORKS BY OWNER | | | | | |
| | ROOF COVERING | TERRA COTTA ROOF TILES TO MATCH EXISTING AS CLOSE AS POSSIBLE, REUSE EXISTING TILES WHERE SHOWN. | • C | REMOVAL \$ INSTALLATION OF T.V ANTENNA IF REQUIRED \$ CONNECTION NEW AND EXISTING TV POINTS. CONNECTION OF NEW COAXIAL CABLE "T.V.POINT" TO EXISTING AND/C NEW T.V. AFRIAL. | | | | |
| | ROOF SARKING | FLAME RETARDANT DOUBLE SIDED ALUMINIUM FOIL | | PHONE AND/OR DATA CABLING. SUPPLY TWENTY TWO (22) DOWNLIGHT FITTINGS, ONE (1) HEATED TO | | | | |
| | INSULATION (FIBREGLASS) | R3.0 BATTS TO FIRST FLOOR ADDITION CEILING AREA R2.0 BATTS TO FIRST FLOOR EXTERNAL WALL FRAMES I 2mm POLASTIC INSULATION BLANKET TO FIRST FLOOR EXTERNAL WALL FRAMES | • A | RAIL \$ ONE (1) 3-IN-1 FAN/LIGHT/HEATER UNIT. ALL WORKS ASSOCIATED WITH THE EXTENSION OF THE EXISTING GROUND FLOOR DECK. REMOVAL OF GROUND FLOOR BEDROOM SHELVES TO ALLOW FOR | | | | |
| STRUCTION. | INTERNAL FIXINGS | DAR: FINGER JOINTED PINE SKIRTING: Ex. I 50x25 BULLNOSE ARCHITRAVE: Ex. I 00x25 BULLNOSE | • A | PROPOSED W.I.R. • ALL WORKS ASSOCIATED WITH THE REMOVAL OF THE EXISTING HWU IN ROOF SPACE. | | | | |
| CTRUCT | INTERNAL DOORS | CORINTHIAN "BALMORAL-PBAL4" | | | | | | |
| 121. | STAIRCASE MDF TREADS \$ PINE RISERS MAPLE STRINGERS. | TYPE: CLOSED TIMBER WIDTH: 950mm | | | | | | |
| | MAFEL STRINGERS. | RISE: 18 @ 182mm GOING: 240mm (260mm TREAD) | | FINAL CONSTRUCTION | N.E. | 03-03-17 | | |
| | | | | TO CONTRACTS | 5.M. | 09-02-17 | | |
| | FASCIA \$ | MATERIAL: DAR TIMBER | F | PLAN CHECK | J.E. | 30-11-16 | | |
| | BARGE BOARDS | | | RE-DESIGN FOR COUNCIL | N.E. | 26-10-16 | | |
| | | | | BASIX ADDED \$ TO COUNCIL | N.E. | 09-08-16 | | |
| | GUTTERS & DOWNPIPES | TYPE: QUAD MATERIAL: PREFINISHED ZINCALUME GUTTER COLOUR: DUNE | С | CONSULTANTS CHECK PLAN | N.E. | 27-07-16 | | |
| | | | В | TO CLIENT | 5.C. | 15-07-16 | | |
| | | DOWNPIPE COLOUR: MONOLITH | | TECHNICAL | 5.C. | 30-06-16 | | |
| | HOT WATER UNIT | CONNECT TO EXISTING | | ISSUE | DRAWN | DATE | | |
| | | | DESIGN CONSULTANT: DAREK SZYMANSKI | | | | | |
| | PAINTING - REFER TO SPECIFICATION FOR THE EXTENT OF WORK | SPECIFICATION FOR FIRST FLOOR INTERNAL: BY OWNER | | PROPOSED ADDITIONS # ALTERATIONS | | | | |
| | | | | FOR MR C HOWELLS & MS E BYRON AT 49 YOUNG STREET, | | | | |
| | CONDITIONS. | | | CREMORNE, NSW 2090 | | | | |
| | ALL DIMENSIONS SHOW | DO NOT SCALE OFF DRAWINGS. ALL DIMENSIONS SHOWN ARE THEORETICAL ONLY AND ARE SUBJECT TO SITE | | COUNCIL: NORTH SYDNEY | | | | |
| | MEASURE DURING CONSTRUCTION. | | | A.B.N. 54 (| 000 605 40 | 7 | | |

NO ALLOWANCE HAS BEEN MADE FOR SHRINKAGE OR MILLING.

COPYRIGHT THIS DESIGN AND PRINT IS THE PROPERTY OF CAPE COD AND IS

ISSUED FOR THE SOLE PURPOSE OF ENTERING INTO A BUILDING CONTRACT WITH THE COMPANY, IT MUST NOT BE USED OR REPRODUCED IN WHOLE OR IN PART WITHOUT WRITTEN PERMISSION FROM THE COMPANY.

SPECIFICATION SUMMARY

STRUCTURAL TIMBER - All to ASA 1684.2

ROOF: ROOF TRUSSES

TO MANUFACTURERS

DETAILS @ .600 CTS

WALLS: F5 SOFTWOOD

90 X 35 EXT. STUDS @ .600 CTS 70 X 35 INT. STUDS @ .600 CTS

SPECIAL NOTES

PROVIDE TWO (2) SMOKE DETECTORS AS SHOWN-9-

WITH THE BUILDING CODE OF AUSTRALIA (NCC).

AS3700 AS SITE IS WITHIN I KM OF OCEAN.

ELECTRICIAN TO CHECK/ENSURE THE EXISTING SMOKE DETECTORS COMPLY

AS PER THE NCC - ALL WET AREA WINDOWS TO HAVE TOUGHENED GLASS.

• PROVIDE MARINE GRADE BRICKS, MORTAR AND TIES IN ACCORDANCE WITH

A.B.N. 54 000 605 407

BUILDERS LICENCE NO. 5519

JOB NO: 7775/16

Cape Cod Suite 41, 410 CHURCH STREET, NORTH PARRAMATTA 2151 PHONE: (02) 9849 4444

AUSTRALIA


SHEET: 1 OF 8


Η


EXTERNAL PAINT SCHEDULE


| ITEM | BRAND eg. WATTYL | CODE | COLOUR |
|--------------------------|---------------------|------|-----------|
| Barge Board | Dulux | | Domino |
| Fascia Board | Dulux | | Domino |
| Barge Board - Party Wall | Dulux | | Domino |
| Soffit Lining | Haymes | | Off White |
| Gable Cladding | Haymes | | Off White |
| Wall Cladding | Colorbond | | Dune |
| | | | |
| | | | |
| | | | |

















FOR: MR C HOWELLS & MS E BYRON

| WINDOW SCHED | OULE (BASIX A2566 | S25_03) | CLIENT | ſ: | | | | | | |
|--|-----------------------------------|--------------------------------|--------------------------------------|--|--------------|------------------|-----------------|--|-------|--|
| STANDARD NOTES: | | | | | | | | | | |
| WINDOWS AND DOORS ALL WINDOWS COME W | ARE DRAWN AS VIEWED FROM | OUTSIDE | CLIENT | Γ: | | | | | | |
| WINDOW OPENINGS NO. | TED "R" HAVE RESTRICTED OPEN | NINGS TO COMPLY WITH | H THE BUILDI | ER:DATE: | | | | | | |
| NCC 3.9.2.5 | T 🔿 | 1 | | | | | TERRAIN: 3 WI | IND LOAD: W 33 N | | |
| | (WI) DELETED | | | | _ | | | | | |
| | | | _ | | | | | | | |
| | | | - | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | (W2) DELETED | | | | - | | | | | |
| | | | | | | | | | | |
| | | | - | | | | | | | |
| | | | | | |] [| | 1 | | |
| | | | | | | | | | | |
| | (W3) AAW 0615 | COLOUR PEARL WHITE | GLAZING SINGLE PYROLYTIC | SPECIAL NOTES | - | | | | | |
| | W ELEVATION / STAIRS | | LOW-E, (U-VALUE: | | | | | | | |
| | ALUMINIUM | INSECT SCREEN ALUMINIUM | 5.7, SHGC:0.47) | | | | | | | |
| | AWNING | FIBREGLASS MESH PEARL WHITE | REVEAL | | | | | | | |
| | OPEN / OPEN | | I 40mm | | | | | | | |
| | (W4) ADDH 1218 | COLOUR PEARL WHITE | GLAZING SINGLE PYROLYTIC | SPECIAL NOTES RESTRICT BOTTOM SASH OPENINGS TO | | | | | | |
| | E ELEVATION / BEDROOM 3 | | LOW-E, (U-VALUE: 5.7, SHGC:0.47) | 1 25mm TO COMPLY WITH NCC. | | | | | | |
| X | ALUMINIUM | ALUMINIUM | 3.7, 31190.0.47) | | | 1 | | | | |
| | DOUBLE HUNG | | REVEAL | | | | |] | | |
| | OPEN / OPEN | | 1 40mm | | | | | | | |
| | (W5) DELETED | | | | - | | | | | |
| | | | - | | | | | | | |
| | | | | | | | | | | |
| | | | | | | - | | | | |
| | | COLOUR | GLAZING | | | | | | | |
| | (WG) ADH 1208 | PEARL WHITE | SINGLE PYROLYTIC | TRANSLUCENT FILM BY BUILDER. | 1 | | | | | |
| | E ELEVATION / BATH | INSECT SCREEN | LOW- E, (U-VALUE: 4.48, SHGC: 0.46 | : S) | |] | | | | |
| | ALUMINIUM | ALUMINIUM | | | | | | _ | | |
| _ | DOUBLE HUNG OPEN | FIBREGLASS MESH | REVEAL 140mm | _ | | | | - | | |
| | | COLOUR | GLAZING | | | | | | | |
| | (W7) AAW 0612 | PEARL WHITE | SINGLE CLEAR, (U-VALUE: 7.63, | TRANSLUCENT FILM BY BUILDER. | | | | | | |
| | S ELEVATION / BATH | INSECT SCREEN | SHGC: 0.75) | | | | | | | |
| | ALUMINIUM | ALUMINIUM FIBREGLASS MESH | REVEAL | | | - | | | | |
| | AWNING OPEN | TIBICEGE (GG IVIZOTI | I 40mm | | | | | | | |
| | (W8) AAW 0612 | COLOUR | GLAZING | | | | | | | |
| | | PEARL WHITE | SINGLE CLEAR, (U-VALUE: 7.63, | RESTRICT OPENING TO 125mm TO COMPLY WITH NCC. | | _ | | | | |
| | S ELEVATION / BEDROOM 4 ALUMINIUM | INSECT SCREEN | SHGC: 0.75) | | | | | | | |
| | | ALUMINIUM FIBREGLASS MESH | REVEAL | | | | | - | | |
| | AWNING OPEN | | I 40mm | | | | | 1 | | |
| | (W9) ADDH 1218 | COLOUR | GLAZING | | | | | | | |
| | | PEARL WHITE | SINGLE PYROLYTIC LOW-E, (U-VALUE: | RESTRICT BOTTOM SASH OPENINGS TO 125mm TO COMPLY WITH NCC. | | - | | | | |
| | W ELEVATION / BEDROOM 4 ALUMINIUM | INSECT SCREEN | 5.7, SHGC:0.47) | | | | | | | |
| | DOUBLE HUNG | ALUMINIUM FIBREGLASS MESH | REVEAL | | | 1 | | | | |
| | OPEN / OPEN | | I 40mm | | | | | | | |
| FOR: MR C HOWE | ELLS & MS E BYRON | _ | AT | : 49 YOUNG STREET, CREMORNE, N | ISW 2090 | CALE: 1: NTS ISH | HEET: 8 OF 8 10 | DB NO: 7775/16 | H Car | |