

Hazardous Substance, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Peel Away 1

Synonyms: Mancode
Peel Away 1 PA1

Recommended use: Paint remover; for the removal of multiple layers of common old paints

Supplier: Haymes Paints **ABN:** 14 004 201 638

Street Address: Waringa Drive, Wendouree Industrial Park

Wendouree, VIC 3355

Australia

Telephone: (03) 5342-6200 **Facsimile:** (03) 5342-6200

Emergency telephone number: (03) 5342-6200 (Mon – Fri, 7:30 am – 5:30, AEST)

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word

Danger

Hazard Classification

Corrosive to Metals – Category 1 Skin Corrosion/Irritation – Category 1B Serious Eye Damage/Irritation – Category 1 Sensitisation – Respiratory – Category 1

Specific Target Organ Toxicity (Single Exposure) - Category 3

Hazard Statement(s)

H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation

Prevention Precautionary Statement(s)

P102 Keep out of reach of children P103 Read label before use

P234 Keep only in original container

P260 Do not breathe dust, fume, gas, mist, vapours or spray P261 Avoid breathing dust, fume, gas, mist, vapours or spray

P264 Wash hands, face and all exposed skin thoroughly after handling

P271 Use only outdoors or in a well-ventilated area

P280 Wear protective clothing, gloves, eye/face protection and suitable respirator

Product name: Peel Away 1 Substance Key: HAY0000301 Issued: 13 June 2015 Version: 1.0 Page: 1 of 8



Response Precautionary Statement(s)

P101 If medical advice is needed, have product container or label at hand

P310 Immediately call a POISON CENTER or doctor/physician P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if

present and easy to do - continue rinsing

P363 Wash contaminated clothing before reuse

Storage Precautionary Statement(s)

P405 Store locked up

P406 Store in a corrosive resistant container with a resistant inner liner P403+233 Store in a well ventilated place. Keep container tightly closed

Disposal Precautionary Statement(s)

P501 Dispose of contents/container in accordance with local, regional, national and international

regulations

Poisons Schedule (Aust): S6

DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Class: 8 Corrosive

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Calcium hydroxide Sodium hydroxide Ingredients determined to be non-hazardous	1305-62-0 1310-73-2 -	30-40% 5-15% Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin contact: For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Product name: Peel Away 1 Substance Key: HAY0000301 Issued: 13 June 2015 Version: 1.0 Page: 2 of 8



Eye contact: Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Get to a doctor or hospital quickly.

PPE for First Aiders: Wear overalls, safety glasses and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Can cause corneal burns.

5. FIRE-FIGHTING MEASURES

Hazchem Code: 2X

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Non-combustible material.

Fire fighting further advice: On decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: 37

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat. Keep containers closed when not in use - check regularly for spills.

Product name: Peel Away 1 Substance Key: HAY0000301 Issued: 13 June 2015 Version: 1.0 Page: 3 of 8



This material is classified as a Dangerous Good Class 8 Corrosive as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison S6 and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

However for:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Sodium hydroxide	-	10	Peak Limitation		-
Calcium hydroxide	-	5	-	-	-

As published by the Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15-minute period, which should not be exceeded at any time during a normal eight-hour workday.

Peak Limitation - a ceiling concentration that should not be exceeded over a measurement period, which should be as short as possible, but not exceeding 15 minutes.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use.

Personal protection equipment: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Product name: Peel Away 1 Substance Key: HAY0000301 Issued: 13 June 2015 Version: 1.0 Page: 4 of 8



Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid contact with skin and eyes. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: White viscous paste

Solubility: Soluble in water

Specific Gravity (25 °C): 1.4 **Relative Vapour Density (air=1):** N App Vapour Pressure (20 °C): N App Flash Point (°C): N App Flammability Limits (%): N App **Autoignition Temperature (°C):** N App Melting Point/Range (°C): N App **Boiling Point/Range (°C):** N App 13-14 pH: **Viscosity:** N App Total VOC (g/Litre): N App

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material is an irritant to mucous membranes and respiratory tract. A respiratory sensitiser. Can cause possible allergic reactions.

Skin contact: Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns.

Ingestion: Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.

Product name: Peel Away 1 Substance Key: HAY0000301 Issued: 13 June 2015 Version: 1.0 Page: 5 of 8



Eye contact: A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

Acute toxicity

Inhalation: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >20 mg/L

Skin contact: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

Ingestion: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

Corrosion/Irritancy: Eye: this material has been classified as a Category 1 Hazard (irreversible effects to eyes). Skin: this material has been classified as a Category 1 Hazard (corrosive to skin).

Sensitisation: Inhalation: this material has been classified as a Category 1 Hazard (respiratory sensitiser). Skin: this material has been classified as not a respiratory sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

Long-term aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

Product name: Peel Away 1 Substance Key: HAY0000301
Issued: 13 June 2015 Version: 1.0 Page: 6 of 8



13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

UN No: 3262

Dangerous Goods Class: 8

Packing Group: II

Hazchem Code: 2X

Emergency Response Guide No: 37

Proper Shipping Name: CORROSIVE SOLID, BASIC, INORGANIC, N.O.S (SODIUM HYDROXIDE,

CALCIUM HYDROXIDE)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2), radioactive substances (Class 7) or food and food packaging in any quantity, however exemptions may apply. Note that concentrated strong alkalis are incompatible with concentrated strong acids.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 3262

Dangerous Goods Class: 8

Packing Group: ||

Proper Shipping Name: CORROSIVE SOLID, BASIC, INORGANIC, N.O.S (SODIUM HYDROXIDE,

CALCIUM HYDROXIDE)

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 3262

Dangerous Goods Class: 8

Packing Group: ||

Proper Shipping Name: CORROSIVE SOLID, BASIC, INORGANIC, N.O.S (SODIUM HYDROXIDE,

CALCIUM HYDROXIDE)

Product name: Peel Away 1 Substance Key: HAY0000301
Issued: 13 June 2015 Version: 1.0 Page: 7 of 8



15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

Basic solutions or bases in solid form

This material/constituent(s) is covered by the following requirements:

- The Standard for the *Uniform Scheduling of Medicines and Poisons (SUSMP*) established under the *Therapeutic Goods Act (Commonwealth*).
- All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Literary reference

Reason(s) For Issue: First Issue

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Haymes Paints cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: Peel Away 1 Substance Key: HAY0000301 Issued: 13 June 2015 Version: 1.0 Page: 8 of 8