

## SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

#### 1.1 Product identifier

Product name	COLOURPYNE® PARTICLEBOARD LPM MR
Synonym(s)	COLOURPYNE® E0 MOISTURE RESISTANT PYNEBOARD • COLOURPYNE® E0 MR PYNEBOARD • COLOURPYNE® E1 MOISTURE RESISTANT PYNEBOARD • COLOURPYNE® E1 MR PYNEBOARD • COLOURPYNE® MOISTURE RESISTANT PYNEBOARD • COLOURPYNE® MR PYNEBOARD • COLOURPYNE® PYNEBOARD MR • PYNEBOARD® WHITE E0 MOISTURE RESISTANT • PYNEBOARD® WHITE E0 MR • PYNEBOARD® WHITE E0 MR PARTICLEBOARD • PYNEBOARD® WHITE E1 MOISTURE RESISTANT • PYNEBOARD® WHITE E1 MOISTURE RESISTANT PARTICLEBOARD • PYNEBOARD® WHITE E1 MR • PYNEBOARD® WHITE E1 MR PARTICLEBOARD • PYNEBOARD® WHITE MOISTURE RESISTANT • PYNEBOARD® WHITE MOISTURE RESISTANT PARTICLEBOARD • PYNEBOARD® WHITE MR • PYNEBOARD® WHITE MR PARTICLEBOARD • PYNEPANEL MOISTURE RESISTANT • PYNEPANEL MR • PYNEPANEL THICK EDGE MOISTURE RESISTANT • PYNEPANEL THICK EDGE MR

#### 1.2 Uses and uses advised against

Use(s)	BUILDING BOARD • CABINETS • DOOR FACINGS • FURNITURE
--------	--

#### 1.3 Details of the supplier of the product

Supplier name	CARTER HOLT HARVEY WOODPRODUCTS AUSTRALIAN GROUP OF COMPANIES
Address	22 Prospect St, Box Hill, Victoria, 3128, AUSTRALIA
Telephone	132 321
Fax	1800 891 881
Email	<a href="mailto:enquiriesaus@chhwoodproducts.com.au">enquiriesaus@chhwoodproducts.com.au</a>
Website	<a href="http://www.chhwoodproducts.com.au">www.chhwoodproducts.com.au</a>

#### 1.4 Emergency telephone number(s)

Emergency	132 321
-----------	---------

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### 2.2 Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

#### 2.3 Other hazards

No information provided.

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

#### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
PARAFFIN WAX	8002-74-2	232-315-6	<2%
DYE(S)	-	-	<0.1%
WOOD(S) (SOFTWOOD/HARDWOOD)	-	-	>70%
MELAMINE/UREA/FORMALDEHYDE RESIN	25036-13-9	607-497-9	<15%
MOISTURE	-	-	5 to 13%
PAPER	-	-	<2%

**PRODUCT NAME COLOURPYNE® PARTICLEBOARD LPM MR**

MELAMINE FORMALDEHYDE RESIN	9003-08-1	-	<1%
UREA-FORMALDEHYDE RESIN	9011-05-6	-	<1%

---

**4. FIRST AID MEASURES**

---

**4.1 Description of first aid measures**

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). Due to product form and application, ingestion is considered unlikely.
<b>First aid facilities</b>	None allocated.

**4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

**4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

---

**5. FIRE FIGHTING MEASURES**

---

**5.1 Extinguishing media**

Dry agent, carbon dioxide, foam or water fog. Prevent contamination of drains and waterways.

**5.2 Special hazards arising from the substance or mixture**

Combustible. May evolve toxic gases (carbon/ nitrogen oxides, ammonia, formaldehyde, hydrocarbons) when heated to decomposition. May evolve hydrogen cyanide gas when heated to decomposition.

**5.3 Advice for firefighters**

Dry wood dust in high concentrations-in-air and at the temperatures > 204°C ( >40g of dust per m³ of air) may spontaneously explode. Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

**5.4 Hazchem code**

None allocated.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

**6.2 Environmental precautions**

Prevent product from entering drains and waterways.

**6.3 Methods of cleaning up**

If spilt, collect and reuse where possible.

**6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

**7. HANDLING AND STORAGE**

---

**7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry area.

### 7.3 Specific end use(s)

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Formaldehyde	SWA (AUS)	1	1.2	2	2.5
Paraffin wax (fume)	SWA (AUS)	--	2	--	--
Wood dust (certain hardwoods such as beech & oak)	SWA (AUS)	--	1	--	--
Wood dust (soft wood)	SWA (AUS)	--	5	--	10

### Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

### PPE

<b>Eye / Face</b>	If cutting or sanding with potential for dust generation, wear dust-proof goggles.
<b>Hands</b>	Wear leather gloves.
<b>Body</b>	Not required under normal conditions of use.
<b>Respiratory</b>	If cutting or sanding with potential for dust generation, wear a Class P1 (Particulate) respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	PRESSED BOARDS
<b>Odour</b>	SLIGHT ODOUR
<b>Flammability</b>	COMBUSTIBLE
<b>Flash point</b>	NOT AVAILABLE
<b>Boiling point</b>	NOT AVAILABLE
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT AVAILABLE
<b>pH</b>	NOT AVAILABLE
<b>Vapour density</b>	NOT AVAILABLE
<b>Specific gravity</b>	NOT AVAILABLE
<b>Solubility (water)</b>	INSOLUBLE
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	NOT AVAILABLE
<b>Lower explosion limit</b>	NOT AVAILABLE
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	> 200°C
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT AVAILABLE

### 9.2 Other information

<b>Density</b>	500 kg/m <sup>3</sup> to 800 kg/m <sup>3</sup>
----------------	--

## 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

No information provided.

### 10.6 Hazardous decomposition products

May evolve toxic gases (carbon/ nitrogen oxides, ammonia, formaldehyde, hydrocarbons) when heated to decomposition.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

**Acute toxicity** This product is generally considered to be of low toxicity, however over exposure to dust should be avoided.

Information available for the ingredient(s):

Ingredient	Oral Toxicity (LD50)	Dermal Toxicity (LD50)	Inhalation Toxicity (LC50)
MELAMINE FORMALDEHYDE RESIN	3161 mg/kg (rat)	--	--

<b>Skin</b>	Not classified as a skin irritant. Prolonged or repeated contact with dusts may be abrasive and mildly irritating to the skin.
<b>Eye</b>	Not classified as an eye irritant. However, dusts may be abrasive and irritating to the eyes.
<b>Sensitisation</b>	Not classified as causing skin or respiratory sensitisation. Contains formaldehyde which is known to cause skin sensitisation, at levels below that required for classification.
<b>Mutagenicity</b>	Not classified as a mutagen.
<b>Carcinogenicity</b>	Not classified as a carcinogen. However, repeated exposure to wood dust may result in nasal and paranasal sinus cancers (IARC Group 1). Adverse health effects are usually associated with long-term exposure to high dust levels. This product is bonded by formaldehyde resin and formaldehyde may be released during machining. Formaldehyde is classified as a confirmed human carcinogen (IARC Group 1).
<b>Reproductive</b>	Not classified as a reproductive toxin.
<b>STOT - single exposure</b>	Not classified as causing organ damage from single exposure. An inhalation hazard is not anticipated unless cut, drilled or sanded with dust generation, which may result in irritation of the nose and throat.
<b>STOT - repeated exposure</b>	Not classified as causing organ damage from repeated exposure.
<b>Aspiration</b>	This product does not present an aspiration hazard.

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

No information provided.

### 12.2 Persistence and degradability

No information provided.

### 12.3 Bioaccumulative potential

No information provided.

### 12.4 Mobility in soil

No information provided.

### 12.5 Other adverse effects

No information provided.

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

<b>Waste disposal</b>	Reuse where possible. Not regulated as a hazardous waste by Australian environmental authorities. Off-cuts and general waste material should be placed in containers and disposed of at approved landfill sites or burnt in an approved furnace or incinerator in accordance with disposal authority guidelines. Do not burn in barbeques, combustion stoves or open fires in the home as irritating gases may be evolved.
<b>Legislation</b>	Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

### NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	None allocated.	None allocated.	None allocated.
<b>14.2 Proper Shipping Name</b>	None allocated.	None allocated.	None allocated.
<b>14.3 Transport hazard class</b>	None allocated.	None allocated.	None allocated.
<b>14.4 Packing Group</b>	None allocated.	None allocated.	None allocated.

### 14.5 Environmental hazards

No information provided.

### 14.6 Special precautions for user

<b>Hazchem code</b>	None allocated.
---------------------	-----------------

## 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>Poison schedule</b>	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
<b>Classifications</b>	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.  The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].
<b>Hazard codes</b>	None allocated.
<b>Risk phrases</b>	None allocated.
<b>Safety phrases</b>	None allocated.
<b>Inventory listing(s)</b>	<b>AUSTRALIA: AICS (Australian Inventory of Chemical Substances)</b> All components are listed on AICS, or are exempt.

## 16. OTHER INFORMATION

<b>Additional information</b>	The dust generated from this product is hazardous according to the criteria of Safe Work Australia. Early fire hazard properties when tested to AS/NZS 1530 Part 3: Ignitability index: 14 - 16 Spread of flame index: 7 - 8 Heat evolved index: 6 - 10 Smoke developed index: 3 - 4  RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.
-------------------------------	---

**COMBUSTIBLE - EXPLOSIVE CARBONACEOUS DUST:** Carbonaceous/organic dusts have the potential, with dispersion, to present an explosion hazard if an ignition source exists. All equipment used to handle, transfer or store this product **MUST BE** cleaned thoroughly prior to cutting, welding, drilling or exposure to any other form of heat or ignition sources. If bulk stored, containers should be ventilated on a routine basis to avoid vapour accumulation (where applicable, eg for flocculants).

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmt.com.au](http://www.rmt.com.au)

**[ End of SDS ]**