

Fresh Start

Safe Work Method Statement

version 1.0

Activity / Task: **Carpenter**

Project / Location: All Jobs

Company: Fresh Start

Signed by: Chris Moerman

Date: 09/11/2015

Principle Contractor: Cape Cod

Accepted by: Robert Moerman

Date: 10/11/2015

Steps	Potential Hazards	Controls / Responsible Person(s)
1. Access to site	<ul style="list-style-type: none">● Slips, trips, falls and accessibility.● UV light / weather exposure.	<ul style="list-style-type: none">● Site specific induction. By: Fresh Start● All "workers" to register before entering the site; to read the General Construction Safety Plan signage; and to read the Site Specific Risk Assessment form. By: Fresh Start● Tool box talk to highlight any WHS concerns relative to the site. By: Fresh Start● Ensure that the site and work place access is unobstructed. By: Principle Contractor & Fresh Start● Ensure all weather access to work areas. By: Fresh Start● Wear appropriated PPE - hat, long sleeves, sun screen, sunglasses, and fluids and reduce exposure where possible. By: Fresh Start● Provision of designated waste areas. By: Fresh Start● Storage of materials in designated areas. By: Fresh Start● Provide and maintain barricades to all materials stored on footpath and on site. By: Principle Contractor● Regular site clean ups. By: Principle Contractor & Fresh Start
2. Unloading plant, equipment and tools	<ul style="list-style-type: none">● Manual task injuries● Slips, trips and falls.● Proximity of other "workers".● Public access.	<ul style="list-style-type: none">● Team lifting and carrying. By: Fresh Start● Training of "workers" in correct lifting methods. By: Fresh Start● Unload and move the plant and equipment to designated area to keep footpath / work place access clear. By: Fresh Start
3. Setting up equipment	<ul style="list-style-type: none">● Manual task injuries● Slips, trips and falls.● Proximity of other "workers".● Public access.	<ul style="list-style-type: none">● Set up in a clear area and maintain a clear travel path. By: Fresh Start● Training of "workers" in setting up of electrical leads, power tools and nail guns. By: Fresh Start● Ensure the proper use of all safety guards provided. By: Fresh Start● Ensure that all power tools and electrical leads have current tagging. By: Fresh Start● Ensure that all power tools are attached to a residual current device [RCD]. By: Fresh Start
4. Setting up access ramp	<ul style="list-style-type: none">● Slips, trips, falls and accessibility.● Fall from height● Manual task injuries● Proximity of other "workers".● Public access.	<ul style="list-style-type: none">● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start● Team lifting and carrying. By: Fresh Start● Training of "workers" in correct lifting and carrying methods. By: Fresh Start● Ensure that workers have protective footwear and gloves. By: Fresh Start● Check the ladder for damage / defects before use. By: Fresh Start● Check that the ladder is stable and secured top and bottom before use. By: Fresh Start● Install handrail and ensure adequate bracing to ramp. By: Fresh Start● Provide a gate to the ramp with warning signage. By: Fresh Start
5. Stripping of existing roof frame and covering	<ul style="list-style-type: none">● Slips, trips, falls and accessibility.● UV light / weather exposure● Fall from height.● Hazardous materials.● Identification of services.	<ul style="list-style-type: none">● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start● Identify any products or materials that may contain asbestos [ACM]. By: Principle Contractor● Identify services and make sure all electrical, gas, water and sewerage services have been isolated or safely relocated before commencing. By: Fresh Start● Use Licensed Electrician and Plumber to isolate, disconnect and relocate existing services. By: Principle Contractor● Training of "workers" in safe working at heights and safe movement on roof. By: Fresh Start● Provide "Demolition in Progress" and "Restricted Access" warning signage. By: Principle Contractor

	<ul style="list-style-type: none"> ● Electrocution ● Gas explosions ● Falling objects ● Exposure to dust ● Exposure to noise ● Manual task injuries ● Sprains and strains ● Cuts and abrasions ● Proximity of other “workers”. ● Public access. 	<ul style="list-style-type: none"> ● Establish a “No access area” below overhead work areas by barricading to prevent access to the area of work. Provide a spotter where necessary. By: Fresh Start ● Ensure that the scaffolding is safe and erected by a qualified Scaffolder. By: Principle Contractor ● Ensure that the perimeter protection is in place [scaffolding and edge protection] before commencing By: Fresh Start ● Check the access ladder for damage / defects before use. By: Fresh Start ● Check that the ladder is stable and secured top and bottom before use. By: Fresh Start ● Correct use of access ladder. By: Fresh Start ● Limit use of ladders as working platforms. By: Fresh Start ● Use appropriate PPE - safety glasses, footwear, noise / hearing protection, dust protection [disposable], gloves and hard hats. By: Fresh Start ● Systematic safe removal of materials. By: Fresh Start ● Team lifting and carrying. By: Fresh Start ● Ensure that the stairwell and openings / voids in floor are covered. By: Fresh Start ● Ensure all roof tarps are tied down and not weighted with tiles. By: Principle Contractor & Fresh Start ● Ensure that materials are not stored on roof or scaffold. By: Fresh Start ● Provide a chute for materials into designated waste area as required. Provide a ‘spotter’ where necessary. By: Fresh Start ● Provide shade cloth around work area and wet down dust as required to prevent wind borne dust. By: Principle Contractor ● Storage of materials in designated waste area. By: Fresh Start ● Regular site clean ups. By: Principle Contractor
6. Cut out existing roof structure	<ul style="list-style-type: none"> ● Slips, trips, falls and accessibility ● Fall from height ● Sharp and penetrating objects ● Manual task injuries ● Exposure to dust ● Exposure to noise ● Proximity of other “workers”. ● Public access. 	<ul style="list-style-type: none"> ● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start ● Identify that the electrical services have been isolated and that ‘tiger tails’ are in place as protection from overhead wires and points of attachment before commencing installation work. By: Principle Contractor & Fresh Start ● Training of “workers” in safe working at heights and safe movement on roof. By: Fresh Start ● Provide “Demolition in Progress” and “Restricted Access” warning signage. By: Principle Contractor ● Establish a “No access area” below overhead work areas by barricading to prevent access to the area of work. Provide a spotter where necessary. By: Principle Contractor ● Ensure that the perimeter protection is in place [scaffolding and edge protection] before commencing. By: Principle Contractor ● Check the access ladder for damage / defects before use By: Fresh Start ● Check that the ladder is stable and secured top and bottom before use. By: Fresh Start ● Correct use of access ladder. By: Fresh Start ● Limit use of ladders as working platforms. By: Fresh Start ● Use appropriate PPE - safety glasses, footwear, noise / hearing protection, dust protection [disposable], gloves, and hard hats. By: Fresh Start ● Training of “workers” in safe use of power tools, chain saws and reciprocating saws. By: Fresh Start ● Ensure all power tools have working safety guards. By: Fresh Start ● Systematic safe removal of materials. By: Principle Contractor & Fresh Start ● Ensure that correct lifting and carrying techniques are used. By: Fresh Start ● Ensure that the existing stairwell and openings in floor are covered and / or protected by guard rails. By: Principle Contractor ● Ensure that materials are not stored on roof or scaffold. By: Fresh Start ● Ensure that all exposed nails are removed. By: Fresh Start ● Storage of materials in designated waste areas. By: Fresh Start ● Regular site clean ups. By: Principle Contractor
7. Carry materials up ramp - Installation of floor platform members	<ul style="list-style-type: none"> ● Slips, trips, falls and accessibility. ● UV light / weather exposure ● Fall from height. ● Manual task injuries ● Exposure to dust. ● Exposure to noise. ● Proximity of other “workers”. ● Public access 	<ul style="list-style-type: none"> ● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start ● Identify that the electrical service has been isolated and that ‘tiger tails’ are in place as protection from overhead wires and points of attachment before commencing the installation work. By: Fresh Start ● Ensure that the guard rails to the ramp are in place and that the surface of ramp is clean before commencing. By: Principle Contractor & Fresh Start ● Ensure that the perimeter protection is in place [scaffolding and edge protection] before commencing. By: Principle Contractor & Fresh Start ● Ensure that all openings and voids in the floor platform are covered or protected by a guard rail. By: Principle Contractor & Fresh Start ● Training of “workers” in correct lifting and carrying methods. By: Fresh Start

		<ul style="list-style-type: none"> ● Ensure correct lifting and carrying techniques are used at all times. By: Fresh Start ● Team lifting and carrying By: Fresh Start ● Ensure that “workers” have safety glasses, noise protection, dust protection [disposable], protective footwear. By: Fresh Start ● Provide MSDS for chemically treated timber floor framing and sheet particleboard flooring. By: Fresh Start ● Training of “workers” in the safe handling and use of chemically treated timber products and sheet particleboard flooring. By: Fresh Start ● Training of “workers” in the safe use of power tools and nail guns. By: Fresh Start ● Ensure that all power tools have working safety guards. By: Fresh Start ● Storage of materials in designated areas By: Fresh Start ● Maintain a clean and tidy work area. By: Fresh Start
8. Carrying structural steel members up ramp - Installation of steel beams and posts.	<ul style="list-style-type: none"> ● Slips, trips and falls. ● UV light / weather exposure ● Fall from height ● Manual task injuries ● Proximity of other “workers”. ● Public access. 	<ul style="list-style-type: none"> ● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start ● Identify that the electrical service has been isolated and that ‘tiger tails’ are in place as protection from overhead wires and points of attachment before commencing the installation work. By: Principle Contractor & Fresh Start ● Ensure that the guard rails to the ramp are in place and that the surface of the ramp is clean before commencing. By: Principle Contractor & Fresh Start ● Ensure that the perimeter protection is in place [scaffolding and edge protection] before commencing. By: Principle Contractor & Fresh Start ● Training of “workers” in correct lifting and carrying methods By: Fresh Start ● Ensure that correct lifting and carrying techniques are used at all times By: Fresh Start ● Ensure that “workers” have protective footwear and gloves. By: Fresh Start ● Use of mechanical aids to lift and place steel beams and posts. By: Fresh Start ● Team lifting and carrying By: Fresh Start ● Use short beams where possible. By: Fresh Start ● Maintain a clean and tidy work area. By: Fresh Start
9. Carry frames and components up ramp - Erection of timber wall frames	<ul style="list-style-type: none"> ● Slips, trips, falls and accessibility. ● UV light / weather exposure. ● Fall from height. ● Manual task injuries ● Sprains and strains. ● Exposure to noise. ● Hazardous materials. ● Proximity of other “workers”. ● Public access. 	<ul style="list-style-type: none"> ● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start ● Identify that the electrical service has been isolated and that ‘tiger tails’ are in place as protection from overhead wires and points of attachment before commencing the installation work. By: Fresh Start ● Ensure that the guard rails to the ramp are in place and that the surface of the ramp is clean before commencing. By: Fresh Start ● Ensure that the perimeter protection is in place [scaffolding and edge protection] before commencing. By: Fresh Start ● Provide MSDS for chemically treated timber framing. By: Fresh Start ● Training of “workers” in the safe handling and use of chemically treated timber products. By: Fresh Start ● Training of “workers” in correct lifting and carrying methods. By: Fresh Start ● Ensure correct lifting and carrying techniques are used at all times. By: Fresh Start ● Team lifting and carrying. By: Fresh Start ● Ensure “workers” have safety glasses, noise protection, protective footwear and gloves. By: Fresh Start ● Limit use of ladders as working platforms. By: Fresh Start ● Training of “workers” in safe use of power tools and nail guns. By: Fresh Start ● Ensure all power tools have working safety guards. By: Fresh Start ● Storage of materials in designated areas By: Fresh Start ● Maintain a clean and tidy work area. By: Principle Contractor & Fresh Start
10. Carry up materials and components up ramp - Installation of structural timber beams	<ul style="list-style-type: none"> ● Slips, trips, falls and accessibility ● UV light / weather exposure ● Fall from height ● Manual task injuries ● Exposure to noise ● Proximity of other “workers”. ● Public access. 	<ul style="list-style-type: none"> ● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start ● Identify that the electrical service has been isolated and that ‘tiger tails’ are in place as protection from overhead wires and points of attachment before commencing the installation work. By: Principle Contractor & Fresh Start ● Ensure that the guard rails to the ramp are in place and that the surface of the ramp is clean before commencing. By: Fresh Start ● Ensure that the perimeter protection is in place [scaffolding and edge protection] before commencing. By: Principle Contractor & Fresh Start ● Training of “workers” in correct lifting and carrying methods. By: Fresh Start ● Ensure correct lifting and carrying techniques are used at all times. By: Fresh Start ● Ensure “workers” have protective footwear and gloves. By: Fresh Start

		<ul style="list-style-type: none"> ● Use of mechanical aids to lift and place hangers and beams. By: Fresh Start ● Limit use of ladders as working platforms. By: Fresh Start ● Team lifting and carrying By: Fresh Start ● Maintain a clean and tidy work area. By: Principle Contractor & Fresh Start
11. Carry trusses up ramp - Erection of timber roof trusses	<ul style="list-style-type: none"> ● Slips, trips, falls and accessibility. ● UV light / weather exposure ● Fall from height ● Manual task injuries ● Exposure to noise. ● Proximity of other "workers". ● Public access. 	<ul style="list-style-type: none"> ● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start ● Identify that the electrical service has been isolated and that 'tiger tails' are in place as protection from overhead wires and points of attachment before commencing the installation work. By: Principle Contractor & Fresh Start ● Ensure that the guard rails to the ramp are in place and that the surface of the ramp is clean before commencing. By: Fresh Start ● Ensure that the perimeter protection is in place [scaffolding and edge protection] before commencing. By: Fresh Start ● Training of "workers" in safe working at heights and safe movement on roof. By: Fresh Start ● Training of "workers" in correct lifting and carrying methods. By: Fresh Start ● Ensure correct lifting and carrying techniques are used at all times. By: Fresh Start ● Team lifting and carrying By: Fresh Start ● Ensure "workers" have safety glasses, noise protection, protective footwear and gloves. By: Fresh Start ● Limit use of ladders as working platforms. By: Fresh Start ● Training of "workers" in the safe use of power tools and nail guns. By: Fresh Start ● Ensure all power tools have working safety guards. By: Fresh Start ● Storage of materials in designated areas By: Fresh Start ● Maintain a clean and tidy work area. By: Principle Contractor & Fresh Start
12. Carrying materials up ramp. - Installation of timber fascia, eaves and associated timber trims.	<ul style="list-style-type: none"> ● Slips, trips, falls and accessibility ● UV light / weather exposure ● Fall from height. ● Manual task injuries ● Exposure to dust. ● Exposure to noise. ● Proximity of other "workers". ● Public access. 	<ul style="list-style-type: none"> ● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start ● Identify that the electrical service has been isolated and that 'tiger tails' are in place as protection from overhead wires and points of attachment before commencing the installation work. By: Principle Contractor & Fresh Start ● Ensure that the perimeter protection is in place before commencing. [Scaffold as working platform] By: Fresh Start ● Team lifting and carrying By: Fresh Start ● Ensure "workers" have safety glasses, noise protection, dust protection [disposable], protective footwear. By: Fresh Start ● Training of "workers" in the safe use of power tools and nail guns. By: Fresh Start ● Ensure all power tools have working safety guards. By: Fresh Start ● Storage of materials in designated areas By: Fresh Start ● Maintain a clean and tidy work area. By: Fresh Start
13. Carrying materials up ramp. - Installation of external wall cladding.	<ul style="list-style-type: none"> ● Slips, trips, falls and accessibility. ● UV light / weather exposure ● Fall from height. ● Manual task injuries ● Exposure to dust. ● Exposure to noise. ● Proximity of other "workers". ● Public access. 	<ul style="list-style-type: none"> ● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start ● Identify that the electrical service has been isolated and that 'tiger tails' are in place as protection from overhead wires and points of attachment before commencing the installation work. By: Fresh Start ● Ensure that the perimeter protection is in place before commencing. [Scaffold as working platform] By: Fresh Start ● Team lifting and carrying. By: Fresh Start ● Ensure workers have safety glasses, noise protection, dust protection [disposable], protective footwear. By: Fresh Start ● Limit use of ladders as working platforms. By: Fresh Start ● Training of "workers" in safe use of power tools and nail guns. By: Fresh Start ● Ensure all power tools have working safety guards. By: Fresh Start ● Storage of materials in designated areas. By: Fresh Start ● Maintain a clean and tidy work area. By: Fresh Start
14. Carrying window and door assemblies up ramp. - Installation of window and door assemblies.	<ul style="list-style-type: none"> ● Slips, trips, falls and accessibility. ● UV light / weather exposure ● Fall from height. ● Manual task injuries ● Exposure to noise. ● Proximity of other 	<ul style="list-style-type: none"> ● Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start ● Identify that the electrical service has been isolated and that 'tiger tails' are in place as protection from overhead wires and points of attachment before commencing the installation work. By: Fresh Start ● Ensure that the perimeter protection is in place before commencing. [Scaffold as working platform] By: Fresh Start ● Training of "workers" in correct lifting and carrying methods. By: Fresh Start

	<ul style="list-style-type: none"> “workers”. Public access. 	<ul style="list-style-type: none"> Ensure that correct lifting and carrying techniques are used at all times. By: Fresh Start Team lifting and carrying By: Fresh Start Ensure “workers” have safety glasses, noise protection, dust protection [disposable], protective footwear. By: Fresh Start Training of “workers” in the safe use of power tools and nail guns. By: Fresh Start Ensure all power tools have working safety guards. By: Fresh Start Maintain a clean and tidy work area. By: Fresh Start
15. Positioning of external timber stairs.	<ul style="list-style-type: none"> Slips, trips, falls and accessibility. UV light / weather exposure Fall from height. Manual task injuries Exposure to noise. Proximity of other “workers”. Public access. 	<ul style="list-style-type: none"> Assess the site conditions including the weather and conduct a Site Specific Risk Assessment before commencing. By: Fresh Start Training of “workers” in correct lifting and carrying methods. By: Fresh Start Ensure correct lifting and carrying techniques are used at all times. By: Fresh Start Ensure “workers” have protective footwear and gloves. By: Fresh Start Use of mechanical aids to lift and place stairs. By: Fresh Start Limit use of ladders as working platforms. By: Fresh Start Team lifting and carrying. By: Fresh Start Provide MSDS for chemically treated timber framing. By: Fresh Start Training of “workers” in the safe handling and use of chemically treated timber products. By: Fresh Start Maintain a clean and tidy work area. By: Fresh Start
16. Site clean up on completion of work	<ul style="list-style-type: none"> Manual task injuries Exposure to dust Exposure to hazardous substances- 	<ul style="list-style-type: none"> Remove any temporary barricades if no longer required By: Principle Contractor Place all rubbish / debris in designated waste storage area By: Fresh Start Leave site / work area in a clean and tidy condition By: Principle Contractor & Fresh Start

Person responsible for ensuring compliance with SWMS:
Person responsible for reviewing SWMS control measures: