



According to Safe Work Australia

Printing date 22.05.2014 Revision: 22.05.2014

1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Name: SILVER SOLDER - Sn96.5/Ag3.5 (1.6mm - 15g - ACID CORE) - 211623

Recommended Use of the Chemical and Restriction on Use: Acid flux core solder

Details of Manufacturer or Importer:

Primus Australia Pty Ltd 3/20 Enterprise Drive Bundoora VIC 3083

Phone Number: 03 9468 4400

Emergency telephone number: National Poison Information Centre: 13 11 26

2. HAZARDS IDENTIFICATION

Hazardous Nature: The product is not classified as hazardous according to the Globally Harmonized System (GHS).

Label Elements
Signal Word Void

Hazard Statements Void

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Characterisation: Substances

CAS No. Description 7440-31-5 tin 96.5%

Chemical Characterization: Mixtures

Hazardous Components:

7440-22-4 Silver 3.5%

Additional information: Unlisted percentages are non-hazardous stabilizers, and water.

4. FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Contact with molten material will cause severe burns.

Eye Contact:

In case of eye contact, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention. Contact with molten material will cause severe burns.

Ingestion: Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Special mixtures of dry chemicals suitable for metal fires such as dry sand, dolomite, graphite, salt, and soda ash. Do not apply water to burning or melted metal.

Specific Hazards Arising from the Chemical:

(Contd. on page 2)





According to Safe Work Australia

Printing date 22.05.2014 Revision: 22.05.2014

Product Name: SILVER SOLDER - Sn96.5/Ag3.5 (1.6mm - 15g - ACID CORE)

(Contd. of page 1)

Harmful organic fumes and toxic oxide fumes may be formed at elevated temperatures.

The solid metal form is not a fire hazard. However, when material is in the form of dust and exposed to heat and flames may present a moderate fire or explosion hazard. Hazards also exist when this product is involved in chemical reactions or in contact with powerful oxidizers.

Special Protective Equipment and Precautions for Fire Fighters:

Wear Safe Work Australia approved self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear Safe Work Australia approved safety glasses or goggles, rubber gloves and protective clothing (overall). Evacuate all non-essential personnel from affected area. Do not generate dust. Provide adequate ventilation.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Pick up solids and put in container for reuse or recycling. Do not sweep, use vacuum. Reduce airborne dust by moistening with water. Provide adequate ventilation.

7. HANDLING AND STORAGE

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Users should wear protective gloves and glasses when handling solder paste. Soldering should be conducted in a well-ventilated area

Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Protect from humidity. Keep away from strong oxidizing agents, acids and alkalies.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Standards:

7440-31-5 tin

NES STEL: 0.2** mg/m³

TWA: 2* 0.1** mg/m³

*metal, oxide, inorg. comp.;**org. comp.(as Sn):Sk

7440-22-4 Silver

NES TWA: 0.1* 0.01** mg/m3

*metal;**soluble comp. (as Ag)

Engineering Contols:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapour below occupational exposure standards.

Personal Protective Equipment (PPE):

Respiratory Protection:

Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. See Australian Standards AS/NZS 1715 and 1716 for more information.

(Contd. on page 3)





According to Safe Work Australia

Printing date 22.05.2014 Revision: 22.05.2014

Product Name: SILVER SOLDER - Sn96.5/Ag3.5 (1.6mm - 15g - ACID CORE)

(Contd. of page 2)

Skin Protection:

Rubber gloves and protective clothing. See Australian Standards AS/NZS 2161, 2210.1 and 2210.2 for more information.

Eye and Face Protection:

Safety glasses with top and side shields or goggles. See Australian Standards AS/NZS 1336 and 1337 for more information.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form: Solid metal
Colour: White metalic
Odour: Odourless
Odour Threshold: Not applicable
pH-Value: Not applicable.

Melting point/Melting range: 221 °C Initial Boiling Point/Boiling Range: 2250 °C Flash Point: Not applicable.

Flammability: Product is not flammable.

Auto-ignition Temperature: No information available

Decomposition Temperature: No information available

Explosion Limits:

Lower:Not applicableUpper:Not applicableVapour Pressure:Not applicable.

Relative Density: 7.1

Vapour Density:Not applicable.Evaporation Rate:Not applicable.Solubility in Water:Insoluble

10 . STABILITY AND REACTIVITY

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: Humidity.

Incompatible Materials: Strong oxidizing agents, acids and alkalies.

Hazardous Decomposition Products:

Harmful organic fumes and toxic oxide fumes may be formed at elevated temperatures.

11. TOXICOLOGICAL INFORMATION

Toxicity:

LD₅₀/LC₅₀ Values Relevant for Classification:

7440-22-4 Silver

Oral LD₅₀ >2000 mg/kg (rat)

Acute Health Effects

Inhalation: Inhalation of fumes or dust may cause respiratoryirritation.

Skin:

Contact with the molten core solder will cause skin burns. Fumes generated during soldering operations may be irritating to the skin.

(Contd. on page 4)





According to Safe Work Australia

Printing date 22.05.2014 Revision: 22.05.2014

Product Name: SILVER SOLDER - Sn96.5/Ag3.5 (1.6mm - 15g - ACID CORE)

(Contd. of page 3)

Eve:

Contact with the wire form of this product can be physically damaging to the eye. Contact with the molten core solder will cause burn to the eyes. Fumes generated during soldering operations or dust may cause moderate irritation, tearing, and reddening.

Ingestion: Harmful if swallowed.

Skin Corrosion / Irritation: Based on classification principles, the classification criteria are not met.

Serious Eye Damage / Irritation: Based on classification principles, the classification criteria are not met.

Respiratory or Skin Sensitisation: No sensitising effects known.

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity: This product does NOT contain any IARC listed chemicals.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Single Exposure:

Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.

Chronic Health Effects:

Prolonged or repeated exposure to tin fumes can result in benign pneumoconiosis, which causes inflammation of the lungs, but there is no distinct fibrosis or evidence of disability.

Argyria, a blue-gray discoloration of the skin, mucous membranes, and eyes may result from inhalation of silver. This discoloration may become permanent.

Existing Conditions Aggravated by Exposure: No information available

Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available

Aquatic toxicity: No information available

Persistence and Degradability: No information available Bioaccumulative Potential: No information available

Mobility in Soil: No information available

13. DISPOSAL CONSIDERATIONS

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14. TRANSPORT INFORMATION

UN Number Not regulated

ADG, IMDG, IATA Void

Proper Shipping Name Not regulated

(Contd. on page 5)





According to Safe Work Australia

Printing date 22.05.2014 Revision: 22.05.2014

Product Name: SILVER SOLDER - Sn96.5/Ag3.5 (1.6mm - 15g - ACID CORE)

(Contd. of page 4)

ADG, IMDG, IATA Void

Dangerous Goods Class Not regulated

ADG Class: Void

Packing Group: Not regulated

ADG, IMDG, IATA Void
Marine pollutant: No

15. REGULATORY INFORMATION

Australian Inventory of Chemical Substances:

7440-31-5 tin 7440-22-4 Silver

16. OTHER INFORMATION

Creation Date: 22.05.2014

Prepared by: MSDS.COM.AU Pty Ltd www.msds.com.au

Abbreviations and acronyms:

ADG: Australian Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Disclaimer

This MSDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - December 2011"

The information contained in this material safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Primus Australia Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.