

## PACKER LAYOUT

SCALE 1:100

\* STEEL BEAM DIMENSIONS SHOWN IN BRACKETS IS THE DISTANCE BETWEEN TOP OF EXISTING (MAIN) CEILING JOISTS AND TOP OF NEW STEEL BEAM

\* PROVIDE 90 X 45 PLATE TO TOP OF STEEL BEAMS TO ALLOW FIXING OF JOISTS OVER

FOR: MR M \$ MRS T TOURLE

FINAL CONSTRUCTION - 26.06.15


AMENDED - 22.06.15 SDS AMENDED - 04.06.15 SDS

AMENDED - 04.06.15 SDS PREPARED - 20.04.15 SDS SHEET: 1 OF 7

JOB NO: 7645/15 D

AT: 60 RUTHVEN STREET, BONDI JUNCTION

Cape Co



#### FLOOR JOISTS - UPPER

SCALE 1:100

- \* SET DOWN WET AREA JOISTS 35mm AND SHOWER RECESS JOISTS AN ADDITIONAL 25mm
- \* PROVIDE 70 X 45 TRIMMERS FOR FIXING WET AREA FLOORING WHERE SHOWN DASHED
- \* SJ DENOTES TILLING SMART JOISTS
- \* LVL DENOTES TILLING SMART LVL


FOR: MR M & MRS T TOURLE	FINAL CONSTRUCTION - 26.06. I
--------------------------	-------------------------------

AMENDED - 22.06.15 SDS AMENDED - 04.06.15 SDS

AMENDED - 04.06.15 SDS PREPARED - 20.04.15 SDS SHEET: 2 OF 7

JOB NO: 7645/15 D

Cope Cod



### FLOOR JOISTS - LOWER

SCALE 1:100

\* SJ - DENOTES TILLING SMART JOISTS

\* LVL - DENOTES TILLING SMART LVL

FOR: MR M & MRS T TOURLE

FINAL CONSTRUCTION - 26.06.15


AMENDED - 22.06.15 SDS AMENDED - 04.06.15 SDS

PREPARED - 20.04.15 SDS

SHEET: 3 OF 7

JOB NO: 7645/15 D

AT: 60 RUTHVEN STREET, BONDI JUNCTION



#### RAFTERS - GROUND FLOOR

SCALE 1:100

\* RAFTERS TO BE AT MAXIMUM 450mm CTS WITH 450mm EAVE OVERHANG TO REAR

FOR: MR M & MRS T TOURLE


FINAL CONSTRUCTION - 26.06.15

AMENDED - 22.06.15 SDS

AMENDED - 04.06.15 SDS PREPARED - 20.04.15 SDS

SHEET: 4 OF 7

JOB NO: 7645/15 D



# CEILING JOISTS - GROUND FLOOR

SCALE 1:100

- \* CEILING JOISTS TO BE AT MAXIMUM 450mm CTS
- \* HANG CEILING JOISTS FROM FLOOR FRAME/RAFTERS OVER AS REQUIRED

FOR: MR M & MRS T TOURLE


FINAL CONSTRUCTION - 26.06.15

AMENDED - 22.06.15 SDS

AMENDED - 04.06.15 SDS PREPARED - 20.04.15 SDS

SHEET: 5 OF 7

JOB NO: 7645/15 D



#### ROOF LAYOUT - FIRST FLOOR

SCALE 1:100

- \* RAFTERS TO BE AT MAXIMUM 600mm CTS
- \* PROVIDE 90 X 90 POSTS IN INTERNAL WALLS UNDER RIDGE
- \* PROVIDE 90 X 90 POSTS AT GABLE ENDS TO BEAR ONTO 140 X 90 F5 HEADS OVER WINDOWS

FOR: MR M & MRS T TOURLE

FINAL CONSTRUCTION - 26.06.15

AMENDED - 22.06.15 SDS AMENDED - 04.06.15 SDS

PREPARED - 20.04.15 SDS

SHEET: 6 OF 7

JOB NO: 7645/15 D

