

EXTERNAL FINISHES SCHEDULE (FOR 20 NO. DWELLINGS)

GREAT HOUSE FARM SITE LLANDOUGH.

ACCOMMODATION SPECIFICATION FOR HOUSE TYPES:

BUDWORTH, DENHAM, AND SUTTON

OVERALL DESIGN CONCEPT

'VILLAGE' House types constructed fully in accordance with the working drawings, general details and specific details.

SPECIFICATION

MAIN BRICKWORK

2 types of bricks used:

BUTTERLEY OLD ENGLISH RUSSET

or

BUTTERLEY STONELEIGH BUFF MULTI

(See attached schedule for plot selection.)

CONTRASTING BRICKWORK All the bullseye brickwork, projecting band courses, arched brickwork, gable slots and window cills.

SMOOTH RED AGAINST STONELEIGH B. MULTI
SMOOTH BUFF AGAINST OLD ENGLISH RUSSET

MORTAR AND JOINTS OF MAIN BRICKWORK

For the above bricks use TILCON
coloured Mortar

REF: Y6R for OER and SBM main facing bricks

Mix:- Use one part OP cement to four and half parts by volume, gauged on site for above ground work. Add the suffix X/L for all below ground work.

Mix is also to be 1: 4 1/2 for below ground work
All joints slightly raked out 3mm. deep.

MORTAR AND JOINTS OF CONTRASTING BRICKWORK	Use TILCON Mortar ref. Y27P for smooth buff.
	Use TILCON Mortar ref. Y54R for smooth red.
	MIX one part OPC to four and half parts by volume gauged on site.
	Raked Joints - 3mm. only.
MAIN ROOFS	Marley Modern SMOOTH GREY interlocking concrete roof tiles with nail holes.
RIDGE	Marley Modern Ridge Tiles Ref.209 to also SMOOTH GREY colour.
CANOPY/PORCH ROOFS	Marley concrete plain tiling in SMOOTH GREY. (conopy roofs plain tiled unless connected to garage adjacent, in which case tiles as main roof)
BAY ROOFS	SHEET LEAD See plumbing Specification.
WINDOW/DOOR FRAME	T.L. Bennett Softwood High Performance severe rated. Pattern as working drawing. - weather stripped - glazing bead - 140mm softwood cill - 2 lockable fasteners per sash: colour gold suffolk. - friction hinges - Plastic night vent in head.colour white to glossed windows, brown to stained windows. - 31 x 15mm glazing rebates - all door frames to have GOLDSEAL finish from factory. fixed sash to all direct glazed openings. - all garage up & over door frames to have 100 x 75 head. - all thresholds to entrance frames to have 63mm finished thickness. Window frames either primed or stained GOLDSEAL (see schedule for plot selection).
WINDOW FINISH	All stained components to be finished on site with CROWN WOODSTAIN colour TEAK. see painting specification for full details. All primed components painted CROWN gloss: WHITE
FRONT DOOR	THORNBURY Finished with CROWN WOODSTAIN, TEAK. Double glazed obscure.
FRONT DOOR FRAME	Finished on site with CROWN WOODSTAIN, TEAK.
BACK DOOR AND FRAME FINISH	ALL NYLAND - finished as front door; double glazed Obscure.

PATIO DOOR	Double glazed: WHITE/BROWN, to match window finish. Polyester coated aluminium doors in HARDWOOD , having 63mm. finished hardwood cill,4 point locking system. Frame and thresholds always stained as front door specification. This is whether the patio door is white or Brown :
GARAGE DOORS high	CHEVRON PATTERN IN STEEL.. Size 7'6" wide x 7'0" (see attached analysis for painting colour .)
RAINWATER GOODS	Osma Amazon to high level roofs using overhead gutter brackets. Osma Squareline to all low level roofs. Both items in BROWN.
SOFFITS/FASCIAS	FINISHED WITH: CROWN WOODSTAIN, TEAK. (see painting specification for full information)
RENDERING.	Specific plots have an area of rendering See schedule attached for plot selection.

TO DENHAM AND BUDWORTH ON SPECIFIC PLOTS

SMOOTH FACED RENDERING - PAINTED WHITE; AREA ABOVE BAND COURSE ON FRONT PROJECTION ONLY, FROM LANDING WINDOW CORNER AROUND TO CHIMNEY STACK CORNER.

TO SUTTON ON SPECIFIC PLOTS

SMOOTH FACED RENDERING PAINTED WHITE ABOVE BAND COURSE ONLY ON FRONT ELEVATION. AREA FROM ENSUITE WINDOW CORNER AROUND TO CHIMNEY STACK PROJECTION.

ALL RENDERING TO BE IN ACCORDANCE WITH SPECIFICATION AS ATTACHED.

PATIO DOOR	Double glazed: WHITE/BROWN, to match window finish. Polyester coated aluminium doors in HARDWOOD , having 63mm. finished hardwood cill,4 point locking system. Frame and thresholds always stained as front door specification. This is whether the patio door is white or Brown :
GARAGE DOORS high	CHEVRON PATTERN IN STEEL.. Size 7'6" wide x 7'0" (see attached analysis for painting colour .)
RAINWATER GOODS	Osma Amazon to high level roofs using overhead gutter brackets. Osma Squareline to all low level roofs. Both items in BROWN.
SOFFITS/FASCIAS	FINISHED WITH: CROWN WOODSTAIN, TEAK. (see painting specification for full information)
RENDERING.	Specific plots have an area of rendering See schedule attached for plot selection.

TO DENHAM AND BUDWORTH ON SPECIFIC PLOTS

SMOOTH FACED RENDERING - PAINTED WHITE; AREA ABOVE BAND COURSE ON FRONT PROJECTION ONLY, FROM LANDING WINDOW CORNER AROUND TO CHIMNEY STACK CORNER.

TO SUTTON ON SPECIFIC PLOTS

SMOOTH FACED RENDERING PAINTED WHITE ABOVE BAND COURSE ONLY ON FRONT ELEVATION. AREA FROM ENSUITE WINDOW CORNER AROUND TO CHIMNEY STACK PROJECTION.

ALL RENDERING TO BE IN ACCORDANCE WITH SPECIFICATION AS ATTACHED.

IDEAL HOMES WALES LTD.

SPECIFICATION FOR EXTERNAL RENDERING

9/8/1993

MATERIALS

Cement shall be to either BS.12: BS.146: BS.4207 or BS.5224

Sand shall be to BS.1200. Sand must be properly graded.

Waterproofers must be used in accordance with manufacturers recommendations.

Metal quoin beads/bell mouths etc. must be stainless steel

Nails must be stainless steel

Background - to be concrete blockwork NOT CLAY brickwork of any kind.

Concrete bricks in limited quantities are permissible to achieve the coursing of the concrete blockwork.

WEATHER

Be aware that very hot or very wet weather will require attention by the site foreman of the most appropriate form of action.

Mortar mixes shall be used within 2 hours in summer and within 3 hours in winter.

Mortar should be mixed dry and water then added.

MIX : TWO COAT RENDERING

UNDERCOAT Shall not exceed 16mm. thick and not be less than 8mm thick. 12mm thick is preferable. Provide scratch key for finishing coat.

USE 1:2 1/2 to 3 1/2 masonry cement to sand with a waterproofer (no plasticiser)

FINISHING COAT

10mm thick; plain float finish with wood float, not a steel float. The background coat should be fully dry and set before applying the finishing coat (normally 3 days).

USE: 1:4 to 5 masonry cement to sand with waterproofer (no plasticiser).

FINAL FINISH 2 coats of masonry paint; COLOUR 'WHITE'. Use Crown Stronghold Ploway. See painting Specification for full details.

TILCON MORTAR MIX

COLOURED MORTAR SPECIFICATION

ADDITIONAL INFORMATION

GAUGING WATER:

Only clean water should be used. As uniformity of colour is important, care should be taken to ensure that the mortar is mixed regular consistency.

CEMENT GAUGING:

It is strongly advised that the same brand, type and source of cement be used throughout the Contract, and that the site gauging is carried out accurately by weight or volume to ensure colour consistency.

SITE STORAGE:

Mortar should be tipped on to a clean banker board with a sealed base and sheeted when not in use.

MASONRY PROTECTION:

Stacked bricks and blocks should be protected from the weather at all time. Never use wet bricks/blocks and always protect the top course of new work during construction against the weather. This is very important to guard against disfiguration of the brickwork from efflorescence and/or lime bloom, and also during winter conditions when there is a danger of attack by frost.

EXTERNAL FINISHES SCHEDULE

LLANDOUGH

PLOT	TYPE	HAND	GARAGE	MAIN BRICK	RENDER	GARAGE DOOR COL.
------	------	------	--------	---------------	--------	---------------------

1	SUTTON	OPP	DG	SBM	-	08C 39
2	DENHAM	OPP	SAG	OER	YES	12C 39
3	SUTTON	AS	DG	SBM	-	08C 39
4	BUDWORTH	OPP	DDG	OER	YES	12C 39
5	SUTTON	OPP	SIG	OER	YES	12C 39
6	SUTTON	OPP	SIG	SBM	-	08C 39

Stoneleigh Buff Multi
Old English Russet.

7	DENHAM	AS	SAG	OER	YES	12C 39
8	SUTTON	OPP	SIG	SBM	-	08C 39
9	DENHAM	OPP	SDG	OER	YES	12C 39
10	BUDWORTH	AS	DDG	OER	YES	12C 39

11	SUTTON	AS	SIG	SBM	-	08C 39
12	DENHAM	AS	SAG	OER	YES	12C 39
13	SUTTON	AS	DG	OER	YES	12C 39

14	DENHAM	OPP	SAG	SBM	-	08C 39
15	BUDWORTH	AS	DDG	OER	YES	12C 39

16	BUDWORTH	OPP	DAG	OER	YES	
17	SUTTON	AS	SIG	SBM	-	08C 39
18	BUDWORTH	OPP	DDG	OER	YES	12C 39
19	SUTTON	OPP	SIG	SBM	-	
20	DENHAM	OPP	SAG	OER	YES	08C 39

GARAGE CODES

SINGLE ATTACHED GAR.	SAG
DOUBLE DETACHED GAR.	DDG
DOUBLE GAR. 1/INT.1/ATT	DG
SINGLE INTEGRAL GAR.	SIG

WINDOW FINISH

ALL PLOTS WITH OLD ENGLISH
RUSSET BRICKWORK TO BE
GLOSS FINISHED.
ALL OTHER PLOTS STAIN FINISH TEAK.

MAIN BRICKWORK CODES

OLD ENGLISH RUSSET
STONELEIGH BUFF MULTI

CONTRASTING BRICKWORK

SMOOTH BUFF
SMOOTH RED

EXTERNAL FINISHES SCHEDULE

LLANDOUGH

PLOT	TYPE	HAND	GARAGE	MAIN BRICK	RENDER	GARAGE DOOR COL.
------	------	------	--------	---------------	--------	---------------------

1	SUTTON	✓	OPP	DG	SBM	- 08C 39
2	DENHAM	✓	OPP	SAG	OER	YES 12C 39
3	SUTTON	✓	AS	DG	SBM	- 08C 39
4	BUDWORTH	✓	OPP	DDG	OER	YES 12C 39
5	SUTTON	✓	OPP	SIG	OER	YES 12C 39
6	SUTTON	✓	OPP	SIG	SBM	- 08C 39

7	DENHAM	✓	AS	SAG	OER	YES 12C 39
8	SUTTON	✓	OPP	SIG	SBM	- 08C 39
9	DENHAM	✓	OPP	SDG	OER	YES 12C 39
10	BUDWORTH	✓	AS	DDG	OER	YES 12C 39

11	SUTTON	✓	AS	SIG	SBM	- 08C 39
12	DENHAM	✓	AS	SAG	OER	YES 12C 39
13	SUTTON	✓	AS	DG	OER	YES 12C 39

14	DENHAM	✓	OPP	SAG	SBM	- 08C 39
15	BUDWORTH	✓	AS	DDG	OER	YES 12C 39

16	BUDWORTH	✓	OPP	DAG	OER	YES
17	SUTTON	✓	AS	SIG	SBM	- 08C 39
18	BUDWORTH	✓	OPP	DDG	OER	YES 12C 39
19	SUTTON	✓	OPP	SIG	SBM	-
20	DENHAM	✓	OPP	SAG	OER	YES 08C 39

GARAGE CODES

SINGLE ATTACHED GAR.	SAG
DOUBLE DETACHED GAR.	DDG
DOUBLE GAR. 1/INT.1/ATT	DG
SINGLE INTEGRAL GAR.	SIG

WINDOW FINISH

ALL PLOTS WITH OLD ENGLISH
RUSSET BRICKWORK TO BE
GLOSS FINISHED.
ALL OTHER PLOTS STAIN FINISH TEAK.

MAIN BRICKWORK CODES

OLD ENGLISH RUSSET
STONELEIGH BUFF MULTI

CONTRASTING BRICKWORK

SMOOTH BUFF
SMOOTH RED

9. Sutton.

5 Denham.

5 Budworth.