

Device Session Collection (Kount Integration)

Before making verification requests, you must implement device fingerprinting using the Kount SDK. This is required for fraud detection and risk assessment.

1. Install the Kount SDK:

Shell

```
npm install @kount/kount-web-client-sdk
```

2. Generate a Session ID:

- Must be exactly 32 characters
- Alphanumeric with dashes and underscores allowed
- Must be unique forever (never recycled)
- Store in `sessionStorage` for reuse during the browser session

3. Initialize Device Collection:

JavaScript

```
import kountSDK from '@kount/kount-web-client-sdk';

// Generate unique 32-character session ID
const generateSessionId = () => {
  const timestamp = Date.now().toString(36);
  const random1 = Math.random().toString(36).substring(2, 10);
  const random2 = Math.random().toString(36).substring(2, 10);
  const processId = Math.floor(Math.random() * 1000).toString(36);

  const combined =
`${timestamp}-${random1}-${random2}-${processId}`;
  return combined.length > 32
    ? combined.substring(0, 32)
    : (combined +
Math.random().toString(36).substring(2)).substring(0, 32);
};

const sessionId = generateSessionId();

// Configure Kount
const kountConfig = {
```

```
clientId: 'YOUR_KOUNT_CLIENT_ID', // Provided by AffiliateTech
environment: 'PROD', // or 'TEST' for staging
isSinglePageApp: true,
callbacks: {
  'collect-begin': (params) => {
    console.log('Kount collection started:', params);
  },
  'collect-end': (params) => {
    console.log('Kount collection completed:', params);
    // Device fingerprinting is now complete
    // You can now make API calls with this sessionId
  }
}
};

// Initialize Kount SDK
kountSDK(kountConfig, sessionId);
```

4. **Use Session ID in API Calls:** Include the `device_session_id` in your verification requests:

```
JSON
{
  "device_session_id": "your-32-character-session-id",
  "firstName": "John",
  "lastName": "Smith",
  // ... other fields
}
```

Important Notes

- **One Collection Per Session:** Only initialize Kount once per browser session
- **Reuse Session IDs:** Store the session ID in `sessionStorage` and reuse it for multiple API calls within the same session
- **Client ID:** Your Kount client ID will be provided by ViewThru during onboarding
- **Environment:** Use `TEST` for staging/development, `PROD` for production
- **Timing:** Allow device collection to complete before making verification API calls
- **Error Handling:** Implement proper error handling for SDK loading and initialization failures

Session ID Requirements

The `device_session_id` must meet these requirements:

- Exactly 32 characters long
- Contains only alphanumeric characters, dashes (-), and underscores (_)
- Must be unique across all time (never reuse a session ID)
- Should be generated client-side for each browser session

See the "**Device Session Collection (Kount Integration)**" section above for implementation details.

About Device Session ID: While technically optional, the `device_session_id` is strongly recommended for all production implementations. It enables:

- Enhanced fraud detection and risk assessment
- Improved verification accuracy
- Better protection against synthetic identity fraud
- Compliance with industry best practices

About Account Creation URL: The `account_creation_url` parameter provides important context to Kount's fraud detection system:

- Pass the actual URL where your verification form is hosted
- This helps Kount understand the legitimate context of the verification
- Examples:
 - <https://www.yoursite.com/claim-now>
 - <https://www.yoursite.com/motor-finance/application>
 - <https://app.yoursite.com/verify-identity>
- This URL should be the page where the user is completing the verification, not your API endpoint
- Providing this parameter can improve fraud detection accuracy and reduce false positives

About IP Address: The `ip_address` parameter helps improve fraud detection accuracy:

- Provide the actual IP address of the end user completing your form
- This is especially important if your API calls come from a server rather than directly from the user's browser
- If not provided, we'll use the IP address of the API request, which may be your server's IP
- Accurate IP information helps detect:
 - Geographic anomalies
 - VPN/proxy usage
 - Known fraudulent IP addresses
- Format: Standard IPv4 (e.g., "192.168.0.1") or IPv6 addresses are accepted