users

column	type
user_id 🔑	integer
username	varchar
email	varchar
password	varchar
created_at	timestamp

sales_notes

column	type
sales_id 🔗	integer
notes_id 🔗	integer

item_category

column	type
category_id 🔑	integer
category_name	varchar
created_at	timestamp

item_unit

column	type
unit_id 🔑	integer
unit_name	varchar
created_at	timestamp

customers

column	type
customer_id 🔑	integer
customer_name	varchar
phone	varchar(10)
address	varchar
customer_type	varchar
join_date	timestamp
created_at	timestamp
updated_at	timestamp

sales

column	type
sales_id 🔑	integer
sales_number 🔗	varchar
customer_id 🔗	integer
customer_name	varchar
customer_address	varchar
gst_number	varchar
subtotal_amount	decimal(10,2)
gst_amount	decimal(10,2)
discount_amount	decimal(10,2)
total_amount	decimal(10,2)
paid_amount	decimal(10,2)
balance_amount	decimal(10,2)
status	varchar
payment_method	varchar
notes	varchar
issue_date	timestamp
due_date	timestamp
created_at	timestamp
updated_at	timestamp

notes

column	type
notes_id 🔑	integer
notes_title	varchar
notes_content	varchar
notes_operation	varchar(1)
notes_flag	varchar
created_at	timestamp
updated_at	timestamp

inventory

column	type
item_id 🔑	integer
item_code	varchar
item_name	varchar
category_name 🔗	varchar
unit_name 🔗	varchar
available_quantity	decimal(10,2)
reorder_level	decimal(10,2)
stock_status	varchar
sale_cost	decimal(10,2)
order_status	varchar
created_at	timestamp
updated_at	timestamp

sold_items

column	type
sold_item_id 🔑	integer
sale_number	varchar
item_id 🔗	integer
item_name	varchar
item_unit	varchar
sold_quantity	decimal(10,2)
sold_cost	decimal(10,2)
sold_amount	decimal(10,2)
is_processed	bool
created_at	timestamp

users
user_id 🔑	integer
username	varchar
email	varchar
password	varchar
created_at	timestamp

sales_notes
sales_id 🔗	integer
notes_id 🔗	integer

item_category
category_id 🔑	integer
category_name	varchar
created_at	timestamp

item_unit
unit_id 🔑	integer
unit_name	varchar
created_at	timestamp

customers
customer_id 🔑	integer
customer_name	varchar
phone	varchar(10)
address	varchar
customer_type	varchar
join_date	timestamp
created_at	timestamp
updated_at	timestamp

sales
sales_id 🔑	integer
sales_number 🔗	varchar
customer_id 🔗	integer
customer_name	varchar
customer_address	varchar
gst_number	varchar
subtotal_amount	decimal(10,2)
gst_amount	decimal(10,2)
discount_amount	decimal(10,2)
total_amount	decimal(10,2)
paid_amount	decimal(10,2)
balance_amount	decimal(10,2)
status	varchar
payment_method	varchar
notes	varchar
issue_date	timestamp
due_date	timestamp
created_at	timestamp
updated_at	timestamp

notes
notes_id 🔑	integer
notes_title	varchar
notes_content	varchar
notes_operation	varchar(1)
notes_flag	varchar
created_at	timestamp
updated_at	timestamp

inventory
item_id 🔑	integer
item_code	varchar
item_name	varchar
category_name 🔗	varchar
unit_name 🔗	varchar
available_quantity	decimal(10,2)
reorder_level	decimal(10,2)
stock_status	varchar
sale_cost	decimal(10,2)
order_status	varchar
created_at	timestamp
updated_at	timestamp

sold_items
sold_item_id 🔑	integer
sale_number	varchar
item_id 🔗	integer
item_name	varchar
item_unit	varchar
sold_quantity	decimal(10,2)
sold_cost	decimal(10,2)
sold_amount	decimal(10,2)
is_processed	bool
created_at	timestamp

dbdiagram.io