

# 1 Review

Last time:

- Last week's HW was using Jupyter notebook. Any questions on Jupyter?
  - I use Jupyter notebook on the browser...so are my notebooks stored online?
- Basic Python types and operations.
- Conditionals

## 2 Conditionals Example

**Fizz Buzz!** You are given a number `num`. Your program should:

1. Print 'fizz' if divisible by 3
2. Print 'buzz' if divisible by 5
3. Print 'fizzbuzz' if divisible by 3 and 5
4. Print the number otherwise

```
num = 15 # some number
d3 = (num%3)==0
d5 = (num%5)==0
if d3 and d5:
    print('fizzbuzz')
elif d3:
    print('fizz')
elif d5:
    print('buzz')
else:
    print(num)
```

## 3 Loops

- We often want to run a piece of code many times
- While and for loops

**While loop:** runs WHILE a condition true

```
import random as rand
num = 0
while num!=5:
    print('The number is ' + str(num))
    num = rand.randint(1,10) # random integer between 1-10
```

```
print('The number is 5!')
```

**For loop:** iterates through a type of object called ITERABLE. There are two types of iterable objects that we're concerned with,

1.  $\text{range}(a, b) = \{x : a \leq x < b\}$
2.  $\text{range}(b) = \{0 : a \leq x < b\}$
3. lists

```
# prints 1, 2, ..., 10
```

```
for i in range(1,11):  
    print(i)
```

```
# prints contents of the list
```

```
lst = [3, 1, 4, 1, 5]
```


```
for i in lst:  
    print(i)
```

```
# double the contents of a list
```

```
for i in range(len(lst)):  
    lst[i] = lst[i]*2
```

## 4 Functions

- Perform a repetitive task that reacts to some input and has some output
- Functions are black boxes. Someone can hand you a function they wrote and you don't have to understand HOW it works but only WHAT it does.



- The name of a function is always followed by ()
- Defining a function:

```
def say_hi():  
    print('hi!')
```

- Calling a function:

```
>>> say_hi()  
hi!
```

- Functions can take arguments: information that you pass to the code inside the function.

```
def greet(name):
    print('Hi {}, how are you today?'.format(name))

>>> greet('James')
Hi James, how are you today?
```

- Function can return arguments:

```
def add(x, y):
    sum = x+y
    return sum

>>> result = add(1, 2)
>>> print(result)
3
```

- Notice that the order of your arguments matters!
- If no return statement is provided, Python returns None by default
- Default arguments: you can specify that an argument should have a default value if not provided by the user.

```
def get_harmonic(freq, harmonic=2):
    return freq*harmonic

>>> get_harmonic(100) #200
>>> get_harmonic(100, 3) #300
>>> get_harmonic(100, harmonic=3) #300, more explicit
```

- (OPTIONAL) Unpacking an iterable: taking an iterable object (e.g. list) and unpacking its contents.

```
>>> lst = [1, 2]
>>> add(lst[0], lst[1])
3
>>> add(*lst)
3
>>> print(*lst)
1 2
```

- (OPTIONAL) Packing an iterable: what if you want to write a function that takes an unspecified number of arguments?

```
def add(*args):
    sum = 0
```

```

    for n in args:
        sum = sum + args
    return sum

>>> add(1, 2, 3)
6
>>> add(*lst)
3

```

We can also pack a keyworded iterable:

```

def print_keyword_args(**kwargs):
    for key in kwargs:
        print('{ }-->{ }'.format(key, kwargs[key]))

>>> print_keyword_args(first_name='Undergrad', last_name='Lab' )
first_name-->Undergrad
last_name-->Lab

```

- Docstrings: string literals ('''') that appear right after the definition of a function, class, or module. Docstrings are vital in properly documenting your code and should describe the functions arguments, functions, return types, and exceptions thrown.

```

def multiply(a, b):
    ''' Returns the product of two arguments.'''
    return a*b

```

- The docstring is associated with the `__doc__` variable. To view a functions docstring in Jupyter, press shift-tab with your cursor on a call statement.

### Demo: finding all primes up to 1000

- We only need to check factors up to  $\lfloor n/2 \rfloor$ . Proof: suppose  $\{x_1, x_2\}$  are factors of  $n$ . Then,

$$x_1 \cdot x_2 = n \implies x_2 = n/x_1 \leq n/2 \quad \text{because both } x_1, x_2 > 2 \quad (4.1)$$

Therefore, either  $x_1 < n/2$  or  $x_2 < n/2$ .

```

def is_prime(n):
    ''' Determines if an integer n is prime.'''
    for i in range(2, int(n/2)):
        if n%i==0:
            return False
    return True

```

```

primes = []
for n in range(1, 10001):
    if is_prime(n):

```

```
        primes.append(n)

print(*primes, sep=',')
```

## 5 Errors

There are can be many sources of error in your code:

- syntax
- runtime errors

Whenever an error arises **and is not handled by your code**, your program terminates and a stack trace is initiated.

```
1 # returns if n is divisible by x
2 def is_divisible(n, x):
3     return n%x == 0
4
5 print(is_divisible(1,0))
```

```
>>> python Demo.py
Traceback (most recent call last):
  File "demo.py", line 1, in <module>
  File "demo.py", line 2, in f
ZeroDivisionError: integer division or modulo by zero
```

**Traceback:**

- The traceback traces back the sources of the error
- Read the traceback from bottom to top
- Bottom line: What error caused the code to stop and any messages that accompany the error.
- Moving bottom to top, the most recent line of code where the error occurred.
- Read the traceback to effectively debug code!!

**Catching exceptions:** sometimes, when an error occurs, you want your code to move on.

```
try:
    print(is_divisible(1,0))
except ZeroDivisionError:
    print('There was a zero division error!')

print(is_divisible(3,2))
```

```
>>> python Demo.py
```

```
There was a zero division error!  
False
```

- to handle any error, catch `Exception`

### Raising exceptions:

- Sometimes, you want your code to cause exceptions. sometimes, you want your code to cause exceptions.
- E.g. want to make sure that the arguments that the user passes to your function make sense
- You can cause an error with the `raise` keyword
- Assertion error: `assert` that a condition is true, otherwise an `AssertionError` is thrown.

```
def dogs(name):  
    if type(name) != str:  
        raise TypeError("Dog's name is not a string.")  
  
    assert len(name)>0, "Name your dog, you bastard!"  
  
    print("Your dog's name is " + name)
```

## 6 Next Week

- A miscellany of topics
- List comprehensions, dictionaries, lambda functions, importing, pip