

Homework 09


1. Show the detailed information of all files whose names end with “.conf” or “.gpg” at all levels under the directory “/etc/apt/”.

ANS:

(command)

```
find /etc/apt/ \( -name '*.conf' -o -name '*.gpg' \) -exec ls -l {} \;
```

(screenshot)



```
Ubuntu-18.04 [執行中] - Oracle VM VirtualBox
檔案 機器 檢視 輸入 裝置 說明
Activities Terminal 15:15
s4112064205@s4112064205-VirtualBox: ~/class/hw_9
File Edit View Search Terminal Help
s4112064205@s4112064205-VirtualBox:~/class/hw_9$ find /etc/apt/ \( -name '*.conf' -o -name '*.gpg' \) -exec ls -l {} \;
-rw-r--r-- 1 root root 604 七 27 2021 /etc/apt/apt.conf.d/20apt-esm-hook.conf
-rw-r--r-- 1 root root 127 十二 1 2022 /etc/apt/apt.conf.d/20snapd.conf
-rw-r--r-- 1 root root 2796 三 29 2021 /etc/apt/trusted.gpg.d/ubuntu-keyring-2012-archive.gpg
-rw-r--r-- 1 root root 2794 三 29 2021 /etc/apt/trusted.gpg.d/ubuntu-keyring-2012-cdimage.gpg
-rw-r--r-- 1 root root 1733 三 29 2021 /etc/apt/trusted.gpg.d/ubuntu-keyring-2018-archive.gpg
s4112064205@s4112064205-VirtualBox:~/class/hw_9$
```

2 is a Question Group

2. Follow the following steps:
 - a. Use command “sudo apt install git” to install git
 - b. Use command “git clone https://gitlab.com/aidslab902/unix-class.git” to download the directory “unix-class/”.
 - c. Change the working directory to “unix-class/hw9/” and answer the below questions.
-

- I. Use regular expression to find the lines contains “.obstacle {” in the file “index.html” and show the corresponding line number.


Example: `21: .obstacle {`

ANS:

(command)

`egrep -n '.obstacle {' index.html`

(screenshot)



- II. Use regular expression to find the lines contains “@app.route(‘/’)” in the file “app.py” and show the corresponding line number. (All text in that line should be all red.)


Example: `20:@app.route("/api/echo", methods=["POST"])`
`32:@app.route("/api/time")`
`41:@app.route("/api/add", methods=["POST"])`

ANS:

(command)

`grep -nE '^@app.route\("/api/.*' app.py`

(screenshot)




III. Sort file “Starbucks-Venti” in ascending order using the first column (with the leftmost column as the first) and you should ignore lowercase and uppercase (= consider lowercase and uppercase be equivalent)

ANS:

(command)

`sort -k 1 -f Starbucks-Venti`

(screenshot)




- IV. Only use “cut” and “paste” to display a table that only has drink_name, Grande_price, Venti_price at column 1, 2, 3.

ANS:

(command)

```
Paste -d\ Starbucks-Grande Starbucks-Venti | cut -d\ -f1,2,4
```

(screenshot)



- V. Sort file “Starbucks-Grande” in descending order using the second column (with the leftmost column as the first) and the sorting must be based on actual numeric values.

ANS:

(command)

```
sort -gr -k 2 Starbucks-Grande
```

(screenshot)

