The record after a ClusterMAX test
ClusterMAX 3.0 mapped to SQCD-1



ClusterMAX 3.0 tests and rates GPU clouds. SemiAnalysis's SLA documents set three tiers and define acceptance testing, and SemiAnalysis encourages buyers, GPU clouds, lenders and insurers to use these terms "as a basis for their contracts." SQCD-1 is an open format for compute delivery records, from which a party with no account on either side can recompute each party's delivery figure for each window.

This is a field map from the free text of SemiAnalysis's ClusterMAX 3.0 article; the SLA documents and the paid closing section are outside it.

Stage	ClusterMAX 3.0 tests and terms	SQCD-1 requirements	SQCD-1 clauses
Audit	Checks of inventory, versions, GPU access, containers, scheduler, network, storage, monitoring and security each report pass, warn, fail or skipped.	Inventory, network and version results are read against Grade Class fields. Each field carries a verifiability tier: physically measurable by the buyer, hardware-attested, provider-mediated, or declared, with a required evidence class, in a statement signed before the window.	A8.1–A8.4 · A8.9 A8.10 · A8.11
Compute and fabric	GPU tests run GEMM, GEMV, nvbandwidth and HPL-MxP; network tests run NCCL or RCCL collectives from 8 B to 16 GB, RDMA per rail, and scale-out runs with NVLink off.	Memory, peer-to-peer link and scale-out fabric bandwidth each have a named procedure. A reading is the median of repeated runs under declared conditions, filed with an uncertainty inside the procedure's bound.	7.0.1 · 7.0.2 7.0.3 · 7.0.5 MP–01 – MP–03
Storage and internet	Storage tests run fio sweeps and checkpoint benchmarks and measure S3 throughput and latency; lifecycle tests measure internet speed and image pulls.	Storage readings under MP-04 test the throughput and IOPS floors; external-network readings under MP-05 test the egress and ingress floors against an outside endpoint named in the filing plan.	A8.5 · A8.6 MP–04 · MP–05
Reliability	Tests include an eight-hour burn-in on GPUs and network together, fabric loops, storage endurance and Kubernetes churn; reboots and injected XID faults are timed until the node runs a command again.	Each party files its own interval series every window. An interval is delivered only where every covered layer was simultaneously conforming; a missing reading is filed as a signed gap with a coded cause.	B2 · B7.1 · B7.2 C1–C4 · H1
SLA tiers	Bronze, Silver and Gold set downtime thresholds and credits, with "two-way commitments for measuring downtime and providing credits," recommended exclusions such as patches and maintenance, and a recommended monthly review cadence. The most common GB300 NVL72 term that SemiAnalysis sees applies the SLA to each node and counts the whole rack down when 3 or more of its 18 nodes fail at once.	Thresholds, exclusions and credit schedules are fixed before the window, each exclusion with the evidence required to invoke it. Both parties file every window, and a material divergence is located to its first interval. Each node is named as a measured subject, and the rule that counts the whole rack down is stated in full in the filing plan, with a worked example over at least one hundred intervals, before the window.	A4 · A5 · A6 · A7 A10 · H1 · H2 · H4 B3 · A2
Acceptance	The SLA documents define acceptance testing across GPU compute, networking, storage and software, and give the buyer a termination right for a missed acceptance date. SemiAnalysis encourages including its Technical Assessment in acceptance testing and monthly SLA reviews.	The buyer's reading at commencement establishes that each physically measurable field of the Grade Class contracted for was delivered. A third-party tester's readings are filed under a party's own key, naming the tester as measuring party. On each window's delivery claim, the buyer signs its decision (accept, reject, dispute or abstain) under a stated authority by the review deadline the agreement sets, W+12 in SQCD-1's timetable. Silence produces the state "expired," on terms fixed before the window.	B8.4 · B8.5 · B4 D1 · D2 · F1–F3 I.1 · I.1.1 Annex 2.4 Annex 8
Finality	The article's free text sets no finality date.	Corrections close at W+30. Quantity is final at W+45 and money at W+90, in business days after the window unless the agreement states otherwise. Records are kept at least 36 months after money finality.	I.1 · I.1.4 · K1 Annex 8

ClusterMAX 3.0 names the tests. SQCD-1 records who measured each reading and who signed its filing, each window's review deadline and the date its quantity is final. A lender that reads both holds a rating of the GPU cloud and a delivery record whose figures it can recompute itself.

Sources "ClusterMAX 3.0: The Industry Standard GPU Cloud Rating System Returns," SemiAnalysis, September 23, 2026 · SQCD-1 v1.1, psyche-0.com/sqcd-1.html

Fée-Fée Yang · PSYCHE · purr@psyche-0.com

November 2026