Creating A New Electronite Release

v44.9.3

Summary

- Electronite is a fork of Electron (latest release notes at https://github.com/unfoldingWord/electronite/releases) that is patched for Graphite Font support (About Graphite from SIL).
    - See the release notes for links https://github.com/unfoldingWord/electronite/releases to build notes, etc.
- There is a paired repo https://github.com/unfoldingWord-dev/electronite-cli/releases that is for the Electronite installer that is posted on the repository site (https://www.npmjs.com).
- Also there is the Electronite Packager

Creating The Release

Notes

- ☐ Before starting In the steps below, make copy of this document so you can check off the boxes as you go, and:
    - ☐ Replace the version `44.9.3` with the version of the new Electron version you want to build on (see releases at https://github.com/electron/electron/releases)
    - ☐ Then replace version `39.2.6` with last Electronite version released (e.g. `44.9.3`)

a. you need to build on Intel computer (currently for Windows and Linux, but for MacOS builds you now can build on ARM):
    i. Building for MacOS on Arm64 is now supported. Can build faster than the Intel 6 core Mac Mini if the processor has more than 6 performance cores. Was able to build locally using a Mac VM running on UTM (3.2.4).

b. for each OS (Mac, Windows, Linux), it can take a day or two to build each of the targets (depending on the performance of the build PC).

c. It's best to have dedicated build PCs or dedicated VMs (even better is cloud based VPC which enables setting up multiple machines in parallel). Here are some build requirements:
    i. Using a fast internet connection and fast drive it can take as little as 45 minutes to download and patch source files with cached git files. Otherwise it can take over 4 hours on a clean PC.
    ii. doing the builds can use over 100GB of disk space (particularly for arm64 builds). So it's best to have at least 160GB of primary disk space (80GB free after old builds are deleted) or have a second drive with 100GB of storage.
    iii. It's best to have at least 4 cores and a fast disk.
    iv. Best to have at least 16GB RAM and fast disk or the final link phase can take many hours due to disk swapping.
    v. It looks like **Oracle Cloud Compute** is cheapest and fastest for doing Windows and Linux builds (no Mac). It's only about $10 a build for Windows and Linux architectures.
        - The most efficient configuration I found was (each build takes 3 to 4 hrs):
            Shape: VM.Standard.E3.Flex

OCPU count: 6
CPU Model: AMD EPYC 7742 64-Core
CPU Core: 12
Network bandwidth (Gbps): 6
Memory (GB): 32

- Seems to give fast builds at minimal cost

vi. **AWS Compute** looks much more expensive, but has MacOS support (unfortunately you are required to rent the Mac for a minimum of 24 hours). The full costs seem to be about 2x the cost of the EC2 compute instance (due higher EC2 rates and extra charges for internet data, storage size, storage bandwidth, etc.).

d. Note that the build process is always changing for Electron, so if it doesn't build you should check the build instructions at `docs/development/build-instructions-*.md` in the repo of the latest release.

Create a new Electronite beta release

- Creating new Electronite beta branch
  - ☐ If you haven't done this yet, you will need to clone https://github.com/unfoldingWord/electronite onto a local PC.
  - ☐ In terminal, change directer to the base `Electronite` folder in project
  - ☐ Run script file to create new branches and copy files from previous Electronite branch.
    - ☐ First do `chmod +x ./docs/development/Electronite/make_new_electronite.sh`.
    - ☐ Make sure `--no-verify` Is applied to pushes in script.
    - ☐ Then do `./docs/development/Electronite/make_new_electronite.sh v44.9.3 electronite-v39.2.6` (source below) which will:
      - get the tag `v44.9.3` from the upstream electron repo
      - make both a new electron branch `v44.9.3-electron` and a new Electronite branch `electronite-v44.9.3-beta` in the electronite repo
      - copy files from old electronite branch `electronite-v39.2.6`
      - commit changes to new electronite branch `electronite-v44.9.3-beta`
  - ☐ Update the `./electronite/docs/development/Electronite/electronite.patch`
    - ☐ Manually go through `electronite.patch` tweaking line numbers to match line numbers in new files (or could use claude code).
      - In the example `@@ -11,12 +11,14 @@ vars = {`
        - The first 11 is the first line to match, the 12 is the number of lines in the section to be modified
        - The second 11 is the first line number in the new patched file, the 14 is the new number of lines in the modified section
        - The `@@ vars = {` is the content in first line of the section
    - ☐ Next step is to pretend you are the patch tool and manually go through the patch and make the changes to the files (except for creating the file `./electronite/patches/chromium/add_graphite.patch`) (or could use claude code):

- [ ] edit `./DEPS`
- [ ] edit `./patches/chromium/.patches`

- [ ] search and replace in the source files for instances old version number (such as `39.2.6`) and replace with `44.9.3`

- [ ] Commit changes and push up.
  - [ ] Do git commit: the newer Electron releases are running pre-commit hooks which may fail on your setup. So skip precommit hooks by doing: `` `git commit --no-verify` ``
  - [ ] Do git push: `` `git push --no-verify https://<<TOKEN>>@github.com/unfoldingWord/electronite.git` ``

- [ ] Test the patch by building using either a Intel computer on Windows or on Arm for Mac (or Intel):
  - *Search through the yml files in **`.github/workflows/*`** to see what OS's are being used for latest Electronite builds.*
  - *If you run into trouble with build (also see the **Troubleshooting, General** section):*
    - [ ] Delete the cached Electronite repo in git_cache (should be in electronite build folder):
      - Look in `git_cache` and delete the folder and lock file that matching `` `github.com-unfoldingword-electronite*` ``. Otherwise it will not use the recent changes, branches, commits.
    - [ ] Use appropriate instructions in this document in the sections: AWS Windows VM Setup , AWS Linux VM Setup , or AWS MacOS VM Setup.

    - [ ] Follow steps for setting up the build environment (if not up to date).
    - [ ] And follow the steps to build all.
    - [ ] while add graphite patch fails:
      - [ ] Test manually to see where it fails: `` `cd src; git apply --check --verbose ./electron/patches/chromium/add_graphite.patch; echo "exit=$?"` ``
      - [ ] Record the sections failed - you will have to apply those manually.
      - [ ] Now automatically apply patches that are still good (remove dry run): `` `git apply --check --verbose ./electron/patches/chromium/add_graphite.patch; echo "exit=$?"` ``
      - [ ] Now manually apply the failed parts of patch in `./electron/patches/chromium/add_graphite.patch`.
        - [ ] Create an updated patch file by `cd src` and `git diff HEAD > ../patch.patch`
        - [ ] Copy the content of `patch.patch` and paste it into the first part of the `add_graphite.patch` file (except for the files to create).
        - [ ] Commit the changes and push it up to the branch
        - [ ] Clear cached git files: `rm -rf ./git_cache/github.com-unfoldingword-electronite` `rm ./git_cache/github.com-unfoldingword-electronite.locked`

- [ ] Delete source folder (e.g. `~/Develop/Electronite-Build/src`)
- [ ] Start over again with test

- [ ] If build fails on graphite due to cpp deprecations, then you will have to update our custom patch `add_graphite_cpp_std_iterator.patch`. If hand editing doesn't work, then apply the changes to the files from `src` folder do `git diff HEAD > ../patch.patch` to generate the first part of the file (except for files to create).
  - [ ] fix the compile error in the cpp source code in `.\src\third_party\graphite\graphite2`. *Note - We hope that eventually SIL will update their code, and then we can remove this patch from build scripts/batch.*
  - [ ] Once it compiles past graphite make an updated patch by doing:
    - [ ] `cd src/third_party/graphite/graphite2 && git diff HEAD > ~/graphite.patch`
    - [ ] make copy of patch for Electronite: `cp ~/graphite.patch ~/add_graphite_cpp_std_iterator.patch`
    - [ ] in `~/add_graphite_cpp_std_iterator.patch` do search for instances of `a/src` and replace with `a/third_party/graphite/graphite2/src`
    - [ ] Also create issue in `https://github.com/silnrsi/graphite/issues/78` to share the fix with others and give content of `graphite.patch`
    - [ ] update `./electronite/docs/development/Electronite/add_graphite_cpp_std_iterator.patch` in ELectronite branch with contents of `~/add_graphite_cpp_std_iterator.patch` and commit/push
- [ ] Make sure that `.\src\third_party\graphite` has been downloaded. Otherwise fix patches and start over with test

- *If you need to retry checkout after making changes to Electronite repo, do* `./electronite-tools-4.sh get electronite-v44.9.3-beta` *and then restart build with* `./build_all_mac.sh electronite-v44.9.3-beta results/mac/v44.9.3`

- [ ] Save the latest version of these instructions (with boxes unchecked) to Electronite repo at `docs/development/Electronite/Creating new Electronite Release.pdf`
- [ ] Commit and Push up your fixes to the Electronite branch

Make and Test Builds for each OS:

- [ ] Do builds for Mac, Windows, and Linux using notes in this document in the sections: AWS Windows VM Setup , AWS Linux VM Setup , or AWS MacOS VM Setup.

- [ ] *Note* - builds take up lots of disk space, so after building each target, copy the `dist.zip` folder from `./src/out/Release-*` and rename it appropriate to version/OS/architecture such as `electronite-v44.9.3-graphite-beta-win32-x64.zip`. Then delete folder`./src/out` before building for the next architecture.
    - [ ] If you run out of space while building, particularly building for arm64, you can delete the files within the `git_cache` folder which should free up over 20GB of space.

- Test The Graphite support in each electronite build by:
    - Once you have a compiled Electronite binary you can test it by visiting this page https://graphite.sil.org/graphite_fontdemo.html. Do this by:
        - Run Electronite (or optionally you could use translation Core build with this version of Electronite)
        - Open the developer console in the running Electronite instance.
        - execute `window.location="https://graphite.sil.org/graphite_fontdemo#normal-truetype-font-loaded-from-a-server"`
    - Under elements, inspect text below "`Normal TrueType font loaded from a server`"
    - In this paragraph element, the padauk font uses a Mozilla specific css flag, but since Electronite is based on chromium those don't work. Therefore, it is necessary to tweak the css a little. The larger font-size makes it easier to see the change (toggle "`font-feature-settings`" off and on to see difference).

```diff
.padauk-ttf {
 font-family: PadaukT, sans-serif;
 font-size: 150%;
 -moz-font-feature-settings: "wtri=1";
 -moz-font-feature-settings: "wtri" 1;
+ font-feature-settings: "wtri" 1;
}
```

    - Ensure all the tests pass by visually inspecting the rendered fonts and comparing against the image samples on the site.

    - [ ] **Mac** - graphite validated
    - [ ] **Linux** - graphite validated
    - [ ] **Windows** - graphite validated

- [ ] At https://github.com/unfoldingWord/electronite/releases, create a draft release on Electronite using the previous release as a template (set Release title to be `Electronite v44.9.3-Beta` , and set it up to create a tag with name `v44.9.3-graphite-beta` when release is made).

- [ ] Attach all the builds renaming the dist.zip file to match the tag name (`v44.9.3-graphite-beta`) and architecture of the build (again using the previous release as a template) (e.g. name of `` `electronite-v44.9.3-graphite-beta-win32-arm64.zip` ``)
- [ ] Attach the patched `` `electron.d.ts` `` from Electronite branch (in `` `./docs/development/Electronite/electron.d.ts` ``)
- [ ] Create a pre-release for testing

Create a new electronite-cli beta release

- [ ] *If you haven't already done this*, then clone the repo**:** https://github.com/unfoldingWord-dev/electronite-cli
- [ ] Checkout the latest release and create a branch `electronite-v44.9.3-beta`
  - [ ] Update version in package.json to be `44.9.3-graphite-beta`
  - [ ] Replace `` `electron.d.ts` `` with the patched `` `electron.d.ts` `` from above
  - [ ] Commit and push the changes
- [ ] Test package by **deleting the dist folder**, and then run `` `npm i --legacy-peer-deps && npm pack` ``, this should create a file `electronite-44.9.3-graphite-beta.tgz`
- [ ] Create a test branch in translationCore project (such as `` `feature-electronite-v44.9.3` ``)
  - [ ] Import the electronite tgz file from step 2: `` `npm i --legacy-peer-deps --save-dev <<path-to-tgz>>` `` **<=** replace `` `<<path-to-tgz>>` `` with actual path to file
  - [ ] Make sure translationCore will start up `` `npm i --legacy-peer-deps && npm start` ``
    - [ ] If it fails on start, may have to update: `` `@electron/remote` ``
  - [ ] make sure the translationCore version is correctly displayed in the app.
  - [ ] Check the log file (latest in ~/translationCore/logs) or console to make sure it is running the right **version of electron** (e.g. `` `Electron 44.9.3` ``)
  - [ ] Make sure graphite is working:
    - [ ] Look at this issue for how to test: https://github.com/unfoldingWord/translationCore/issues/6788
    - [ ] Example Myanmar test bible: https://github.com/unfoldingWord/translationCore/files/4621965/57-TIT_myanmar_judson_1835_utf8.usfm.txt
    - [ ] Example `ar` project: https://git.door43.org/ElsyLambert/ar_new_phm_book
- [ ] Now back in `` `electronite-cli` `` project delete the dist folder, and npm publish the electronite-cli beta branch: `` `npm i --legacy-peer-deps && npm publish --tag beta` ``
- [ ] in translationCore project remove electronite tgz file dependency: `` `npm uninstall electronite` ``
- [ ] update translationCore to use the published package: `` `npm i --legacy-peer-deps --save-dev electronite@v44.9.3-graphite-beta` ``
- [ ] in package.json remove the ^ before Electronite version.
- [ ] Create builds and test by doing:
  - [ ] commit and push up changes
  - [ ] for translationCore project (`` `https://github.com/unfoldingWord/translationCore` ``) create a PR for this branch so github actions will automatically try to create all the versions (which ensures that all Electronite dist zip files are named correctly)
  - [ ] test the builds - particularly macos universal and windows x64:
    - [ ] install and start up translationCore builds.

- [ ] Check the log file to make sure it is running the right version of electron
- [ ] Make sure graphite is working:
    a. Look at this issue for how to test: https://github.com/unfoldingWord/translationCore/issues/6788
    b. Example Myanmar test bible: https://github.com/unfoldingWord/translationCore/files/4621965/57-TIT_myanmar_judson_1835_utf8.usfm.txt
    c. Example `ar` project: https://git.door43.org/ElsyLambert/ar_new_phm_book

- [ ] At https://github.com/unfoldingWord-dev/electronite-cli/releases, create a prelim release:
    - [ ] Commit and push up the changes to the new branch.
    - [ ] Draft a new release based on `electronite-v44.9.3-beta`
    - [ ] Set up to create a new tag `v44.9.3-graphite-beta` on publish.
    - [ ] Publish as pre-Release

Creating the final releases

- [ ] Make another Electronite draft release (https://github.com/unfoldingWord/electronite/releases)
    - [ ] Checkout the latest branch `` `electronite-v44.9.3-beta` `` and create new branch `` `electronite-v44.9.3` ``
    - [ ] Update pdf and odf files of `` `Creating A New Electronite Release` `` with latest changes
    - [ ] Git Push the changes

    - [ ] Make an Electronite draft release using the branch `` `electronite-v44.9.3` `` and select to create tag `v44.9.3-graphite` on release
        - [ ] Attach the same Electronite builds as the prerelease beta, but rename them by removing `` `beta-` `` from name.
        - [ ] Change description to take beta out of links
        - [ ] Attach the latest `` `electron.d.ts` `` patched for electronite
        - [ ] Publish this draft as a pre-release for the moment

- [ ] Make another electronite-cli branch: https://github.com/unfoldingWord-dev/electronite-cli
    - [ ] Checkout the latest branch `electronite-v44.9.3-beta` and create a new branch `electronite-v44.9.3`:
        - [ ] Update version in package.json to be `44.9.3-graphite`
        - [ ] Commit and push the changes
    - [ ] Test package by deleting the dist folder, and then run `` `npm i --legacy-peer-deps && npm pack` ``, this should create a file such as `electronite-44.9.3-graphite.tgz`
    - [ ] If that succeeds, commit changes and push up new branch.
    - [ ] Make an electronite-cli release selecting to create tag `v44.9.3-graphite` when done
    - [ ] change release description to take beta out.
    - [ ] delete the dist folder, and then publish branch: `` `npm i --legacy-peer-deps && npm publish` ``

- [ ] Test builds in translationCore:
    - [ ] Remove electronite tgz file dependency: `` `npm uninstall electronite` ``

- [ ] update translationCore to use the published package: `` `npm i --legacy-peer-deps --save-dev electronite@v44.9.3-graphite` ``
- [ ] in package.json remove the ^ before Electronite version.
- [ ] Do `` `npm i --legacy-peer-deps && npm start` `` to make sure electronite downloads and runs
- [ ] Commit and push the tCore changes.
- [ ] Wait for github actions to auto-build the updated branch. If it succeeds then the electronite dist zip files are named correctly

- [ ] Make the Electronite (https://github.com/unfoldingWord/electronite/releases) pre-release for `v44.9.3-graphite` the latest release.

- [ ] ~~*Not sure this is needed anymore now that we directly check out the build branch in the build scripts:* Merge released branch into graphite branch and push - lots of changes typically~~
  - [ ] ~~checkout and update the released branch,~~
  - [ ] ~~merge in origin/graphite~~
  - [ ] ~~diff with released branch - download all changes from branch~~
  - [ ] ~~commit and push~~
  - [ ] ~~make PR for merge to graphite~~
  - [ ] ~~merge PR~~

Troubleshooting, General

Build Problems

- Get latest build tools:
  - Do `cd depot_tools`, run `update_depot_tools` or `update_depot_tools.bat`
  - ~~do `cd depot_tools`, if not on main branch, do `git switch main`, do `git pull`~~

- Search through the yml files in **`.github/workflows/*`** to see what OS's are needed for latest Electronite builds.

- **try building a pure electron** branch (e.g. `v44.9.3-electron`) of the same version as electronite to see if it is a problem with the Electronite patch or a problem with electron's changing build requirements.

- To troubleshoot build problems, turn on **verbose builds** by doing `export BUILD_EXTRAS=-vvvvv` or `set BUILD_EXTRAS=-vvvvv` before doing build (or by appending `-vvvvv` to the ninja or `e build` command you are using)

- **Check paths** - make sure build tools are first in path and that there is a python in the path that is python2 (python --version), and that there is a python3 in the path (python3 --version)

- **branch not found:**
  - Force fetch tags: `git fetch --tags -f`
  - Invalid electron version number - starting with v21.2.3 electron is using the git tag to identify the version (maybe `git describe --tags`). Also:

- **latest changes not seen:**
  - build tool creates a git_cache for git operations, so you cannot fetch the latest content on unfoldingWord/electronite. Need to delete the folder and lock file (*github.com-unfoldingword-electronite*) from git_cache and run get or sync again.

- r**unning out of disk space:**
  - to free up memory on a drive can move folders to another drive and do symbolic linking. For example `mklink /d git_cache c:\Users\blm\git_cache`

- Doing git commit on Electronite repo runs pre-commit hooks that crash: do `git commit --no-verify`
- missing or invalid npm dependencies
  - try doing `npm i` and then continued build, but still same preflight error

- **MacOS:**
  - Determining xCode version used for build:
    - Download the Electron application. Look for the Info.plist file:
      - For macOS apps, the Info.plist file within the application's bundle can contain information about the build tools used. Open the .app bundle, right-click, and

select "Show Package Contents". Then, navigate to the "Contents" folder and find the Info.plist file. Open it with a text editor and look for a key like DTXcode. It will show something like 1540 (or 15.4)

  - Determine current MacOs SDK being used on system: `` `xcrun --show-sdk-version` ``
  - Find all the MacOS SDK installed on system: `` `xcodebuild -showsdks` ``

  - Up to electron v21.2.2 mac uses xcode 12.2 (but Monterey will refuse to use it, succeeded in getting v12.5.1 to work on Monterey with xcode-select --switch...). Starting v21.2.3 it uses xcode 13
  - To select a specific xcode do: `` `sudo xcode-select --switch /Applications/Xcode.app` ``

- **Windows:**
  - ~~Chromium build instructions say to use VisualStudio 2022, but Electron seems to use 2017 or 2019. Currently on 2019, WIndows SDKs I currently have installed are 10.0.19041.0 & 10.0.20348.0.~~
  - ~~If get build error at final stage : error: expected int, +, ~, or (, got graphite~~
    - ~~now building after this fix:~~
      ~~Looks to be parsing of tags that it doesn't like the `-graphite` at end of tag. This doesn't seem to affect the other OS's:~~

      ~~cd src\electron~~
      ~~git describe --tags~~

      ~~# if last tag has -graphite, then local delete tags and recreate:~~

      ~~git tag -d <version>-graphite~~
      ~~git tag -d <version>~~
      ~~git tag <version>~~

      ~~# make sure just version tag shows up~~
      ~~git describe --tags~~

- ~~So in `script/lib/util.py` changed `cached_electron_version` to be `"22.0.0"`, which calls `script/lib/get version.js`, which calls `git describe --tags --abbrev=0`. Build is continuing now - failed.~~

- on fail, try starting over after deleting the git_cache
- remove and reinstall build-tools ~/.electron_build_tools/
  - third_party/build_tools installed by `e sync`
- Try building with basic chromium build tools:

  - install the depot_tools here: `` `git clone https://chromium.googlesource.com/chromium/tools/depot_tools.git` ``
  - download build script to this folder from: ~/docs/development/Electronite/electronite-tools-4.sh
  - set execute permission on scripts: `` `chmod +x ./*.sh` ``
  - before build do: `` `export PATH=/path/to/depot_tools:$PATH` ``

- **Linux:**
  - Arm64 build is failing with missing include file `<libnotify/notify.h>`. This is because the arm64 build sources that are loaded by `./build/linux/sysroot_scripts/install-sysroot.py --arch=arm64` into `./build/linux/debian_bullseye_amd64-sysroot-default` do not include the libnotify package (the amd64 and x86 are preloaded by electron sync tool).
    - Updated the build scripts to add support for setting the environment variable `GCLIENT_EXTRA_ARGS="--custom-var=checkout_arm64=True"` and remove the call to `./build/linux/sysroot_scripts/install-sysroot.py --arch=arm64`
  - ~~Trying to get the right files from Ubuntu 22 Arm64 and saving them in the repo at `docs/development/Electronite/linux_arm64_missing_build_sources`.~~ <= *No longer needed.*

VM Setups

MacOS VM Setup

Summary

Now on AWS can build on Arm Macs (much faster) as well as Intel

To find out the **xcode and SDK versions**, look at the Info.plist file in the MacOS Electron (or ask claude code about which version to use). You can have multiple xcode versions on a build system and select them by…

On AWS - can run on Dedicated Mac Intel or Arm Hardware:

- mac1.metal - intel - which must be reserved for at least 24hr (about $26)

    Mac mini (2018)
    3.2 GHz 6-Core Intel Core i7
    32 GB 2667 MHz DDR4

- create an instance with Monterey OS and mac1.metal. Allocate storage as gb3, 300GB now 300MB/s, 6000iops (tried setting to max 1000MB/s, 16000iops, but didn't see speed-up). When the instance starts the partition will only have 100GB allocated. Using the Disk Utility add a new partition and apply it. It only seems to create the new partition with 6GB and will fail any resize attempt using the Disk Utility. So use the section below `Using the Mac Mini's Built-in SSD`

- Could build using the Mac Mini's SSD - but didn't see significant speedup. It is only 128GB (which might explain the slowness) . But after getting the sources, Electronite does not require a super fast storage - only large amounts.

Build Steps

Automated Build of All Architectures

Change to build folder and do (where <version> is like v44.9.3):

Get Newest Build scripts for version, for example download:

```
https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3
-beta/docs/development/Electronite/meta_builds/build_all_mac.sh

https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3
-beta/docs/development/Electronite/meta_builds/build_target_mac.sh

https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3
-beta/docs/development/Electronite/electronite-tools-4.sh
```

Initial Clear:

If you want to do a clean build where all sources are fetched again do:

```
rm -rf ./git_cache/*
```

Otherwise if you just want to clear the Electronite cache:

```
rm -rf ./git_cache/github.com-unfoldingword-electronite
rm ./git_cache/github.com-unfoldingword-electronite.locked
```

Next do setup:

```
# setup:
export PATH=$(pwd)/depot_tools:$PATH
# clear old sources
mv src src.old
rm -rf src.old &
```

Start the build:

```
# and start the build
./build_all_mac.sh electronite-<version>-beta results/mac/<version>
```

(e.g. `` `./build_all_mac.sh electronite-v44.9.3-beta results/mac/v44.9.3` ``)

Troubleshooting:

- If you need a different version of xcode, best to download the specific version directly from Apple - while need developer account
- If you then get asked again to download xcode command-line tools, do: `` `sudo xcode-select -switch /Library/Developer/CommandLineTools` ``

Manual Build of All Architectures

Get Newest Build scripts for version, for example download:

```
https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3-beta
/docs/development/Electronite/electronite-tools-4.sh
```

Next do:

```
export PATH=$(pwd)/depot_tools:$PATH
./electronite-tools-4.sh get electronite-v44.9.3-beta

./electronite-tools-4.sh build x64
./electronite-tools-4.sh release x64

./electronite-tools-4.sh build arm64
./electronite-tools-4.sh release arm64
```

Connect with VNC over SSH

```
# open ssh with tunnel
ssh -i "~/.Keys/BruceMcL.pem" -C -L 25900:localhost:5900
ec2-user@ec2-18-236-233-104.us-west-2.compute.amazonaws.com

# do vnc over tunnel
open vnc://localhost:25900
```

Using the Mac Mini's Built-in SSD

Initializing It

```
diskutil list
diskutil info /dev/disk0

# initialize and format disk as BuildDisk
diskutil eraseDisk APFS BuildDisk /dev/disk0
```

Using it for builds

- To use Mac Mini's internal (128GB) SSD for builds (see writes peaking at 520MB/s):

```
mkdir -p /Volumes/BuildDisk/Build-Electronite
cd /Volumes/BuildDisk/Build-Electronite

cp /Volumes/DataDisk/Build-Electronite/*.sh
/Volumes/BuildDisk/Build-Electronite

ln -s /Volumes/DataDisk/Build-Electronite/git_cache
ln -s /Volumes/DataDisk/Build-Electronite/logs
ln -s /Volumes/DataDisk/Build-Electronite/results
```

VM Setup Steps for Electronite Build

- Need MacOS Ventura

- Arm64-specific prerequisites
  - Rosetta 2

- We recommend installing Rosetta if using dependencies that need to cross-compile on x64 and arm64 machines. Rosetta can be installed by using the softwareupdate command line tool.

```
softwareupdate --install-rosetta
```

- enable VNC over SSH access:

```
sudo defaults write /var/db/launchd.db/com.apple.launchd/overrides.plist
com.apple.screensharing -dict Disabled -bool false
sudo launchctl load -w
/System/Library/LaunchDaemons/com.apple.screensharing.plist

# the first time set user password
#   sudo /usr/bin/dscl . -passwd /Users/ec2-user
```

- Install Build tools needed by Electronite in MacOS

Note - need to add step of creating new partition named DataDisk

```
# Fix Disk - in AWS does not use all the volume space
diskutil list
diskutil repairdisk /dev/disk1
# grow partition, to fill disk use 0
diskutil apfs resizeContainer disk1s3 0

# xcode 13.3.1 direct download URL - will prompt to login - download to
/Volume/MacData/Mac_install
#
https://developer.apple.com/services-account/download?path=/Developer_Tools/Xcode_13.3.1/Xcode_13.3.1.xip

# Install brew (not needed for AWS)
# /bin/bash -c "$(curl -fsSL
https://raw.githubusercontent.com/Homebrew/install/HEAD/install.sh)"

# accept xcode license
sudo xcodebuild -license accept

# uncompress xcode into current folder
cd ~
xip -x /Volume/MacData/Mac_install/Xcode_14.3.0.xip
mv ~/Xcode.app /Applications/Xcode.app
# select new xCode
sudo xcode-select --switch /Applications/Xcode.app
```

manually launch Xcode, and accept prompt to install additional debug tools

WARNING
don't use the python 3 installed by brew, it doesn't have certificates

download python 3.10 mac installer from (3.11 has problems with v21)
https://www.python.org/downloads/release/python-3109/
run the installer

next go into `/Library/Frameworks/Python.framework/Versions/3.10/bin/python3` and run the `Install Certificates.command`

download python 2 mac installer from https://www.python.org/downloads/release/python-2718/
run the installer

```
# set default python to be python 2
sudo cp /bin/python2 /bin/python

# Install Node Version Manager
curl -o- https://raw.githubusercontent.com/nvm-sh/nvm/v0.37.2/install.sh | bash

# initialize Node Version Manager
#    Note: if using zsh, then need to add the following into .zshrc file
export NVM_DIR="$HOME/.nvm"
[ -s "$NVM_DIR/nvm.sh" ] && \. "$NVM_DIR/nvm.sh"  # This loads nvm
[ -s "$NVM_DIR/bash_completion" ] && \. "$NVM_DIR/bash_completion"  # This
loads nvm bash_completion

# install node version 20
nvm install v20

# create build location, this is on a separate partition
mkdir -p /Volumes/DataDisk/Build-Electronite/
cd /Volumes/DataDisk/Build-Electronite/

# install chromium build tools
git clone https://chromium.googlesource.com/chromium/tools/depot_tools.git
```

Notes for Future:

Linux VM Setup

Summary

Started with Ubuntu since Amazon Linux uses yum and setup would have to be transposed.

Troubleshooting:

- If you get this permissions error running:

```
./electron
[211372:1102/050036.948941:FATAL:sandbox/linux/suid/client/setuid_sandbox_host.cc:166] The SUID sandbox helper binary was found, but is not configured correctly. Rather than run without sandboxing I'm aborting now. You need to make sure that ~/Downloads/dist/chrome-sandbox is owned by root and has mode 4755.
[1]    211372 trace trap (core dumped)  ./electron
```

- Need to set permissions:

```
sudo chown root:root ./chrome-sandbox
sudo chmod 4755 ./chrome-sandbox
```

Runs on EC2 Instances:

- Allocate storage volume as gb3, 300GB now 300MB/s, 6000iops.

- EC2 instance config:
  - **c6a.4xlarge -** AMD processor**,** 16 cpus, 32GB RAM - and will take about 10hrs
  - Using models with less RAM will take much longer at the link phase and use serious disk swap
  - Could use larger models, for example the **c6a.8xlarge -** costs about twice as much per hour as the 4x but should take ½ the time, 32 cpus, 64GB

  - Comparing compute types: https://aws.amazon.com/ec2/instance-types/
  - Comparing prices: https://us-west-2.console.aws.amazon.com/ec2/home?region=us-west-2#InstanceTypes:
  - Within a family, prices seem to be linear with performance for Electronite Builds (e.g. going from 4xLarge to 8xLarge doubles price but takes half as long)
  - Don’t see a huge difference between c5 and c6 for Electronite Builds
  - currently c6 (or c6a) seems to be best price and value

Build Steps

Automated Build of All Architectures

Change to build folder and do (where <version> is like v44.9.3):

Get Newest Build scripts for version, for example download:

```
https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3
-beta/docs/development/Electronite/meta_builds/build_all_linux.sh

https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3
-beta/docs/development/Electronite/meta_builds/build_target_linux.sh

https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3
-beta/docs/development/Electronite/electronite-tools-4.sh
```

Initial Clear:

If you want to do a clean build where all sources are fetched again do:

```
rm -rf ./git_cache/*
```

Otherwise just clear Electronite repo from the cache:

```
rm -rf ./git_cache/github.com-unfoldingword-electronite
rm ./git_cache/github.com-unfoldingword-electronite.locked
```

Next do setup:

```
# setup:
export PATH=$(pwd)/depot_tools:$PATH
# clear old sources
mv src src.old
rm -rf src.old &
```

Start the build:

```
# and start the build
./build_all_linux.sh electronite-<version>-beta
results/linux/<version>
```

(e.g. `./build_all_linux.sh electronite-v44.9.3-beta results/linux/v44.9.3`)

Manual Build of All Architectures

Get Newest Build scripts for version, for example download:

```
https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3-beta
/docs/development/Electronite/electronite-tools-4.sh
```

Next do:

```
export PATH=$(pwd)/depot_tools:$PATH
./electronite-tools-4.sh get electronite-v44.9.3-beta

./electronite-tools-4.sh build x64
./electronite-tools-4.sh release x64

cd ./src
build/linux/sysroot_scripts/install-sysroot.py --arch=arm64
cd ..

./electronite-tools-4.sh build arm64
./electronite-tools-4.sh release arm64
```

VM Setup Steps for Electronite Build

```
#!/bin/bash
# Install Build tools needed by Electronite in Linux

sudo apt-get update
sudo apt-get upgrade -y

sudo apt-get install build-essential clang libdbus-1-dev libgtk-3-dev \
                     libnotify-dev libasound2-dev libcap-dev \
                     libcups2-dev libxtst-dev \
                     libxss1 libnss3-dev gcc-multilib g++-multilib curl \
                     gperf bison python3-dbusmock openjdk-8-jre -y

sudo apt-get install libc6-dev-arm64-cross linux-libc-dev-arm64-cross \
                     g++-aarch64-linux-gnu -y

sudo apt-get install binutils-aarch64-linux-gnu

sudo apt-get install python3 python2 nano -y

# set default python to be python 2
sudo cp /bin/python2 /bin/python

# Install Node Version Manager
curl -o- https://raw.githubusercontent.com/nvm-sh/nvm/v0.37.2/install.sh | bash

# initialize Node Version Manager
export NVM_DIR="$HOME/.nvm"
[ -s "$NVM_DIR/nvm.sh" ] && \. "$NVM_DIR/nvm.sh"  # This loads nvm
[ -s "$NVM_DIR/bash_completion" ] && \. "$NVM_DIR/bash_completion"  # This loads nvm
bash_completion

# install node version 20
nvm install v20

# create build location
```

```
mkdir -p ~/Develop/Build-Electronite
cd ~/Develop/Build-Electronite

# install chromium build tools
git clone https://chromium.googlesource.com/chromium/tools/depot_tools.git
```

Windows VM Setup

Summary

Troubleshooting

If you get errors due to defender AV blocking files. Run PowerShell ****as Administrator**** and do:

```
# exclude the build tree and toolchain dirs
Add-MpPreference -ExclusionPath 'E:\Build-Electronite'
Add-MpPreference -ExclusionPath "$env:USERPROFILE\.electron_build_tools"
if ($env:CIPD_CACHE_DIR) { Add-MpPreference -ExclusionPath
$env:CIPD_CACHE_DIR }
```

~~Not yet working -~~ if build error at final stage saying `error: expected int, +, ~, or (, got graphite` . Make this fix:

Looks to be parsing of tags that it doesn't like the `-graphite` at end of tag. This doesn't seem to affect the other OS's:

```
cd src\electron
git describe --tags

# if last tag has -graphite, then local delete tags and recreate
git tag -d <version>-graphite
git tag -d <version>
git tag <version>

# make sure just version tag shows up
git describe --tags
```

~~Now only arm64 build is failing~~ - needed to go back to older Python 3.10 version

Runs on Windows 11 VM or EC2 Instances:

- Allocate storage volume as gb3, 300GB now 300MB/s, 6000iops.

- EC2 instance config:
  - **c6a.4xlarge -** AMD processor**,** 16 cpus, 32GB RAM - and will take about 10hrs
  - Using models with less RAM will take much longer at the link phase and use serious disk swap
  - Could use larger models, for example the **c6a.8xlarge -** costs about twice as much per hour as the 4x but should take ½ the time, 32 cpus, 64GB

  - Comparing compute types: https://aws.amazon.com/ec2/instance-types/
  - Comparing prices: https://us-west-2.console.aws.amazon.com/ec2/home?region=us-west-2#InstanceTypes:
  - Within a family, prices seem to be linear with performance for Electronite Builds (e.g. going from 4xLarge to 8xLarge doubles price but takes half as long)

- Don’t see a huge difference between c5 and c6 for Electronite Builds
- currently c6 (or c6a) seems to be best price and value

Build Steps

Automated Build of All Architectures

Change to build folder and do (where <version> is like v44.9.3):

Initial Clear:

Get Newest Build scripts for version, for example download:

```
https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3-beta/docs/development/Electronite/meta_builds/build_all_win.bat

https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3-beta/docs/development/Electronite/meta_builds/build_target_win.bat

https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3-beta/docs/development/Electronite/electronite-tools-4.bat
```

If you want to do a clean build where all sources are fetched again do:

```
rmdir /s /q .\git_cache
```

Or in powershell do:

```
Remove-Item .\git_cache -Recurse -Force
```

Otherwise just clear the Electronite cache:

```
rmdir /s /q .\git_cache\github.com-unfoldingword-electronite
del .\git_cache\github.com-unfoldingword-electronite.locked
```

Or in powershell do:

```
Remove-Item -Path
".\git_cache\github.com-unfoldingword-electronite"
-Recurse -Force
Remove-Item -Path
".\git_cache\github.com-unfoldingword-electronite.locked"
-Force -ErrorAction SilentlyContinue
```

Next cd to the build folder:

Setup:

```
git config --global core.autocrlf false
git config --global core.filemode false
```

```
git config --global core.fscache true
git config --global core.preloadindex true
git config --global depot-tools.allowGlobalGitConfig true
```

If you haven't added depot_tools to path do:

```
set Path=%cd%\depot_tools;%Path%
```

Or in powershell do:

```
$env:Path = "$($PWD.Path)\depot_tools;$env:Path"
```

Now to start build do:

```
# remove old source files so desire branch is fetched
rename src src.old
rmdir /s /q src.old
```

Or in powershell do:

```
# Remove old source files so desired branch is fetched
Rename-Item -Path "src" -NewName "src.old"
Remove-Item -Path "src.old" -Recurse -Force
```

```
# and start the build
build_all_win.bat electronite-<version> results\<version>
```

Example: `.\build_all_win.bat electronite-v44.9.3-beta results\v44.9.3`

Manual Build of All Architectures

Get Newest Build scripts for version, for example download:

```
https://github.com/unfoldingWord/electronite/blob/electronite-v44.9.3-beta
/docs/development/Electronite/electronite-tools-4.bat
```

Next cd to build folder and do:

```
.\electronite-tools-4.bat get electronite-<version>
```

```
.\electronite-tools-4.bat build x64;
.\electronite-tools-4.bat release x64;
```

~~`.\electronite-tools-4.bat build x86;`~~
~~`.\electronite-tools-4.bat release x86;`~~

```
.\electronite-tools-4.bat build arm64;
.\electronite-tools-4.bat release arm64;
```

VM Setup in Windows 11

VM Setup Steps for Electronite Build

```
rem Run in powershell with admin privileges
echo off
set working_dir=%cd%

echo "Install Electronite Build tools"

echo "%date% - %time%" > start_time_configure.txt
```

Switch to VS 2022

```
~~echo "Installing VS 2019 Community"~~
~~vs_community_2019.exe ^~~
~~      --wait --quiet --norestart ^~~
~~      --installWhileDownloading ^~~
~~      --add Microsoft.VisualStudio.Workload.NativeDesktop ^~~
~~      --add Microsoft.VisualStudio.Component.VC.ATLMFC ^~~
~~      --add Microsoft.VisualStudio.Component.VC.Tools.ARM64 ^~~
~~      --add Microsoft.VisualStudio.Component.VC.MFC.ARM64 ^~~
~~      --add Microsoft.Component.MSBuild ^~~
~~      --add Microsoft.VisualStudio.Component.VC.CLI.Support ^~~
~~      --add Microsoft.VisualStudio.Component.VC.Llvm.Clang ^~~
~~      --add Microsoft.VisualStudio.Component.VC.CMake.Project ^~~
~~      --add Microsoft.VisualStudio.Component.VC.Tools.x86.x64 ^~~
~~      --add Microsoft.VisualStudio.Component.VC.CoreIde ^~~
~~      --add Microsoft.VisualStudio.Component.VC.Llvm.ClangToolset ^~~
~~      --add Microsoft.VisualStudio.Component.VC.14.20.ATL ^~~
~~      --add Microsoft.VisualStudio.Component.VC.14.20.ATL.ARM64 ^~~
~~      --add Microsoft.VisualStudio.Component.VC.14.20.CLI.Support ^~~
~~      --add Microsoft.VisualStudio.Component.VC.14.20.MFC ^~~
~~      --add Microsoft.VisualStudio.Component.VC.14.20.MFC.ARM64 ^~~
~~      --includeRecommended~~

~~rem not sure if this is needed:~~
~~echo "Installing VS 2019 Build Tools"~~
~~vs_BuildTools_2019.exe~~

rem It looks like this is the SDK being used for builds (download from
https://developer.microsoft.com/en-us/windows/downloads/windows-sdk/)
~~echo "Installing WinSDK 20348"~~
~~winsdksetup_10.0.20348.0.exe /features + /q /norestart~~
echo "Installing WinSDK 22621"
winsdksetup_10.0.22621.0.exe /features + /q /norestart
```

Now using SDK 10.0.2610.0

```
~~rem Not needed anymore?~~
~~echo "Installing WinSDK 19041 -- hopefully everything gets selected"~~
~~winsdksetup_10.0.19041.0.exe /features + /q /norestart~~

echo "Setting up Python 2.7.18"
msiexec /log python27_install.log /i python-2.7.18.amd64.msi /qn ALL=1 TARGETDIR=c:\python27
ALLUSERS=1
mklink c:\python27\python2.exe c:\python27\python.exe
```

```
echo "Setting up Python 3.9.13"
python-3.9.13-amd64.exe /quiet TargetDir=c:\python311 InstallAllUsers=1 PrependPath=1
Include_test=0
rename c:\python311\python.exe c:\python311\python3.exe

Git-2.39.0-64-bit.exe /VERYSILENT /NORESTART

git config --system core.longpaths true
git config --global user.email "you@example.com"
git config --global user.name "Your Name"

echo "Install node v22"
msiexec /i node-v16.19.0-x64.msi /log node_install.log /qn
```

First, ensure that you are using an administrative shell - you can also install as a non-admin, check out Non-Administrative Installation.

```
echo "Install chocolatey"

# Install with powershell.exe
# from https://chocolatey.org/install#individual do

Set-ExecutionPolicy Bypass -Scope Process -Force;
[System.Net.ServicePointManager]::SecurityProtocol =
[System.Net.ServicePointManager]::SecurityProtocol -bor 3072; iex ((New-Object
System.Net.WebClient).DownloadString('https://community.chocolatey.org/install.ps1'))

npm i -g yarn
npm i -g @electron/build-tools
C:
cd %HOMEPATH%\.electron_build_tools
npm i

# create build location
md %HOMEDRIVE%%HOMEPATH%\Develop\Build-Electronite
cd %HOMEDRIVE%%HOMEPATH%\Develop\Build-Electronite

# install chromium build tools
git clone https://chromium.googlesource.com/chromium/tools/depot_tools.git

echo "Restore initial directory
cd %working_dir%

echo "%date% - %time%" > end_time_configure.txt
```

In settings-> WIndows Defender -> Exclusions, and an exclusion for the build folder

Set system environment variables

```
set vs2019_install=c:\Program Files (x86)\Microsoft Visual Studio\2019\Community
set WINDOWSSDKDIR=c:\Program Files (x86)\Windows Kits\10
set DEPOT_TOOLS_WIN_TOOLCHAIN=0
```

Setup System Environment Variables

```
set vs2022_install=...
set WINDOWSSDKDIR=c:\Program Files (x86)\Windows Kits\10
set DEPOT_TOOLS_WIN_TOOLCHAIN=0

set
Path=C:\Users\Administrator\Develop\Build-Electronite\depot_tools;C:\python27\S
cripts;C:\python27;C:\Program Files\Python39\Scripts\;C:\Program
Files\Python39\;C:\Windows\system32;C:\Windows;C:\Windows\System32\Wbem;C:\Wind
ows\System32\WindowsPowerShell\v1.0\;C:\Program
Files\Amazon\cfn-bootstrap\;C:\Program Files (x86)\Windows Kits\10\Windows
Performance Toolkit\;C:\Program
Files\nodejs\;C:\ProgramData\chocolatey\bin;C:\Program
Files\Git\bin;C:\Users\Administrator\AppData\Local\Microsoft\WindowsApps;C:\Use
rs\Administrator\AppData\Roaming\npm
```

Visual Studio 2022 Configuration

```
{
  "version": "1.0",
  "components": [
    "Microsoft.VisualStudio.Component.CoreEditor",
    "Microsoft.VisualStudio.Workload.CoreEditor"
  ],
  "extensions": []
}
```

Notes for Future: