

UNG FACILITIES PLANNING & GIS

Version 1.1

May 2026

Calculates and renders the six briefing statistics from pipeline output files

Pipeline_Summary_Stats_V1.1.py

Purpose

Reads the parsed AD file and the Unmatched_AD_Rooms file from a given pipeline run and calculates the six statistics shown in the Pre-Meeting Briefing: Total AD Accounts, Mappable Records, GIS Polygons Populated, Placement Rate, Campuses Live, and Gap Records. Outputs both a console summary and a UNG-branded HTML page ready to copy to GitHub for Leaflet or Hub presentation.

When to Run

- On demand after each weekly pipeline run to generate the briefing statistics
- Any time historical statistics are needed — point at any matching pair of files

Requirements

- Python with pandas (no ArcGIS required)
- Matched pair: parsed AD file and Unmatched_AD_Rooms file from the same run
- Updater V3.4+ required for full gap breakdown (Reason column in unmatched file)

Inputs

Item	Value	Notes
Parsed AD Excel	PARSED_AD_FILE config variable	Must match the same run as the unmatched file
Unmatched_AD_Rooms Excel	UNMATCHED_FILE config variable	Must match the same run as the parsed file

Key Statistics Calculated

- Total AD Accounts — primary source rows in parsed file
- Mappable Records — complete Building + Room + City, not suspect, not online/blank
- GIS Polygons Populated — Mappable minus no_match minus duplicates (requires Reason column)
- Placement Rate — GIS Populated ÷ Mappable
- Campuses Live — always 5
- Gap Records — no_match + duplicates from Reason column

Outputs

Item	Value	Notes
Console summary	Printed to screen	All six statistics plus population and gap breakdowns
pipeline_summary.html	ActiveDirectoryParsing\	UNG-branded HTML page with six stat boxes, tables, and pipeline step list; copy to GitHub for Hub/Leaflet display

HTML Output

The HTML file uses UNG navy and gold branding and is self-contained (no external dependencies beyond Google Fonts). The placement rate box changes color automatically: green at 80%+, amber at 65-79%, red below 65%. The datestamp is auto-detected from the parsed filename (MMDDYYYY format). Copy pipeline_summary.html to the unggis GitHub repository after each run.

Historical Review

To reconstruct statistics for any past run, set PARSED_AD_FILE and UNMATCHED_FILE to the files from that run. The script will auto-detect the run date from the filename. Pre-V3.4 unmatched files lack the Reason column — the script warns clearly and falls back to total-only gap reporting.

Version Notes

V1.1: Reads Reason column from unmatched file; derives GIS Populated as Mappable minus no_match minus duplicates; gap breakdown shows both buckets; warns when pre-V3.4 file is used; generates UNG-branded HTML output

V1.0: Initial release; GIS Populated derived as Mappable minus total gap (inaccurate without Reason column)