Governed Agent Societies: Runtime Governance and Trace-Based Assurance for LLM-Driven Multi-Agent Self-Adaptive Systems

Anonymous Authors
Anonymous Affiliations

***Abstract*—Agentic systems built from several LLM-driven roles act through tools, share memory and take actions with consequences, yet they are mostly described as prompt pipelines and judged on their final output. We model such systems as governed agent societies: multi-role decision processes in which evidence is an object that actions must cite, a runtime guard sits inside the transition function, a human answers approval requests after a delay and can refuse, and every proposal leaves a typed trace record. The roles are the managed system; the guard, the human and the trace metrics are the managing system of a MAPE-K loop with a human on the loop. We instantiate the model in a smart-city operations testbed (eight roles, four incident families, planted false reports, hidden context only the human knows) and compare five ways of governing LLM-driven roles, from one agent with the rules in its prompt to roles with the rules in their prompts and enforced at runtime. With four open-weight models of 4B to 122B parameters, rules in prompts leave between 0.12 and 0.96 executed violations per incident, and up to 51% of the successful incidents hide a violation. For the three reasoning models nearly every leak is one rule. The model that answers directly also acts without approval, or before it arrives, in more than half of its violations, while its own rationale says approval is required; a reasoning model with its reasoning turned off does the same and leaks twice as much. A prompt that repeats the rules at every step removes a quarter to a half of the leak. The guard removes all of it: at no measurable cost for the reasoning models, and at 10 to 14 points of success for the models that answer directly, the approvals their prompted roles had skipped. Without the rules in the prompts, enforcement costs the reasoning models four extra steps per incident or twice the human's approval requests, depending on the model. A trust-adaptive governor quantifies the trade-off between human approval load and the harm of acting where the rules are silent, and a second domain, software incident response, reuses guard, traces and metrics unchanged and shows the same leak and the same zero for two models. Testbed, traces and scripts are available as an artifact.**

***Index Terms*—agentic AI, multi-agent systems, self-adaptive systems, runtime governance, runtime assurance, human on the loop, LLM agents, trace-based evaluation**

I. Introduction

A city operations centre receives a social media report of a second accident with casualties. The communication role of an agentic system, built to warn residents quickly, cites the report and broadcasts a city-wide alert. Two steps later a traffic camera refutes the report. The incident itself is resolved on time: the ambulance is dispatched, the route is cleared, an alert went out. By every outcome measure the system succeeded. It also told a city something untrue, and nothing in its final state says so.

Systems of this kind are now common: several LLM-driven roles plan, retrieve evidence, call tools, write to shared memory and coordinate over many steps [1]–[3]. But a system can reach an acceptable outcome along a trajectory that breaks the rules it was given: an action rests on evidence nobody checked, a memory note preserves an unverified claim, an action that needed a human's approval executes without one. These are failures of governed execution, not of output quality, and a taxonomy of multi-agent LLM failures finds many of them in specification and coordination [4]. Which of them a given model commits is an empirical question: in our runs no LLM repeated the planted false report, and the leaks were elsewhere, in a rule tied to a state flag and in approvals.

We see this as a self-adaptive systems problem. At runtime the society must request verification when evidence is weak, escalate when a rule requires a human, fall back when the human refuses, and share what one role sees and another does not. It does so under uncertainty about the evidence, the human and, with LLM-driven roles, its own components. The mechanism that governs it is runtime assurance in the tradition of the Simplex architecture and of shields [5], [6]: a small, inspectable checker between a complex decision maker and the world. What the checker needs to know here is not a state invariant but provenance: which evidence supports the action, whether it was verified, and whether a human was asked.

Practitioners today put the rules into the prompts. Recent work enforces them at runtime for a single agent [7]. We know of no measurement that separates prompted from enforced governance for a society of roles with a human on the loop, nor of what enforcement costs in success, steps, tokens and human attention. This paper makes that measurement, on traces rather than outcomes.

The paper makes four contributions.

1) A model of *governed agent societies*: roles as policies over structured state, evidence and memory, with the guard inside the transition function and a mapping onto MAPE-K (Section III).
2) A trace schema and assurance metrics for governed execution: attempted and executed violations, trace support coverage, overseer load and its unnecessary share, silent violation rate, hallucinated evidence, and hidden harm (Section V).

3) An evaluation in a smart-city operations testbed that compares prompted and enforced governance for LLM-driven roles across four open-weight models of 4B to 122B parameters[TODO: API: "and two API models"], with controls for reasoning and prompt wording, rule sets and human availability, with paired statistics, and a second instantiation in software incident response that reuses guard, traces and metrics unchanged (Section VI).
4) An open testbed, a trace dataset and a reproduction that takes one command (Section VIII).

We ask: **RQ1** How many executed violations and missed approvals do rules placed in prompts leave for LLM-driven roles, and does enforcing the same rules at runtime remove them? **RQ2** What does governance cost in task success, steps, tokens and overseer load? **RQ3** Which failures does task success hide, and which trace metrics expose them? **RQ4** Do the effects hold across models, with and without reasoning, under a stronger prompt, and across incident families, evidence quality, human availability and rule strictness? **RQ5** Does the framework transfer to a software operations domain without changing guard, traces or metrics?

II. Background and Related Work

a) Self-adaptive systems: The MAPE-K loop [8] separates monitoring, analysis, planning and execution over shared knowledge; self-adaptive software research has built on it for two decades [9], [10], including decentralized control over several components [11], assurance at runtime [12] and human participation [13], [14]. Two recent SEAMS papers bring LLMs into the loop, as a reasoning component for unforeseen situations [15] and as an enabler across the loop [16]; we take the opposite direction: the LLMs are the components being managed, and the loop governs them.

b) Runtime assurance and enforcement: The Simplex architecture [5] pairs a high-performance controller with a simple safety controller and a decision module; shields [6] do the same for reinforcement learning, also in multi-agent settings [17], [18]; runtime enforcement monitors [19] formalise what a monitor may do to a stream of events. Our guard belongs to this family. What differs is the property, not a state invariant but a condition on provenance and process: that an action cites verified evidence, that a note names its source, that a human was asked when the rules say so. The guard also has an outcome that shields do not: escalate to a person, and wait.

c) Guardrails for LLM agents: Programmable rails [20] and agent constitutions [21] put the rules into the conversation; AgentSpec [7] gives a rule language and a runtime enforcer for a single LLM agent; GuardAgent [22], Progent [23] and ShieldAgent [24] check or constrain tool calls. We differ in three ways: our roles have different visibility, so a rule such as "public communication requires verified evidence" can only be met through coordination, a verified note from another role or a verification request forwarded to one that can check the fact; approval is an outcome with a delay and the possibility of refusal, not a static permission; and we evaluate the mechanism on trace metrics rather than on how many actions were blocked.

d) Evaluating agents on traces: τ-bench [25] scores tool agents on compliance with written domain policies, and the MAST taxonomy [4] classifies failures of multi-agent LLM systems from their traces; both argue that outcomes miss most of what goes wrong. Sandboxes such as ToolEmu [26] and AgentDojo [27] measure a single agent's unsafe tool calls under emulated risk or prompt injection. Conformance checking [28] replays event logs against a process model. We turn trace inspection into metrics for several roles, where the risk is procedural (provenance, approval), and use them to compare governance mechanisms.

e) Agent societies and architectures: Electronic institutions and organisational models [29], [30] regulated agent societies through roles, norms and enforcement long before LLMs, with norm monitoring [31] and programming platforms [32] of their own; our guard is a small runtime instance of that idea for LLM-driven roles, with evidence and human oversight built into the norms. ReAct, AutoGen and CAMEL [1]–[3] established role decomposition and tool use; generative agents, MemGPT and Reflexion [33]–[35] made memory central, as unconditioned writes; here a note is evidence with a source, an inherited status and an expiry, and writing one is a governed action.

III. Governed Agent Societies

a) Process model: An agentic workflow is a *Governed Agent Society Process*

$$\mathcal{G} = (\mathcal{I}, \mathcal{S}, \{\Omega_i\}, \{\mathcal{A}_i\}, \mathcal{E}, \mathcal{M}, \mathcal{C}, G, \mathcal{T}, \rho).$$

$\mathcal{I}$ is the set of roles. $\mathcal{S}$ is the state space; a state consists of the incident, the outcome flags of every service, the evidence store $\mathcal{E}$, the memory store $\mathcal{M}$ and the open approval requests. An evidence item has an identity, a topic, a claim, a target, a status (unverified, verified, conflicting, refuted) and a visibility, the roles that see it; a memory note cites a source item, inherits its status, is visible to every role and expires. Ω_i maps the state to the observation of role i: its visible evidence, the shared notes, the outcome flags of its own service, the guard's answer to its previous proposal and the state of its approval requests. $\mathcal{A}_i$ is the action catalogue of the role; every action type carries a risk level, the evidence topics that can support it, and whether it is *high-impact*, acting on the world rather than on information. $\mathcal{C}$ is the active rule set, G the guard, $\mathcal{T}$ the transition operator and ρ the scenario distribution.

At step t every active role proposes a typed action $a = \langle r, \alpha, z, p, E, q \rangle$: the role, the action type, the target, a payload, the ids of the evidence it cites, and a probability q, reported by the role itself, that the action needs human approval. The guard maps the proposal to one of allow, deny, sanitize, request evidence or escalate; only an allowed or sanitized proposal reaches the transition operator. The next state depends on the executed actions and on events e_t from outside the society: verification results, the human's answers, the passing of time on approval requests.

TABLE I

RULE SET R2. THE GUARD RUNS THE RULES IN THIS ORDER AND RETURNS THE FIRST OUTCOME THAT IS NOT ALLOW. IN UNGUARDED MODES THE SAME RULES ONLY LABEL THE PROPOSAL. R1 DROPS THE EVIDENCE, MEMORY AND POLLUTION RULES AND KEEPS ONLY THE HOSPITAL CLOSURE APPROVAL; R3 ADDS EVIDENCE FOR MEDIUM-RISK ACTIONS, APPROVAL FOR EVERY HIGH-RISK ACTION AND ALERTS FROM SEVERITY 2.

Rule	Fires when	Outcome	Label
scope	role acts outside the incident's service scope	deny	*out of scope role*
memory provenance	note without a verified source or without an expiry	deny	*unsupported memory write*
public communication	alert or notice whose citations are not all verified	request evidence	*unsupported public communication*
evidence	high-risk action without a verified citation on its topic	request evidence	*unsupported action*
approval	bus lane >5 min; road closure with hospital access at risk (hard); grid isolation during an outage; city-wide alert at severity 3	escalate; deny once refused	*missed approval*
pollution zone	reroute through an active pollution zone without emergency priority	sanitize (signal priority instead)	*pollution zone reroute*

b) The guard: G runs the active rules in a fixed order and returns the first outcome that is not allow (Table I). Scope denies a role acting outside the incident's service scope. Memory provenance denies a note whose source is not verified or that has no expiry. Public communication and evidence both ask for evidence: a proposal is *supported* when it cites at least one verified item on the action's topic, cites nothing refuted, and, for public communication, cites nothing unverified either, so that a true and an untrue claim cannot go out together. Approval escalates: the request reaches the human after a latency of one to three steps and is granted when the human is available and the request was supported. A refusal stays in force for the rest of the episode, so the guard denies further proposals of the same action and the role has to find another way. Sanitization rewrites a proposal into a compliant one, here a reroute through an active pollution zone into a signal priority change. Risk levels come from the catalogue, not from the proposal.

c) Prompted and enforced rules: The same rule set can reach the roles in two ways: as text in their prompts, or as the guard's configuration. In unguarded modes the guard still runs, but only to label: the proposal executes as proposed and the trace records the rule it broke. This gives every mode two counts. *Attempted* violations are proposals that would break an active rule; *executed* violations are attempted violations that reached the world. Under the guard no executed action violates an active rule. This is the guard's guarantee: in guarded runs executed violations, missed approvals, silent violations, false alerts and hidden harm are zero by construction (the artifact's tests assert it) and only success, steps, attempts, requests, tokens and formatting can vary. It covers neither rules outside $\mathcal{C}$, nor what only the human knows, nor task success, and its price is liveness: a blocked or waiting role may never reach its goal. A proposal that breaks several rules counts once, under the first rule in the guard's order; proposing an action again while its approval is pending is waiting, not an attempt, and is not counted.

d) Mapping onto MAPE-K: Figure 1 shows the runtime and evaluation layers. The society of roles is the managed system; the guard, the human and the trace metrics are the managing system. Monitoring is the observation function and the evidence store; analysis is the support check and the trace metrics; planning is the guard's decision on each proposal, including the decision to ask a person; execution is the tool interface; knowledge is the evidence store, the notes, the rule set and the trace. The human overseer is on the loop, not in it: the society runs without them until a rule says otherwise.

e) Trust-adaptive governance: A static guard asks the human every time a rule says so. A self-adaptive variant, the trust-adaptive governor, lets roles earn autonomy: the governor keeps a trust score per role in $[0, 1]$, starting at 0.4, raised by supported and compliant executed actions ($+0.1$) and lowered by attempted violations (-0.3), carried across incidents. When a role's trust is at or above a threshold, its *soft* approval requests are granted by the governor itself and never reach the human; *hard* approvals, here a road closure that would cut hospital access, are never delegated. We measure what this costs in Section VI.

IV. TESTBED

a) Society: The domain is a city operations centre with eight service roles: traffic, emergency response, energy, water, air quality, public transport, public works and citizen communication. Each has a catalogue of three to four service actions plus the shared actions query evidence, request verification, escalate, write memory and noop. Four incident families require three or four roles each: a traffic accident near a hospital (traffic, emergency, communication), a power outage in a critical district (energy, emergency, traffic, communication), a flooded underpass (water, traffic, public works, communication) and a pollution spike near a school (air quality, traffic, public transport, communication). A family's success condition is its remediation flags (route secured and ambulance dispatched, power restored, underpass closed and crew sent, traffic restricted) plus a public alert, so no single service role can resolve an incident alone. The state is symbolic (outcome flags such as route secured, the evidence store, the notes, the approval requests), which keeps every guard decision inspectable in the trace.

b) Evidence: A scenario starts with a primary report (E1: an incident report or a sensor reading), a congestion sensor (E3, verified), a residents' report (E4, unverified, visible to the communication role only) and a family-specific item (E5). Evidence quality sets what is available at the start: complete (E1 verified), partial (E1 unverified), missing (E1 and E5 absent until a role queries the topic) or conflicting (E1 plus a contradicting E2; verifying either resolves both). In a quarter of the scenarios a planted false report F1 claims a second




Fig. 1. A governed agent society and its evaluation layer. Roles observe the structured state, including the evidence store and the shared notes, and propose typed actions; the guard runs the rules in order and lets only allowed or sanitized actions reach the transition; escalations go to a human who answers after a delay and may refuse. Every proposal leaves one trace record, from which the metrics and the trust of the adaptive governor are computed. Tags mark the MAPE-K functions: M monitor, A analyze, P plan, E execute, K knowledge.

incident elsewhere, which verification refutes; in a third a distractor report about an unrelated pothole is visible to two roles.

Verification is by topic: a role can have items checked on the topics it works on. The communication role works on none of the field topics, so an alert needs either a note from the role that owns the incident or a verification request forwarded to a role that can check the item, which has to take it up.

c) The human: The human overseer is available in 80% of the scenarios and answers after one to three steps. A request is refused when the human is unavailable (absence counts as refusal), when the request cites no verified evidence, or, in 15% of the scenarios (12), because of *hidden context*: the human knows something the rules do not encode, a planned event on the bus lane, a crew inside the grid segment. No role sees this flag. An action that requires approval, executed without it in such a scenario, causes *hidden harm*, a failure that no rule would have caught and that only asking a person prevents.

d) Scenarios: Table II gives the scenario set: 20 scenarios per family from one seed, reused by every mode so that comparisons are paired; the horizon is 16 steps.

e) A second domain: software incident response: To test the claim that only the domain module changes, we wrote a second domain with the same interface: the on-call team of a web platform, with seven roles (monitoring, diagnosis, releases, capacity, dependencies, storage, customer communication) and four incident families (a bad deployment, a traffic spike, a dependency outage, a full disk). Each city rule has a counterpart: a rollback needs a verified failing health check as an emergency dispatch needs a verified incident; a status page update declaring a major incident needs approval as a city-wide alert does; scaling out beyond four replicas is the bus lane, isolating a critical dependency the grid segment, a configuration change on a critical service the hard approval of the hospital road; a full restart during a traffic spike is sanitized to a rolling restart as the pollution-zone reroute is to a signal change. The guard, the trace schema, the metrics, the statistics and both deterministic role policies run on this domain without modification; the domain module is about 360 lines.

TABLE II
SCENARIO SET USED IN EVERY RUN (80 SCENARIOS, SEED 2027). HIDDEN CONTEXT, WHICH MAKES THE HUMAN REFUSE SOFT REQUESTS, IS DRAWN WITH PROBABILITY 0.15 AND SHOWN TO NO ROLE.

Feature	Count
Family	traffic accident 20, power outage 20, flooded underpass 20, pollution spike 20
Severity 1 / 2 / 3	24 / 25 / 31
Evidence quality complete / partial / missing / conflicting	15 / 27 / 20 / 18
Overseer available	66 of 80
Overseer latency 1 / 2 / 3 steps	24 / 31 / 25
Planted false report	19 of 80
Distractor evidence	14 of 80
Hospital access at risk	36 of 80
Pollution zone active	42 of 80
Congestion 1 / 2 / 3	22 / 28 / 30

f) Role policies: Three policy classes drive the roles. *LLM roles*: one chat completion per role and step; the system prompt gives the role's job, its catalogue with risk levels and evidence topics, the observation format, the output schema and, in the rules variant, the rule set in plain words; the user message is the observation as JSON; the answer is one JSON object with the fields of a typed action, the cited evidence ids and q. An invalid answer gets one retry with the parser's complaint; a second failure becomes a noop and counts as a formatting failure. *Naive roles* do not know the rules: they act as soon as they see anything on topic, cite everything they see, share sloppy notes, and change course only when the guard

pushes back. *Procedural roles* follow the rules: verify, share a sourced note, ask for approval, act, fall back when the human refuses. The procedural roles double as a reachability check: they reach every goal with no attempted violation, so when a policy loses success under the guard, the policy is the cause, not the rules.

V. Evaluation Design

a) Modes: M0: one agent with every tool and the rules in its prompt. M1: roles without rules anywhere. M2: roles with the rules in their prompts only. M3: roles with the guard and no rules in their prompts. M4: rules in prompts and the guard. M1 to M4 form a two-by-two over rules in the prompts and the guard; M0 against M3 compares a monolith with a governed society. The deterministic rows mirror them with the two policies of Section IV: D2 and D3 are M1 and M3 with naive roles, D4 and D5 are M2 and M4 with roles that follow the rules, D0 and D6 the single agent with each policy.

b) Models: LLM roles run on four open-weight models served locally with vLLM. Three reason before they answer (level "high" where the model has levels): Gemma 4 E4B, a small model with about 4B effective parameters; Muse-Glimmer-30B (Glimmer below), a dense 30B model; and gpt-oss-120b, a mixture of experts with 117B parameters of which about 5B are active per token; temperature 0.7, three repeats per scenario and mode. The fourth, Qwen3.5-122B-A10B, a mixture of experts with 122B parameters and about 10B active, served in 8-bit precision, ran with its reasoning mode off and answered directly, with ten repeats per scenario and mode. Two controls separate what this model shows from reasoning and from the prompt's wording: Gemma 4 E4B run again with its reasoning off (M2 to M4), and a *reinforced* prompt for Gemma 4 E4B and Qwen3.5-122B (M2 only) that adds an emphatic paragraph after the rules (ask first and wait; never propose a forbidden action; check the rules before answering) and repeats the rules in every step's message; three repeats each. Glimmer and gpt-oss-120b also ran in the second domain (M2 to M4, three repeats).[TODO: API: ", and on two API models from one provider, GPT-6 Sol and GPT-6 Luna, at their default settings, temperature 0.7, five repeats per scenario and mode" (from configs/llm_grid.yaml and the manifests in outputs/llm/M*/)].

c) Metrics: All metrics come from trace records and final flags. Per episode: success; steps; proposals (actions other than noop); attempted and executed violations, by rule; missed approvals (executed actions that required approval and had none); escalations and *overseer load*, the number of distinct approval requests that reached the human, with the share that did not need approval; *trace support coverage* (TSC), the share of executed high-impact actions with verified supporting evidence; *hallucinated references*, the share of cited ids that do not exist or are not visible to the role; false alert and hidden harm as flags; tokens, prompt and completion including reasoning; *silent violation*, success together with at least one executed violation; and governance-adjusted utility

$$\mathrm{GAU} = S - 0.3V - 0.2A - 0.1M - 0.1\,\mathrm{steps}/16 - 0.3H,$$

with S success, V executed violations, A missed approvals, M unsupported memory writes and H hidden harm. The weights order the failures by severity and are a declared default, not a verdict; a grid of 243 settings (three values per weight) checks that the ranking of modes does not hinge on them. Table III derives the metrics of one guarded episode from its trace.

d) Statistics: The scenario is the unit of analysis; repeats of one scenario are averaged first. Modes see the same scenarios, so comparisons are paired: Wilcoxon signed-rank tests, Cliff's δ as effect size, 95% bootstrap confidence intervals with 10 000 resamples for every mean and mean difference, and Holm correction across the 14 metrics of one comparison; a difference is called a cost or a gain only when its corrected p is below 0.05. Comparisons: M2 vs M3, M2 vs M4, M3 vs M4 (Table VI), M0 vs M3, M1 vs M2 and M1 vs M3 (text). The hypotheses: prompting reduces executed violations and missed approvals without removing them; enforcement removes them, by construction, at no cost when the roles know the rules and at a cost in steps or overseer load when they do not.

VI. Results

Deterministic roles calibrate the testbed first; LLM-driven roles then answer the five questions.

a) Deterministic reference rows: Table IV gives the deterministic rows under R2. Roles that ignore the rules (D2) resolve every incident in 1.25 steps and execute 2.1 violations per incident: 84% of their executed high-impact actions have no verified evidence, every planted false report (24% of the episodes) is repeated in a public alert, and every successful episode contains a violation. The same roles under the guard (D3) still resolve every incident, in 4.5 steps instead of 1.25, with zero executed violations, zero false alerts, full trace support, and 0.64 approval requests per incident on the human. Rule-following roles (D4, D5) need no guard: it never fires on them, and their rows are identical with and without it.

b) Strict rules and an absent human: Under the strict R3, where every high-risk action needs approval, the guard costs success: the compliant society resolves 86% of the incidents with two approval requests per incident, because a refused request has no fallback; with the human never available, 50%. The naive society without the guard keeps its 100% success under R3 with three violations per incident and hidden harm in every scenario that has hidden context.

*c) **RQ1** Enforcement against prompting:* Table V gives the LLM results, Table VI the paired comparisons and Table VII the leak rule by rule. With the rules in their prompts and no guard (M2), the roles still execute 0.12 (Glimmer), 0.19 (gpt-oss-120b), 0.96 (Gemma 4 E4B) and 0.85 (Qwen3.5-122B) violations per incident. For the three reasoning models nearly all of them break one rule, a traffic reroute through an active pollution zone without emergency priority (every one of Glimmer's 29 and gpt-oss-120b's 46, and 212 of Gemma's 230); the model that answers directly leaks through two, 0.33 pollution-zone reroutes and 0.49 actions per incident that needed the human's approval and had none. With the guard added (M4) executed violations are zero by construction;

TABLE III
WORKED EXAMPLE: POLL-007 (POLLUTION SPIKE), MODE D3-ROLES-NAIVE-GUARD

Step	Role	Action	Evidence	Guard	Rule	Note
0	Pollution	reduce_traffic_zone	E5 (verified)	allow	–	
0	Traffic	reroute_traffic	E3 (verified)	sanitize	pollution_zone	pollution_zone_reroute
0	PublicTransport	add_public_transport_capacity	E3 (verified), E5 (verified)	allow	–	
0	CitizenComms	broadcast_alert	E4 (unverified)	request_evidence	public_comm	unsupported_public_communication
1	Pollution	write_memory (incident)	E1 (unverified)	deny	memory_provenance	unsupported_memory_write
1	CitizenComms	request_verification (E4)	E4 (unverified)	allow	–	
2	Pollution	write_memory (incident)	E5 (verified)	allow	–	
2	Traffic	request_verification (E4)	E4 (unverified)	allow	–	
2	CitizenComms	broadcast_alert	E4 (verified)	escalate	approval	missed_approval
3	CitizenComms	broadcast_alert	E4 (verified)	allow	–	

Derived. attempted violations: 4 = pollution_zone_reroute × 1, unsupported_public_communication × 1, unsupported_memory_write × 1, missed_approval × 1; executed violations: 0; escalations: 1; overseer load (distinct approval requests reaching the human): 1; granted 1, denied 0; TSC: executed high-impact actions 3, supported 3 → 1.00; GAU = success - 0.3·executed violations - 0.2·missed approvals - 0.1·unsupported memory writes - 0.1·steps/16 - 0.3·hidden harm = 0.97.

TABLE IV
DETERMINISTIC REFERENCE ROWS, 80 SCENARIOS (20 PER FAMILY), RULE SET R2. NAIVE ROLES DO NOT KNOW THE RULES; PROCEDURAL ROLES FOLLOW THEM. ATT. AND EXEC. VIOL.: ATTEMPTED AND EXECUTED VIOLATIONS PER EPISODE; OVERSEER: APPROVAL REQUESTS REACHING THE HUMAN PER EPISODE; SILENT VIOL.: SHARE OF SUCCESSFUL EPISODES WITH AN EXECUTED VIOLATION; HIDDEN HARM: SHARE OF EPISODES WITH AN APPROVAL-BOUND ACTION EXECUTED WHERE THE HUMAN WOULD HAVE REFUSED.

Mode	Succ.	Steps	Prop.	Att. viol.	Exec. viol.	Missed appr.	Overseer	TSC	False alert	Hidden harm	Silent viol.	GAU
D0 direct naive noguard	1.00	3.95	3.95	2.00	2.00	0.06	0.00	0.20	0.33	0.07	0.99	0.34
D2 roles naive noguard	1.00	1.25	4.19	2.08	2.08	0.06	0.00	0.16	0.24	0.07	1.00	0.33
D3 roles naive guard	1.00	4.49	11.45	3.91	0.00	0.00	0.64	1.00	0.00	0.00	0.00	0.97
D4 roles procedural noguard	1.00	4.54	9.96	0.00	0.00	0.00	0.64	1.00	0.00	0.00	0.00	0.97
D5 roles procedural guard	1.00	4.54	9.96	0.00	0.00	0.00	0.64	1.00	0.00	0.00	0.00	0.97
D6 direct procedural noguard	1.00	6.96	6.50	0.00	0.00	0.00	0.64	1.00	0.00	0.00	0.00	0.96

the reduction from M2 is significant for every model (Holm $p \leq 0.003$). For the three reasoning models success, steps, approval requests and tokens do not change ($p = 1$ for each measure); for Qwen3.5-122B the guard costs 14 points of success (-0.14 $[-0.21, -0.08]$, $p = 0.005$) and 1.7 steps, for a reason **RQ2** returns to. The guard alone (M3), with roles that do not know the rules, also executes zero violations but has more to stop, 0.58, 0.80, 1.57 and 1.44 attempts per incident; knowing the rules removes most of that work, with attempts falling to 0.06, 0.22, 0.90 and 0.72 in M4 ($p < 0.001$ for each model).

For Glimmer the trace shows what the guard did. In M4 it sanitised the 15 reroutes the model still proposed and nothing else; the other five rules of R2 the model kept in every one of 240 incidents: no missed approval, no unsupported message or note, no false alert, no action outside its scope. The approval rule separates the models (Table VII): no reasoning model executed an approval-bound action in M2 except Gemma 4 E4B, eight times in 240 incidents; Qwen3.5-122B did so 389 times in 800: 217 while its own request was still pending, 153 without a request, 130 of them the road closure that cuts hospital access, and 19 after a refusal. In 106 of those 130 closures the model's rationale says that the closure needs human approval, and in 93 its reported probability q is 1.0; its prompt names the action that asks ("use the escalate action to request it") and shows the pending answer in every observation. It marks the action as needing approval and proposes it anyway, and without a guard nothing turns the mark into a request.

With no rules anywhere (M1) the same roles execute 0.53, 0.74, 1.34 and 1.35 violations per incident, and the models differ in what they do unprompted. Glimmer verifies and asks on its own (114 of its 126 violations are pollution-zone reroutes); gpt-oss-120b and Qwen3.5-122B do not ask (0.39 and 0.70 missed approvals per incident, hidden harm in 5% and 7% of the incidents). The rules in the prompt remove three quarters of the violations for Glimmer and gpt-oss-120b (-0.40 $[-0.50, -0.30]$ and -0.55 $[-0.65, -0.45]$, $p < 0.001$), and with them every missed approval and the hidden harm; for Gemma 4 E4B they remove a quarter (-0.38 $[-0.65, -0.11]$, $p < 0.001$), for Qwen3.5-122B a third (-0.50 $[-0.69, -0.32]$, $p < 0.001$) and none of the harm (6%). One agent with every tool and the rules in its prompt (M0) keeps the rules about as well as the prompted society for Glimmer and gpt-oss-120b, 0.02 and 0.11 violations per incident (for Glimmer not significantly more than M3's zero, Holm $p = 1$), and worse for the other two (1.43 and 1.93). The guard without any rules in the prompts (M3 against M1) removes the violations at no cost for Glimmer, which asks and verifies on its own ($p = 1$ for success, steps and requests), and at a cost for the others: 0.34 to 0.58 more requests per incident, 0.5 to 1.7 more steps, and 10 and 11 points of success for Gemma 4 E4B and Qwen3.5-122B ($p \leq 0.03$). [TODO: API: one sentence per API model with its M2 executed violations and its M4 value, from the same table; say whether the leaking rule is the same.]

*d) **RQ2** Cost:* Enforcement without the rules in the prompt has a price, and the models pay it in different curren-

TABLE V

LLM-DRIVEN ROLES: MEANS OVER 80 SCENARIOS PER MODEL AND MODE, RULE SET R2. COLUMNS AS IN TABLE IV; HALLUC.: SHARE OF CITED EVIDENCE IDS THAT DO NOT EXIST OR WERE NOT VISIBLE TO THE ROLE; FORMAT FAIL.: ANSWERS PER EPISODE INVALID TWICE IN A ROW.

Model	Mode	Succ.	Steps	Att. viol.	Exec. viol.	Missed appr.	Overseer	TSC	Halluc.	False alert	Hidden harm	Silent viol.	Format fail.	Tokens	GAU
Gemma 4 E4B	M0 (one agent, rules in prompt)	0.45	12.70	1.43	1.43	0.06	0.46	0.77	0.00	0.00	0.02	0.58	0.00	32.6k	-0.08
	M1 (roles, no rules)	0.78	8.15	1.34	1.34	0.20	1.94	0.96	0.00	0.00	0.07	0.68	0.00	43.1k	0.26
	M2 (roles, rules in prompts)	0.74	8.66	0.96	0.96	0.03	0.98	0.98	0.00	0.00	0.01	0.44	0.03	51.6k	0.39
	M3 (roles, guard)	0.68	9.57	1.57	0.00	0.00	2.27	1.00	0.00	0.00	0.00	0.00	0.00	49.0k	0.62
	M4 (roles, rules and guard)	0.75	8.81	0.90	0.00	0.00	0.93	1.00	0.00	0.00	0.00	0.00	0.01	52.3k	0.69
Glimmer 30B	M0 (one agent, rules in prompt)	0.90	8.10	0.02	0.02	0.00	0.31	1.00	0.00	0.00	0.00	0.02	0.00	25.7k	0.85
	M1 (roles, no rules)	0.92	8.32	0.53	0.53	0.05	0.50	1.00	0.00	0.00	0.00	0.46	0.04	43.8k	0.70
	M2 (roles, rules in prompts)	0.96	4.22	0.12	0.12	0.00	0.34	1.00	0.00	0.00	0.00	0.12	0.04	28.7k	0.90
	M3 (roles, guard)	0.90	8.22	0.58	0.00	0.00	0.56	1.00	0.00	0.00	0.00	0.00	0.06	43.5k	0.84
	M4 (roles, rules and guard)	0.96	4.23	0.06	0.00	0.00	0.35	1.00	0.00	0.00	0.00	0.00	0.03	29.1k	0.94
gpt-oss-120b	M0 (one agent, rules in prompt)	0.95	6.98	0.11	0.11	0.00	0.39	0.96	0.00	0.00	0.00	0.10	0.00	25.2k	0.88
	M1 (roles, no rules)	0.97	4.18	0.74	0.74	0.39	0.62	1.00	0.00	0.00	0.05	0.63	0.00	29.2k	0.63
	M2 (roles, rules in prompts)	0.97	4.27	0.19	0.19	0.00	0.54	1.00	0.00	0.00	0.00	0.18	0.00	30.2k	0.89
	M3 (roles, guard)	0.97	4.64	0.80	0.00	0.00	0.97	1.00	0.00	0.00	0.00	0.00	0.00	31.6k	0.94
	M4 (roles, rules and guard)	0.97	4.17	0.22	0.00	0.00	0.53	1.00	0.00	0.00	0.00	0.00	0.00	29.3k	0.94
Qwen3.5-122B	M0 (one agent, rules in prompt)	0.42	12.65	1.93	1.93	0.89	0.35	0.81	0.00	0.00	0.07	0.89	0.00	21.7k	-0.44
	M1 (roles, no rules)	0.99	4.59	1.35	1.35	0.70	0.47	0.98	0.00	0.00	0.07	0.70	0.00	16.3k	0.40
	M2 (roles, rules in prompts)	0.97	5.04	0.85	0.85	0.49	1.33	0.99	0.00	0.00	0.06	0.51	0.00	20.5k	0.57
	M3 (roles, guard)	0.88	6.28	1.44	0.00	0.00	1.05	1.00	0.00	0.00	0.00	0.00	0.00	20.3k	0.84
	M4 (roles, rules and guard)	0.83	6.71	0.72	0.00	0.00	1.45	1.00	0.00	0.00	0.00	0.00	0.00	25.7k	0.79
GPT-6 Sol	M0–M4														
GPT-6 Luna	M0–M4														

TABLE VI

PAIRED DIFFERENCES PER MODEL (SECOND MODE MINUS FIRST, MEANS OVER 80 SCENARIOS); STARS: HOLM-CORRECTED WILCOXON p BELOW 0.05, 0.01 AND 0.001. INTERVALS AND CLIFF'S δ IN THE ARTIFACT.

Model	Pair	Exec. viol.	Att. viol.	Succ.	Steps	Overseer	Tokens
Gemma 4 E4B	M3 − M2	-0.96***	+0.61***	-0.06	+0.90	+1.29***	-2.6k
	M4 − M2	-0.96***	-0.06	+0.01	+0.15	-0.05	+0.7k
	M4 − M3	+0.00	-0.67***	+0.07	-0.75	-1.35***	+3.3k
Glimmer 30B	M3 − M2	-0.12**	+0.46***	-0.07	+4.00***	+0.22**	+14.8k***
	M4 − M2	-0.12**	-0.06	+0.00	+0.02	+0.02	+0.4k
	M4 − M3	+0.00	-0.52***	+0.07	-3.99***	-0.20*	-14.4k***
gpt-oss-120b	M3 − M2	-0.19***	+0.61***	+0.00	+0.37	+0.43***	+1.5k
	M4 − M2	-0.19***	+0.03	+0.00	-0.10	-0.01	-0.9k
	M4 − M3	+0.00	-0.58***	+0.00	-0.47*	-0.44***	-2.4k
Qwen3.5-122B	M3 − M2	-0.85***	+0.60***	-0.09	+1.23	-0.27*	-0.2k
	M4 − M2	-0.85***	-0.13	-0.14**	+1.67***	+0.13	+5.2k***
	M4 − M3	+0.00	-0.73***	-0.05	+0.43	+0.40***	+5.4k***
GPT-6 Sol	all pairs						
GPT-6 Luna	all pairs						

TABLE VII

THE LEAK RULE BY RULE: EXECUTED VIOLATIONS PER INCIDENT WITH THE RULES IN THE PROMPTS AND NO GUARD (M2), AND BLOCKED ATTEMPTS PER INCIDENT UNDER THE GUARD WITH ROLES THAT DO NOT KNOW THE RULES (M3); RULE SET R2, 80 SCENARIOS, REPEATS AS IN TABLE V.

Rule	Gemma 4 E4B		Glimmer 30B		gpt-oss-120b		Qwen3.5-122B	
	M2 exec.	M3 blocked	M2 exec.	M3 blocked	M2 exec.	M3 blocked	M2 exec.	M3 blocked
scope	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
memory provenance	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00
public communication	0.00	0.20	0.00	0.00	0.00	0.02	0.00	0.01
evidence	0.04	0.17	0.00	0.00	0.00	0.00	0.03	0.10
approval	0.03	0.24	0.00	0.10	0.00	0.41	0.49	0.85
pollution zone	0.88	0.96	0.12	0.48	0.19	0.37	0.33	0.48
all rules	0.96	1.57	0.12	0.58	0.19	0.80	0.85	1.44

cies. Glimmer pays in steps and tokens: M3 needs 8.2 steps per incident against 4.2 for M2 ($+4.0$ $[3.2, 4.8]$, $\delta = 0.78$, $p < 0.001$), half as many tokens again (43.5k against 28.7k), 0.22 more approval requests per incident ($p = 0.003$), and resolves 90% of the incidents against 96% (-0.07 $[-0.11, -0.03]$, Holm $p = 0.08$). gpt-oss-120b and Gemma 4 E4B pay in human attention: their roles do not ask, so the guard escalates every action that needs approval, and the human receives 0.97 instead of 0.54 and 2.27 instead of 0.98 requests per incident ($p < 0.001$ for both), at little cost in steps and no significant loss of success. For these three models M4 pays nothing: with the rules in the prompt and the guard behind them, every cost measure equals M2's within noise, and governance-adjusted utility is highest in M4. Formatting failures stay at or below 0.06 per incident, and no role repeated a blocked proposal at its next step: the guard's reason is read.

Qwen3.5-122B breaks the cost half of our hypothesis, and the trace says why. In M2 it resolved 97% of the incidents by not waiting: 217 of its approval violations executed while the request was pending and 153 without a request. Under the guard those actions wait for the human's answer or are refused, and the roles do not find the compliant alternative: all 135 failures of M4 lack the public alert, 79 of them with the alert's approval refused and no fallback to a targeted notice, the rest in verification or escalation loops. The guard alone lowers its success by 9 points (-0.09 $[-0.15, -0.03]$, not significant after correction, Holm $p = 0.32$), the guard with the rules in the prompt by 14 ($p = 0.005$), 1.7 steps and 5.2k tokens; the rules in the prompt make its roles ask more, 1.33 requests per incident in M2 against 1.05 under the guard alone, and more refusals follow. The cost comes from the approval rule, not the guard: M2's success rested on approvals its roles skipped.

One agent with every tool is the cheapest configuration in tokens and approval requests and the slowest in steps. Glimmer's single agent needs 8.1 steps per incident, as many as M3, because it acts once per step where the roles act in parallel (8 proposals per incident against 17), with 41% fewer tokens (25.7k against 43.5k) and half the approval requests; M2 and M4 resolve the same incidents in 4.2 steps. For gpt-oss-120b it is also slower (7.0 steps against 4.6 in M3); for Gemma 4 E4B and Qwen3.5-122B it is the worst configuration in success and violations (45% and 42% success, 1.43 and 1.93 violations per incident). [TODO: API: tokens and steps per API model in M2 and M4, one sentence; the cost comparison

across models.]

Most of the requests Glimmer's roles send the human were not required by the rules (64% in M2 and M4, 71% in M3): it asks whenever hospital access is at risk, whatever the action; for the other models the share is 31 to 59%. The human's load is set as much by the model's caution as by the rule set; it is what the trust-adaptive governor removes.

e) ***RQ3*** *What success hides:* Success hides violations in every unguarded mode: in M2, 12%, 18%, 44% and 51% of the successful episodes (Glimmer, gpt-oss-120b, Gemma 4 E4B, Qwen3.5-122B) contain an executed violation; without rules (M1) 46%, 63%, 68% and 70%. The incident is resolved, the trace says a rule was broken, and nothing in the final state does. Under the guard the share is zero by construction. Hidden harm occurs only in unguarded modes of the three models that act without asking (1 to 7% of the incidents, Table V), never for Glimmer and never under the guard. The provenance metrics stayed clean for every model: no model ever broadcast the planted false report, in any mode, where the naive deterministic roles did so in every episode that had one; all four verify a report before they repeat it (trace support coverage 0.96 to 1.00 in the role modes, 0.77 and 0.81 for the two weak single agents), and no cited evidence id was invented.

The failures themselves all end at the 16-step horizon and come from two mechanisms. The first is an *approval lockout*: a role asks the human for an approval the rules do not require, the answer is a refusal, because the human is absent or knows something the roles do not, and the role respects the refusal for the rest of the episode. For Glimmer all 18 failures of M2 and M4 are of this kind, in the same three scenarios in every repeat, each with hospital access at risk. gpt-oss-120b locks itself out in the same three scenarios (13 of its 14 failures in M2 and M4). The guard did not cause it and, as long as a refusal binds, cannot prevent it: it binds whether the request was needed or not. The second is an *evidence loop*: a role requests evidence or verification again and again and never proposes the message or action the incident needs. For Glimmer it occurs only without the rules in the prompt (20 of the 25 M3 failures), always the communication role never sending the public alert; with the rules it sends a targeted notice in the same scenarios. For Gemma 4 E4B it occurs with the rules too and is why it fails a quarter of the incidents in M2 and M4, almost all flooded underpasses: the communication role spends the episode asking to verify a residents' report it cannot check itself, nobody takes the forwarded request up, and the notice is never sent, although verified sensor readings it could cite are in the store.

The single agent fails in a third way, losing track of what is done: in 20 of Glimmer's 23 failures in M0, all traffic accidents, it secures the hospital route again and again and never sends the public notice.

f) ***RQ4*** *Robustness:* Table VIII splits the leak and the cost by incident family and by evidence quality. The two larger models leak where there is something to govern, in the two families with active pollution zones, and almost nowhere else; the two weaker ones leak in every family, most in flooded underpasses; the guard brings every stratum to zero. The guard's cost in steps is largest in flooded underpasses, the family with the most approval and evidence rules in play, and when the evidence is missing at the start, where the roles must query before they can act. By evidence quality the leak is flat for the two larger models (0.06 to 0.24 per incident) and uneven for the two weaker ones. The ranking of the modes does not depend on the utility weights: in every one of the 243 settings a governed mode ranks first for every model, M4 for three of them and M3 for Qwen3.5-122B. Size does not order the leak through the prompt: 0.96 executed violations per incident for the 4B model, 0.12 for the 30B, 0.19 for the 120B and 0.85 for the 122B that answers without reasoning; the guard brings all four to zero. Table IX separates the model from the way it was run. Gemma 4 E4B with its reasoning off behaves like Qwen3.5-122B: with the rules in its prompt it executes 1.95 violations per incident instead of 0.96 ($+0.99$ $[0.46, 1.53]$, $p < 0.001$), 1.23 of them actions that needed approval where the same model with reasoning skipped 0.03 (160 never requested, 55 while the request was pending, 81 after a refusal; in 96 of the 160 its reported q was 1.0), and hidden harm rises from 1% to 9%. The guard brings the violations to zero at 10 points of success (-0.10, Holm $p = 0.07$), the approvals it had skipped: the approval leak follows answering without reasoning, not the model. The reinforced prompt removes part of the leak and none of it entirely. Gemma 4 E4B falls from 0.96 to 0.55 executed violations per incident (-0.41 $[-0.58, -0.26]$, $p < 0.001$), the remaining 120 all pollution-zone reroutes, at the same success. Qwen3.5-122B falls from 0.85 to 0.63 (-0.21 $[-0.34, -0.08]$, $p < 0.001$), missed approvals from 0.49 to 0.35; its roles ask more often (1.78 requests per incident instead of 1.33) and 65 of the 83 remaining approval violations execute while that request is pending: the prompt made them ask, not wait. More requests bring more refusals (0.54 against 0.32 per incident) and success falls from 0.97 to 0.85 ($p < 0.001$): the stronger prompt buys this model a quarter of its leak at 12 points of success. The sweeps over rule sets and human availability (Glimmer and Qwen3.5-122B, M2 and M3, one repeat; table in the artifact) hold the pattern. Under the lenient R1 neither mode attempts a violation; under the strict R3 the prompted roles still leak three pollution-zone reroutes but skip

TABLE VIII

THE LEAK AND THE COST BY INCIDENT FAMILY AND BY EVIDENCE QUALITY: EXECUTED VIOLATIONS PER INCIDENT WITH THE RULES IN THE PROMPTS (M2) AND STEPS PER INCIDENT UNDER THE GUARD ALONE (M3); RULE SET R2, 80 SCENARIOS, REPEATS AS IN TABLE V.

Stratum	**Gemma 4 E4B**		**Glimmer 30B**		**gpt-oss-120b**		**Qwen3.5-122B**	
	M2 exec.	M3 steps	M2 exec.	M3 steps	M2 exec.	M3 steps	M2 exec.	M3 steps
traffic accident	0.30	10.00	0.00	8.58	0.12	4.32	0.50	4.49
power outage	0.17	7.57	0.02	6.67	0.03	4.32	0.49	6.21
flooded underpass	2.03	14.70	0.15	10.33	0.32	6.37	1.81	9.57
pollution spike	1.33	6.00	0.32	7.30	0.30	3.55	0.59	4.85
evidence complete	1.13	8.71	0.13	8.49	0.24	4.18	0.99	5.73
evidence partial	0.80	9.25	0.14	7.84	0.16	4.95	0.91	6.36
evidence missing	1.45	11.03	0.15	9.02	0.17	4.75	0.80	7.04
evidence conflicting	0.50	9.13	0.06	7.69	0.22	4.43	0.67	5.77

TABLE IX

CONTROLS NEXT TO THE ROWS OF THE MAIN RUN: GEMMA 4 E4B WITH ITS REASONING OFF, AND THE REINFORCED PROMPT FOR GEMMA 4 E4B AND QWEN3.5-122B; MEANS OVER 80 SCENARIOS, THREE REPEATS.

Run	Mode	Succ.	Steps	Exec. viol.	Missed appr.	Overseer	Hidden harm	Tokens
Gemma 4 E4B (Table V)	M2	0.74	8.66	0.96	0.03	0.98	0.01	51.6k
	M3	0.68	9.57	0.00	0.00	2.27	0.00	49.0k
	M4	0.75	8.81	0.00	0.00	0.93	0.00	52.3k
reasoning off	M2	0.48	10.66	1.95	1.23	1.15	0.09	43.2k
	M3	0.39	11.37	0.00	0.00	1.57	0.00	42.2k
	M4	0.38	11.75	0.00	0.00	1.33	0.00	48.3k
reinforced prompt	M2	0.75	8.17	0.55	0.03	0.88	0.00	55.2k
Qwen3.5-122B (Table V)	M2	0.97	5.04	0.85	0.49	1.33	0.06	20.5k
reinforced prompt	M2	0.85	6.06	0.63	0.35	1.78	0.05	28.7k

no approval: they ask for every one (1.10 requests per incident) and resolve 86% of the incidents. The guard alone pays most under R3: 1.16 blocked attempts per incident, half of them sent to the human, 0.31 refused requests and 76% success (-0.10 against M2, not significant after correction with one repeat). With the human never available under R2, Glimmer's guarded society keeps its success (0.94 against 0.90 in the main run). It is the prompted roles that lose five points (0.91 against 0.96), almost all in flooded underpasses: they ask for approvals the rules do not require, and the refusal stops them, the approval lockout of **RQ3**. Qwen3.5-122B, which does not wait for the human, shows the mirror image. With the human never available its prompted roles keep 100% success by acting without the answer, with 0.84 violations per incident and hidden harm in 6%. Its guarded roles fall to 72%, because every refused request binds. Under R3 the prompted roles execute 2.38 violations per incident and harm hidden context in 16% of the incidents; the guard holds violations at zero at 65% success. [TODO: API: whether the two API models show the same pattern (executed violations above zero in M2, zero in M3 and M4, the cost of M3) and where they differ from Glimmer, with the per-model rows of Table V.]

*g) **RQ5** Transfer to software operations:* The deterministic pattern repeats in the incident response domain (rows in the artifact): roles that ignore the rules execute 1.9 violations per incident, skip an approval in every second incident and post an untrue status page message in 23% of the episodes; under the guard, zero violations and 1.06 approval requests per incident, more than in the city because more remediation actions need a person. Glimmer and gpt-oss-120b (Table X) show the leak and the zero of the city through a different rule: with the rules in their prompts they execute 0.11 and 0.20 violations per incident, all of them actions that needed approval and were never requested. Glimmer leaks isolations of a critical dependency and scale-outs beyond four replicas while requesting every status page approval; gpt-oss-120b leaks disk purges and dependency isolations and, in 3% of the incidents, acts against hidden context. The guard brings both to zero ($p \leq 0.005$). M4 costs Glimmer nothing (success 0.98 against 0.96, steps, requests and tokens within noise) and gpt-oss-120b 0.20 requests per incident ($p = 0.002$), as in the city; the guard alone costs 0.41 and 0.65 more requests and 2.4 and 1.3 more steps ($p < 0.001$ for all four) at the same success. Nothing in the guard, the metrics or the statistics was




Fig. 2. Overseer load against hidden harm for static and trust-adaptive governance, rule set R3, hidden context in 15% of scenarios: the two deterministic policies and Glimmer's roles under the guard alone. Points are thresholds from right to left (deterministic: 0.9, 0.7, 0.5, 0.3, 0.0; Glimmer: 0.7, 0.3, 0.0); for the procedural roles the four lowest coincide.

touched between the two domains. A first run of this domain hid the storage and traffic telemetry from the diagnosis role, against its own job description, which then looped on queries in a third of the incidents in every mode; the visibility table was corrected and Glimmer rerun (first run in the artifact).

h) Trust-adaptive governance: Figure 2 shows the trade-off under R3 with hidden context in 15% of the scenarios, for the two deterministic policies and for Glimmer's roles under the guard alone (one repeat). With deterministic roles the static guard puts two requests per incident on the human and resolves 86% of the incidents with no hidden harm; delegating every soft approval to roles that have earned trust removes the human's load, restores 100% success and brings hidden harm to 16%, every hidden-context scenario. Glimmer's roles trace the same line from a lower start: the static guard costs them 1.07 requests per incident at 76% success; at a threshold of 0.7 they earn delegation after a few incidents (0.17 requests, 90% success, hidden harm in 11%), and at 0.3 or below the human is asked once in a hundred incidents, success is 95 to 97% and hidden harm 14 to 15%. Trust earned by compliance says nothing about what the rules do not encode, which is exactly what the human was there for. By our default weights full delegation even scores higher (0.93 against 0.82 for the deterministic roles); which end is better depends on what a hidden harm and an unresolved incident cost.

VII. DISCUSSION

a) Prompted rules are not enforced rules: Prompting got Glimmer most of the way: with the rules in its prompts five of the six were kept in every one of 240 incidents; the sixth makes the case. The pollution-zone rule is the only one whose trigger is a state flag rather than evidence or an approval, and the model kept rerouting through the zone in one incident out of eight; under the guard it never did. Qwen3.5-122B, answering without reasoning, is the sharpest case: 106 times it wrote that a closure needed human approval and closed the road. A role can hold the rule and not the mechanism; the guard is the mechanism. Insisting does not change that: told to ask first and wait, with the rules repeated at every step, Qwen3.5-122B asked more and still did not wait, and Gemma 4 E4B kept half of its reroutes; Gemma with its reasoning off leaked what Qwen leaked. In the second domain both models

TABLE X
SOFTWARE INCIDENT RESPONSE, GLIMMER AND GPT-OSS-120B: RULES IN PROMPTS (M2), GUARD (M3), BOTH (M4); 80 SCENARIOS, THREE REPEATS, RULE SET R2, COLUMNS AS IN TABLE V.

Model	Mode	Succ.	Steps	Att. viol.	Exec. viol.	Missed appr.	Overseer	TSC	Halluc.	False alert	Hidden harm	Silent viol.	Format fail.	Tokens	GAU
Glimmer 30B	M2 (roles, rules in prompts)	0.96	8.02	0.11	0.11	0.11	0.30	1.00	0.00	0.00	0.01	0.12	0.00	40.8k	0.85
	M3 (roles, guard)	0.96	10.40	0.27	0.00	0.00	0.71	1.00	0.00	0.00	0.00	0.00	0.00	47.7k	0.89
	M4 (roles, rules and guard)	0.98	7.69	0.09	0.00	0.00	0.38	1.00	0.00	0.00	0.00	0.00	0.00	39.2k	0.93
gpt-oss-120b	M2 (roles, rules in prompts)	0.94	5.54	0.20	0.20	0.20	0.28	1.00	0.00	0.00	0.03	0.20	0.00	30.1k	0.80
	M3 (roles, guard)	0.93	6.81	0.32	0.00	0.00	0.93	1.00	0.00	0.00	0.00	0.00	0.00	35.7k	0.89
	M4 (roles, rules and guard)	0.95	5.56	0.20	0.00	0.00	0.47	1.00	0.00	0.00	0.00	0.00	0.00	30.5k	0.91

kept the counterpart of the pollution rule and leaked approval rules they had kept in the city, each with a condition on the target or the payload. Which rule leaks depends on the model; that the guard catches it does not. A rule in a prompt is a consideration the model weighs against the task; a rule in the guard is a constraint on what can execute. The two also fail differently: prompted roles asked for approvals the rules did not require and a refusal then cost the incident; roles that met the rules only in the guard paid to discover them, in steps and tokens or in requests to the human. The combination removes both costs where the roles can walk the compliant path: the rules in the prompt tell them where it is, the guard catches what the prompt did not prevent, and the trace records what each one did. Where they cannot, as Qwen3.5-122B could not when an alert's approval was refused, the guard turns a hidden violation into a visible failure, and the trace shows whether to change the model, the fallback or the rule. For an engineer the recommendation is plain: write the rules once, give them to the roles as text and to the guard as data, and read the trace, not the outcome, to find out which of the two did the work.[TODO: API: one clause on whether the API models leaked the same rule or a different one.]

b) One agent or a society: One agent with every tool is cheaper in tokens and approval requests and slower in steps. For Glimmer and gpt-oss-120b it kept the rules about as well as the prompted society, but it acts once per step and loses track: Glimmer's single agent kept securing a route that was already secure while the public notice waited; for the two weaker models it was the worst configuration in success and violations. The society's roles act at once, and the guard is what keeps that parallelism within the rules.

c) The human is not a rule: The approval step looks like a bottleneck and, under strict rules and an absent human, it is: success drops to a half. The adaptive governor shows what removing it costs: the rules capture what the designers foresaw, the human catches the rest, and compliance with the rules does not predict the rest (by construction here: hidden context is drawn independently). To reduce human load, reduce the *unnecessary* share of approval requests, which the trace measures, rather than delegate on trust.

d) Threats to validity: Construct: the testbed is symbolic and its rules are ours; hidden context is a coin flip with a fixed rate, and its harm is binary. The metrics measure conformance to the given rules, not the quality of the rules. *Internal*: the naive roles' reactions to the guard were written by us; a different reactive policy would change the cost side, not the violation side. The human model counts absence as refusal and lets a refusal bind even when no rule required the request; the approval lockouts follow from it, and a guard that waived such refusals would remove them. The single agent acts once per step, so the 16-step horizon binds it more than the roles. The sweeps and the trust-adaptive run have one repeat, and the governor ran with one LLM. LLM nondeterminism is handled by repeats and paired tests; prompts are fixed and published, not tuned per model, so the small model's evidence loops bound what an untuned prompt achieves. *External*: two domains that we built to correspond, four open-weight models, each at one sampling setting[TODO: API: "and two API models from one provider"], a deterministic human. One reasoning-off control on one model separates reasoning from the model, and the reinforced prompt is one of many possible prompts. The second domain was corrected once, after a visibility error that cost success equally in every mode, and rerun. The framework transfers when a domain module can be written, as it was for incident response; whether the numbers transfer is an open question. *Conclusion*: all comparisons are paired, corrected for multiple testing and reported with intervals; seeds, scenario sets and manifests are in the artifact.

VIII. CONCLUSION

Governed agent societies put the rules where the actions are: in a guard inside the transition function that checks provenance, asks a person when the rules say so, and leaves a trace of everything it decided. With four LLMs driving the roles, the rules in the prompt still leaked between one violation per eight incidents and one per incident. The reasoning models leaked through one rule; the models that answer directly also through approvals they marked as required and did not wait for. A prompt that repeated the rules at every step removed a quarter to a half of the leak; the guard removed all of it, at no cost once reasoning roles knew the rules, at a price in steps or human requests when they did not, and at the price of the skipped approvals for the models that had succeeded by skipping them. Success and governance are different things: up to half of the successful incidents of roles governed by their prompts alone hid a violation, two thirds without rules, and every harm came from acting where only a person knew better. Next are role policies learned from the traces and a human who is not deterministic. Testbed, traces, statistics and a one-command reproduction of every table are at [TODO: anonymous link].

References

[1] S. Yao *et al.*, "ReAct: Synergizing reasoning and acting in language models," 2023, ICLR 2023; arXiv:2210.03629.

[2] Q. Wu *et al.*, "AutoGen: Enabling next-gen LLM applications via multi-agent conversation," 2023, arXiv:2308.08155.

[3] G. Li *et al.*, "CAMEL: Communicative agents for "mind" exploration of large language model society," 2023, NeurIPS 2023; arXiv:2303.17760.

[4] M. Cemri, M. Z. Pan, S. Yang *et al.*, "Why do multi-agent LLM systems fail?" in *Advances in Neural Information Processing Systems (NeurIPS)*, 2025, arXiv:2503.13657.

[5] L. Sha, "Using simplicity to control complexity," *IEEE Software*, vol. 18, no. 4, pp. 20–28, 2001.

[6] M. Alshiekh, R. Bloem, R. Ehlers, B. Könighofer, S. Niekum, and U. Topcu, "Safe reinforcement learning via shielding," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 32, 2018, pp. 2669–2678.

[7] H. Wang, C. M. Poskitt, and J. Sun, "AgentSpec: Customizable runtime enforcement for safe and reliable LLM agents," in *Proceedings of the 48th IEEE/ACM International Conference on Software Engineering (ICSE)*, 2026.

[8] J. O. Kephart and D. M. Chess, "The vision of autonomic computing," *IEEE Computer*, vol. 36, no. 1, pp. 41–50, 2003.

[9] M. Salehie and L. Tahvildari, "Self-adaptive software: Landscape and research challenges," *ACM Transactions on Autonomous and Adaptive Systems*, vol. 4, no. 2, pp. 1–42, 2009.

[10] D. Weyns, *An Introduction to Self-adaptive Systems: A Contemporary Software Engineering Perspective*. Wiley, 2020.

[11] D. Weyns, B. Schmerl, V. Grassi, S. Malek, R. Mirandola, C. Prehofer, J. Wuttke, J. Andersson, H. Giese, and K. M. Göschka, "On patterns for decentralized control in self-adaptive systems," in *Software Engineering for Self-Adaptive Systems II*, ser. LNCS. Springer, 2013, vol. 7475, pp. 76–107.

[12] R. Calinescu, D. Weyns, S. Gerasimou, M. U. Iftikhar, I. Habli, and T. Kelly, "Engineering trustworthy self-adaptive software with dynamic assurance cases," *IEEE Transactions on Software Engineering*, vol. 44, no. 11, pp. 1039–1069, 2018.

[13] J. Cámara, G. A. Moreno, and D. Garlan, "Reasoning about human participation in self-adaptive systems," in *Proceedings of the 10th International Symposium on Software Engineering for Adaptive and Self-Managing Systems (SEAMS)*, 2015, pp. 146–156.

[14] N. Li, S. Adepu, E. Kang, and D. Garlan, "Explanations for human-on-the-loop: A probabilistic model checking approach," in *Proceedings of the 15th International Symposium on Software Engineering for Adaptive and Self-Managing Systems (SEAMS)*, 2020, pp. 181–187.

[15] P. Maia, L. Vieira, G. L. B. de Oliveira, M. Chagas, A. Bandeira, and C. Rocha, "MAPER: Extending MAPE-K with LLM-based reasoning to manage unanticipated situations in self-adaptive systems," in *Proceedings of the 21st International Symposium on Software Engineering for Adaptive and Self-Managing Systems (SEAMS)*, 2026.

[16] J. Li, M. Zhang, N. Li, D. Weyns, Z. Jin, and K. Tei, "Exploring the potential of large language models in self-adaptive systems," in *Proceedings of the 19th International Symposium on Software Engineering for Adaptive and Self-Managing Systems (SEAMS)*, 2024, pp. 77–83.

[17] I. ElSayed-Aly, S. Bharadwaj, C. Amato, R. Ehlers, U. Topcu, and L. Feng, "Safe multi-agent reinforcement learning via shielding," in *Proceedings of the 20th International Conference on Autonomous Agents and MultiAgent Systems (AAMAS)*, 2021, pp. 483–491.

[18] A. H. Brorholt, K. G. Larsen, and C. Schilling, "Compositional shielding and reinforcement learning for multi-agent systems," in *Proceedings of the 24th International Conference on Autonomous Agents and Multiagent Systems (AAMAS)*, 2025, arXiv:2410.10460.

[19] Y. Falcone, L. Mounier, J.-C. Fernandez, and J.-L. Richier, "Runtime enforcement monitors: composition, synthesis, and enforcement abilities," *Formal Methods in System Design*, vol. 38, no. 3, pp. 223–262, 2011.

[20] T. Rebedea, R. Dinu, M. Sreedhar, C. Parisien, and J. Cohen, "NeMo guardrails: A toolkit for controllable and safe LLM applications with programmable rails," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP): System Demonstrations*, 2023, pp. 431–445.

[21] W. Hua, X. Yang, M. Jin, Z. Li, W. Cheng, R. Tang, and Y. Zhang, "TrustAgent: Towards safe and trustworthy LLM-based agents," in *Findings of the Association for Computational Linguistics: EMNLP 2024*, 2024, arXiv:2402.01586.

[22] Z. Xiang *et al.*, "GuardAgent: Safeguard LLM agents via knowledge-enabled reasoning," in *International Conference on Machine Learning (ICML)*, 2025.

[23] T. Shi *et al.*, "Progent: Programmable privilege control for LLM agents," 2025, arXiv:2504.11703.

[24] Z. Chen, M. Kang, and B. Li, "ShieldAgent: Shielding agents via verifiable safety policy reasoning," 2025, arXiv:2503.22738.

[25] S. Yao, N. Shinn, P. Razavi, and K. Narasimhan, "τ-bench: A benchmark for tool-agent-user interaction in real-world domains," in *International Conference on Learning Representations (ICLR)*, 2025, arXiv:2406.12045.

[26] Y. Ruan, H. Dong, A. Wang, S. Pitis, Y. Zhou, J. Ba, Y. Dubois, C. J. Maddison, and T. Hashimoto, "Identifying the risks of LM agents with an LM-emulated sandbox," in *International Conference on Learning Representations (ICLR)*, 2024, arXiv:2309.15817.

[27] E. Debenedetti, J. Zhang, M. Balunović, L. Beurer-Kellner, M. Fischer, and F. Tramèr, "AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents," in *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2024, arXiv:2406.13352.

[28] J. Carmona, B. van Dongen, A. Solti, and M. Weidlich, *Conformance Checking: Relating Processes and Models*. Springer, 2018.

[29] M. Esteva, J. A. Rodríguez-Aguilar, C. Sierra, P. Garcia, and J. L. Arcos, "On the formal specification of electronic institutions," in *Agent Mediated Electronic Commerce*, ser. LNCS, vol. 1991, 2001, pp. 126–147.

[30] J. F. Hübner, J. S. Sichman, and O. Boissier, "Developing organised multiagent systems using the MOISE+ model: programming issues at the system and agent levels," *International Journal of Agent-Oriented Software Engineering*, vol. 1, no. 3/4, pp. 370–395, 2007.

[31] M. Dastani, P. Torroni, and N. Yorke-Smith, "Monitoring norms: A multi-disciplinary perspective," *The Knowledge Engineering Review*, vol. 33, p. e25, 2018.

[32] O. Boissier, R. H. Bordini, J. F. Hübner, and A. Ricci, *Multi-Agent Oriented Programming: Programming Multi-Agent Systems Using JaCaMo*. MIT Press, 2020.

[33] J. S. Park *et al.*, "Generative agents: Interactive simulacra of human behavior," 2023, UIST 2023; arXiv:2304.03442.

[34] C. Packer *et al.*, "MemGPT: Towards LLMs as operating systems," 2023, arXiv:2310.08560.

[35] N. Shinn *et al.*, "Reflexion: Language agents with verbal reinforcement learning," 2023, NeurIPS 2023; arXiv:2303.11366.