TRACE-Eval: change-aware, cost-bounded regression test selection for LLM agent systems

Ciprian Păduraru
University of Bucharest
ciprian.paduraru@unibuc.ro

Draft of 10 November 2026

Abstract

An LLM agent system is assembled from skills, prompts, tools, harness code and configuration, and verified by a suite T of tests whose cost $c(t)$ is dominated by tokens. After a change Δ, a team either reruns all of T or guesses. We formulate selection, prioritization and stopping as one problem: choose tests from T, one at a time, under a budget B, so that the regressions Δ introduces are found with high probability at low cost. The change becomes a set of components $C(\Delta)$ (code lines and functions, skill procedures and prose, agent fields, configuration keys), each broken with a prior probability π_c. A test's sensitivity $s_{tc} = P(t \text{ fails} \mid c \text{ broken})$ is calibrated from the dependencies observed in execution traces and from the record of earlier changes, and a test that already fails on the unchanged system, with rate f_t, is discounted. The posterior over the $2^{|C(\Delta)|}$ subsets of broken components is kept exactly; the next test maximises the expected information gain per token; the run stops with REGRESSION at the first failure of a test that used to pass, with CLEAN when $P(\text{some component broken} \mid \text{outcomes}) < \varepsilon$, and not before every mandatory property Δ may affect has been tested. We evaluate on a testbed: a multi-agent content-operations application whose agents are played by an open model (Gemma 4 E4B), 176 tests, 43 controlled changes applied as file edits, and a ground truth measured per model by majority over three runs. Declared dependencies miss 39% of the regressions; trace-informed selection finds 86% within 20% of the full-suite tokens; two published methods reproduced on the testbed, CASPER's slices and a risk-aware bandit, find 50% and 59% because neither reads the change; the proposed method finds 79% for 3% of the tokens, 86% of the changes that break a safety property, and gives no false verdict on the 14 changes no test reveals.

1 Introduction

A platform such as Adobe Experience Manager's agent layer ships dozens of agents. Each is a bundle of a system prompt, a list of tools, a list of skills (prompt files with a procedure the model follows), and settings, running on a shared harness that dispatches tool calls, retries, enforces approvals and delegates between agents. The platform is verified by scenario tests, which run a request end to end and check the final state and the trace, and by datasets of prompts with expected routings or tool calls. Every test is a run of a model. It costs tokens and seconds, and the cost varies by a factor of ten to a hundred between a one-shot routing item and a workflow across five agents.

After a change, the question is the one regression testing has always asked [33]: which tests to run (selection), in what order (prioritization), and when to stop. Three things make the classic answers [24, 25] hard to transfer. Much of the "code" is natural language, so coverage of a skill or a prompt is not a line of a control-flow graph. The outcome of a test is the behaviour of a model, so it is not a function of the code alone and can vary from run to run. And the cost of a test is not one unit, so an order that finds a fault after three tests can still have spent a third of the budget.

The literature on efficient evaluation of language models [10, 20, 23] answers a different question: which subset of a benchmark reproduces a score. It selects once, for all models, and not after a change. The closest work, CASPER [19], is a regression method for LLM-based systems, but it is change-aware only through drift: it runs representatives of behavioural slices on the new version and ranks the slices by how much their outcomes moved. Risk-aware adaptive evaluation [15] allocates a budget of runs with a bandit, by impact and by the outcomes seen so far. Neither reads the diff. This paper's claim is that the diff, mapped to the tests through execution traces, is worth a lot, and that a sequential Bayesian treatment of the outcomes turns selection, prioritization and stopping into one decision.

The contributions are:

1. a formulation of change-aware, cost-bounded testing of agent systems, with the metrics of regression testing adapted to token costs (Section 2);
2. a method that extracts a change set at the granularity of code lines, skill procedures, agent fields and configuration keys, maps it to tests through dependencies observed in traces, ranks tests by expected information per token in a Bayesian model whose sensitivities are calibrated from history, and stops with a verdict (Section 4);
3. a testbed with a multi-agent application, 176 tests, 43 controlled changes and a mutation-based ground truth derived per model, on which strategies are compared by offline replay (Section 5);
4. an evaluation against six baselines and two published methods reproduced on the testbed (Section 6).

2 The problem

Objects. A system has a current version V_0 and a changed version $V_1 = V_0 + \Delta$. The suite T holds tests and eval items, each with a cost $c(t) > 0$ measured in tokens (prompt and completion tokens over every model call the test makes). A budget B is a number of tokens, given as a fraction of the cost of the whole suite, $\sum_{t \in T} c(t)$. Running t on a version V gives an outcome $X_t(V) \in \{\text{pass}, \text{fail}\}$, which is random because a model produces it. K repetitions on V_0 give the baseline fail rate $f_t = \hat{P}(X_t(V_0) = \text{fail})$; a test with $f_t \geq \frac{1}{2}$ is one the model already fails, a mistake of the model rather than a fault of the system.

Ground truth. A test t *reveals* Δ when its majority outcome flips: the pass rate on V_0 is at least $\frac{1}{2}$ and the pass rate on V_1 is below $\frac{1}{2}$, both over K repetitions. $\mathcal{R}(\Delta)$ is the set of revealing tests; Δ is a regression when $\mathcal{R}(\Delta) \neq \emptyset$. A test the model already fails cannot reveal anything. The ground truth therefore belongs to the model: a change the model cannot see, because it ignores the rule with and without the change, is revealed by no test under that model, and a different model may give a different $\mathcal{R}(\Delta)$.

Policies. A policy sees the change set $C(\Delta)$, the baseline facts about every test (its traced dependencies, cost and fail rate), and the outcomes of earlier changes on which it may calibrate, but never $\mathcal{R}(\Delta)$. It chooses a test, observes its outcome and cost on V_1, and either chooses again or stops, within B. A non-adaptive policy is an order of T run greedily within the budget. An adaptive one may also return a verdict, CLEAN or REGRESSION, and a probability.

Metrics. For a regression, *detection* is whether a revealing test was run and failed, and the *cost to first detection* is the tokens spent up to that failure. *Tokens spent* is the cost of every test run, on regressions and on changes that break nothing. A *false alarm* is a failure of a test




Figure 1: From a diff to a verdict. The three inputs on the left exist before the change is tested: the diff, a traced run of the current version, and earlier changes with their known outcomes. The loop on the right runs one test at a time on the changed version.

outside $\mathcal{R}(\Delta)$, which on a change that breaks nothing is a failure the change did not cause. A verdict is *correct* when it agrees with $\mathcal{R}(\Delta) \neq \emptyset$. Prioritization alone, with every test run and no stopping, is scored by the average percentage of faults detected [25]. With $n = |T|$, $m = |\mathcal{R}(\Delta)|$ and TF_i the position in the order of the test that reveals fault i,

$$\mathrm{APFD} = 1 - \frac{\sum_{i=1}^{m} TF_i}{n\,m} + \frac{1}{2n}, \tag{1}$$

which is near 1 when the first tests find every fault and near 0 when the last ones do; a random order scores about $\frac{1}{2}$. Because costs differ by an order of magnitude, we read its cost-cognizant form [6, 16]. With c_j the cost of the j-th test in the order, $C = \sum_j c_j$, and σ_i the severity of fault i (the risk weight of its revealing test, 1 to 4),

$$\mathrm{APFD}_c = \frac{\sum_{i=1}^{m} \sigma_i \big(C - \sum_{j<TF_i} c_j - \frac{1}{2} c_{TF_i}\big)}{C \sum_{i=1}^{m} \sigma_i}. \tag{2}$$

Finding a fault after a few cheap tests costs little and scores high; finding it after the long workflows scores low, however few tests came before. An order can score well on APFD and poorly on APFD_c by putting the expensive tests first.

3 Overview

Figure 1 follows one change from the diff to a verdict. Three inputs exist before the change is tested: the diff, which becomes a change set; a traced full run of the current version, which gives every test its observed dependencies, its cost and its pass rate; and the earlier changes whose full-suite outcomes are known, which calibrate how often a test that touches a changed component of a given kind actually reveals the change. From these the model assigns a prior to every changed component and a sensitivity to every (test, component) pair. The loop then picks the test with the most expected information per token, runs it on the changed version, updates the posterior over the subsets of broken components, and repeats until a stopping rule fires: a failure of a test that used to pass, a posterior probability of any breakage below ε, or an exhausted budget. A run that found nothing does not end before every mandatory property the change may affect has a test. In a team's pipeline the nightly full-suite runs supply the traced baseline and the record of earlier changes; a pull request supplies the diff.

4 Methods

4.1 What a diff becomes

The change-set extractor compares the current and the changed trees and emits *components* with the identifiers the dependency model uses: `code:<file>::<function>` for a function whose normalised syntax tree changed, `line:<file>:<n>` for each changed line of code, `tool:<name>` when the function is a registered tool adapter, `skill:<name>#procedure`, `#prose` or `#meta` for the three parts of a skill file, `agent:<name>.<field>` for a changed field of an agent definition (an agent's tool or skill list that only lost items names them), `config:<key>` for a changed effective setting, and `fixture:<name>`. Comments, docstrings, blank lines, formatting and the order of configuration mappings add nothing: no component, no file and no diff line, so no policy and no probability can depend on them. Skill files are prompts the model reads word for word, so all of their text counts.

4.2 Dependencies

Declared dependencies are the metadata a test's author wrote. They are incomplete on purpose, as in practice: shared skills reached through an include, harness code and most configuration keys are not declared. *Observed* dependencies come from the traced baseline runs: the agents started, the agent fields the orchestrator consulted, the skills loaded, the tools called, the configuration keys read, and the code functions and lines executed, with a dynamic coverage context per test and repetition. For a test t and a dependency d, $\phi_t(d) \in [0, 1]$ is the share of t's baseline runs that exercised d. A component matches a dependency set when the set holds the component, its base (`skill:x` for `skill:x#procedure`), or a function of a module changed at module level.

4.3 Baselines

Six strategies span the design space of the literature. All see the same inputs as the method.

- `full`: the suite in catalog order (the reference). `random`: a random permutation.
- `declared`: the tests whose declared dependencies match a changed component, by risk then affinity then cost; classic selection on metadata [24].
- `ir_tfidf`: every test ranked by the TF-IDF cosine between the text of the change (file names, component ids, the diff of the code) and the text of the test (name, request, expectations), as in REPiR [26]. It uses no traces.
- `observed`: the tests whose observed dependencies match a changed component, scored by $a_t \cdot \rho_t / c(t)$, where a_t is the affinity (the matching components weighted by ϕ_t; line hits count once per file) and ρ_t the risk weight. Trace-informed selection.
- `cost_aware`: the whole suite ranked by $\rho_t \, (0.05 + a_t + [\text{line hit}]) \, (2 - p_t)/c(t)$, with p_t the baseline pass rate: affected tests first, cheap ones before expensive ones, and the unaffected tests after them so that the budget is used [6, 17].

Two optional baselines, predictive selection with a logistic model over the same features [14] and a diversity-based order [22], are in the code and not in the tables.

4.4 The proposed method

Hypotheses. Each changed component $c \in C(\Delta)$ is broken with a prior π_c that depends on its kind: about 0.45 to 0.5 for code, skill procedures, configuration and agent fields, 0.12 to 0.15 for prompt wording and skill prose. Tool and line components are views of a code change, not separate causes, and are folded into it. The posterior is kept exactly over all 2^k subsets $h \in \{0, 1\}^{C(\Delta)}$, with $k \leq 8$ (the likeliest components are kept when there are more).

Likelihood. A test passes only if it would pass on the current version and none of the broken components makes it fail:

$$q_t(h) = P(t \text{ fails} \mid h) = 1 - (1 - f_t) \prod_{c:\, h_c = 1} (1 - s_{tc}). \tag{3}$$

A test the model already fails (f_t near 1) fails under every hypothesis, so its outcome carries no information, which is what keeps the method from mistaking the model's mistakes for regressions.

Sensitivity. Covering a component is weak evidence by itself: most tests that execute a changed function do not fail when it breaks. The sensitivity is therefore calibrated (Algorithm 2) from the earlier changes whose outcomes are known, never from the change under test:

$$s_{tc} = \mathrm{clip}\big(r_{k(c)} \cdot \ell_{t,k(c)} \cdot \phi_t(c) \cdot \tau_t,\ 0.02,\ 0.9\big), \tag{4}$$

where r_k is the reveal ratio of the component's kind k (among the tests that statically looked impacted by earlier changes of that kind, the share that revealed them, with the kinds separating a test that executed a changed line from one that only called the changed function, and agent fields calibrated per field); $\ell_{tk} = (O_{tk} + m)/(E_{tk} + m)$ is the test's own lift on that kind, with O_{tk} the earlier changes of kind k it revealed, E_{tk} the number an average impacted test would have revealed (the sum of those changes' reveal rates), and $m = 2$ a padding that keeps a short record from moving the lift far; $\phi_t(c)$ is how often the baseline runs exercised the component, or, for an agent that lost tools or skills, how often t used one of the lost items; and $\tau_t \in [0.5, 2]$ tilts the sensitivity up for a test whose text shares vocabulary with the diff and for one whose author declared the dependency. The lift matters because a change that breaks most of the suite says little about each test it breaks, while a change that one test alone caught says a lot about that test. A test with no link to the component gets a small constant $s_{\text{ind}} = 0.02$; one declared but never observed gets half the kind's ratio.

Policy, stopping and the mandatory rule. Algorithm 1 runs the loop. The next test maximises the expected reduction of the posterior's entropy [11], tilted by risk, per token. After a pass, tests that behave exactly like the one that passed (same agents, tools, fault profile and dataset in the baseline) have their sensitivities discounted by $\delta = 0.35$, because near-duplicates give correlated evidence rather than independent draws. Each test runs at most once: the models decode greedily, so a rerun would almost always repeat the answer. The run stops with REGRESSION at the first failure of a test that passed on the current version, because under greedy decoding that failure is a changed behaviour, which is what the ground truth calls revealing. It stops with CLEAN when $1 - P(h = \mathbf{0}) < \varepsilon$, with $\varepsilon = 0.05$, and otherwise when the budget is spent or no test can still move the posterior. Before a run ends without a regression, every mandatory property the change may affect (the properties whose sources the change touches, and those of the tests that ran a changed component on the current version) gets a test if it has none yet: the cheapest test of that property that passes on the current version, while the budget allows. A failure there is a regression like any other.

Algorithm 1 Adaptive Bayesian selection with stopping

Input: components $C(\Delta)$ with priors π_c; tests T with costs $c(t)$, fail rates f_t, risk tilts ρ_t and sensitivities s_{tc} (Algorithm 2); near-duplicate groups; budget B; ε, δ

$P(h) \propto \prod_c \pi_c^{h_c}(1-\pi_c)^{1-h_c}$ for $h \in \{0,1\}^{C(\Delta)}$ ▷ $h = \mathbf{0}$: nothing is broken
$q_t(h) \leftarrow 1 - (1-f_t)\prod_{c:\, h_c=1}(1-s_{tc})$ for every t and h ▷ Equation 3
$R \leftarrow \emptyset$; $b \leftarrow B$
loop
    if $1 - P(\mathbf{0}) < \varepsilon$ **then**
        return FINISH(CLEAN)
    end if
    $p_t \leftarrow \sum_h P(h)\, q_t(h)$ ▷ $P(t$ fails$)$ under the posterior
    $g_t \leftarrow H(P) - p_t\, H(P \mid t \text{ fails}) - (1-p_t)\, H(P \mid t \text{ passes})$ ▷ expected information gain
    $t^\star \leftarrow \arg\max\{\, g_t\, \rho_t / c(t) : t \notin R,\ c(t) \le b,\ g_t > 0 \,\}$
    if there is no such $t^\star$ **then**
        return FINISH(BUDGET)
    end if
    run $t^\star$ on V_1: outcome x, cost κ; $R \leftarrow R \cup \{t^\star\}$; $b \leftarrow b - \kappa$
    $P(h) \leftarrow P(h)\, q_{t^\star}(h)$ if $x =$ fail, else $P(h)\,(1 - q_{t^\star}(h))$; normalise
    if $x =$ fail and $f_{t^\star} < \frac{1}{2}$ **then**
        return REGRESSION ▷ a test that used to pass has failed
    end if
    if $x =$ pass **then**
        $s_{uc} \leftarrow \delta\, s_{uc}$ and recompute q_u for every unrun u in the group of $t^\star$
    end if
end loop

procedure FINISH(verdict)
    for all mandatory properties p the change may affect, in id order **do**
        if no test in R checks p **then**
            $u \leftarrow$ the cheapest $u \notin R$ with $p \in \text{props}(u)$, $f_u < \frac{1}{2}$, $c(u) \le b$; **continue** if none
            run u; $R \leftarrow R \cup \{u\}$; $b \leftarrow b - \kappa$; update P as above
            if u failed **then**
                return REGRESSION
            end if
        end if
    end for
    return verdict, with $1 - P(\mathbf{0})$
end procedure

Algorithm 2 Calibration of the sensitivities from the earlier changes

Input: earlier changes $\mathcal{D}$ with their revealing sets $\mathcal{R}(\Delta')$; defaults r_k^0 per kind; padding m; the change under test $\Delta \notin \mathcal{D}$

for all $\Delta' \in \mathcal{D}$ and components $c' \in C(\Delta')$ of kind k **do**
  $I \leftarrow$ the tests that look impacted by c': executed a changed line, called the changed function, or match the component
  rate $\leftarrow |\mathcal{R}(\Delta') \cap I|/|I|$; append rate to A_k
  O_{tk} += $[t \in \mathcal{R}(\Delta')]$ and E_{tk} += rate for $t \in I$ ▷ once per change and kind
end for
$r_k \leftarrow \mathrm{clip}((\sum A_k + m\, r_k^0)/(|A_k| + m),\ 0.01,\ 0.9)$ for every kind k
for all tests t and components $c \in C(\Delta)$ of kind k **do**
  $\ell_{tk} \leftarrow (O_{tk} + m)/(E_{tk} + m)$; $\tau_t \leftarrow 0.5 + \mathrm{text}(t, \Delta) + 0.5$ [declared]
  $s_{tc} \leftarrow \mathrm{clip}(r_k\, \ell_{tk}\, \phi_t(c)\, \tau_t,\ 0.02,\ 0.9)$ if $\phi_t(c) > 0$; $\frac{1}{2} r_k$ if declared only; s_{ind} otherwise
end for

Order for the prioritization metrics. APFD and APFD$_c$ score a complete order. The method's order is the greedy sequence it would pick if every test passed, with no stopping, followed by the untouched tests in cost-aware order.

4.5 Two published methods, reproduced

CASPER [19] and risk-aware adaptive evaluation [15] are the closest published methods. Both are reproduced on the testbed (Algorithms 3 and 4) with the adaptations the setting forces, which the code documents. Neither reads the diff, so comparing with them isolates what change-awareness adds.

CASPER mines ten behavioural signals from the logs of the current version, cuts the suite into slices that are coherent in signal space and consistent in outcome, runs a few representatives of every slice on the new version, and ranks the slices by how much a model of the signals changed its prediction. Here the signals are the counterparts for an agent that calls tools and hands off to other agents (turns, tool calls, distinct tools, the share of the most-called tool, the entropy of the calls, hand-offs, skills loaded, settings read, the size of the run and the share the model wrote); the slices come from k-means [12] on the standardised signals with the baseline outcome as a heavier column, in place of the paper's evolutionary search; two representatives per slice run first, cheapest slices first; and, because the replay oracle returns an outcome and a cost rather than a trace, a slice is scored by the shift of its representatives' failure rate.

Risk-aware adaptive evaluation is a contextual Thompson-sampling bandit [3, 30]: a scenario's context is a vector of features of its definition, its impact a fixed score, the reward of a trial impact times failure. Each round, a logistic regression on every outcome so far gives every scenario a failure probability; a Beta posterior per scenario mixes it, with weight λ, with the scenario's own outcomes; one draw per scenario, times the impact, picks the next. Here the scenarios are the tests, the context is the case's definition and the shape of its baseline runs, the impact is the risk weight, the budget is in tokens and each test runs once. As in the paper, any failure is a reward, so a test the model already fails counts as a find, and there is no stopping rule and no verdict.

Algorithm 3 CASPER's slices, reproduced

Input: baseline runs of every test; slice size n_s, minimum size $n_{\min}$, outcome weight w, representatives K; budget B

$Z \leftarrow$ the standardised behavioural signals of every test, with $w\cdot$ (standardised pass rate) as an extra column
slices $\leftarrow$ k-means$(Z, \lceil |T|/n_s \rceil)$; merge every slice smaller than $n_{\min}$ into the slice whose centre is nearest
for all slices j **do**
    reps$_j \leftarrow$ the member nearest the centre, then farthest-point sampling, K in all
end for
run the representatives of every slice on V_1, cheapest slices first, while the budget allows
shift$_j \leftarrow$ failure rate of reps$_j$ on V_1 minus their baseline failure rate
order the slices: shift > 0 by size, then shift < 0, then unchanged
run the members of each slice in that order, nearest the centre first, until the budget is spent

Algorithm 4 Risk-aware adaptive evaluation, reproduced

Input: context x_t of every test (standardised, with an intercept), impact ι_t, costs $c(t)$; mixing weight λ, ridge penalty λ_2; budget B

$n_t \leftarrow 0$, $k_t \leftarrow 0$ for every t; $b \leftarrow B$
run a test chosen uniformly at random among those with $c(t) \le b$
while some unrun t has $c(t) \le b$ **do**
    $w \leftarrow \arg\min_w \sum_{t:\, n_t>0} \mathrm{logloss}(\sigma(w^\top x_t), k_t) + \frac{\lambda_2}{2}\|w\|^2$ ▷ Newton's method, warm start
    $p_t \leftarrow \sigma(w^\top x_t)$; $\theta_t \sim \mathrm{Beta}\big(1+\lambda p_t + k_t,\ 1+\lambda(1-p_t)+n_t-k_t\big)$ for every unrun t that fits
    run $t^\star \leftarrow \arg\max_t \iota_t\, \theta_t$ on V_1; $n_{t^\star} \leftarrow 1$; $k_{t^\star} \leftarrow$ [failed]; $b \leftarrow b - \kappa$
end while

5 The testbed

The application. ContentOps is a content-operations platform in the style of a web content manager: pages with versions, assets, publishing with reviews and schedules, link validation, SEO metadata, translation, governance with consent and approval tokens, rollback, brand rules, analytics and a site audit. Eleven agents (an orchestrator and ten specialists, three of them modelled on Adobe's) run on a shared harness with thirteen skills and 32 tools over deterministic services. The orchestrator delegates a request to one specialist or, when it needs several, plans the steps and asks a person before any step that publishes, schedules or takes pages down. The structure is deliberate: some components are shared with a wide blast radius (a governance skill included by several skills, a permission check available to eight specialists, a retry helper around every tool call), others are narrow, and some policies are enforced only in a skill while others also in a tool. The agents are played by a real model, Gemma 4 E4B, served with vLLM and decoding greedily.

The suite. The recording holds 176 cases: scenario tests, fifteen of which run one of six multi-agent workflows end to end, and the items of two datasets (prompt to expected delegation, prompt to expected tool call). A case defines its entry agent, request, fixture and fault profile (healthy, one transient failure of a tool, one lost acknowledgement, a tool permanently down), a risk level (critical to low, weights 4 to 1), the properties it checks, declared dependencies, and expectations on the final state, the tools required and forbidden, attempt and audit counts, the answer, the step limit and the order of agents and tools. The properties come from a catalog of fifteen (correctness, safety, resilience, orchestration, efficiency, quality), each with how it is

Table 1: The 43 controlled changes.

category	count	examples
code	10	argument swap in a tool adapter; retries drop idempotency keys; approval gate bypassed; external links treated as reachable; a shared read reports the wrong review flag; ranking sorted the wrong way; case-sensitive search and brand check
runtime	3	the agent loop stops six steps early; a delegated answer is truncated; a delegation drops the ids of earlier steps
skill	11	publishing drops link validation or the permission check; authoring drops its metadata step; translation hard-codes a default; rollback restores the wrong version; governance drops the consent check; the routing skill stops asking for approval, or drops the brand gate
agent definition	2	an agent loses a tool
configuration	7	link validation disabled; review not required; a step budget of five; no retries; a title limit of twenty; another default agent; no approval needed to take a page down
combined	1	a keyword rule in code and a very low limit in configuration
benign	9	prose reflowed or reworded; a comment or docstring edited; local variables renamed; configuration comments reordered; an unused tool added; prompt wording; lists reordered

checked, a threshold and a mandatory flag; the six safety properties are mandatory. A model can draft the catalog from the requirements alone, for a person to edit. A judge model reads the answer only for the two cases with a rubric, and only after the deterministic checks pass.

The changes. Forty-three controlled changes are applied as file edits (Table 1), in the spirit of mutation analysis [5, 9]: ten to tool adapters, services and the harness, three to the runtime loop, eleven to skills, two to agent definitions, seven to configuration, one combined change whose two halves are harmless alone, and nine benign changes. A change has to touch an input a model acts on, and a removed step has to go from both the procedure and the prose of a skill, or the model does the step anyway. Candidates that told nothing about selection were left out: twins of other changes, crashes, and a change that broke most of the suite. Ten of the changes aim at the workflows.

Protocol. The full suite runs $K = 3$ times on the current version with coverage contexts, which gives the observed dependencies, costs and pass rates, and $K = 3$ times on each of the 43 changed copies, which gives the ground truth. Every strategy is then replayed offline: for every change, budget in $\{2, 5, 10, 20, 30, 50, 100\}\%$ of the full-suite tokens and five seeds, the strategy sees the baseline facts and the change set, and each test it runs is answered from a recorded run of that changed copy. The method calibrates on the other 42 changes, never on the one under test. The environment's failures (a server that did not answer) are marked and left out, as if the run had not been made.

6 Results

Ground truth. On the current version 170 of 176 tests pass. The six failures are the model's own mistakes, which clearer wording did not fix: it schedules a page without an approved review, requests a review nobody asked for, applies an over-long title, goes on to publishing after a failed link check, and stops a whole plan after a refused step the other steps do not depend on. Of the 34 regressions, 29 are revealed by at least one test. The model does not act on the five remaining

Table 2: Detection of the 29 revealed regressions by nominal budget (share of the full-suite tokens), and the tokens actually spent: on regressions at a 20% and a 100% budget, and on the benign changes at 100%. Five seeds; the last three columns are shares of the full-suite tokens.

strategy	2%	5%	10%	20%	50%	100%	spent@20	spent@100	benign@100
`full`	0.00	0.14	0.21	0.34	0.90	0.99	0.20	0.98	1.00
`random`	0.17	0.21	0.33	0.52	0.84	0.99	0.20	0.98	1.00
`declared`	0.45	0.55	0.55	0.61	0.61	0.61	0.07	0.10	0.13
`ir_tfidf`	0.59	0.70	0.71	0.92	0.99	0.99	0.20	0.98	0.99
`observed`	0.48	0.62	0.69	0.86	0.86	0.99	0.15	0.49	0.32
`cost_aware`	0.38	0.59	0.62	0.83	0.86	0.99	0.20	0.98	0.99
`casper_slices`	0.17	0.28	0.43	0.50	0.88	0.99	0.20	0.98	1.00
`risk_aware_ts`	0.12	0.27	0.43	0.59	0.81	0.99	0.20	0.98	1.00
`adaptive_bayes`	0.59	0.76	0.79	0.79	0.83	0.83	0.03	0.03	0.20

Table 3: Order quality and verdicts. APFD and APFD_c of the complete order; cost to the first true detection as a share of the full suite (detected cases); detection of the 21 regressions that break a safety property at a 10% and a 20% budget; share of replays, over all budgets, in which the strategy saw a failure on one of the 14 changes no test reveals.

strategy	APFD	APFD_c	first detection	safety@10	safety@20	false alarm
`full`	0.63	0.57	0.19	0.10	0.24	0.71
`random`	0.56	0.53	0.14	0.36	0.57	0.63
`declared`	0.81	0.76	0.025	0.52	0.55	0.51
`ir_tfidf`	0.78	0.77	0.040	0.79	0.98	0.70
`observed`	0.75	0.79	0.048	0.57	0.81	0.57
`cost_aware`	0.75	0.78	0.056	0.57	0.76	0.91
`casper_slices`	0.59	0.54	0.12	0.50	0.60	0.57
`risk_aware_ts`	0.60	0.61	0.13	0.55	0.73	0.71
`adaptive_bayes`	0.83	0.81	0.017	0.86	0.86	0.00

guards (a review flag, a length limit, a non-blocking asset reference) with or without the change, so it behaves the same, wrongly, on both versions. No benign change fails a test. Across the 43 changes the three runs disagreed on five (change, test) pairs, which the majority vote absorbs. The 29 revealed regressions and the 14 changes no test reveals are the population below.

Selection (RQ1, RQ2). Declared metadata caps detection at 61% however large the budget (Table 2), because shared skills reached through an include, harness code and most configuration keys are not declared. The observed dependencies recover full selection recall at half the suite's cost and reach 86% within a 20% budget. The argument for trace-informed selection holds.

Prioritization (RQ3). The informed strategies raise APFD_c from 0.53 (random) to 0.76–0.81 (Table 3). The adaptive method's order is the best and finds the first regression soonest, after 1.7% of the suite's tokens. The two reproduced methods order no better than random (0.54 and 0.61) and find their first regression after 12–13% of the suite, where the change-aware strategies need 2–6%.

Budget (RQ4). The adaptive method is the only strategy that returns budget. It finds 76% of the regressions at a 5% budget and 79% at 20%, for under 3% of the tokens, and spends a tenth of the suite on a benign change at a 20% budget (Figure 2). TF-IDF over the diff is the strongest selector at 20% (92%) and the strongest on the safety-breaking changes (98%), and it spends the whole budget every time, on benign changes too. The adaptive method's ceiling is 83%: on a regression that only one to five tests reveal it can become confident that nothing




Figure 2: Detection of the 29 revealed regressions against the tokens actually spent, every strategy and budget. The adaptive method sits at the left: it stops.

Table 4: Detection by the method with three text measures, with the tokens spent in parentheses, against `ir_tfidf` alone.

budget	word overlap	TF-IDF	no text	`ir_tfidf` alone
5%	0.76 (2.1%)	0.79 (2.0%)	0.62 (2.4%)	0.70 (5%)
20%	0.79 (2.9%)	0.83 (2.4%)	0.69 (3.5%)	0.92 (20%)
50%	0.83 (2.9%)	0.83 (2.4%)	0.69 (4.5%)	0.99 (50%)

broke before reaching them (145 of 1,015 replays of regressions ended CLEAN). The changes it misses at 20% are the delegation that drops the ids of earlier steps, the loop that stops six steps early, retries without idempotency keys, the routing skill without its brand gate, the authoring skill without its metadata step, and the combined change, which runs out of budget.

Verdicts and the model's own mistakes. The six tests that fail on the current version fail on every changed copy too. A strategy that runs one sees a failure the change did not cause: on the 14 changes no test reveals, this happens to `full` in 71% of its replays, to `cost_aware` in 91%, to the bandit in 71% and to CASPER's slices in 57% (Table 3). The adaptive method discounts a test by its failures on the current version (Equation 3) and stops only on a test that used to pass, so it gave no REGRESSION verdict on any of these changes in 490 replays.

The text factor. The tilt τ_t can use word overlap (the default), the TF-IDF similarity of `ir_tfidf`, or no text at all (Table 4). TF-IDF brings forward the one test that reveals a narrow change and gains up to four points while spending less; without any text the method loses ten points. Text matters, and coverage and history carry most of the result. The testbed is textual, since tests, skills and configuration keys share vocabulary, which favours any text measure.

The mandatory rule. Without the rule, a run that found no regression had tested every mandatory property the change may affect in 33% of the replays at a 20% budget; with it, in 90%, for 0.8 extra tests per change on average, and detection rose from 76% to 79%. The rule is also a detector: it catches the publishing skill without its link validation, which the model alone

calls clean, because the method must test the mandatory property "no broken publish" before ending, and that test fails. The rule never caused a false verdict. Below a 10% budget it often cannot afford the extra test.

The reproduced methods, and where CASPER fits. CASPER's slices and the risk-aware bandit find 50% and 59% of the regressions at a 20% budget, between random (52%) and the change-aware strategies (83–92%). The bandit's impact is the test's risk, so it does better on the changes that break a safety property (73% at 20%, 94% at 50%), and it rewards any failure, so it runs the model's red tests early. Neither stops. These numbers measure what the diff is worth, not CASPER in its own setting. CASPER was built for changes that have no diff a test can be mapped to: a model upgrade, a provider's silent update, a prompt-level change whose effect spreads through the model's behaviour. It needs only the logs of the last full run, so it applies to a system whose code the testing team does not own, and its cost does not grow with the suite, since a fixed number of representatives per slice samples a large suite as cheaply as a small one. A platform sees both kinds of change. The change-aware strategies cover the edits to skills, code and settings; CASPER's representatives are the natural first pass after a model update, when every test is affected and the question is which behaviours drifted. The two could be combined: the slices can serve as the near-duplicate groups of the adaptive method, and a slice whose representatives drifted can enter the model as a changed component. On this testbed every change is an edit with a diff and the suite is small (176 tests, twelve slices), which is the case slicing has least to offer.

Other models. The same application was recorded with Qwen3.8-27B and with gpt-oss-120b, served as they are, with greedy decoding. Neither recording is a clean ground truth. Qwen passes 171 of the 176 tests on the current version and reveals every regression, but it also "reveals" every benign change, by two to five tests, including a change whose change set is empty: six tests answer differently when they run 64 at a time, as the changed copies do, than one at a time, as the baseline does, and its three runs disagreed on 260 (change, test) pairs against Gemma's five. vLLM's batch-invariant mode, which would make greedy decoding exactly repeatable, does not support the model's attention layers, and recording the baseline the way the changes are recorded leaves seven of the nine benign changes still flipping tests. gpt-oss-120b, recorded with five repetitions, varies more: the benign changes flip two to five tests under the majority over five runs and one to four under the first three, so more repetitions do not settle the vote; thirteen tests carry the variation, mostly long workflows that pass one at a time on the current version and fail in a batch on nearly every changed copy, whichever the change. A larger model is not automatically a cleaner ground truth, and a pipeline should measure how much its model's answers vary under the serving setup the selection will run on before trusting a ground truth or a stopping rule. The empty change measures exactly that.

7 Threats to validity

The regressions are mutants, not real changes; they were written to resemble regressions a team would ship, and the testbed does not yet pair them with a version history. Which test reveals which change was measured, not designed, and no strategy is told, but the tests and the changes were written by the same people. One primary application, built for the purpose, and one model with a stable ground truth: the second and third models show that the ground truth depends on the model and on how it is served. The testbed is textual, which favours the text factor and `ir_tfidf`; a second application with differently worded tests and changes (tau-bench [1, 32]) is planned. The calibration uses the other recorded changes, so leakage is controlled by leaving the change under test out, but the 42 training changes are few, which is why every learned ratio is

padded toward a default. The stopping rule assumes greedy decoding; with sampling, a single failure would need repetitions [2, 18].

8 Related work

Regression test selection and prioritization have a long literature [33]: safe selection on control-flow graphs [24], prioritization scored by APFD [7, 25] and its cost-cognizant form [6, 16], information retrieval over the diff [26], history and time windows in continuous integration [8, 17], learned selection [14, 28] and black-box diversity [22]. Ma et al. [13] name the obstacles for LLM applications: no crisp oracle, brittle prompts, nondeterminism. CASPER [19] is the closest work and is reproduced here; it is change-aware through drift and does not map an edit to tests. Risk-aware adaptive evaluation [15] allocates runs with a bandit and ignores the change. GBV-PD [4] ranks tests from a parameter update, which needs gradients the models here do not expose. Efficient benchmarking [10, 20, 23, 31] selects subsets that reproduce a score rather than detect a change. Fault injection for agents [27, 29] perturbs the runtime; the testbed here mutates the artefacts under change. The trace export follows the OpenTelemetry conventions for agents [21].

9 Conclusion

After a change to an agent system, the diff is worth reading. Mapped to tests through the dependencies observed in traces, it finds 86% of the regressions within a fifth of the suite's tokens where hand-written metadata finds 61%, and the two closest published methods, which do not read it, find 50% and 59%. A Bayesian model over the changed components, with sensitivities calibrated from the record of earlier changes, turns selection, prioritization and stopping into one decision: it finds 79% of the regressions for 3% of the tokens, orders the suite best, gives no false verdict on the changes no test reveals, and tests every mandatory property a change may affect before it calls the change clean. The price is a ceiling on narrow regressions, which the mandatory rule lowers for the properties that matter most. What remains is a second application, real version histories beside the mutants, and the repetitions that a model with varying answers needs.

References

[1] Victor Barres, Honghua Dong, Soham Ray, Xujie Si, and Karthik Narasimhan. τ^2-bench: evaluating conversational agents in a dual-control environment, 2025. arXiv:2506.07982.

[2] Bjarni Haukur Bjarnason, André Silva, and Martin Monperrus. On randomness in agentic evals, 2026. arXiv:2602.07150.

[3] Olivier Chapelle and Lihong Li. An empirical evaluation of Thompson sampling. In *Advances in Neural Information Processing Systems 24 (NeurIPS)*, 2011.

[4] Eunho Cho, Donghwan Shin, and In-Young Ko. Evolution-aware regression test prioritization of ML-enabled systems using gradient-based behavior vectors, 2026. arXiv:2606.28037.

[5] Richard A. DeMillo, Richard J. Lipton, and Frederick G. Sayward. Hints on test data selection: help for the practicing programmer. *IEEE Computer*, 11(4):34–41, 1978.

[6] Sebastian Elbaum, Alexey G. Malishevsky, and Gregg Rothermel. Incorporating varying test costs and fault severities into test case prioritization. In *Proceedings of the 23rd International Conference on Software Engineering (ICSE)*, pages 329–338, 2001. doi: 10.1109/ICSE.2001.919106.

[7] Sebastian Elbaum, Alexey G. Malishevsky, and Gregg Rothermel. Test case prioritization: a family of empirical studies. *IEEE Transactions on Software Engineering*, 28(2):159–182, 2002. doi: 10.1109/32.988497.

[8] Sebastian Elbaum, Gregg Rothermel, and John Penix. Techniques for improving regression testing in continuous integration development environments. In *Proceedings of the 22nd ACM SIGSOFT International Symposium on Foundations of Software Engineering (FSE)*, pages 235–245, 2014. doi: 10.1145/2635868.2635910.

[9] Yue Jia and Mark Harman. An analysis and survey of the development of mutation testing. *IEEE Transactions on Software Engineering*, 37(5):649–678, 2011.

[10] Peiyu Li, Xiuxiu Tang, Si Chen, Ying Cheng, Ronald Metoyer, Ting Hua, and Nitesh V. Chawla. Adaptive testing for LLM evaluation: a psychometric alternative to static benchmarks, 2025. arXiv:2511.04689.

[11] Dennis V. Lindley. On a measure of the information provided by an experiment. *The Annals of Mathematical Statistics*, 27(4):986–1005, 1956.

[12] Stuart P. Lloyd. Least squares quantization in PCM. *IEEE Transactions on Information Theory*, 28(2):129–137, 1982.

[13] Wanqin Ma, Chenyang Yang, and Christian Kästner. (Why) is my prompt getting worse? Rethinking regression testing for evolving LLM APIs. In *Proceedings of the IEEE/ACM 3rd International Conference on AI Engineering: Software Engineering for AI (CAIN)*, 2024. arXiv:2311.11123.

[14] Mateusz Machalica, Alex Samylkin, Meredith Porth, and Satish Chandra. Predictive test selection. In *Proceedings of the 41st International Conference on Software Engineering: Software Engineering in Practice (ICSE-SEIP)*, pages 91–100, 2019. doi: 10.1109/ICSE-SEIP.2019.00018.

[15] Priyanath Maji and Spandan Ghose Chowdhury. Risk-aware adaptive evaluation: finding high-impact failures under limited budgets, 2026. URL `https://arxiv.org/abs/2609.38914`. arXiv:2609.38914; NeurIPS 2026 workshop on the evaluation of interactive agents.

[16] Alexey G. Malishevsky, Joseph R. Ruthruff, Gregg Rothermel, and Sebastian Elbaum. Cost-cognizant test case prioritization. Technical Report TR-UNL-CSE-2006-0004, University of Nebraska–Lincoln, 2006.

[17] Atif Memon, Zebao Gao, Bao Nguyen, Sanjeev Dhanda, Eric Nickell, Rob Siemborski, and John Micco. Taming Google-scale continuous testing. In *Proceedings of the 39th International Conference on Software Engineering: Software Engineering in Practice (ICSE-SEIP)*, pages 233–242, 2017. doi: 10.1109/ICSE-SEIP.2017.16.

[18] Evan Miller. Adding error bars to evals: a statistical approach to language model evaluations, 2024. arXiv:2411.00640.

[19] Biruk Asmare Muse, Lionel Briand, Yiwei Lu, and Keheliya Gallaba. CASPER: change-aware slice prioritization for efficient regression testing of LLM-based systems, 2026. URL `https://arxiv.org/abs/2608.00378`. arXiv:2608.00378.

[20] Franck Ndzomga. Efficient benchmarking of AI agents, 2026. arXiv:2603.23749.

[21] OpenTelemetry. Semantic conventions for generative AI: agent spans. `https://github.com/open-telemetry/semantic-conventions-genai/blob/main/docs/gen-ai/gen-ai-agent-spans.md`, 2026.

[22] Rongqi Pan, Taher A. Ghaleb, and Lionel C. Briand. LTM: scalable and black-box similarity-based test suite minimization based on language models. *IEEE Transactions on Software Engineering*, 50(11), 2024. arXiv:2304.01397.

[23] Felipe Maia Polo, Lucas Weber, Leshem Choshen, Yuekai Sun, Gongjun Xu, and Mikhail Yurochkin. tinyBenchmarks: evaluating LLMs with fewer examples. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, 2024. arXiv:2402.14992.

[24] Gregg Rothermel and Mary Jean Harrold. A safe, efficient regression test selection technique. *ACM Transactions on Software Engineering and Methodology*, 6(2):173–210, 1997. doi: 10.1145/248233.248262.

[25] Gregg Rothermel, Roland H. Untch, Chengyun Chu, and Mary Jean Harrold. Prioritizing test cases for regression testing. *IEEE Transactions on Software Engineering*, 27(10):929–948, 2001. doi: 10.1109/32.962562.

[26] Ripon K. Saha, Lingming Zhang, Sarfraz Khurshid, and Dewayne E. Perry. An information retrieval approach for regression test prioritization based on program changes. In *Proceedings of the 37th International Conference on Software Engineering (ICSE)*, pages 268–279, 2015. doi: 10.1109/ICSE.2015.47.

[27] Zahra Seyedghorban, Egor Klimov, Arie van Deursen, Annibale Panichella, and Burcu Kulahcioglu Ozkan. Observability and fault injection for LLM-based multi-agent systems in software engineering, 2026. arXiv:2608.24271.

[28] Helge Spieker, Arnaud Gotlieb, Dusica Marijan, and Morten Mossige. Reinforcement learning for automatic test case prioritization and selection in continuous integration. In *Proceedings of the 26th ACM SIGSOFT International Symposium on Software Testing and Analysis (ISSTA)*, pages 12–22, 2017. doi: 10.1145/3092703.3092709.

[29] Gou Tan, Zhensu Sun, Jieke Shi, Ting Zhang, Zilong He, Qingfu Wu, Shuai Liang, Weifeng Sun, Junda He, Pengfei Chen, Chuanfu Zhang, Lwin Khin Shar, and David Lo. AgentChaos: chaos engineering for agent systems via programmatic fault injection. In *Proceedings of the 41st IEEE/ACM International Conference on Automated Software Engineering (ASE)*, 2026. arXiv:2608.06790.

[30] William R. Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3–4):285–294, 1933.

[31] Skyler Wu, Yash Nair, and Emmanuel J. Candès. Efficient evaluation of LLM performance with statistical guarantees, 2026. arXiv:2601.20251.

[32] Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ-bench: a benchmark for tool-agent-user interaction in real-world domains, 2024. arXiv:2406.12045.

[33] Shin Yoo and Mark Harman. Regression testing minimization, selection and prioritization: a survey. *Software Testing, Verification and Reliability*, 22(2):67–120, 2012. doi: 10.1002/stvr.430.