# TRACE-Eval: change-aware, cost-bounded regression test selection for LLM agent systems

Ciprian Păduraru
University of Bucharest
ciprian.paduraru@unibuc.ro

**Abstract**

An LLM agent system is assembled from skills, prompts, tools, harness code and configuration, and verified by a suite $T$ of tests whose cost $c(t)$ is dominated by tokens. After a change $\Delta$, a team either reruns all of $T$ or guesses. We formulate selection, prioritization and stopping as one problem: choose tests from $T$, one at a time, under a budget $B$, so that the regressions $\Delta$ introduces are found with high probability at low cost. The change becomes a set of components $C(\Delta)$ (code lines and functions, skill procedures and prose, agent fields, configuration keys), each broken with a prior probability $\pi_c$. A test's sensitivity $s_{tc} = P(t \text{ fails} \mid c \text{ broken})$ is calibrated from the dependencies observed in execution traces and from the record of earlier changes, and a test that already fails on the unchanged system, with rate $f_t$, is discounted. The posterior over which subset of the components is broken is kept exactly; the next test maximizes the expected information gain per token; the run stops with REGRESSION at the first failure of a test that used to pass, with CLEAN when $P(\text{some component broken} \mid \text{outcomes}) < \varepsilon$, and never before every mandatory property that $\Delta$ may affect has had a test. We evaluate on a testbed: a multi-agent content-operations application whose agents are played by an open model (Gemma 4 E4B), 180 tests, 43 controlled changes applied as file edits, and a ground truth measured per model by majority over five runs. Dependencies the test authors declared by hand miss 38% of the regressions; dependencies observed in traces find 86% within 20% of the full-suite tokens; two published methods reproduced on the testbed, CASPER's slices and a risk-aware bandit, find 59% and 57% because neither reads the change; the proposed method finds 78% for 3% of the tokens, 84% of the changes that break a safety property, and gives no false verdict on the 14 changes no test reveals.

## 1 What a team needs

### 1.1 The setting

A platform such as the agent layer of Adobe Experience Manager (AEM) ships dozens of agents. Each is a bundle of a system prompt, a list of tools, a list of skills (prompt files with a procedure the model follows), and settings, running on a shared harness that dispatches tool calls, retries, enforces approvals and delegates between agents. One prompt may cross several agents, through a plan the orchestrator writes (Section 2). The platform is verified by scenario tests, which run a request end to end and check the final state and the trace, and by datasets of prompts with expected routings or tool calls. Every test is a run of a model. It costs tokens and seconds, and the cost varies by a factor of ten to a hundred between a one-shot routing item and a workflow across five agents.

After a change, the question is the one regression testing has always asked [33]: which tests to run (selection), in what order (prioritization), and when to stop. Three things make the classic answers [24, 25] hard to transfer:

- much of the "code" is natural language, so coverage of a skill or a prompt is not a line of a control-flow graph;

- the outcome of a test is the behaviour of a model, so it is not a function of the code alone and can vary from run to run;
- the cost of a test is not one unit, so an order that finds a fault after three tests can still have spent a third of the budget.

### 1.2 The desired features

The AEM team, asked what they lack and want in a prototype, listed the following. Each is built into the testbed; the section in parentheses shows it.

- **Selection, prioritization and stopping under a budget**, with a verdict a developer can act on (Section 4).
- **A catalog of properties**, the behavioural requirements the tests check, drafted by a model and edited by people (Section 2).
- **Coverage of each change**: the share of what it touches that the selected tests exercised (Section 3).
- **Per-test metadata**, declared by the author and observed in traces (Section 3).
- **Trace assertions** on the final state, the tools and the order of agents (Section 2).
- **Workflows** across several agents as a unit of testing and of coverage (Section 2).
- **Environment failures kept apart** from the agent's failures (Section 3).
- **OpenTelemetry traces** with the plan, the routing and the approvals as events [21] (Section 2).

### 1.3 What exists, and what is missing

Regression test selection and prioritization have a long literature [33]: safe selection on control-flow graphs [24], prioritization scored by the average percentage of faults detected (APFD) [7, 25] and its cost-cognizant form [6, 16], information retrieval over the diff [26], history and time windows in continuous integration [8, 17], learned selection [14, 28] and black-box diversity [22]. Ma et al. [13] name the obstacles for LLM applications: no crisp oracle, brittle prompts, nondeterminism. The literature on efficient evaluation of language models [10, 20, 23, 31] answers a different question, which subset of a benchmark reproduces a score: it selects once, for all models, and not after a change. GBV-PD [4] ranks tests from a parameter update, which needs gradients the models here do not expose. Fault injection for agents [27, 29] perturbs the runtime; the testbed here mutates the artefacts under change. The closest work, CASPER [19], is a regression method for LLM-based systems that is change-aware only through drift: it runs representatives of behavioural slices on the new version and ranks the slices by how much their outcomes moved. Risk-aware adaptive evaluation [15] allocates a budget of runs with a bandit, by impact and by the outcomes seen so far. Neither reads the diff. This paper's claim is that the diff, mapped to the tests through execution traces, is worth a lot, and that a sequential Bayesian treatment of the outcomes turns selection, prioritization and stopping into one decision.

The contributions are:

1. a formulation of change-aware, cost-bounded testing of agent systems, with the metrics of regression testing adapted to token costs (Section 3);
2. a method that extracts a change set at the granularity of code lines, skill procedures, agent fields and configuration keys, maps it to tests through dependencies observed in traces, ranks tests by expected information per token in a Bayesian model calibrated from history, and stops with a verdict (Section 4);
3. a testbed: a multi-agent application, 180 tests, 43 controlled changes and a mutation-based ground truth derived per model, on which strategies are compared by offline replay (Sections 2 and 5);

4. an evaluation against six baseline strategies and two published methods reproduced on the testbed (Section 5).

## 2 How we built the testbed

**The application.** We wanted an application small enough to read in an afternoon and shaped like the platforms the question comes from. ContentOps (Figure 1) is a content-operations platform in the style of a web content manager: pages with versions, assets, publishing with reviews and schedules, link validation, SEO metadata, translation, governance with consent and approval tokens, rollback, brand rules, analytics and a site audit. An orchestrator and ten specialists, three of them (brand governance, data insights, site optimization) modelled on Adobe's, run on a shared harness. Each specialist follows a skill: a Markdown file with prose rules and a machine-readable procedure that the model reads as numbered steps, with the skills it includes written out and every setting shown with its value. Thirteen skills, 32 tools over deterministic in-memory services and one configuration file make up the rest. The orchestrator delegates a request to one specialist or, when it needs several, writes a plan, hands each step its own instruction and the ids earlier steps reported, and asks a person before any step that publishes, schedules or takes pages down; the approver's answer is fixture data, so a run is repeatable.

The structure is deliberate: components with a wide blast radius (the shared skills, the permission check most specialists may call, the retry helper around every tool call) beside narrow ones (the approval gate matters to one test), and rules that live only in a skill (publish only with permission) beside rules a tool or a service also enforces (approval tokens, roles). That is what makes selection hard, and what lets us discuss defence in depth: when a change removes a check from a skill, usually nothing below the skill catches the mistake.

**The tests.** We wrote the tests the way a team would write them for the application, before and independently of the changes. A scenario test gives:

- an entry agent and a request in plain language ("Please publish the welcome page");
- a context (the user the agent acts for, the ids the request is about and any approval token) and a fixture (the platform's starting data);
- a fault profile: healthy, one transient failure of a tool, one lost acknowledgement, or a tool permanently down;
- deterministic expectations: the final state (the page is published, the audit log has one entry), the tools required and forbidden, attempt counts, facts the answer must report (a job id, which link is broken), a step limit, and, for the workflows, the order of agents and of tools;
- its risk level, the properties it checks, and the components its author declares it depends on.

We check facts, not wording: a check that the answer contains "broken" would fail a model that says "invalid". Two cases with a rubric also have their answer judged by a model, after the deterministic checks pass. Two datasets add items of the kind the AEM team runs nightly: a prompt with its expected delegation, and a prompt with its expected tool call. Fifteen tests run one of six multi-agent workflows end to end (a campaign launch across five specialists, a site optimization across four, a legal takedown, a localized price update, the rollback of a broken release, a privacy request), each with a variant where a step must stop the plan. The declared block is incomplete on purpose, as it is in practice: nobody declares the shared skill reached through an include, the harness code or the configuration keys.





Figure 1: ContentOps, one request from top to bottom. Grey: shared by many agents, so a change there has a wide blast radius.

**The properties.** The AEM team wanted "prompt, properties and threshold", with categories. The catalog holds fifteen properties in six categories (correctness, safety, resilience, orchestration, efficiency, quality); each has a description, how its tests check it (the final state, the trace, a judge or a dataset), a threshold on the pass rate of its tests, a flag that makes it a release blocker, and the components that state it, its sources. The six safety properties (authorization, guarded mutation, no broken publish, privacy, human approval, brand compliance) are mandatory with threshold one. Each test lists the properties it checks. A model can draft the same catalog from the skills' rules, the agent definitions and the configuration guards, and tag the tests, for a person to edit: its catalog is good and traces every property to the component that states it; its tags of the tests need the person's review.

**The environment.** An open model plays the agents: Gemma 4 E4B, served with vLLM and decoding greedily, so that the same prompt gives the same answer up to the arithmetic of batching. Qwen3.8-27B and gpt-oss-120b are second and third models, used as they are served, without sampling. Every run is traced (the agents started, the skills loaded, the tools called with their status, the configuration keys read, and the code functions and lines executed, each line attributed to the test and repetition that ran it) and exports as OpenTelemetry spans, with the plan, the delegations and the approvals as span events. A run the environment broke, because the server or the network did not answer, is marked and left out, as if it had not been made. The whole suite runs $K = 5$ times on the current version and on every changed copy; the strategies are compared afterwards by replaying the recorded outcomes (Section 5).

**The changes.** We wrote 43 controlled changes as file edits, in the spirit of mutation analysis [5, 9], each to resemble a regression a team would ship (Table 1). Two rules shaped the set:

Table 1: The 43 controlled changes.

| category | count | examples |
|---|---|---|
| code | 10 | argument swap in a tool adapter; retries drop idempotency keys; approval gate bypassed; external links treated as reachable; a shared read reports the wrong review flag; ranking sorted the wrong way; case-sensitive search and brand check |
| runtime | 3 | the agent loop stops six steps early; a delegated answer is truncated; a delegation drops the ids of earlier steps |
| skill | 11 | publishing drops link validation or the permission check; authoring drops its metadata step; translation hard-codes a default; rollback restores the wrong version; governance drops the consent check; the routing skill stops asking for approval, or drops the brand gate |
| agent definition | 2 | an agent loses a tool |
| configuration | 7 | link validation disabled; review not required; a step budget of five; no retries; a title limit of twenty; another default agent; no approval needed to take a page down |
| combined | 1 | a keyword rule in code and a very low limit in configuration |
| benign | 9 | prose reflowed or reworded; a comment or docstring edited; local variables renamed; configuration comments reordered; an unused tool added; prompt wording; lists reordered |

- a change meant to break something touches an input the model acts on; a keyword weight or the order of an agent's intents is not one;
- a removed step goes from both the procedure and the prose of a skill, or the model does the step anyway.

We left out what told nothing about selection: twins of other changes, crashes, and a change that broke most of the suite. Ten of the changes aim at the workflows. Which test reveals which change was measured afterwards, never designed, and no strategy is told.

# 3 Abstractions

**Versions, tests, costs, budget.** A system has a current version $V_0$ and a changed version $V_1 = V_0 + \Delta$. The suite $T$ holds tests and eval items, each with a cost $c(t) > 0$ in tokens (prompt and completion tokens over every model call the test makes), a risk weight $\rho_t \in \{1, 2, 3, 4\}$, a set of properties $\mathrm{props}(t)$ from the catalog $\mathcal{P}$, and a declared dependency set $D_t^{\mathrm{decl}}$. A budget $B$ is a number of tokens, given as a fraction of the cost of the whole suite, $\sum_{t \in T} c(t)$.

**Outcomes and the baseline.** Running $t$ on a version $V$ gives an outcome $X_t(V) \in \{\mathrm{pass}, \mathrm{fail}\}$, which is random because a model produces it. A run the environment broke is not an outcome and is left out. $K$ repetitions on $V_0$ give the baseline fail rate $f_t = \hat{P}(X_t(V_0) = \mathrm{fail})$; a test with $f_t \geq \frac{1}{2}$ is one the model already fails, a mistake of the model rather than a fault of the system.

**Components and the change set.** A component is a part of the system that a change can touch and a run can exercise, named in one vocabulary (Table 2); its kind is $k(c)$. The change set $C(\Delta)$ is the set of components the diff of $V_0$ and $V_1$ touches. Comments, docstrings, blank lines, formatting and the order of configuration mappings add nothing: no component, no file and no diff line, so no strategy and no probability can depend on them. Skill files are prompts the model reads word for word, so all of their text counts.

Table 2: The component vocabulary, shared by change sets and dependencies.

| component | what it names |
|---|---|
| `code:<file>::<function>` | a function whose normalized syntax tree changed |
| `line:<file>:<n>` | a line of code |
| `tool:<name>` | a registered tool adapter |
| `skill:<name>#procedure`, `#prose`, `#meta` | the three parts of a skill file |
| `agent:<name>.<field>` | a field of an agent definition; when a tool or skill list only lost items, the component records which, so that only the tests that used one of them are reached |
| `config:<key>` | an effective setting |
| `fixture:<name>` | the platform's starting data |

**Dependencies.** The observed dependencies of a test come from its traced baseline runs. For a test $t$ and a component $d$, $\phi_t(d) \in [0, 1]$ is the share of $t$'s baseline runs that exercised $d$; $D_t^{\text{obs}} = \{d : \phi_t(d) > 0\}$. A component matches a dependency set when the set holds the component, its base (`skill:x` for `skill:x#procedure`), or a function of a module changed at module level. A test's behaviour signature is the tuple of agents, tools, fault profile and dataset of its first baseline run; tests with the same signature are near-duplicates.

**Ground truth.** A test $t$ *reveals* $\Delta$ when its majority outcome flips: the pass rate on $V_0$ is at least $\frac{1}{2}$ and the pass rate on $V_1$ is below $\frac{1}{2}$, both over $K$ repetitions. $\mathcal{R}(\Delta)$ is the set of revealing tests; $\Delta$ is a regression when $\mathcal{R}(\Delta) \neq \emptyset$. A test the model already fails cannot reveal anything. The ground truth therefore belongs to the model: a change the model cannot see, because it ignores the rule with and without the change, is revealed by no test under that model, and a different model may give a different $\mathcal{R}(\Delta)$. A property $p$ is affected by $\Delta$ when $C(\Delta)$ touches one of its sources, or when a test that checks $p$ exercised a changed component on $V_0$; $\mathcal{P}(\Delta)$ is the set of affected properties.

**Strategies.** A strategy sees $C(\Delta)$, the baseline facts about every test ($D_t^{\text{obs}}$, $\phi_t$, $c(t)$, $f_t$, $\rho_t$, props($t$), $D_t^{\text{decl}}$ and the test's text), and the outcomes of earlier changes on which it may calibrate, but never $\mathcal{R}(\Delta)$. It chooses a test, observes its outcome and cost on $V_1$, and either chooses again or stops, within $B$. A non-adaptive strategy is an order of $T$ run greedily within the budget. An adaptive one may also return a verdict, CLEAN or REGRESSION, and a probability.

**Metrics.** For one change and one run of a strategy:

- *detection*: a revealing test was run and failed; the *cost to first detection* is the tokens spent up to that failure;
- *tokens spent*: the cost of every test run, on every change;
- *false alarm*: a failure of a test outside $\mathcal{R}(\Delta)$, which on a change no test reveals is a failure the change did not cause;
- *verdict correct*: the verdict agrees with $\mathcal{R}(\Delta) \neq \emptyset$;
- *change coverage*, which needs no ground truth: the share of $C(\Delta)$ the executed tests exercised, the share of $\mathcal{P}(\Delta)$ they checked, whether every mandatory property in $\mathcal{P}(\Delta)$ got a test, and the shares of the affected workflows and features they reached.

Prioritization alone, with every test run and no stopping, is scored by APFD [25]. With $n = |T|$, $m = |\mathcal{R}(\Delta)|$ and $TF_i$ the position in the order of the test that reveals fault $i$,

$$\text{APFD} = 1 - \frac{\sum_{i=1}^{m} TF_i}{n\,m} + \frac{1}{2n}, \tag{1}$$

Table 3: The strategies compared. Every non-adaptive order runs greedily within the budget and never stops.

| strategy | reads | does | after |
|---|---|---|---|
| `full` | nothing | the suite in catalog order | reference |
| `random` | nothing | a random permutation | reference |
| `declared` | $C(\Delta)$; $D_t^{\text{decl}}$, $\rho_t$, $c(t)$ | selects the tests whose declared dependencies match | [24] |
| `ir_tfidf` | the diff's text; the tests' text | orders the suite by TF-IDF similarity to the diff | REPiR [26] |
| `observed` | $C(\Delta)$; $D_t^{\text{obs}}$, $\phi_t$, $\rho_t$, $c(t)$ | selects the tests whose traces reached the change | this paper |
| `cost_aware` | $C(\Delta)$; $D_t^{\text{obs}}$, $\phi_t$, $f_t$, $\rho_t$, $c(t)$ | orders the suite by affinity, risk and cost | [6, 17] |
| `casper_slices` | baseline behaviour signals, pass rates, $c(t)$ | probes representatives of behavioural slices, then runs the slices by drift | CASPER [19] |
| `risk_aware_ts` | a context vector and an impact per test, $c(t)$ | a contextual bandit, one test per round | [15] |
| `adaptive_bayes` | $C(\Delta)$ with kinds; every baseline fact; earlier changes with their outcomes | the most information per token; stops with a verdict | this paper |

which is near 1 when the first tests find every fault and near 0 when the last ones do; a random order scores about $\frac{1}{2}$. Because costs differ by an order of magnitude, we also score its cost-cognizant form [6, 16]. With $c_j$ the cost of the $j$-th test in the order, $C = \sum_j c_j$, and $\sigma_i$ the severity of fault $i$ (the risk weight of its revealing test),

$$\text{APFD}_c = \frac{\sum_{i=1}^{m} \sigma_i \left(C - \sum_{j<TF_i} c_j - \frac{1}{2} c_{TF_i}\right)}{C \sum_{i=1}^{m} \sigma_i}. \tag{2}$$

Finding a fault after a few cheap tests costs little and scores high; finding it after the long workflows scores low, however few tests came before. An order can score well on APFD and poorly on $\text{APFD}_c$ by putting the expensive tests first.

# 4 The strategies

Every strategy answers the same question, which tests to run on $V_1$ and in what order, from the inputs listed in Section 3; Table 3 says what each one reads and whether it stops. Five are change-aware, in that they read $C(\Delta)$ or the diff; the two reproduced methods do not. Figure 2 follows the proposed method from the diff to a verdict. Brackets $[\cdot]$ are 1 when the condition inside holds and 0 otherwise.

## 4.1 Four non-adaptive orders

Algorithm 1 gives the four change-aware orders that need no model of the outcomes. Two select a subset and order it; two order the whole suite.





Figure 2: From a diff to a verdict. The three inputs on the left exist before the change is tested: the diff, a traced run of the current version, and earlier changes with their known outcomes. The loop on the right runs one test at a time on the changed version.

**Algorithm 1** The four non-adaptive change-aware orders

**procedure** DECLARED($C(\Delta)$; $D_t^{\text{decl}}$, $\rho_t$, $c(t)$ for every $t$)
  $S \leftarrow \{t : D_t^{\text{decl}}$ matches some $c \in C(\Delta)\}$; $a_t \leftarrow$ the number of components matched
  **return** $S$ sorted by $\rho_t$ descending, then $a_t$ descending, then $c(t)$ ascending
**end procedure**
**procedure** IR_TFIDF(the text of the change; the text of every $t$)
  $q \leftarrow$ TF-IDF vector of the change text over the vocabulary of the tests' texts; $v_t \leftarrow$ TF-IDF vector of the text of $t$
  **return** $T$ sorted by $\cos(q, v_t)$ descending
**end procedure**
**procedure** OBSERVED($C(\Delta)$; $D_t^{\text{obs}}$, $\phi_t$, $\rho_t$, $c(t)$ for every $t$)
  $S \leftarrow \{t : D_t^{\text{obs}}$ matches some $c \in C(\Delta)\}$; $a_t \leftarrow \sum_{c \text{ matched}} \phi_t(c)$, line hits counted once per file
  **return** $S$ sorted by $a_t\, \rho_t / c(t)$ descending
**end procedure**
**procedure** COST_AWARE($C(\Delta)$; $D_t^{\text{obs}}$, $\phi_t$, $f_t$, $\rho_t$, $c(t)$ for every $t$)
  $a_t \leftarrow$ as in `observed`, 0 for an unaffected test; $e_t \leftarrow [t$ executed a changed line]
  **return** $T$ sorted by $\rho_t\,(0.05 + a_t + e_t)\,(1 + f_t)/c(t)$ descending
**end procedure**

- `declared` is classic regression test selection on what the authors wrote down. Cheap, explainable and safe when the metadata is complete; it caps at what the authors declared, which leaves out what Section 2 says nobody declares, so it tops out whatever the budget.
- `ir_tfidf` is information-retrieval prioritization and uses no traces. It needs no instrumentation and is strong wherever tests, skills and settings share vocabulary; it never stops, so it spends the whole budget on every change, and it is blind to code reached without a shared word.
- `observed` is the trace-informed selection this paper argues for. It selects everything the traces show the change can reach, from one traced run per test; it does not stop within its selection and treats a covered component as an affected one, so it spends on tests that execute the changed line without being able to notice the change.
- `cost_aware` is cost-cognizant prioritization with a history factor. Affected tests first, cheap

ones before expensive ones, the rest after them so that the budget is always used; it never stops, and its history factor $(1 + f_t)$ pushes forward the tests the model already fails, which it then reports as failures the change did not cause.

### 4.2 CASPER's slices, reproduced: `casper_slices`

CASPER [19] mines signals from the logs of the current version, cuts the suite into slices that are coherent in signal space and consistent in outcome, runs a few representatives of every slice on the new version, and ranks the slices by how much their behaviour moved. Here (Algorithm 2) the signals are ten per test (turns, tool calls, distinct tools, the share of the most-called tool, the entropy of the calls, hand-offs, skills loaded, settings read, the size of the run and the share the model wrote); the slices come from k-means [12] with the baseline outcome as a heavier column, in place of the paper's evolutionary search; and, because a replay (Section 5) returns an outcome and a cost, not a trace, a slice is scored by the shift of its representatives' failure rate. We run it with $n_s = 8$, $n_{\min} = 4$, $w = 3$ and $K_r = 2$. For the prioritization metrics its order is that of a run without a budget limit in which every test passes.

**Algorithm 2** `casper_slices`

**Input:** the baseline runs of every test, as signals and a pass rate; costs $c(t)$; slice size $n_s$, minimum size $n_{\min}$, outcome weight $w$, representatives per slice $K_r$; budget $B$

**Output:** the tests run on $V_1$, in order

*Slice the suite on the current version*

$Z \leftarrow$ the standardized signals of every test, with $w\cdot$ (standardized pass rate) as an extra column

slices $\leftarrow$ k-means$(Z, \lceil |T|/n_s \rceil)$; merge every slice smaller than $n_{\min}$ into the slice whose centre is nearest

$\text{reps}_j \leftarrow$ the member of slice $j$ nearest its centre, then farthest-point sampling, $K_r$ in all

*Probe the changed version*

run $\text{reps}_j$ of every slice $j$ on $V_1$, cheapest slices first, while the budget allows

$\text{shift}_j \leftarrow$ failure rate of $\text{reps}_j$ on $V_1$ minus their failure rate on $V_0$

*Rank the slices by drift, then run them*

order the slices: $\text{shift}_j > 0$ by size descending, then $\text{shift}_j < 0$, then unchanged

run the members of each slice in that order, nearest the centre first, until the budget is spent

*Good at:* it needs no diff, so it applies to a model upgrade, a provider's silent update or a prompt-level change in a system whose code the testing team does not own; its cost does not grow with the suite, since a fixed number of representatives per slice samples a large suite as cheaply as a small one; and the slices are a map of the suite's behaviours a team can read. *Bad at:* it is blind to an edit, so an edit gives it no signal until the representatives have run; it has no stopping rule; and a representative the model answers unstably drags its whole slice forward.

### 4.3 Risk-aware adaptive evaluation, reproduced: `risk_aware_ts`

Risk-aware adaptive evaluation [15] is a contextual Thompson-sampling bandit [3, 30]: the reward of a trial is impact times failure; each round, a logistic regression on every outcome so far gives every scenario a failure probability, a Beta posterior per scenario mixes it with the scenario's own outcomes, and one draw per scenario, times the impact, picks the next. Here (Algorithm 3) the scenarios are the tests, each with a context vector $x_t$ (features of its definition and of the shape of its baseline runs, standardized, with an intercept) and an impact $\iota_t = \rho_t$; the budget is in tokens and each test runs once; $\sigma$ is the logistic function, the mixing weight is $\alpha = 2$ and the ridge penalty $\lambda = 1$. For the prioritization metrics its order is static: by impact, cheapest first.

**Algorithm 3** `risk_aware_ts`

**Input:** context $x_t$, impact $\iota_t$ and cost $c(t)$ of every test; mixing weight $\alpha$, ridge penalty $\lambda$; budget $B$

**Output:** the tests run on $V_1$, in order

$n_t \leftarrow 0$, $k_t \leftarrow 0$ for every $t$; $b \leftarrow B$ ▷ runs and failures seen per test

run one test drawn uniformly among those with $c(t) \le b$; record it as below

**while** some unrun $t$ has $c(t) \le b$ **do**

*fit, sample, pick*

$\beta \leftarrow \arg\min_\beta \sum_{t:\, n_t>0} \mathrm{logloss}(\sigma(\beta^\top x_t), k_t) + \frac{\lambda}{2}\|\beta\|^2$ ▷ Newton's method, warm start

$\mu_t \leftarrow \sigma(\beta^\top x_t)$ and $\theta_t \sim \mathrm{Beta}\big(1+\alpha\mu_t + k_t,\ 1+\alpha(1-\mu_t) + n_t - k_t\big)$ for every unrun $t$ with $c(t) \le b$

$t^\star \leftarrow \arg\max_t \iota_t\, \theta_t$; run it on $V_1$ at cost $\kappa$

$n_{t^\star} \leftarrow 1$; $k_{t^\star} \leftarrow$ [failed]; $b \leftarrow b - \kappa$

**end while**

*Good at:* it learns from the outcomes it sees and weighs them by impact, so it finds the high-risk failures first once a few have been seen. *Bad at:* any failure is a reward, so a test the model already fails counts as a find; it ignores the diff; with no outcome yet it has only the risk to go on; and it has no stopping rule and no verdict.

### 4.4 The proposed method: `adaptive_bayes`

**Hypotheses.** Each changed component $c \in C(\Delta)$ is broken with a prior $\pi_c$ that depends on its kind: about 0.45 to 0.5 for code, skill procedures, configuration and agent fields, 0.12 to 0.15 for prompt wording and skill prose. Tool and line components are views of a code change, not separate causes, and are folded into it. The posterior is kept exactly over all $2^{|C(\Delta)|}$ subsets $h \in \{0,1\}^{C(\Delta)}$, with $|C(\Delta)| \le 8$ (the likeliest components are kept when there are more).

**Likelihood.** A test passes only if it would pass on the current version and none of the broken components makes it fail:

$$q_t(h) = P(t \text{ fails} \mid h) = 1 - (1 - f_t) \prod_{c:\, h_c = 1} (1 - s_{tc}). \tag{3}$$

A test the model already fails ($f_t$ near 1) fails under every hypothesis, so its outcome carries no information, which is what keeps the method from mistaking the model's mistakes for regressions.

**Sensitivity.** Covering a component is weak evidence by itself: most tests that execute a changed function do not fail when it breaks. The sensitivity is therefore a product of four factors, calibrated (Algorithm 5) from the earlier changes whose outcomes are known, never from the change under test:

$$s_{tc} = \mathrm{clip}\big(r_{k(c)} \cdot \ell_{t,k(c)} \cdot \phi_t(c) \cdot \tau_t,\ 0.02,\ 0.9\big). \tag{4}$$

- $r_k$ is the reveal ratio of the component's kind $k$: among the tests that statically looked impacted by earlier changes of that kind, the share that revealed them. The kinds separate a test that executed a changed line from one that only called the changed function, and agent fields are calibrated per field. The ratio is padded toward a default $r_k^0$: 0.12 for a changed line, 0.03 for a function only called, 0.30 for a skill procedure or an agent field, 0.12 for a configuration key, 0.05 for prose.
- $\ell_{tk} = (O_{tk} + m_0)/(E_{tk} + m_0)$ is the test's own lift on that kind: $O_{tk}$ the earlier changes of kind $k$ it revealed, $E_{tk}$ the number an average impacted test would have revealed (the sum of those changes' reveal rates), $m_0 = 2$ a padding that keeps a short record from moving

the lift far. A change that breaks most of the suite says little about each test it breaks; a change that one test alone caught says a lot about that test.

- $\phi_t(c)$ is how often the baseline runs exercised the component: for code, the changed line they executed most often, or 1 when they only called the changed function; for an agent that lost tools or skills, how often $t$ used one of the lost items.
- $\tau_t = 0.5 + \text{text}(t, \Delta) + 0.5\,[\text{declared}] \in [0.5, 2]$ tilts the sensitivity up for a test whose text shares vocabulary with the diff and for one whose author declared the dependency; $\text{text}(t, \Delta) \in [0, 1]$ is the cosine of the word sets of the test and of the change, scaled so that the closest test gets 1.

A test with no link to the component gets a small constant $s_{\text{ind}} = 0.02$; one declared but never observed gets half the kind's ratio.

**Selection and stopping.** Algorithm 4 runs the loop:

- *next test*: the one with the largest expected reduction of the posterior's entropy [11] per token, the gain multiplied by $1 + \gamma(\rho_t - 1)$ with $\gamma = 0.25$ so that risk tilts the choice. Each test runs at most once: the models decode greedily, so a rerun would almost always repeat the answer;
- *after a pass*: tests with the same behaviour signature as the one that passed have their sensitivities discounted by $\delta = 0.35$, because near-duplicates give correlated evidence rather than independent draws;
- REGRESSION: at the first failure of a test that passed on the current version, because under greedy decoding that failure is a changed behaviour, which is what the ground truth calls revealing;
- CLEAN: when $1 - P(h = \mathbf{0}) < \varepsilon$, with $\varepsilon = 0.05$; BUDGET: when the budget is spent or no test can still move the posterior;
- *the mandatory rule*: before a run ends without a regression, every mandatory property in $\mathcal{P}(\Delta)$ with no test yet gets the cheapest test of that property that passes on the current version, while the budget allows. A failure there is a regression like any other.

*Bad at:* a narrow regression, which few tests reveal, where it can become confident that nothing broke before reaching them (Section 5 counts these); it needs a traced baseline and a record of earlier changes to calibrate on; and its stopping rule assumes greedy decoding. For the prioritization metrics, which score a complete order, the method's order is the greedy sequence it would pick if every test passed, with no stopping, followed by the untouched tests in cost-aware order.

# 5 Evaluation

**Questions.**

- **RQ1** Can the tests relevant to a change be identified, and what do declared and observed dependencies each give?
- **RQ2** Can the tests be ordered so that regressions are found earlier?
- **RQ3** How much budget can be returned while detection and coverage hold, and does the stopping rule give the right verdict?
- **RQ4** What do the two published methods, which do not read the change, find on the same testbed?

**Protocol.** The full suite runs $K = 5$ times on the current version, one test at a time so that coverage can follow each test, and $K = 5$ times on each of the 43 changed copies, many tests at once (Figure 3). Every strategy is then replayed offline, once per change, budget in

**Algorithm 4** `adaptive_bayes`: adaptive Bayesian selection with stopping

**Input:** components $C(\Delta)$ with priors $\pi_c$; for every test $c(t)$, $f_t$, $\rho_t$, props$(t)$ and $s_{tc}$ (Algorithm 5); near-duplicate groups; the affected mandatory properties; budget $B$; $\varepsilon$, $\delta$, $\gamma$

**Output:** the tests run $R$, a verdict, and $1 - P(\mathbf{0})$, the probability that some component is broken

$P(h) \propto \prod_c \pi_c^{h_c}(1-\pi_c)^{1-h_c}$ for $h \in \{0,1\}^{C(\Delta)}$ ▷ $h = \mathbf{0}$: nothing is broken
$R \leftarrow \emptyset$; $b \leftarrow B$
**loop**
  **if** $1 - P(\mathbf{0}) < \varepsilon$ **then return** FINISH(CLEAN)
  **end if**
  $t^\star \leftarrow$ PICK; **return** FINISH(BUDGET) if there is none
  **if** OBSERVE$(t^\star)$ = REGRESSION **then return** REGRESSION
  **end if**
**end loop**

**function** PICK
  $p_t \leftarrow \sum_h P(h)\, q_t(h)$ for every unrun $t$ ▷ $P(t$ fails$)$; $q_t$ from Equation 3
  $g_t \leftarrow H(P) - p_t\, H(P \mid t \text{ fails}) - (1-p_t)\, H(P \mid t \text{ passes})$ ▷ expected information gain
  **return** $\arg\max\{\, g_t\,(1+\gamma(\rho_t-1))/c(t) : t \notin R,\ c(t) \le b,\ g_t > 0 \,\}$
**end function**

**function** OBSERVE$(t)$
  run $t$ on $V_1$: outcome $x$, cost $\kappa$; $R \leftarrow R \cup \{t\}$; $b \leftarrow b - \kappa$
  $P(h) \leftarrow P(h)\, q_t(h)$ if $x =$ fail, else $P(h)\,(1-q_t(h))$; normalize
  **if** $x =$ fail and $f_t < \frac{1}{2}$ **then return** REGRESSION ▷ a test that used to pass has failed
  **end if**
  **if** $x =$ pass **then** $s_{uc} \leftarrow \delta\, s_{uc}$ for every unrun $u$ in the group of $t$ ▷ correlated evidence
  **end if**
  **return** $x$
**end function**

**function** FINISH(verdict)
  **for all** affected mandatory properties $p$ that no test in $R$ checks, in id order **do**
    $u \leftarrow$ the cheapest $u \notin R$ with $p \in$ props$(u)$, $f_u < \frac{1}{2}$, $c(u) \le b$; skip $p$ if there is none
    **if** OBSERVE$(u)$ = REGRESSION **then return** REGRESSION
    **end if**
  **end for**
  **return** verdict, with $1 - P(\mathbf{0})$
**end function**

$\{2, 5, 10, 20, 30, 50, 100\}\%$ of the full-suite tokens and seed, with five seeds; a seed chooses which recorded run answers each test and drives the strategies that draw at random. The method calibrates on the other 42 changes, never on the one under test.

**Ground truth.** On the current version 172 of 180 tests pass. The eight failures are the model's own mistakes, which clearer wording of the requests does not fix: it schedules a page without an approved review, requests a review nobody asked for and where none is required, applies an over-long title, goes on to publishing after a failed link check, reports pages as republished that were not, and stops a whole plan after a refused step the other steps do not depend on. Of the 34 regressions, 29 are revealed by at least one test. The model does not act on the five remaining

**Algorithm 5** Calibration of the sensitivities from the earlier changes

**Input:** earlier changes $\mathcal{D}$ with their revealing sets $\mathcal{R}(\Delta')$; defaults $r_k^0$ per kind; padding $m_0$; the change under test $\Delta \notin \mathcal{D}$; for every test $\phi_t$, $D_t^{\text{decl}}$ and its text

**Output:** $s_{tc}$ for every test $t$ and component $c \in C(\Delta)$

*Learn from the record*

**for all** $\Delta' \in \mathcal{D}$ and components $c' \in C(\Delta')$ of kind $k$ **do**

  $I \leftarrow$ the tests that look impacted by $c'$: executed a changed line, called the changed function, or match the component

  rate $\leftarrow |\mathcal{R}(\Delta') \cap I|/|I|$; append rate to $A_k$

  $O_{tk}$ += $[t \in \mathcal{R}(\Delta')]$ and $E_{tk}$ += rate for $t \in I$ ▷ once per change and kind

**end for**

$r_k \leftarrow \text{clip}((\sum A_k + m_0\, r_k^0)/(|A_k| + m_0),\ 0.01,\ 0.9)$ for every kind $k$

*Apply to the change under test*

**for all** tests $t$ and components $c \in C(\Delta)$ of kind $k$ **do**

  $\ell_{tk} \leftarrow (O_{tk} + m_0)/(E_{tk} + m_0)$;  $\tau_t \leftarrow 0.5 + \text{text}(t, \Delta) + 0.5\,[\text{declared}]$

  $s_{tc} \leftarrow \text{clip}(r_k\, \ell_{tk}\, \phi_t(c)\, \tau_t,\ 0.02,\ 0.9)$ if $\phi_t(c) > 0$; $\frac{1}{2} r_k$ if declared only; $s_{\text{ind}}$ otherwise

**end for**





Figure 3: Recording and replay. The top two rows are recorded once per model; the replay below runs every strategy, budget and seed against the recordings.

guards (a review flag, twice; a title length limit, twice; a non-blocking asset reference) with or without the change, so it behaves the same, wrongly, on both versions. No benign change fails a test. Across the 43 changes the five runs disagreed on four (change, test) pairs, which the majority vote absorbs. The 29 revealed regressions and the 14 changes no test reveals are the population below.

**Selection (RQ1).** Declared metadata caps detection at 62% however large the budget (Table 4), because shared skills reached through an include, harness code and most configuration keys are not declared. The observed dependencies select every revealing test for half the suite's tokens and reach 86% within a 20% budget. The argument for trace-informed selection holds.

**Prioritization (RQ2).** The change-aware strategies raise $\text{APFD}_c$ from 0.54 (random) to 0.76–0.81 (Table 5). The adaptive method's order is the best and finds the first regression soonest, after 1.7% of the suite's tokens. The two reproduced methods order near random (0.52 and 0.60 against 0.54) and find their first regression after 12–14% of the suite, where the change-aware strategies need under 2% to 6%.

**Budget and verdicts (RQ3).** The adaptive method is the only strategy that stops; `declared` and `observed` return budget only by running out of selected tests. It finds 74% of the regressions at a 5% budget and 78% at 20%, for under 3% of the tokens, and spends a fifth of the suite

Table 4: Detection of the 29 revealed regressions by nominal budget (share of the full-suite tokens), and the tokens actually spent: on regressions at a 20% and a 100% budget, and on the 14 changes no test reveals at 100%. Five seeds; the last three columns are shares of the full-suite tokens.

| strategy | 2% | 5% | 10% | 20% | 50% | 100% | spent@20 | spent@100 | unrevealed@100 |
|---|---|---|---|---|---|---|---|---|---|
| `full` | 0.00 | 0.14 | 0.24 | 0.34 | 0.90 | 1.00 | 0.20 | 0.98 | 1.00 |
| `random` | 0.09 | 0.22 | 0.37 | 0.56 | 0.86 | 1.00 | 0.20 | 0.98 | 1.00 |
| `declared` | 0.45 | 0.59 | 0.55 | 0.62 | 0.62 | 0.62 | 0.07 | 0.11 | 0.14 |
| `ir_tfidf` | 0.59 | 0.69 | 0.76 | 0.93 | 1.00 | 1.00 | 0.20 | 0.98 | 0.99 |
| `observed` | 0.48 | 0.62 | 0.69 | 0.86 | 0.86 | 1.00 | 0.15 | 0.49 | 0.33 |
| `cost_aware` | 0.38 | 0.55 | 0.62 | 0.86 | 0.86 | 1.00 | 0.20 | 0.98 | 0.99 |
| `casper_slices` | 0.17 | 0.28 | 0.52 | 0.59 | 0.90 | 1.00 | 0.20 | 0.98 | 1.00 |
| `risk_aware_ts` | 0.11 | 0.28 | 0.35 | 0.57 | 0.83 | 1.00 | 0.20 | 0.98 | 1.00 |
| `adaptive_bayes` | 0.61 | 0.74 | 0.78 | 0.78 | 0.81 | 0.81 | 0.03 | 0.03 | 0.20 |

Table 5: Order quality and verdicts. APFD and $\text{APFD}_c$ of the complete order; cost to the first true detection as a share of the full suite (detected cases); detection of the 21 regressions that break a safety property at a 10% and a 20% budget; share of replays, over all budgets, in which the strategy saw a failure on one of the 14 changes no test reveals.

| strategy | APFD | $\text{APFD}_c$ | first detection | safety@10 | safety@20 | false alarm |
|---|---|---|---|---|---|---|
| `full` | 0.63 | 0.58 | 0.19 | 0.14 | 0.24 | 0.72 |
| `random` | 0.54 | 0.54 | 0.14 | 0.41 | 0.60 | 0.69 |
| `declared` | 0.81 | 0.76 | 0.028 | 0.52 | 0.57 | 0.58 |
| `ir_tfidf` | 0.78 | 0.77 | 0.040 | 0.86 | 1.00 | 0.71 |
| `observed` | 0.75 | 0.79 | 0.049 | 0.57 | 0.81 | 0.58 |
| `cost_aware` | 0.74 | 0.77 | 0.060 | 0.57 | 0.81 | 0.94 |
| `casper_slices` | 0.58 | 0.52 | 0.12 | 0.62 | 0.71 | 0.57 |
| `risk_aware_ts` | 0.60 | 0.60 | 0.14 | 0.47 | 0.71 | 0.76 |
| `adaptive_bayes` | 0.83 | 0.81 | 0.017 | 0.84 | 0.84 | 0.00 |

on a change no test reveals even with the whole budget (Table 4). TF-IDF over the diff is the strongest selector at 20% (93%) and the strongest on the safety-breaking changes (all of them), and it spends the whole budget every time, on changes no test reveals too. The adaptive method's ceiling is 81%: 145 of the 1,015 replays of regressions ended CLEAN, all on regressions that one to five tests reveal, where it became confident that nothing broke before reaching them. At 20% it misses:

- the delegation that drops the ids of earlier steps, the loop that stops six steps early, and retries without idempotency keys;
- the routing skill without its brand gate and the authoring skill without its metadata step;
- the combined change, where it runs out of tests that could still move its estimate;
- the governance skill without its consent step, in two of five seeds.

The eight tests that fail on the current version fail on nearly every changed copy too. A strategy that runs one sees a failure the change did not cause: on the 14 changes no test reveals, this happens to `full` in 72% of its replays, to `cost_aware` in 94%, to the bandit in 76% and to CASPER's slices in 57% (Table 5). The adaptive method discounts a test by its failures on the current version (Equation 3) and stops only on a test that used to pass, so in 490 replays on these changes it neither ran a test that failed (Table 5) nor gave a REGRESSION verdict.

**The text factor.** The tilt $\tau_t$ can use word overlap (the default), the TF-IDF similarity of `ir_tfidf`, or no text at all (Table 6). TF-IDF brings forward the one test that reveals a narrow change and gains up to five points while spending less; without any text the method loses ten to





Figure 4: Detection of the 29 revealed regressions against the tokens actually spent, every strategy and budget. The adaptive method sits at the left: it stops.

Table 6: Detection by the method with three text measures, with the tokens spent in parentheses, against `ir_tfidf` alone.

| budget | word overlap | TF-IDF | no text | `ir_tfidf` alone |
|---|---|---|---|---|
| 5% | 0.74 (2.1%) | 0.79 (1.9%) | 0.57 (2.4%) | 0.69 (5%) |
| 20% | 0.78 (2.9%) | 0.83 (2.4%) | 0.68 (3.5%) | 0.93 (20%) |
| 50% | 0.81 (2.9%) | 0.83 (2.4%) | 0.68 (4.6%) | 1.00 (50%) |

seventeen points. Text matters, and coverage and history carry most of the result. Word overlap stays the default until a second application, with tests and changes worded differently, shows whether TF-IDF's gain holds there too.

**The mandatory rule.** Without the rule, a run that found no regression had tested every mandatory property the change may affect in 33% of the replays at a 20% budget; with it, in 90%, for 0.8 extra tests per change on average, and detection rose from 74% to 78%. The rule is also a detector: it catches the publishing skill without its link validation, which the method without the rule calls clean, because the method must test the mandatory property "no broken publish" before ending, and that test fails. The rule never caused a false verdict. Below a 10% budget it often cannot afford the extra test.

**The reproduced methods (RQ4).** CASPER's slices and the risk-aware bandit find 59% and 57% of the regressions at a 20% budget, close to random (56%) and far from the strategies that read the diff and the traces (78–93%; declared metadata alone 62%). The bandit's impact is the test's risk, so it does better on the changes that break a safety property (71% at 20% and 98% at 50%, against 57% and 83% over all regressions), and it rewards any failure, so it runs the tests the model already fails early (76% false alarms, Table 5). Neither stops. These numbers measure what the diff is worth, not CASPER in its own setting (Section 4): a platform sees changes with a diff, which the change-aware strategies cover, and model or provider updates without one, where CASPER's representatives are the natural first pass. The two could be combined: the slices can serve as the near-duplicate groups of the adaptive method, and a slice whose representatives

Table 7: The three recordings. Tests that pass on the current version; tests that "reveal" a benign change, under the majority over five runs and over the first three; (change, test) pairs on which the two votes differ; pairs on which a change's own five runs disagree; tests that carry the variation.

| model | pass on $V_0$ | benign "revealed", 5 / 3 runs | votes differ | runs disagree | varying tests |
|---|---|---|---|---|---|
| Gemma 4 E4B | 172 | 0 / 0 | 2 | 4 | 0 |
| Qwen3.8-27B | 173 | 3–6 / 2–4 | 75 | 357 | 7 |
| gpt-oss-120b | 153 | 2–5 / 1–4 | 95 | 577 | 13 |

drifted can enter the model as a changed component. On this testbed every change has a diff and the suite is small (180 tests, twelve slices), which is the case slicing has least to offer.

**Other models.** The same application was recorded with Qwen3.8-27B and with gpt-oss-120b, served as they are, with greedy decoding and five repetitions, like Gemma (Table 7). Neither recording is a clean ground truth, and the five repetitions do not settle either vote: every benign change is "revealed" by a few tests, the change whose change set is empty included. Seven tests carry Qwen's variation: one of the two cases a model judges against a rubric, the title at the length limit, four long workflows and one authoring case. Thirteen tests carry gpt-oss's; two of them pass on the current version and fail on nearly every changed copy, whichever the change. Part of the variation is batching: the baseline runs one test at a time and the changed copies many at once, and some tests pass alone and fail in a batch. Two remedies fall short. vLLM's batch-invariant mode, which would make greedy decoding exactly repeatable, does not support Qwen's attention layers; and with the empty change, recorded like the others, as the reference, every other benign change still flips tests (two to five under Qwen, one to four under gpt-oss). The rest is run-to-run variation under identical conditions, and the empty change measures that noise floor. Gemma's vote is stable (four disagreeing pairs, above).

**Threats to validity.**

- The regressions are mutants, not real changes; they were written to resemble regressions a team would ship, and the testbed does not yet pair them with a version history. The tests and the changes were written by the same people.
- One primary application, built for the purpose, and one model with a stable ground truth; the second and third models show that the ground truth depends on the model and on how it is served.
- The testbed is textual, which favours the text factor and `ir_tfidf`; a second application with differently worded tests and changes (tau-bench [1, 32]) is future work (Section 7).
- The calibration uses the other recorded changes, so leakage is controlled by leaving the change under test out, but the 42 training changes are few, which is why every learned ratio is padded toward a default.
- The stopping rule assumes greedy decoding; with sampling, a single failure would need repetitions [2, 18].

## 6 Take-aways

What the experiments say, in the order a team would act on them.

1. **Record traces; do not maintain a map.** Hand-written dependency metadata misses what shared skills, harness code and settings reach; dependencies read from traces recover it (RQ1). One instrumentation of the agent runtime replaces a test-to-component map that nobody keeps current.

2. **Read the diff.** The strategies that read the diff and the traces find most regressions early; the two that do not, CASPER's slices and the risk-aware bandit, sit near a random order and find their first revealing test late (RQ2, RQ4).
3. **Stop when confident, with a safety net.** The adaptive method finds more than any other strategy at equal tokens spent, and most of what the best full-budget strategy finds, for a small fraction of its tokens; it returns the rest. Its price is a ceiling on narrow regressions (RQ3). The mandatory rule covers the safety properties for under one extra test per change and catches a change the stopping rule alone misses. The catalog of properties is where that decision lives: whoever sets the mandatory flag decides what the pipeline never skips.
4. **Discount the tests the model already fails.** Every other strategy reports some of the model's own failures as the change's (RQ3). A pipeline should keep each test's fail rate and act only on a flip.
5. **Measure the model's noise before trusting a verdict.** An empty change, recorded like the others, measures the noise floor of a model under a serving setup (Table 7); record it before trusting a majority vote or a stopping rule.
6. **Text is a strong, cheap baseline.** TF-IDF similarity between the diff and the tests' text has the best detection when the whole budget is spent, and it never stops; it is the fallback order to keep in any pipeline.

# 7 Conclusion and future work

After a change to an agent system, the diff is worth reading. Mapped to tests through the dependencies observed in traces, it finds most of the regressions within a fifth of the suite's tokens, where hand-written metadata and the two closest published methods, which do not read it, find far fewer. A Bayesian model over the changed components, with sensitivities calibrated from the record of earlier changes, turns selection, prioritization and stopping into one decision: it returns most of the budget, orders the suite best, gives no false verdict on the changes no test reveals, and tests every mandatory property a change may affect before it calls the change clean. The price is a ceiling on narrow regressions, which the mandatory rule lowers for the properties that matter most.

Three things come next:

1. a second system under test, tau-bench's airline domain [1, 32], with the same open model playing both the agent and the user, to see whether the text factor and the calibration hold where tests and changes are worded differently;
2. real version histories beside the mutants, with the changes a team shipped and the tests that caught them, so that the reveal ratios are learned from practice;
3. the repetitions that a model with varying answers needs, with the empty change as the instrument: how many runs, under which serving setup, before a majority vote is a ground truth and a single failure is a verdict.

# References


[1] Victor Barres, Honghua Dong, Soham Ray, Xujie Si, and Karthik Narasimhan. $\tau^2$-bench: evaluating conversational agents in a dual-control environment, 2025. arXiv:2506.07982.

[2] Bjarni Haukur Bjarnason, André Silva, and Martin Monperrus. On randomness in agentic evals, 2026. arXiv:2602.07150.

[3] Olivier Chapelle and Lihong Li. An empirical evaluation of Thompson sampling. In *Advances in Neural Information Processing Systems 24 (NeurIPS)*, 2011.

[4] Eunho Cho, Donghwan Shin, and In-Young Ko. Evolution-aware regression test prioritization of ML-enabled systems using gradient-based behavior vectors, 2026. arXiv:2606.28037.

[5] Richard A. DeMillo, Richard J. Lipton, and Frederick G. Sayward. Hints on test data selection: help for the practicing programmer. *IEEE Computer*, 11(4):34–41, 1978.

[6] Sebastian Elbaum, Alexey G. Malishevsky, and Gregg Rothermel. Incorporating varying test costs and fault severities into test case prioritization. In *Proceedings of the 23rd International Conference on Software Engineering (ICSE)*, pages 329–338, 2001. doi: 10.1109/ICSE.2001.919106.

[7] Sebastian Elbaum, Alexey G. Malishevsky, and Gregg Rothermel. Test case prioritization: a family of empirical studies. *IEEE Transactions on Software Engineering*, 28(2):159–182, 2002. doi: 10.1109/32.988497.

[8] Sebastian Elbaum, Gregg Rothermel, and John Penix. Techniques for improving regression testing in continuous integration development environments. In *Proceedings of the 22nd ACM SIGSOFT International Symposium on Foundations of Software Engineering (FSE)*, pages 235–245, 2014. doi: 10.1145/2635868.2635910.

[9] Yue Jia and Mark Harman. An analysis and survey of the development of mutation testing. *IEEE Transactions on Software Engineering*, 37(5):649–678, 2011.

[10] Peiyu Li, Xiuxiu Tang, Si Chen, Ying Cheng, Ronald Metoyer, Ting Hua, and Nitesh V. Chawla. Adaptive testing for LLM evaluation: a psychometric alternative to static benchmarks, 2025. arXiv:2511.04689.

[11] Dennis V. Lindley. On a measure of the information provided by an experiment. *The Annals of Mathematical Statistics*, 27(4):986–1005, 1956.

[12] Stuart P. Lloyd. Least squares quantization in PCM. *IEEE Transactions on Information Theory*, 28(2):129–137, 1982.

[13] Wanqin Ma, Chenyang Yang, and Christian Kästner. (Why) is my prompt getting worse? Rethinking regression testing for evolving LLM APIs. In *Proceedings of the IEEE/ACM 3rd International Conference on AI Engineering: Software Engineering for AI (CAIN)*, 2024. arXiv:2311.11123.

[14] Mateusz Machalica, Alex Samylkin, Meredith Porth, and Satish Chandra. Predictive test selection. In *Proceedings of the 41st International Conference on Software Engineering: Software Engineering in Practice (ICSE-SEIP)*, pages 91–100, 2019. doi: 10.1109/ICSE-SEIP.2019.00018.

[15] Priyanath Maji and Spandan Ghose Chowdhury. Risk-aware adaptive evaluation: finding high-impact failures under limited budgets, 2026. URL `https://arxiv.org/abs/2609.38914`. arXiv:2609.38914; NeurIPS 2026 workshop on the evaluation of interactive agents.

[16] Alexey G. Malishevsky, Joseph R. Ruthruff, Gregg Rothermel, and Sebastian Elbaum. Cost-cognizant test case prioritization. Technical Report TR-UNL-CSE-2006-0004, University of Nebraska–Lincoln, 2006.

[17] Atif Memon, Zebao Gao, Bao Nguyen, Sanjeev Dhanda, Eric Nickell, Rob Siemborski, and John Micco. Taming Google-scale continuous testing. In *Proceedings of the 39th International Conference on Software Engineering: Software Engineering in Practice (ICSE-SEIP)*, pages 233–242, 2017. doi: 10.1109/ICSE-SEIP.2017.16.

[18] Evan Miller. Adding error bars to evals: a statistical approach to language model evaluations, 2024. arXiv:2411.00640.

[19] Biruk Asmare Muse, Lionel Briand, Yiwei Lu, and Keheliya Gallaba. CASPER: change-aware slice prioritization for efficient regression testing of LLM-based systems, 2026. URL `https://arxiv.org/abs/2608.00378`. arXiv:2608.00378.

[20] Franck Ndzomga. Efficient benchmarking of AI agents, 2026. arXiv:2603.23749.

[21] OpenTelemetry. Semantic conventions for generative AI: agent spans. `https://github.com/open-telemetry/semantic-conventions-genai/blob/main/docs/gen-ai/gen-ai-agent-spans.md`, 2026.

[22] Rongqi Pan, Taher A. Ghaleb, and Lionel C. Briand. LTM: scalable and black-box similarity-based test suite minimization based on language models. *IEEE Transactions on Software Engineering*, 50(11), 2024. arXiv:2304.01397.

[23] Felipe Maia Polo, Lucas Weber, Leshem Choshen, Yuekai Sun, Gongjun Xu, and Mikhail Yurochkin. tinyBenchmarks: evaluating LLMs with fewer examples. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, 2024. arXiv:2402.14992.

[24] Gregg Rothermel and Mary Jean Harrold. A safe, efficient regression test selection technique. *ACM Transactions on Software Engineering and Methodology*, 6(2):173–210, 1997. doi: 10.1145/248233.248262.

[25] Gregg Rothermel, Roland H. Untch, Chengyun Chu, and Mary Jean Harrold. Prioritizing test cases for regression testing. *IEEE Transactions on Software Engineering*, 27(10):929–948, 2001. doi: 10.1109/32.962562.

[26] Ripon K. Saha, Lingming Zhang, Sarfraz Khurshid, and Dewayne E. Perry. An information retrieval approach for regression test prioritization based on program changes. In *Proceedings of the 37th International Conference on Software Engineering (ICSE)*, pages 268–279, 2015. doi: 10.1109/ICSE.2015.47.

[27] Zahra Seyedghorban, Egor Klimov, Arie van Deursen, Annibale Panichella, and Burcu Kulahcioglu Ozkan. Observability and fault injection for LLM-based multi-agent systems in software engineering, 2026. arXiv:2608.24271.

[28] Helge Spieker, Arnaud Gotlieb, Dusica Marijan, and Morten Mossige. Reinforcement learning for automatic test case prioritization and selection in continuous integration. In *Proceedings of the 26th ACM SIGSOFT International Symposium on Software Testing and Analysis (ISSTA)*, pages 12–22, 2017. doi: 10.1145/3092703.3092709.

[29] Gou Tan, Zhensu Sun, Jieke Shi, Ting Zhang, Zilong He, Qingfu Wu, Shuai Liang, Weifeng Sun, Junda He, Pengfei Chen, Chuanfu Zhang, Lwin Khin Shar, and David Lo. AgentChaos: chaos engineering for agent systems via programmatic fault injection. In *Proceedings of the 41st IEEE/ACM International Conference on Automated Software Engineering (ASE)*, 2026. arXiv:2608.06790.

[30] William R. Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3–4):285–294, 1933.

[31] Skyler Wu, Yash Nair, and Emmanuel J. Candès. Efficient evaluation of LLM performance with statistical guarantees, 2026. arXiv:2601.20251.

[32] Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. $\tau$-bench: a benchmark for tool-agent-user interaction in real-world domains, 2024. arXiv:2406.12045.

[33] Shin Yoo and Mark Harman. Regression testing minimization, selection and prioritization: a survey. *Software Testing, Verification and Reliability*, 22(2):67–120, 2012. doi: 10.1002/stvr.430.