

GemStone-Pharo-Bridge Operator

Reference

Generated from `GemStonePharoContract` . This is the contract-driven steady-state reference for the active root API, load groups, verification lanes, and live GemStone environment.

Active Root API

Use `bridgeRoot` . The bridge steady state no longer carries the deleted legacy root aliases.

Active Load Groups

- `Original` -> `GemStone-GBS-Converted` , `GemStone-GBS-Tools`
- `Original-Tests` -> `GemStone-GBS-Converted` , `GemStone-GBS-Tools` , `GemStone-Pharo-Tests`
- `Core` -> `GemStone-GBS-Converted` , `GemStone-GBS-Core`
- `Core-Only` -> `GemStone-GBS-Converted` , `GemStone-GBS-Core`
- `Core-Tools` -> `GemStone-GBS-Converted` , `GemStone-GBS-Core` , `GemStone-GBS-Tools` , `GemStone-GBS-Core-Tools`
- `Core-Tests` -> `GemStone-GBS-Converted` , `GemStone-GBS-Core` , `GemStone-GBS-Tools` , `GemStone-GBS-Core-Tools` , `GemStone-Pharo-Core-Tests`
- `MagLev-Core` -> `GemStone-GBS-Converted` , `GemStone-GBS-Core` , `GemStone-GBS-MagLev`
- `MagLev-Tools` -> `GemStone-GBS-Converted` , `GemStone-GBS-Core` , `GemStone-GBS-Tools` , `GemStone-GBS-Core-Tools` , `GemStone-GBS-MagLev` , `GemStone-GBS-MagLev-Tools`
- `MagLev` -> `GemStone-GBS-Converted` , `GemStone-GBS-Core` , `GemStone-GBS-MagLev`
- `Tools` -> `GemStone-GBS-Converted` , `GemStone-GBS-Core` , `GemStone-GBS-Tools` , `GemStone-GBS-Core-Tools`

- `All-Tests` -> `GemStone-Pharo-Tests` , `GemStone-Pharo-Core-Tests` , `GemStone-Pharo-MagLev-Tests`
- `Tests` -> `GemStone-Pharo-Tests` , `GemStone-Pharo-Core-Tests` , `GemStone-Pharo-MagLev-Tests`
- `Full` -> `GemStone-GBS-Converted` , `GemStone-GBS-Core` , `GemStone-GBS-MagLev` , `GemStone-GBS-Tools` , `GemStone-GBS-Core-Tools` , `GemStone-GBS-MagLev-Tools` , `GemStone-Pharo-Tests` , `GemStone-Pharo-Core-Tests` , `GemStone-Pharo-MagLev-Tests`
- `default` -> `GemStone-GBS-Converted` , `GemStone-GBS-Core` , `GemStone-GBS-MagLev` , `GemStone-GBS-Tools` , `GemStone-GBS-Core-Tools` , `GemStone-GBS-MagLev-Tools` , `GemStone-Pharo-Tests` , `GemStone-Pharo-Core-Tests` , `GemStone-Pharo-MagLev-Tests`

Load Matrix

A generated switch matrix for the layered model is available at `doc/LOAD-MATRIX.md` .

Using the MagLev Branch

See `doc/MAGLEV-BRANCH-USAGE.md` for supported Metacello load snippets from local disk and GitHub, clean-switch guidance, and the classic session example.

Verification Lanes

- `core-only` : Verify the Smalltalk core without optional MagLev production packages and without deleted legacy surface.
- `bootstrap-smoke` : Prove that a clean image can micro-bootstrap the helper package and load the requested group before post-load checks run.
- `original` : Verify that the original/base production layer reloads cleanly without the generic Core or optional MagLev overlays.
- `original-drift` : Verify that the original/base production layer stays clean relative to ``56b6db3...`` , allowing only the explicit accepted test-layer exceptions.
- `original-tests` : Verify the original/base production and original/base test layer without the generic Core or optional MagLev overlays. This lane proves the base unit layer only.
- `full` : Verify the steady-state developer load plus the live GemStone lane.

- `artifact-freshness` : Verify that the generated contract artifacts and marker-managed doc sections are already up to date.
- `verify` : Run core-only, bootstrap-smoke, original, original-drift, original-tests, full, artifact-freshness, then the summary-renderer smoke check.

Expected Original-layer Test Exceptions

`make original-drift` reports the original/base production layer as clean and currently accepts only these test-layer exceptions:

- `src/GemStone-Pharo-Tests/GciError.extension.st` : Adds a tiny test-only GciError number accessor shim so the restored base login-error path can run without production drift.
- `src/GemStone-Pharo-Tests/MockGbsSession.class.st` : Keeps only a narrow interpretLoginError override so the restored base GbsSession production file stays clean.

Recommended Entry Points

```
make help
make original-drift
make core-only
make original
make original-tests
make full
make verify
make artifact-freshness
```

`make verify` is sequenced by `GemStonePharoVerifyRunner` ; the live/preflight path inside `full` is handled by `GemStonePharoVerificationRunner` .

Live GemStone Environment

- `GS_USER` : GemStone login user used by both the Topaz and GCI probes.
- `GS_PASS` : GemStone login password used by both the Topaz and GCI probes.
- `GS_STONE` : Optional stone name override. Defaults to ``gs64stone``.
- `GS_SERVICE` : Optional service name override. Defaults to ``gemnetobject``.

- `GS_NETLDI_HOST` : Optional explicit host for netldi routing.
- `GS_NETLDI_NAME_OR_PORT` : Optional explicit netldi name or port, for example ``gs64ldi`` or ``50377``.
- `GEMSTONE` : Optional explicit GemStone client home used by the GCI probe.

```
GS_USER='DataCurator' \  
GS_PASS='swordfish' \  
GS_NETLDI_HOST='localhost' \  
GS_NETLDI_NAME_OR_PORT='50377' \  
GEMSTONE='/Users/tariq/GemStone64Bit3.7.5-arm64.Darwin' \  
make full
```

No-compatibility Proof

The clean reload lane proves that deleted package, class, selector, and method-package ownership surface stays absent from the image and the active source roots.

- deleted package names stay absent
- deleted class names stay absent
- deleted selector surface stays absent
- deleted method-package ownership stays absent