

gemstone-py Setup Guide

Installation, environment, and first successful login

Generated from the Markdown sources in gemstone-py/docs
Assets are local SVG illustrations stored in the repository.

Contents

Setup Guide

What You Need

Install the Package

Required Environment Variables

First Real Login

Recommended First Commands

Transaction Policy: Read This Early

First Useful Persistent Write

First Async Check

Typed and Lifetime Examples

Running the Tests

Troubleshooting

 `GemStoneConfigurationError`

 `OSError` while loading the client library

 Login works in one shell but not another

 Your writes "worked" but the data is missing

 A Flask request wrote partial data after a handled error

 The native backend is not selected

Where to Go Next

Setup Guide

This guide gets you from "I cloned the repo" to "I can log in to GemStone from Python and run the examples without muttering at the terminal."

What You Need

At minimum:

- Python 3.11 or newer
- access to a GemStone/S 64 stone
- the GemStone client library (`libgcirpc`)
- a username and password that can log into the stone

For the full local development experience, you will also want:

- the repository checkout
- a working virtual environment
- the ability to run live tests against your stone
- if you use the self-hosted workflows, a GitHub Actions runner on the GemStone host

Install the Package

From PyPI:

```
python3 -m pip install gemstone-py
```

If you want the optional PyO3 native fast path and a wheel exists for your platform:

```
python3 -m pip install "gemstone-py[fast]"
python -c "from gemstone_py import _gci; print(_gci.IMPLEMENTATION)"
```

From a repository checkout, the fuller backend example is `python -m examples.native_backend.check_backend`.

From a repo checkout:

```
python3 -m venv .venv
source .venv/bin/activate
```

```
python -m pip install -U pip
python -m pip install -e .[dev]
```

Required Environment Variables

The package expects its runtime configuration from environment variables. The minimum set for most local work is:

```
export GS_LIB=/opt/gemstone/product/lib
export GS_STONE=gs64stone
export GS_USERNAME=DataCurator
export GS_PASSWORD=swordfish
```

Common optional variables:

```
export GS_HOST=localhost
export GS_NETLDI=netldi
export GS_GEM_SERVICE=gemnetobject
export GS_HOST_USERNAME=
export GS_HOST_PASSWORD=
export GS_LIB_PATH=/full/path/to/libgcirpc-3.7.x-64.dylib
```

Quick reference:

Variable	Required	Example	Purpose
GS_LIB	Yes	/opt/gemstone/product/lib	GemStone lib/ directory for library discovery
GS_STONE	Yes	gs64stone	Stone name
GS_USERNAME	Yes	DataCurator	GemStone login username
GS_PASSWORD	Yes	swordfish	GemStone login password
GS_LIB_PATH	No	/full/path/libgcirpc.dylib	Pin to a specific libgcirpc file
GS_HOST	No	localhost	Remote stone host
GS_NETLDI	No	netldi	NetLDI service name
GS_GEM_SERVICE	No	gemnetobject	Gem service name
GS_HOST_USERNAME	No		Remote host OS username

Variable	Required	Example	Purpose
GS_HOST_PASSWORD	No		Remote host OS password

First Real Login

The simplest sanity check is a tiny Python script:

```
from gemstone_py import GemStoneConfig, GemStoneSession

config = GemStoneConfig.from_env()

with GemStoneSession(config=config) as session:
    print(session.eval("1 + 2"))
```

If that prints `3`, the package can:

- read your configuration
- load `libgcirpc`
- log in to GemStone
- evaluate Smalltalk in the repository

That is enough to start.

Recommended First Commands

The installed package ships with a few small CLI helpers:

```
gemstone-hello
gemstone-smalltalk-demo
gemstone-examples hello
gemstone-examples smalltalk-demo
gemstone-benchmarks --help
```

From a repository checkout, these examples are also useful first checks:

```
python -m examples.native_backend.check_backend
```

What they are good for:

- `gemstone-hello`

Tiny smoke check for the installed package.

- `gemstone-smalltalk-demo`

Basic bridge demo that is easy to reason about.

- `gemstone-examples ...`

A stable wrapper for the example entry points.

- `gemstone-benchmarks`

The maintained benchmark lane, distinct from the teaching examples.

- `examples.native_backend.check_backend`

Shows whether the current process selected ctypes or the optional native GCI backend.

Transaction Policy: Read This Early

The most important behavioural rule in `gemstone-py` is that transaction intent should be explicit.

`GemStoneSession(...)` defaults to manual transaction control.

That means:

- a plain session does not silently commit just because your `with` block ended
- write scripts must call `commit()` explicitly or use a scoped helper that commits on success
- read-only scripts should usually abort or use an abort-on-exit policy

The common options are:

```
from gemstone_py import GemStoneSession, TransactionPolicy

with GemStoneSession(
    config=config,
    transaction_policy=TransactionPolicy.COMMIT_ON_SUCCESS,
) as session:
    ...
```

Or:

```
from gemstone_py import session_scope

with session_scope(config=config) as session:
    ...
```

Use this rule of thumb:

- one-off write script -> `COMMIT_ON_SUCCESS`

- read-only inspection -> `ABORT_ON_EXIT`
- library or framework code -> manual, unless you deliberately wrap it

First Useful Persistent Write

Once login works, prove that you can store and read data:

```
from gemstone_py import GemStoneConfig, TransactionPolicy
from gemstone_py import GemStoneSession
from gemstone_py.persistent_root import PersistentRoot

config = GemStoneConfig.from_env()

with GemStoneSession(
    config=config,
    transaction_policy=TransactionPolicy.COMMIT_ON_SUCCESS,
) as session:
    root = PersistentRoot(session)
    root["DocsSmokeTest"] = {"status": "ok", "kind": "setup-guide"}

with GemStoneSession(config=config) as session:
    root = PersistentRoot(session)
    print(root["DocsSmokeTest"])
```

If that round trip works, the rest of the package will feel much less mysterious.

First Async Check

If your application is async-first, run the async example after the basic sync login works:

```
python -m examples.async_features.session_root_and_collection
```

The example opens an `AsyncSession`, writes through `AsyncPersistentRoot`, keeps a managed OOP alive, and exercises `AsyncGSCollection`.

For FastAPI:

```
python -m pip install fastapi uvicorn
uvicorn examples.fastapi.app:app --reload
```

Visit `http://127.0.0.1:8000/health/gemstone`.

Typed and Lifetime Examples

Once basic reads and writes work, these examples show the newer type and export-set APIs:

```
python -m examples.typed_access.typed_oops_and_queries
python -m examples.lifetime.managed_oop_handles
```

Use them to confirm that `TypedOop[T]`, typed `GSCollection` predicates, `execute_managed(...)`, and `session.handle(...)` behave against your stone.

Running the Tests

Unit tests:

```
python -m unittest discover -s tests -p 'test*.py'
```

The standard local verification lane:

```
./scripts/run_ci_checks.sh
```

Live GemStone tests:

```
GS_RUN_LIVE=1 ./scripts/run_live_checks.sh
```

Longer live soak tests:

```
GS_RUN_LIVE=1 GS_RUN_LIVE_SOAK=1 ./scripts/run_live_checks.sh
```

Destructive live tests are intentionally separated. They mutate shared state and are not meant to be run casually.

Troubleshooting

GemStoneConfigurationError

Usually means `GS_USERNAME` and/or `GS_PASSWORD` are missing.

OSError while loading the client library

Usually one of:

- `GS_LIB` is wrong
- `GS_LIB_PATH` points at a missing or incompatible `libgcirpc`
- the local machine does not actually have the client library installed

Login works in one shell but not another

Check that both shells export the same environment values. This failure mode is common, boring, and surprisingly effective.

Your writes "worked" but the data is missing

That almost always means you forgot to commit or assumed a session would commit for you. Re-check the transaction policy.

A Flask request wrote partial data after a handled error

Use the request-session integration from `gemstone_py.web` and let request teardown own the final commit-or-abort decision. The web helpers were hardened exactly to avoid this problem.

The native backend is not selected

Check the current process:

```
python -m examples.native_backend.check_backend
```

If `selected backend` is `ctypes`, either the optional package is not installed or `GEMSTONE_PY_GCI_BACKEND=ctypes` was set before Python started. Install `gemstone-py[fast]` and start a fresh Python process. Use `GEMSTONE_PY_GCI_BACKEND=native` when you want import failure instead of silent fallback.

Where to Go Next

- [User Manual](#) for the main abstractions
- [Examples Guide](#) for the runnable demos
- [Cookbook](#) for copy-paste-friendly recipes

This PDF was generated locally from the Markdown sources in `docs/`. If you edit the source files, rerun `python docs/build_pdf_docs.py`.