

gemstone-rs Setup Guide

Install, configure, and complete the first GemStone login



Generated from the Markdown sources in `gemstone-rs/docs`.

Contents

Setup Guide

What You Need

Which Install Path Should I Use?

Environment Variables

First Login

Development Checkout

Setup Guide

This guide gets you from a Rust project or source checkout to a live GemStone login.

What You Need

At minimum:

- Rust stable toolchain
- access to a GemStone/S 64 stone
- GemStone client library access through `libgcirpc`
- GemStone username and password

For the full local development experience:

- a `gemstone-rs` checkout
- `cargo`, `rustfmt`, and `clippy`
- Node.js 22 when working on the VS Code extension
- a Marketplace PAT only when publishing the VSIX
- a crates.io API token only when publishing crates

Which Install Path Should I Use?

Use case	Command
Rust application dependency	<code>cargo add gemstone-rs</code>
CLI tools	<code>cargo install gemstone-rs-cli</code>
Local HTTP explorer	<code>cargo install gemstone-rs-explorer</code>
Source checkout examples	<code>cargo run -p gemstone-rs --example quickstart</code>
VS Code users	Install <code>unicompute.gemstone-rs-workbench</code> from Marketplace

Environment Variables

Most live commands use `Config::from_env()`:

```
export GS_LIB=/opt/gemstone/product/lib
export GS_STONE=gs64stone
export GS_STONE_NAME=gs64stone
export GS_USERNAME=DataCurator
export GS_PASSWORD=swordfish
```

`GS_STONE` is canonical. `GS_STONE_NAME` is accepted as an alias when `GS_STONE` is absent. Setting both to the same value keeps CLI, examples, explorer, and VS Code settings aligned.

Optional variables:

```
export GS_HOST=localhost
export GS_NETLDI=netldi
export GS_GEM_SERVICE=gemnetobject
export GS_HOST_USERNAME=
export GS_HOST_PASSWORD=
export GS_LIB_PATH=/full/path/to/libgcirpc.dylib
```

Variable	Required	Purpose
<code>GS_LIB</code>	Usually	GemStone <code>lib/</code> directory for runtime library discovery.
<code>GS_LIB_PATH</code>	No	Full path to a specific <code>libgcirpc</code> file.
<code>GS_STONE</code>	Yes	Stone name.
<code>GS_STONE_NAME</code>	No	Stone-name alias used when <code>GS_STONE</code> is absent.
<code>GS_USERNAME</code>	Yes	GemStone login username.
<code>GS_PASSWORD</code>	Yes	GemStone login password.
<code>GS_HOST</code>	No	Remote host, defaults to local behavior.
<code>GS_NETLDI</code>	No	NetLDI service name.
<code>GS_GEM_SERVICE</code>	No	Gem service name.

First Login

With the CLI:

```
cargo install gemstone-rs-cli
gemstone-rs doctor
gemstone-rs doctor --live
```

```
gemstone-rs doctor --json
gemstone-rs eval "3 + 4"
```

Expected output:

```
7
```

`gemstone-rs doctor` prints the relevant `GS_*` values with secrets masked, loads the configured `libgcrpc`, and reports setup problems without exposing passwords. Add `--live` when the stone should be reachable; it logs in and asserts that `3 + 4` returns `7`. Add `--json` when a script, CI job, or editor integration needs a parseable report.

From a source checkout:

```
cd /path/to/gemstone-rs
cargo run -p gemstone-rs --example hello_gemstone
cargo run -p gemstone-rs --example quickstart
```

From a Rust application:

```
use gemstone_rs::{Config, Session, Value};

fn main() -> gemstone_rs::Result<()> {
    let mut session = Session::login(Config::from_env())?;
    assert_eq!(session.eval("3 + 4")?, Value::SmallInt(7));
    Ok(())
}
```

Development Checkout

```
git clone git@github.com:unicompute/gemstone-rs.git
cd gemstone-rs
make verify
```

`make verify` runs formatting, `cargo check`, clippy, tests, codegen freshness, the VS Code extension syntax/smoke checks, and PDF generation.

Package the VSIX locally:

```
make vscode-package
```

Verify already-published artifacts:

```
scripts/publish_verify.sh 0.2.0
```

This PDF was generated locally from docs/. If you edit the Markdown sources, rerun python docs/build_pdf_docs.py.