

gemstone-rs User Manual

Core Rust API usage for sessions, OOPs, browser operations, and transactions



Generated from the Markdown sources in gemstone-rs/docs.

Contents

User Manual

Configuration

Sessions

Eval and Perform

OOP and Value Conversion

Globals

Transactions

Export-Set Lifetime

Browser API

Error Handling

User Manual

`gemstone-rs` is the safe Rust client API for GemStone/S over GCI. Rust code imports it as `gemstone_rs`.

Configuration

Use `Config::from_env()` for normal applications:

```
let config = gemstone_rs::Config::from_env()?;
```

Use the builder when you want explicit configuration:

```
use gemstone_rs::Config;

let config = Config::builder()
    .stone("gs64stone")
    .host("localhost")
    .netldi("netldi")
    .username("DataCurator")
    .password("swordfish")
    .build()?;
```

Sessions

`Session` logs out automatically on drop. Calling `logout()` explicitly is still useful in examples and command-line tools.

```
use gemstone_rs::{Config, Session, Value};

let mut session = Session::login(Config::from_env())?;
let value = session.eval("3 + 4")?;
assert_eq!(value, Value::SmallInt(7));
session.logout()?;
```

`Session` is deliberately not `Send` or `Sync`. Keep a session on the thread that logged it in.

Eval and Perform

`eval` returns a marshalled `Value`:

```
let value = session.eval("3 + 4")?;
```

`execute` returns a raw `Obj`:

```
let object_class = session.execute("Object")?;
```

`perform` returns a marshalled `Value`:

```
let seven = session.smallint_oop(7);  
let printed = session.perform(seven, "printString", &[])?;
```

`perform_oop` returns a raw `Obj`:

```
let printed_oop = session.perform_oop(seven, "printString", &[])?;  
let printed = session.fetch_string(printed_oop)?;
```

OOP and Value Conversion

`Value` covers `nil`, booleans, small integers, characters, fetched strings, and raw OOPs:

```
use gemstone_rs::Value;  
  
let oop = session.value_to_oop(&Value::SmallInt(7))?;  
let value = session.eval("true")?;  
println!("{value:?}");
```

Helpers:

```
let nil = session.nil_oop();  
let yes = session.bool_oop(true);  
let seven = session.smallint_oop(7);  
let text = session.new_string("hello")?;  
let symbol = session.new_symbol("ExampleSymbol")?;
```

Globals

`global_get` and `global_put` use `UserGlobals`:

```
let text = session.new_string("hello from Rust")?;  
session.global_put("GemStoneRsText", text)?;
```

```
let stored = session.global_get("GemStoneRsText")?;
println!("{}", session.fetch_string(stored)?);
```

Transactions

Use `transaction` when you want commit-on-success and abort-on-error:

```
session.transaction(|session| {
    let value = session.new_string("committed")?;
    session.global_put("GemStoneRsCommitted", value)
})?;
```

Manual transaction primitives are also available:

```
let needs_commit = session.needs_commit()?;
let in_transaction = session.in_transaction()?;
session.commit()?;
session.abort()?;
```

Export-Set Lifetime

Use `retain_oop` when a raw OOP must be held across calls and protected from GemStone-side collection:

```
let text = session.new_string("retained")?;
let handle = session.retain_oop(text)?;
println!("{}", handle.oop().raw());
handle.release()?;
```

The handle releases on drop if you do not call `release()`.

Browser API

```
use gemstone_rs::browser::{Browser, ALL_PROTOCOLS};

let mut browser = Browser::new(&mut session);
let dictionaries = browser.dictionaries()?;
let classes = browser.classes("UserGlobals")?;
let protocols = browser.protocols("Object", false, "")?;
let methods = browser.methods("Object", ALL_PROTOCOLS, false, "")?;
let source = browser.source("Object", "printString", false, "")?;
```

Pass an empty dictionary to resolve through the active user's symbol list.

Error Handling

Most APIs return `gemstone_rs::Result<T>`. Errors distinguish missing environment, missing config, GCI loading/calls, GemStone errors, illegal OOPs, unexpected typed codegen returns, and conversion issues.

```
match Config::from_env() {  
    Ok(config) => println!("stone {}", config.stone),  
    Err(err) => eprintln!("configuration error: {err}"),  
}
```

The CLI exposes the same checks through `doctor`:

```
gemstone-rs env sample  
gemstone-rs doctor  
gemstone-rs doctor --live  
gemstone-rs doctor --json
```

`env sample` prints a safe shell export template with password placeholders. The non-live doctor form validates environment and GCI library loading. The live form also logs in and checks that `3 + 4` returns `7`. Human and JSON reports show which source selected `libgcirpc`: explicit config, `GS_LIB_PATH`, `GS_LIB`, or `GEMSTONE/lib`, plus the exact path or directory searched. The JSON form is intended for automation and editor integrations, and includes the same remediation hints as the human report.

This PDF was generated locally from `docs/`. If you edit the Markdown sources, rerun `python docs/build_pdf_docs.py`.