

gemstone-rs VS Code Workbench

Sidebar browsing, codegen, and explorer launch workflows



Generated from the Markdown sources in gemstone-rs/docs.

Contents

VS Code Workbench

Setup

Sidebar Tree

Command Palette

Codegen Workflow

Object Mapping Workflow

Embedded Explorer Webview

Develop the Extension

Later Feature Work

VS Code Workbench

`gemstone-rs Workbench` is the VS Code companion for the Rust CLI and local explorer. It keeps the CLI as the stable contract and adds a sidebar, output panel, generated-file previews, and codegen diff prompts.

Marketplace:

```
https://marketplace.visualstudio.com/items?itemName=unicompute.gemstone-rs-workbench
```

Setup

For installed CLI tools:

```
{
  "gemstoneRs.cliPath": "gemstone-rs",
  "gemstoneRs.explorerPath": "gemstone-rs-explorer",
  "gemstoneRs.codegenConfig": "gemstone-rs.codegen"
}
```

For a source checkout:

```
{
  "gemstoneRs.checkoutPath": "/path/to/gemstone-rs",
  "gemstoneRs.useCargo": true,
  "gemstoneRs.codegenConfig": "examples/codegen/gemstone-rs.codegen"
}
```

Use the same `GS_*` environment as the CLI.

Sidebar Tree

Open the GemStone RS activity bar item.

The sidebar contains:

- `Dictionaries`
- `Codegen Config`
- `Explorer`

Dictionaries expands live dictionaries, classes, protocols, and methods. Selecting a method opens its source in an untitled Smalltalk editor.

Codegen Config exposes:

- Discover from Live Stone
- Generate Mapping Config
- Preview BridgeRoot
- List BridgeRoot Keys
- Put BridgeRoot String
- Put BridgeRoot Symbol
- Put BridgeRoot SmallInt
- Put BridgeRoot Bool
- Remove BridgeRoot Key
- Run Generated Mapping Example
- Preview Wrappers
- Diff Generated Output
- Check Freshness
- Generate Wrappers
- Load Project Profiles
- Save Project Profiles
- Export Codegen Profile
- Show Sample Project Profiles
- Create Project Profiles
- Validate Project Profiles
- List Project Profiles
- Show Project Profile
- Resolve Project Profile
- Check Project Profiles
- Open Codegen Docs

Explorer exposes:

- Doctor
- Verify Setup
- Verify Live Setup
- Eval Smalltalk
- Generate Explorer Auth Token
- Clear Explorer Auth Token
- Launch Explorer
- Open Explorer Webview

Command Palette

Commands:

- GemStone RS: Verify Setup
- GemStone RS: Verify Live Setup
- GemStone RS: Verify Strict Setup
- GemStone RS: Doctor
- GemStone RS: Show Environment Template
- GemStone RS: Copy Environment Template
- GemStone RS: Write .env.gemstone-rs
- GemStone RS: Eval Smalltalk
- GemStone RS: Browse Dictionaries
- GemStone RS: Browse Classes
- GemStone RS: Codegen Init
- GemStone RS: Codegen Discover
- GemStone RS: Generate Mapping Config
- GemStone RS: Preview BridgeRoot
- GemStone RS: List BridgeRoot Keys
- GemStone RS: Put BridgeRoot String
- GemStone RS: Put BridgeRoot Symbol
- GemStone RS: Put BridgeRoot SmallInt
- GemStone RS: Put BridgeRoot Bool
- GemStone RS: Remove BridgeRoot Key
- GemStone RS: Run Generated Mapping Example
- GemStone RS: Codegen Preview
- GemStone RS: Codegen Diff
- GemStone RS: Codegen Check
- GemStone RS: Codegen Explain
- GemStone RS: Codegen Generate
- GemStone RS: Codegen Preview Profile
- GemStone RS: Codegen Diff Profile
- GemStone RS: Codegen Check Profile
- GemStone RS: Codegen Explain Profile
- GemStone RS: Codegen Generate Profile
- GemStone RS: Load Project Profiles
- GemStone RS: Save Project Profiles
- GemStone RS: Export Codegen Profile
- GemStone RS: Show Sample Project Profiles
- GemStone RS: Create Project Profiles
- GemStone RS: Validate Project Profiles
- GemStone RS: List Project Profiles
- GemStone RS: Show Project Profile
- GemStone RS: Resolve Project Profile
- GemStone RS: Check Project Profiles

- GemStone RS: Generate Explorer Auth Token
- GemStone RS: Clear Explorer Auth Token
- GemStone RS: Launch Explorer
- GemStone RS: Open Explorer Webview
- GemStone RS: Open Method Source
- GemStone RS: Open Codegen Docs

GemStone RS: Verify Setup and GemStone RS: Doctor both run the CLI `gemstone-rs doctor` report, so the workbench setup view and terminal setup use the same diagnostic path.

GemStone RS: Verify Live Setup runs `gemstone-rs doctor --live` when credentials and a reachable stone are available. GemStone RS: Verify Strict Setup runs `gemstone-rs doctor --strict` for CI-style validation of explicit stone and GCI library settings. All setup checks add the active checkout, CLI, explorer, codegen config, and profile paths, plus whether the configured `gemstoneRs.envFile` exists. When that file exists, Workbench passes `--env-file` automatically to CLI commands and explorer startup. The checks offer result actions to copy the full report, copy a safe `GS_*` environment export script with a placeholder password, or open the extension settings.

GemStone RS: Run Setup Assistant calls the running local explorer at `/api/setup/assistant` and renders the structured env-file, GemStone configuration, GCI library, codegen config, and project profile checks in the output panel. Start the explorer first with GemStone RS: Launch Explorer.

GemStone RS: Show Environment Template, GemStone RS: Copy Environment Template, and GemStone RS: Write `.env.gemstone-rs` call the CLI `gemstone-rs env sample/write` commands. The template uses current non-secret values when available and keeps passwords as placeholders.

Codegen Workflow

1. Set `gemstoneRs.codegenConfig`.
2. Run GemStone RS: Codegen Discover or edit the config manually.
3. Run GemStone RS: Codegen Preview.
4. Run GemStone RS: Codegen Diff.
5. Run GemStone RS: Codegen Explain.
6. Run GemStone RS: Codegen Generate.

Codegen Generate runs the diff first. If output would change, it opens the diff and asks before writing.

Codegen Explain runs `codegen explain --json` and renders the output path, generated test stubs, wrapper classes, selectors, return types, and BridgeRoot mappings in the output panel. Result actions can copy the summary, copy the raw JSON, open the JSON in an editor, or open the config file.

When a project profile file is checked in, use the profile variants instead: `Codegen Preview Profile`, `Codegen Diff Profile`, `Codegen Check Profile`, `Codegen Explain Profile`, and `Codegen Generate Profile`. They prompt for a profile name and `gemstone-rs.codegen-profiles.json`, resolve the profile's `config/root` fields, and then run the same codegen operation.

Object Mapping Workflow

Use `GemStone RS: Generate Mapping Config` when you want the live stone to inspect a `GemStone` class and propose a `BridgeMapped` config. The command asks for:

- config path
- Rust struct name
- `GemStone` class reference, such as `Object` or `UserGlobals:0kzBooking`

Use `GemStone RS: Preview BridgeRoot` after starting the local explorer. It opens:

```
http://127.0.0.1:8787/api/bridge/root
```

Use `GemStone RS: List BridgeRoot Keys` for the same inspection path without opening a browser; it runs `gemstone-rs bridge keys` and writes the key OOPs, class OOPs, `printString` values, and identity ids to the output panel.

Use `GemStone RS: Put BridgeRoot String` when you want a quick live-write smoke test from VS Code. It asks for a key, whether that key is a `String` or `Symbol`, and a string value, then runs:

```
gemstone-rs bridge put-string <key> <value> --key-type String
```

Use `GemStone RS: Put BridgeRoot Symbol` for the same workflow when the stored value should be a `GemStone Symbol`:

```
gemstone-rs bridge put-symbol <key> <value> --key-type String
```

Use `GemStone RS: Put BridgeRoot SmallInt` or `GemStone RS: Put BridgeRoot Bool` when the stored value should be a `GemStone SmallInteger` or `Boolean`:

```
gemstone-rs bridge put-smallint <key> <value> --key-type String
gemstone-rs bridge put-bool <key> <value> --key-type String
```

Use `GemStone RS: Remove BridgeRoot Key` to remove one `BridgeRoot` key after a `String/Symbol` key-type prompt and confirmation prompt:

```
gemstone-rs bridge remove <key> --key-type String
```

Use **GemStone RS: Run Generated Mapping Example** to run:

```
cargo run -p gemstone-rs --example generated_mapping_app
```

Embedded Explorer Webview

Use **GemStone RS: Launch Explorer** first. It starts `gemstone-rs-explorer` in a terminal and opens the browser. Then use **GemStone RS: Open Explorer Webview** to embed the local explorer inside VS Code.

The webview points at:

```
http://127.0.0.1:8787/
```

If you set `gemstoneRs.explorerAuthToken`, **GemStone RS: Launch Explorer** starts the server with `--auth-token-env GEMSTONE_RS_EXPLORER_TOKEN` so the token is not printed in the terminal command. Browser and webview URLs include the matching `token=` query parameter. Use **GemStone RS: Generate Explorer Auth Token** to create a local random token, save it to VS Code settings, and copy it to the clipboard. Use **GemStone RS: Clear Explorer Auth Token** to return to the default loopback-only, no-token mode.

It is still the same loopback-only explorer process. If the explorer is not running, the webview will show a connection error and the output panel will show the URL to start.

The embedded page now acts as the main IDE surface for the local explorer. The iframe remains the full browser UI, while the side inspector can query explorer status, run setup checks, inspect project profile freshness, preview Codegen JSON, inspect diffs, check generated freshness, and inspect BridgeRoot keys. The same shell can hand off to native VS Code commands for generated wrapper preview, diff, check, generate-with-confirmation, profile checks, docs, and opening the last generated output file reported by the explorer.

The explorer page can load and save the selected codegen config file, posting the editor contents as the request body; saves still require the explorer to run with `--allow-write`. Use **Refresh Configs** in the embedded page to populate the **Known configs** picker from the explorer process working tree, or set **Config root** in the page when the explorer was launched from a different directory. The page also keeps a local **Recent configs** picker for paths used by Load, Save, Preview, Diff, Check, and Generate. Use **Save Profile** when you want to switch between named codegen workflows; a profile stores the config root, config path, mapped Rust type, and GemStone class in local browser storage. **Export Profile** writes a JSON payload into **Profile JSON**, and **Import Profile** merges pasted profile JSON from another browser or teammate. **Load Project Profiles** reads `gemstone-rs.codegen-profiles.json` from the configured codegen root, and

`Save Project Profiles` writes the saved profile list back when the explorer was launched with `--allow-write`. Project profile payloads are schema-validated before writing, and imports report which profiles are new, replaced, or unchanged. It remembers its current fields locally, so repeated codegen or BridgeRoot checks keep the same config path and class selection.

Use `GemStone RS: Show Sample Project Profiles` to open the built-in sample from `gemstone-rs profile sample`, `GemStone RS: Create Project Profiles` to write that sample into a project file with `gemstone-rs profile init`, and `GemStone RS: Validate Project Profiles` when you want a direct CLI check without opening the explorer. Validation runs `gemstone-rs profile validate` against the selected profile file and writes the result to the GemStone RS output panel. `GemStone RS: List Project Profiles` and `GemStone RS: Show Project Profile` run `gemstone-rs profile list/show` and render the parsed config/root/mapped/class fields in the same output panel. `GemStone RS: Resolve Project Profile` runs `gemstone-rs profile resolve` and shows the config path that profile-driven codegen will use. `GemStone RS: Check Project Profiles` runs `gemstone-rs profile check --json` across every profile and renders an aggregate summary with ok, stale, and error counts before you commit. The result message can copy the report or open the profile file for quick repair. Profile-specific commands use a QuickPick populated from the project profile file. The extension also contributes JSON validation for files named `gemstone-rs.codegen-profiles.json` and profile check reports named `gemstone-rs.profile-check.json`.

Develop the Extension

```
cd vscode-gemstone-rs-workbench
npm ci
npm run check
npm run test:smoke
npm run package -- --out gemstone-rs-workbench-0.3.4.vsix
```

From the repository root:

```
make vscode-package
```

Later Feature Work

The first embedded webview is available. Next work should make the webview more IDE-like: generate wrapper diffs before writing, edit codegen selections, inspect BridgeRoot payloads visually, and keep browser fallback behavior for users who prefer the external explorer.

This PDF was generated locally from docs/. If you edit the Markdown sources, rerun `python docs/build_pdf_docs.py`.