RCSFILE(5) RCSFILE(5)

NAME

rcsfile - RCS file format

DESCRIPTION

An RCS file's contents are described by the grammar below.

The text is free format: space, backspace, tab, newline, vertical tab, form feed, and carriage return (collectively, *white space*) have no significance except in strings. However, white space cannot appear within an id, num, or sym, and an RCS file must end with a newline.

Strings are enclosed by @. If a string contains a @, it must be doubled; otherwise, strings can contain arbitrary binary data.

The meta syntax uses the following conventions: '|' (bar) separates alternatives; '{' and '}' enclose optional phrases; '{' and '}*' enclose phrases that can be repeated zero or more times; '{' and '}+' enclose phrases that must appear at least once and can be repeated; Terminal symbols are in **boldface**; nonterminal symbols are in *italics*.

```
::= admin {delta}* desc {deltatext}*
rcstext
admin
          := head
                           {num};
              { branch
                           {num};}
              access
                           {id}*;
              symbols
                           \{sym:num\}*;
              locks
                           {id : num}*; {strict ;}
              { integrity { string }; }
              { comment { string }; }
              { expand
                           {string}; }
delta
          ::= num
              date
                           num;
              author
                           id;
              state
                           {id};
              branches
                           \{num\}^*;
              next
                           {num};
              { committed sym; }
desc
          ::= desc
                           string
deltatext ::= num
                           string
              log
              text
                           string
          ::= \{digit | .\} +
num
          ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9
digit
id
          ::= \{idchar \mid .\}+
sym
          ::= \{idchar\}+
idchar
          ::= any visible graphic character except special
special
          ::= $|,|.|:|;|@
string
          ::= @{any character, with @ doubled}*@
word
          ::= id \mid num \mid string \mid :
```

Identifiers are case sensitive. Keywords are in lower case only. The sets of keywords and identifiers can overlap. In most environments RCS uses the ISO 8859/1 encoding: visible graphic characters are codes 041–176 and 240–377, and white space characters are codes 010–015 and 040.

Dates, which appear after the **date** keyword, are of the form Y.mm.dd.hh.mm.ss, where Y is the year, mm the month (01–12), dd the day (01–31), hh the hour (00–23), mm the minute (00–59), and ss the second (00–60). Y contains just the last two digits of the year for years from 1900 through 1999, and all the digits


RCSFILE(5) RCSFILE(5)

of years thereafter. Dates use the Gregorian calendar; times use UTC.

The *delta* nodes form a tree. All nodes whose numbers consist of a single pair (e.g., 2.3, 2.1, 1.3, etc.) are on the trunk, and are linked through the **next** field in order of decreasing numbers. The **head** field in the *admin* node points to the head of that sequence (i.e., contains the highest pair). The **branch** node in the admin node indicates the default branch (or revision) for most RCS operations. If empty, the default branch is the highest branch on the trunk.

All *delta* nodes whose numbers consist of 2n fields ($n \ge 2$) (e.g., 3.1.1.1, 2.1.2.2, etc.) are linked as follows. All nodes whose first 2n-1 number fields are identical are linked through the **next** field in order of increasing numbers. For each such sequence, the *delta* node whose number is identical to the first 2n-2 number fields of the deltas on that sequence is called the branchpoint. The **branches** field of a node contains a list of the numbers of the first nodes of all sequences for which it is a branchpoint. This list is ordered in increasing numbers.

The following diagram shows an example of an RCS file's organization.



IDENTIFICATION

Author: Walter F. Tichy.

Manual Page Revision: 5.8; Release Date: 2011-08-30.

Copyright © 2010, 2011 Thien-Thi Nguyen.

Copyright © 1990, 1991, 1992, 1993, 1994, 1995 Paul Eggert.

Copyright © 1982, 1988, 1989 Walter F. Tichy.

SEE ALSO

rcsintro(1), ci(1), co(1), ident(1), rcs(1), rcsclean(1), rcsdiff(1), rcsmerge(1), rlog(1).

Walter F. Tichy, RCS—A System for Version Control, *Software—Practice & Experience* **15**, 7 (July 1985), 637-654.