

NAME

nlmconv – converts object code into an NLM.

SYNOPSIS

```
nlmconv [-I bfdname] --input-target=bfdname
        [-O bfdname] --output-target=bfdname
        [-T headerfile] --header-file=headerfile
        [-d] --debug [-l linker] --linker=linker
        [-h] --help [-V] --version
        infile outfile
```

DESCRIPTION

nlmconv converts the relocatable **i386** object file *infile* into the NetWare Loadable Module *outfile*, optionally reading *headerfile* for NLM header information. For instructions on writing the NLM command file language used in header files, see the **linkers** section, **NLMLINK** in particular, of the *NLM Development and Tools Overview*, which is part of the NLM Software Developer's Kit ("NLM SDK"), available from Novell, Inc. **nlmconv** uses the GNU Binary File Descriptor library to read *infile*;

nlmconv can perform a link step. In other words, you can list more than one object file for input if you list them in the definitions file (rather than simply specifying one input file on the command line). In this case, **nlmconv** calls the linker for you.

OPTIONS

-I *bfdname*

--input-target=*bfdname*

Object format of the input file. **nlmconv** can usually determine the format of a given file (so no default is necessary).

-O *bfdname*

--output-target=*bfdname*

Object format of the output file. **nlmconv** infers the output format based on the input format, e.g. for a **i386** input file the output format is **nlm32-i386**.

-T *headerfile*

--header-file=*headerfile*

Reads *headerfile* for NLM header information. For instructions on writing the NLM command file language used in header files, see the **linkers** section, of the *NLM Development and Tools Overview*, which is part of the NLM Software Developer's Kit, available from Novell, Inc.

-d

--debug

Displays (on standard error) the linker command line used by **nlmconv**.

-l *linker*

--linker=*linker*

Use *linker* for any linking. *linker* can be an absolute or a relative pathname.

-h

--help

Prints a usage summary.

-V

--version

Prints the version number for **nlmconv**.

SEE ALSO

the Info entries for *binutils*.

COPYRIGHT

Copyright (c) 1991, 92, 93, 94, 95, 96, 97, 98, 99, 2000, 2001, 2002, 2003 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free

Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled “GNU Free Documentation License”.