IMPLEMENTATION DOCUMENTATION

MyRota Web Application

Technical handover and implementation record for the rota management, live home dashboard, ONCALL reporting, Firestore-backed rota data, Oracle-backed APF microsites, and Netlify-hosted Jira dashboard integration.

PREPARED ON	CODE REVISION	PRIMARY URL	FIREBASE PROJECT
April 6, 2026	`main / bbbec66+`	https://myrota.netlify.app/	`myrota-13aa3`

1. Executive Summary

MyRota is a React and Vite based rota management application that now opens directly into a live operational dashboard instead of a login landing page. The application supports user-facing rota visibility, admin-controlled rota editing, live team status and leave planning, ONCALL reporting with Excel export, a Jira dashboard backed by a Netlify Function, and linked Oracle-backed microsites for APF, SFTP, Documentation, and Certificate operations.

Firestore remains the source of truth for users, rota assignments, admin configuration, and audit logs. The non-rota microsites now persist to Oracle tables `MYROTA_APF`, `MYROTA_SFTP`, `MYROTA_DOCUMENTATION`, and `MYROTA_CERTIFICATE`. Jira integration was intentionally moved away from Firebase Functions because production Firebase Functions required a paid plan. The current production Jira proxy runs on Netlify Functions and supports a mock mode for preview and branch deploys.

Business Outcome

- Home page shows live working status and next three days of leave planning.

Key Technical Outcome

- Netlify now hosts both the frontend and the Jira backend proxy.

- Users can view rota data but only admin can modify shifts or leave.
- Jira issue counts and details are visible directly inside the app.
- ONCALL / night / weekend shift reporting can be exported to Excel.
- APF, SFTP, and Certificate microsites support Excel template download and bulk publish.

- Firestore user ordering follows the numeric `position` field.
- Browser Firestore reliability was improved with long-polling configuration.
- Preview environments can show mock Jira data without using live credentials.
- Oracle-backed Node APIs now serve APF, SFTP, Documentation, and Certificate data.

Current production state: the live Jira endpoint `/.netlify/functions/jiraDashboard?mode=summary` was validated on April 4, 2026 and returned live counts successfully.

2. Technology Stack

LAYER	IMPLEMENTATION	CURRENT ROLE
Frontend	React 19 + Vite 7	Main web UI, navigation, dashboard rendering, report export, and Jira views.
Styling	Tailwind utility classes plus inline component styles and `src/App.css`	Glassmorphism panels, responsive layout, mobile sticky table behavior, branded header.
Primary data store	Firebase Firestore	Users, rota assignments, logs, and admin configuration.
Microsite data store	Oracle Database	APF directory links, SFTP partner records,

LAYER	IMPLEMENTATION	CURRENT ROLE
		documentation notes, and certificate tracking.
Authentication gate	Simple admin password validation from Firestore	Controls access to rota editing and log visibility.
Reporting	`xlsx` + `file-saver`	Excel export of ONCALL / C / WS report rows.
Jira backend	Netlify Functions	Secure server-side Jira querying without exposing credentials to the browser.
Hosting	Netlify	Production frontend deployment and Jira serverless runtime.

3. Solution Architecture

```
Browser (myrota.netlify.app)
  |
  +-- React / Vite frontend
  |     |
  |     +-- Home dashboard
  |     +-- ROTA dashboard
  |     +-- ONCALL report
  |     +-- Jira dashboard cards
  |     +-- Jira detail page
  |
  +-- Firestore reads / writes
  |     |
  |     +-- users collection
  |     +-- rota/master document
  |     +-- config/admin document
  |     +-- logs collection
  |
  +-- Oracle microsite API (APF/APF_NEW/directory-data-server.js)
  |     |
  |     +-- MYROTA_APF
  |     +-- MYROTA_SFTP
  |     +-- MYROTA_DOCUMENTATION
```

```
|     +-- MYROTA_CERTIFICATE
|
+-- Netlify Function: /.netlify/functions/jiraDashboard
      |
      +-- Reads Netlify environment variables
      +-- Executes Jira JQL queries
      +-- Returns summary or detail JSON to frontend
      +-- Uses mock data in preview / branch deploy contexts
```

Important architectural change: Firebase Functions are no longer the intended production path for Jira. The active production Jira proxy is the Netlify Function located at `netlify/functions/jiraDashboard.js`.

Storage split: ROTA remains on Firestore. APF, SFTP, Documentation, and Certificate microsites now use Oracle-backed APIs and no longer depend on browser-local temporary storage for active records.

4. Delivered Functional Scope

4.1 Home Page

- The application opens directly into the home dashboard instead of a login landing banner.
- The main title is **What about Today?**.
- Two glassmorphism panels are shown side by side on large screens and stacked on mobile.
- The live status panel uses green glass styling.
- The leave plan panel uses red / rose glass styling.
- Below those two panels, the Jira dashboard appears inside a yellow glass section.

4.2 Live Team Status Panel

- Shows the current date in IST.
- Displays who is on leave today.
- Displays who is doing morning shift today.
- Displays who is doing night shift today.

- On weekends, shows weekend support availability in the simplified format *{name} is available on weekend*.
- Avoids duplicate weekend notifications.

4.3 Leave Plan Panel

- Shows leave information for the next three days.
- Uses relative wording such as *tomorrow* and *day after tomorrow*.
- Falls back to a positive empty state when no leave is planned.

4.4 ROTA Dashboard

- Opens from the **ROTA** button in the top navigation.
- The ROTA button is visually highlighted and marked with a **NEW** ribbon.
- Supports week tabs plus a whole-month view.
- Supports month and year selection.
- The year selector is dynamic and allows the next year once the current month is December.
- Tables use a readable sticky employee column on mobile.

4.5 ONCALL Report

- The old dialer icon was replaced by a labeled **ONCALL** button.
- The ONCALL page lists C and WS assignments for the selected month.
- The resulting report can be exported to Excel.

4.6 Jira Dashboard

- Shows **EDI_MAPPING**, **EDI_SUPPORT**, and **CHANGE_REQUEST** sections.
- Each count opens a separate Jira detail page inside the application.
- The details page links out to the underlying Jira issue.
- Refresh actions are available on both summary and detail views.
- Preview environments can run with mock Jira data instead of live credentials.

4.7 Oracle-Backed Microsites

- APF now shows only **Inbound** and **Outbound** sections with BU selection moved into the side column.
- APF supports add, edit, Excel template download, and bulk upload for Oracle-backed link publishing.

- SFTP supports add, edit, delete, Excel template download, and bulk Oracle publish.
- Documentation stores notes in Oracle but does not expose bulk Excel import.
- Certificate supports add, edit, delete, Excel template download, bulk import, tracked count, and popup add/edit windows.

5. Access Control and User Experience Rules

5.1 Admin Mode

- Admin mode is entered by clicking the MyRota logo.
- When already in admin mode, clicking the logo returns the user to home.
- The admin password is read from `users/admin` first and falls back to `config/admin`.
- Only admin users can change rota data or see the change log page.

5.2 User Mode Restrictions

- Regular users have view-only access.
- The user-facing leave update path was removed.
- The employee document with ID `admin` is hidden from user-facing employee lists and notifications.

5.3 Employee List Rules

- Users are read from Firestore collection `users`.
- Display order follows the numeric `position` field.
- Missing or invalid positions sort to the bottom.
- The display name replacement rule maps `Asutosh` to `Komal`.
- Duplicate names are removed after ordering.

5.4 Mobile UX Updates

- The mobile logo size was reduced to prevent overlap with the ROTA button.
- The week table preserves horizontal scroll position while editing.
- The sticky name column keeps employee names visible while scrolling horizontally.

6. Business Logic Rules

6.1 Shift and Leave Codes

A = Morning Shift | **B = Normal Shift** | **C = Night Shift** | **WS = Weekend Shift**

W = Weekend Off | **PL = Personal Leave** | **RH = Restricted Holiday**

CH = Company Holiday | HD = Half Day

6.2 Calendar Rules

- Base year is 2025.
- For 2025, only November and December are available.
- All years after 2025 expose the full January to December range.
- When the current month is December, the next year is added to the selector.

6.3 Report Rules

- The ONCALL report includes only rows where the effective shift is `C` or `WS`.
- Report rows are built from the selected month, selected year, employee list, and final resolved shift values.

6.4 Rota Value Resolution

- Assignments support both name-based and index-based rota keys.
- Object values may carry both `shift` and `leave`.
- Fallback scanning is used for leave detection where old key shapes or older data formats still exist.

7. Data Model and Persistence

FIRESTORE PATH	PURPOSE	USAGE
`users/{username}`	User master data	Document IDs provide employee names. `position` controls display order. The `users/admin` document is the primary source for the Edit ROTA admin password.
`rota/master`	Central rota document	Stores key-based day assignments such as `year-month-week-employee-day`, with values containing shift / leave information.
`config/admin`	Admin configuration	Optional backup location for admin configuration if `users/admin` is

FIRESTORE PATH	PURPOSE	USAGE
		unavailable.
`logs/{logId}`	Audit history	Tracks shift changes and update events for admin review.

Firestore client configuration: the frontend now uses `initializeFirestore()` with long-polling assistance in `src/firebase.js` to reduce connection issues in deployed browsers.

7.1 Oracle Microsite Tables

ORACLE TABLE	PURPOSE	ACTIVE UI BEHAVIOR
`MYROTA_APF`	Inbound / outbound partner links by BU	Add, edit, Excel template download, and bulk import from the APF UI.
`MYROTA_SFTP`	SFTP partner connection records	Add, edit, delete, Excel template download, and bulk import.
`MYROTA_DOCUMENTATION`	Documentation notes and media attachments	Oracle-backed note editing without bulk import.
`MYROTA_CERTIFICATE`	Certificate tracking, uploads, and renewal notes	Add, edit, delete, popup form flow, tracked-count panel, and Excel bulk import.

8. Jira Integration

8.1 Current Runtime Model

- The browser never calls Jira directly.
- The frontend calls `/.netlify/functions/jiraDashboard`.

- The Netlify Function reads `JIRA_BASE_URL`, `JIRA_USERNAME`, and `JIRA_PASSWORD` from environment variables.
- The backend performs Jira REST API search requests using Basic authentication.

8.2 Why Netlify Functions Were Introduced

- Firebase Functions deployment required paid billing enablement for the project.
- The application was already hosted on Netlify, making Netlify Functions the simplest free production path.
- Netlify deploy contexts also made it easy to introduce a test / preview mode.

8.3 Jira Views Implemented

VIEW ID	BUSINESS MEANING	SOURCE PROJECT / FILTER
`mappingInProgress`	EDI mapping stories in progress	Project `EDI`, issue type `Story`, status `In Progress`
`mappingOpenEpic`	EDI open epics for mapping leads	Project `EDI`, issue type `Epic`, status `Open`, assignees `MudigoNa` and `naveen.mudigonda`
`supportInProgress`	HCL-EDI support tickets in progress	Project `HCLSM`, custom field team = `HCL-EDI`, status `In Progress`
`supportOnHold`	HCL-EDI support tickets on hold	Project `HCLSM`, custom field team = `HCL-EDI`, status `ON-HOLD`
`changesThisWeek`	Tracked change requests for selected assignees	Project `HCLCR`, defined status list, defined assignee list

8.4 Preview / Test Environment Strategy

- `netlify.toml` sets `JIRA_DASHBOARD_USE_MOCK=true` for preview and branch deploys.
- Production keeps `JIRA_DASHBOARD_USE_MOCK=false`.
- The frontend shows **Preview** instead of **Live** whenever mock data is active.
- Mock summary and detail payloads are maintained in `netlify/jira/mockData.js`.

Production environment variables required in Netlify: `JIRA_BASE_URL`, `JIRA_USERNAME`, `JIRA_PASSWORD`.

9. Deployment and Local Development

9.1 Production Deployment

- Frontend and Jira backend deploy from GitHub to Netlify.
- No Firebase Functions deployment is required for Jira anymore.
- Firestore remains active for data storage and admin / user data retrieval.

9.2 Local Development Commands

COMMAND	PURPOSE
`npm start`	Runs the Vite development server.
`npm run build`	Build validation for production assets.
`npm run netlify:dev`	Runs Netlify local dev so the frontend and Jira function share one origin.
`cd APF/APF_NEW && npm start`	Runs the APF React UI, Oracle-backed directory API, and certificate workspace together.

9.3 Legacy / Non-Production Items

- The `functions/` directory still exists in the repository but is no longer the intended production Jira backend.
- Preview Jira behavior should be validated against the Netlify function path, not the older Firebase function URL.

10. Validation Snapshot

The following checkpoints were validated while preparing this document on April 6, 2026:

- `npm run build` completed successfully on the current machine.
- The live Jira summary endpoint returned status 200 from Netlify.
- The frontend bundle on production updated after the Netlify migration and heading cleanup.

- The Oracle-backed APF API returned `ok: true` and `dbReady: true` on `http://localhost:3001/api/health`.
- The certificate bulk API was smoke-tested for create / update / delete restore behavior.

LIVE JIRA METRIC	OBSERVED VALUE	OBSERVATION DATE
EDI_MAPPING - In Progress	13	April 4, 2026
EDI_MAPPING - Open Epic	5	April 4, 2026
EDI_SUPPORT - In Progress	6	April 4, 2026
EDI_SUPPORT - On Hold	9	April 4, 2026
CHANGE_REQUEST - Total Count	9	April 4, 2026

11. Key Files for Maintenance

FILE	RESPONSIBILITY
`src/App.jsx`	Main application shell, home page, rota dashboard, admin flow, ONCALL report, and core Firestore interactions.
`src/firebase.js`	Firebase initialization and Firestore connectivity configuration.
`src/jira/JiraDashboardSection.jsx`	Jira summary cards on the home page.
`src/jira/JiraIssuesPage.jsx`	Detailed issue list view for any Jira card or metric.
`src/jira/api.js`	Frontend Jira API client and endpoint fallback behavior.

FILE	RESPONSIBILITY
`netlify/functions/jiraDashboard.js`	Netlify serverless entry point for Jira summary and detail requests.
`netlify/jira/viewDefinitions.js`	Canonical JQL view definitions and detail field list.
`netlify/jira/mockData.js`	Preview / test environment Jira payloads.
`netlify/jira/client.js`	Jira environment variable parsing, auth header creation, and REST search execution.
`netlify.toml`	Netlify build, functions, dev, and deploy-context environment configuration.
`APF/APF_NEW/directory-data-server.js`	Oracle-backed API and static app host for APF, SFTP, Documentation, and Certificate routes.
`APF/shared/oracle-db.js`	Shared Oracle connection and schema helper layer for the microsites.
`APF/SFTP_NEW/db.js`	Oracle schema and record persistence for SFTP data, including bulk upsert.
`APF/CERTIFICATE_NEW/public/app.js`	Certificate UI, popup add/edit flow, row actions, tracked-count card, and Excel bulk import.

Document generated from the current codebase and validated production behavior as of April 6, 2026. This file is intended for handover, maintenance planning, and deployment reference.