

# Index

## A

- a channel, 171-172
- a digital current sensor, 146
- a model for computer simulation, 38
- a quantitative examination, 3
- a silicon hall-effect transducer, 9
- A/D converter, 166-167
- A/m, 219
- about the author, 233
- ABS, xi, 151-152
- AC coupler, 170
- AC coupling, 163-165
- AC-coupled, 164-166, 170
  - architecture, 164
  - detection scheme, 166
  - geartooth, 164-165
  - sensor, 165
  - scheme, 166, 170
- accurate instruments, 191
- accurate modeling of nonlinear behaviors, 200
- active area – the surface of a Hall-effect, 219
- actual Hall-effect transducer, 227
- actual levels of B, 208
- ADC, 67-68
  - input, 67-68
- Additional,
  - IR voltage losses, 133
  - signal processing, 152
- adjustable temperature compensation, 74
- AGC, 170-171

- Agilent, 188
- air gap – the distance, 219
- all linear electronic systems, 71
- all of the terminal functions, 59
- Allegro Microsystems, 62, 86, 146-147, 173, 182, 192, 211
- Alnico magnet, 159-160, 162, 219
- Alnico-type magnets, 125
- Ampere – MKS unit, 219
- Ampere, Andre A., 2
- Amperes/meter, 219, 224
- Ampere-turn – One ampere passing, 219
- amplifier, vi, 14-15, 20-21, 24, 32, 41, 43-44, 48-54, 56-58, 62-63, 68, 75, 85, 148-149, 170-171, 178-179, 223, 225
  - circuits, vi, 51, 53, 63
- an electrical transducer model, 36
- an example current sensor, 145
- analog,
  - ICs, 79
  - integrated circuits, 232
  - temperature compensation, vi, 54-55
- analog-to-digital converter (ADC), 66-67, 83
- analysis of slotted Toroid, 141-142
- AND function, 93
- Andre A. Ampere, 2
- Anisotropic, 219, 223, 225
- Ansoft's MAXWELL simulator, 199-200
- Appendix D: References and Bibliography, 231

Appendix A: A Brief Introduction, 203  
 Appendix B: Supplier List, 211  
 Appendix C: Glossary of Common Terms, 219  
 application-specific,  
     devices, 62  
     Hall-effect, 185  
     Sensors, 177  
 art of electronics, 232  
 ASIC, 177  
 assembly costs, 184-185  
 assortment of digital Hall-effect ICs available today, 81  
 ATE, 188  
 attenuation, 69  
 automotive, xii, 15, 71-72, 79, 103, 151-152, 155-156, 167-168, 180  
 auto-nulling,  
     a group of techniques, 220  
     circuit waveforms, 60  
     linear Hall-effect IC, 63  
 auto-zeroing – see Auto-nulling, 220  
 AV, 149-150  
 available,  
     differential geartooth sensor ICs, 166-167  
     Hall switches, 124  
     Hall-effect IC packages, 143  
     Hall-effect transducers, 32-33  
 available IC processes, 21  
 Avogadro, 6

## B

B axis of the flux density vs, 128  
 B channel, 171-172  
 Baltes, 30, 231  
 bandwidth, vi, 15-16, 48-50, 68-69, 102-103, 173-174, 188-189, 220  
 basic arrangement of a voltage-biased Hall-effect, 41  
 basic Hall-effect transducer, v, 29-31  
 batch nature of IC fabrication processes, 126

Bate, 231  
 behavior of,  
     a digital-output Hall, 76  
     a switch, 77  
 B-H curve showing magnetic hysteresis, 207  
 B-H, 143, 207-208, 220-221, 223, 225-226  
 B-H-series Hall transducer, 12  
 bias circuits, 42-43  
 bias current, photolithographic processing, 17  
 bias voltages, 38  
 bibliography, ix, 231-232  
 binary-weighted encoding, 100  
 Biot-Savart law, 203-204  
 bipolar,  
     having two polarities, 220  
     Darlington transistors, 95-96  
     input amplifiers, 50  
     switch, 78, 82, 125, 220, 228  
     transistor, 95, 220  
     TTL, 90  
 blocks implementing Hall-effect, 62  
 blue LEDs, 93-94  
 Bode plot, 68-69  
 Boltzmann's, 15  
 BOP = BRP, 76-78, 86, 108, 110, 128, 146, 154, 161, 163-165, 169, 220, 223-224, 228  
 BOP and/or BRP, 124  
 BOP of the Hall, 163  
 BOP threshold, 86  
 Bosch, 103  
 boundary conditions, 200  
 breadboards, 187-188, 190  
 BRP,  
     specifications, 78  
     switch, 224  
     threshold, 86  
     thresholds, 86, 161  
     values, 86, 128  
 brushless DC motor, 183-185  
 brute-force constant-current bias circuit, 45  
 built-in pull-up resistors, 90  
 bulk transducers, 16

bulk transducers, v, 16-17, 42

## C

calibrated Hall-effect ICs, 192

calipers and micrometers, 197

calipers, ix, 197

CAN bus support, 103

capacitance, 42, 96, 105, 190, 193-194, 220

capacitive, 43, 105, 194

capacitor CB, 53

case of,

    a Hall-effect transducer, 43

    a linear Hall-effect, 63-64

    a single-ended AC-coupled, 170

    CMOS logic, 90

    Hall transducers, 9

    the silicon Hall-effect transducer, 10

Castagnetti, 231

CGS-derived units, 220

    unit of magnetic field intensity, 225

    unit of magnetic flux density, 222

    unit, 222, 224-225

chemical vapor deposition (CVD), 21

Cheng, 232

Chih-wen, 232

chopper-stabilization circuitry, 173-174

circuit designers, 36

circuits, vi, xi-xii, 9, 25, 27, 36-38, 41-44, 47,

    51, 53, 60-61, 63-64, 68, 71, 80-81, 83-86,

    91-95, 110, 170, 172, 180-181, 183, 187-

    188, 190, 220, 223, 225, 227-228, 231-233

circular flux concentrator, 119-120

clamp-on current probes, 189

closed-form analytic solutions, 199

closed-loop current sensors, viii, 148-149

closed-loop, viii, 148-150, 220, 225

CMOS, 25, 51, 59, 63-64, 80, 90, 181, 220,

    228, 231

    amplifier circuits, 63

    digital inputs look, 90

    Hall-effect sensor can, 63-64

    inputs, 90, 181

    logic gate, 90

    logic inputs, 181

    logic, 80, 90, 181, 228

    processes, 63-64

    switches, 59

    technologies, 80

    transistors, 63-64

CMRR, 49, 52

coercive force, 144, 208, 221, 223

coercivity, 221

coil – a, 96-97, 137, 151-152, 191, 194-196,

    206, 222, 226

color-scale maps, 201

column V of the periodic table, 8

combining equations, 7

common,

    Hall transducer, 26

    IC processes, 9

    magnet materials, 210

    target geometries, 155-156

    mode rejection, 48-49, 53

    mode signal, 43, 48

    mode voltage, 43, 131-132

comparator, 221

comparison of Hall-effect speed sensing

    methods because, 170-171

comparison of various geartooth, 171

competitive technologies speed, 151

computer simulation, vi, 38-39, 199

concentrator, 221

conductor geometry, 134-136

constant current sources, 46

construction of a Hall-effect transducer, 26

construction of the digital-output Hall-effect

    ICs, 60

consumer devices, xi

contemporary devices, 68, 76, 79

context of Hall-effect, 227

continuous behavior of the Hall-effect, 1-2

contour maps, 201

contrast bipolar, 220, 228

contrast closed-loop, 225

contrast unipolar, 220, 228  
 conventional Hall-effect transducer, 31  
 copper, 1, 6-9, 19-20, 137, 174-175, 221  
 corner frequency FC, 69  
 correcting transducer offset, 58  
 corrosion resistance, 210  
 CSA, 135-136  
 C-shaped structure, 141-142  
 Cunife, 221  
 Cu-Ni-Fe, 221  
 curie temperature, 221, 224  
 current consumption, 71  
 current probe, 189  
 current sensing, vii, 131-133, 135, 145  
 current sensor, viii, 131-140, 143-150, 232
 

- closed-loop, 148, 150
- digital, viii, 146
- PCB-based, 135
- Toroidal, 144, 147-148

 current sensors, vii-viii, 133-137, 139-141, 145-149, 189, 217, 227  
 current through RS, 46  
 current-mode biasing, vi, 45, 47  
 current-sensing techniques, 131  
 customer support, iv  
 CVD, 21

**D**

D flip-flop, 173  
 DAC, 63-64, 73  
 Darlington transistors, 95-96  
 DC,
 

- average, 164
- bias signal, 164
- brushless, 183-185
- fan, 183-185
- steady-state behavior of a loop, 148-149
- steady-state, 148-149, 173-174, 200

 DC-blocking filter, 165  
 DC-coupled differential sensor can, 167-168  
 definition of switch, 76-77  
 definition of switch vs. latch, 77

demagnetization, 221
 

- curve, 221

 demonstration of the Hall effect, 1  
 design of a Hall-effect, 41  
 design of integrated circuits, 231  
 designing high-quality Hall-effect sensor assemblies, 202  
 designing proximity sensors, vii, 126-127, 129  
 desired output current IO, 89  
 development tools, 187  
 device,
 

- switches ON, 180
- technology VN, 51

 Dewar flask, 199  
 Dexter Magnetic Technologies, 231  
 Dickinson, 232  
 different technologies, 50  
 differential,
 

- a difference, 221
- amplifier, 43-44, 48-49, 51-52, 62, 223
- fixed-threshold, viii, 169-170
- gain, 43-44, 48-49, 52-53
- geartooth sensors, 166-167
- variable-threshold, 170

 digital current sensor, viii, 146  
 digital devices, vi, 61-62, 64, 66, 68, 70, 72, 74, 76, 78-82, 90, 103
 

- Hall, 64, 79, 93, 108
- Hall-effect devices, 76, 79
- Hall-effect sensor output, 80
- Hall-effect sensor turns OFF, 226
- Hall-effect sensors, 88, 154
- Hall-effect switch, 146, 153
- Hall-effect, 75-82, 88, 90, 93-96, 98-99, 106, 112, 146, 153-154, 161-162, 171-173, 221, 223-226
- linear Hall sensor, 64

 digital,
 

- on/off output, 75, 221
- output susceptible, 152
- sensor reaction, 76

- sensors digital devices, 79
  - sensors, vi, 76-82, 88, 90, 93-95, 98-100, 106, 108, 154, 171-172, 221
  - digital-output threshold-triggered devices, 62
  - digital-to-analog,
    - converter, 63-64
    - encoding, vii, 99, 101
  - direction sensing, viii, 171
  - dirty environments, 152
  - disadvantage of a simple AC-coupled scheme, 165
  - disadvantage of the vertical Hall structure, 31
  - discovery of the Hall effect, 1-2
  - discrete implementation of switch, 87
  - discrete logic circuits, 92
  - discrete logic, vii, 90-93, 103-104
  - discrete-transistor logic, 91
  - R. Helmholtz, 223
  - DMMs, viii, 188-189
  - doghouse magnet, 125
  - down side of Johnson noise, 15-16
  - drift, vi, 5-7, 14, 19-20, 48, 57, 66, 78
    - velocity, 6-7
  - driving loads, vii, 42-43, 93, 182
  - DSP, 64, 166-167
  - D-type flip-flop, 172
  - dual hall-sensors, 231
  - duty-cycle, 221
  - DVMs, 90, 132, 195-196
  - dynamic offset cancellation technique, vi, 58-59
  - dynamic threshold, 158-159, 163-165
- E**
- earth, 107, 134, 162, 222
  - ECKO, 151-152
  - E-core polepiece, 125
  - Edwin Hall, xi, 1-2
  - effect of clamping, 74
  - effective air gap, 227
  - effective thickness of the reverse-biased P-N junction, 22
  - effects of,
    - excessive supply-line noise, 80
    - rotating bias, 59
    - transistor VBE variation, 46
  - EH, 5
  - electrical,
    - model, vi, 14-15, 36-37, 39, 43, 73
    - offsets, 170
    - transducer model to, 36
    - bench equipment, viii, 187, 189
  - electrons, 2-3, 5-6, 8, 15, 203, 219-220
  - EMI, 181-182
  - encoder, 221
  - encoding and serialization, vii, 98-99
  - encoding multiple digital hall-effect, 99
  - encoding, vii, 98-101
  - energy loss, 131-132
  - Engel, 232
  - engineering electromagnetics, 232
  - environmental chamber, 199
  - Epi, 22-23
  - epitaxial Hall-effect transducer, 21, 23
  - epitaxial N-type silicon layer, 21
  - equal-valued resistors, 101
  - equivalent model of linear Hall-effect sensor
    - output, 68
  - Erickson, 231
  - ESD, 181-182
  - Ethernet, 102
  - Exact frequency response of the sensor IC, 173-174
  - Example,
    - Current Sensor, viii, 145
    - of a commercial thin-film Hall transducer, 19-20
    - of a Hall device, 23
    - of a micropower Hall-effect switch, 178
    - of a silicon Hall-effect IC, 25
    - of a silicon Hall-effect transducer's, 33
    - of a two-wire Hall-effect switch, 180-181
    - of a typical Hall-effect, 151
    - of finite element mesh, 201

- of liquid-level, 115
- of miniature lathe, 198
- of ring, 139
- of system benefiting, 67
- of ASICs, 177
- of Hall Effect Transducers, v, 32-33
- of sensor ICs, 170-171
- of signals present, 60
- external connections, 53
- external flux concentrators, 31
- extraneous uniform fields, 138
- extreme example of an application-specific Hall IC, 183

## F

- F.W. Bell, 12, 16, 19-20, 39, 231
- face of an Alnico magnet, 162
- fall time, 81
- FEA, 199
- feedback loop, 148-150
- feedback, negative, 68, 148, 150, 220
- feedback, positive, 87
- ferrite, 222
- ferromagnetic article detector, 231
- ferromagnetic materials, 205
- ferrous targets minimum, 152
- FET input op-amps, 52
- FET technology, 50
- FETs, 49
- field-programmable,
  - linear hall, 73
  - linear hall-effect, 71-72
  - linear sensors, vi, 71-72
- film deposition, 17-18
- filter – an electronic circuit, 222
- fine gain – a coarse gain setting, 72
- first-order system, 68-71
- fixed-threshold signal processing method, 169
- flexibility, 17, 83, 137, 158-159
- float-level sensing one position-sensing application, 114
- float-level sensing, 114
- float-level sensor, 114-116
- flow meter, 155
- flux decay, 122
- flux density, 38, 83, 108, 115-117, 122-123, 125, 128, 140-141, 144, 158-160, 166-167, 190-191, 201-202, 207-209, 220, 222-227
- flux leakage, 122-123, 141, 143, 224
- flux maps of magnetic systems, 222
- flux variation, 117-119, 161, 163
- flux, 30-32, 38, 40, 65, 73, 76, 83, 107-112, 115-123, 125, 127-129, 133-136, 138, 140-144, 146-149, 151-154, 156-168, 174-175, 190-191, 201-203, 206-209, 220-227, 232
- fluxmeter, ix, 191-192, 195-196, 222, 226
- force-sense bias circuit, 43-44
- formulae, 121
- four Hall-effect devices, 138
- four Hall-effect transducers, 31-32
- four possible classes of Hall-effect-based, 158-159
- four-way symmetric Hall-effect transducer, 58
- Fowle, 231
- Frederick E., 231
- free-space,
  - current sensing conceptually, 133
  - current sensing, vii, 133, 135
  - current sensors ii, 136
  - current sensors ii, vii, 135-137, 139
- frequency,
  - counter, viii, 188-189
  - response of the Hall transducer, 173-174
- functional block diagram of fluxmeter, 192
- functional block diagram of threshold-sensitive hall IC, 75
- fundamental limitations of traditional Hall-effect transducers, 30
- fundamental units, 227

## G

- G/A, 16-17, 149
- gain – the incremental ratio of an output signal, vi, 11, 37, 39-44, 48-50, 52-57,

62-69, 71-74, 83-86, 95, 118-119, 139-140, 143-144, 146, 148-150, 170-171, 221-223, 225, 227  
 adjustment, 83-84  
 of a Hall-effect transducer, 56-57  
 sensor, 227  
 gate of a power MOSFET, 96  
 gate terminal of a MOSFET, 96  
 gauss, 7, 14, 16-17, 24, 32, 38-40, 66, 72-73, 87-88, 118, 134, 140, 143-147, 162, 181, 191, 194-195, 206, 208, 220, 222, 224, 227  
 gaussmeter, 190-191, 208, 222, 224  
 geartooth sensor, viii, 151, 155-161, 163-168, 170-171, 173, 200-201, 221-222, 226-227  
 sensing, viii, 156-157, 170-171  
 sensor architecture, 157-158  
 sensor assembly, 151  
 sensor, differential, 166-168, 221  
 geometric interpretation of vector, 204  
 Gilbert, 231  
 GND, 40, 99  
 gradient, 26, 109-110, 158-159, 166-168, 221-222

## H

Hall-effect in metals, 5, 7

Hall-effect in semiconductors, v, 7

Hall,

electric field, 5  
 generators, 231  
 ICs, 62, 65, 71-72, 75, 110, 166-167, 173-174, 219  
 output voltage, 43, 45, 59  
 sensor IC, 62, 64-68, 71-73, 76, 86, 89-90, 93, 109, 122, 178, 183, 231  
 sensor's output, 89  
 switch, 110, 122, 180  
 transducer, 4-5, 7, 9, 12, 15-16, 19-20, 26, 29-30, 40, 62-64, 75, 115-116, 159, 173-174

Hall, Edwin, xi, 1-2

Hall's.

experiments, xi

hypothesis, 2

question, 2

time, 2

Hall-effect,

applications, xi-xii, 31, 61-62, 66, 78

element, 19-20, 158

ferromagnetic article proximity sensor, 232

generator, 231

home-position, 113-114

IC manufacturers, 78, 192

IC parameters, 127

IC, 25, 63, 78, 126-127, 129, 143, 156-157, 174-175, 181-182, 190, 192

latch, 77

physics, 1

sensor assemblies, 187, 202

sensor elements, 190

sensor IC packages, 174-175

sensor IC, 25, 126, 156-157, 174-175, 190

sensor ICs, 21, 66-67, 103, 107, 173-174, 191

sensor system, 36

sensor's output saturation, 146

sensor's output voltage, 73

sensors theory, iii

sensors, i, iii, xi-xiii, 20-21, 35, 61-66, 71-72, 75-78, 80-84, 86, 88, 90, 93-95, 98-99, 102-107, 111-112, 114-116, 118, 122, 131, 137, 139, 145, 154, 156-157, 177-178, 185, 221, 227-228, 233

switch, 77, 88, 90, 122-126, 146, 153, 177-178, 180-183, 192

switch's output, 90

switches, 88, 124-125, 146, 161-162, 179-180, 182

transducer elements, 167-168

transducer out of silicon, 20

transducer's behavior, 11

vane switch assembly, 126

- vane switch, 125-126
  - version of a Rogowski, 137
  - voltage, 1-2, 15
  - based applications, 107
  - based speed-sensing methods, 155
- Hall-offset, 57-58
- handheld DVM, 132
- hardness, 210
- head-on,
  - actuation mode, 108
  - actuation, 107-108
  - sensing, vii, 107-109
- Hedeen, 232
- Helmholtz Coil, ix, 194-196, 223
- Hewlett-Packard, 188
- Hideki, 231
- high BOP switch, 109
- HIGH state, 86, 221
- high-coercivity materials, 207
- higher bandwidth, 220
- high-pass hall voltage filter, 231
- high-quality hall-effect transducers, xi, 25
- Hill, iv, 214, 232
- Horowitz, 232
- Howland current source, 47
- hypothetical lot-to-lot variation, 127
- hysteresis, xii, 76, 78, 86-88, 109, 113-114, 128-129, 166-167, 179, 181-182, 206-207, 220, 223
- I**
- IC,
  - manufacturers, 23, 78, 126-127, 192
  - processes, 9, 21, 29, 126
  - specs, 129
  - surface, 31-32
  - bandwidth, 173-174
- ICs, ix, xi-xii, 21, 28, 30, 60-62, 65-67, 71-72, 74-75, 79, 81, 103, 107, 110, 117-118, 126-127, 166-167, 170-171, 173-174, 177, 190-192, 194-195, 219-220
- ideal Helmholtz, 195
- illustration of a Helmholtz, 194-195
- IMC Hall-effect transducers, 32
- IMCs, 31
- impedance, 15-16, 50-52, 68-69, 85, 223
- implement Linbus protocols, 103
- inaccurate instruments, 191
- incandescent lamps, vii, 94-96, 182
- increasing sensitivity with multiple turns, 144
- increasing sensitivity, viii, 66-67, 144
- individual characteristics of the sensor ICs, 127
- inductance, 190, 223
- inductive loads, vii, 96-97, 182
- inductive, vii, 96-98, 137, 151-152, 182, 189
- industrial controls, xi
- infineon, 211
- inhomogeneities, 13, 118
- input and output resistances 14
- input bias current, 48-49
- input offset voltage, 48-49, 57-58
- input resistance ROUT, 38
- instrumentation amplifier, 48, 50, 52-54, 57-58, 223
- instrumentation-grade Hall-effect sensor can, xiii
- integrated,
  - AND gate, 93
  - current sensors, 147
  - Hall transducers, 20
  - Hall-effect devices, 83-84, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106
  - Hall-effect devices, vi
  - sensors: linear and digital devices, 61
- integration of flux, 136
- interface issues—linear output sensors, 83
- interfaces, vii, 83, 93
- interfacing to integrated hall-effect devices, 83
- interfacing to standard logic devices, 90-91
- interfacing to switches and latches, 88
- intrinsic carrier concentrations, 8
- intrinsic coercive force, 208, 223



irreversible losses, 223  
isotropic, 219, 223, 228

## J

Johnson noise, 15-16  
Jordan Hill, iv

## K

Kawaji, 231  
Keithley Instruments, 188  
Kelvin degree, 227

## L

lamp ON, 95  
large DC common mode signal, 43, 48  
large number of digital Hall-effect, 98  
large number of discrete Hall-effect, 137  
latches, vi-vii, 62, 71, 75, 79, 86, 88, 154, 171-173, 221  
latch-type digital Hall-effect, 112, 154  
lateral surface of a magnet, 232  
layers of pure silicon, 9  
leakage field, 122-123  
LED,  
    interfaces, 93-94, 192  
    lights, 93  
    voltage drop, 94  
level of the HIGH/LOW threshold, 181-182  
like CMOS inputs, 90  
Linbus, 103  
linear devices, vi, 62-64, 71, 74-76, 162  
linear Hall, 62, 64, 73, 75, 86, 227  
linear Hall-effect, 62-68, 70-72, 74, 83-84, 86, 103, 118, 133, 137, 139, 145, 190, 192, 224,  
    IC, 63, 192  
    sensor IC, 190  
    sensor transfer, 66  
linear,  
    output devices, 62  
    output hall, 86  
    output, vi, 61-62, 65, 83, 86, 115-116,

140, 146  
    position sensing in addition, 115-116  
    position sensing, vii, 109, 115-117  
    linear positioning slides, ix, 195-196  
    sensors, vi, 61-66, 68, 70-74, 76, 78, 80, 82-84, 118, 137, 139, 145, 162, 227  
    transfer curve, vi, 64-65

Linearity Because Hall-effect transducers, 14  
linear-output Hall transducer, 115-116

LOAD line, 99

Load, 40, 42-43, 46-47, 65, 68-69, 87-88, 95-99, 105, 155, 177

Logic,

    AND, 80, 92-93, 173  
    HIGH, 90  
    NOT functions, 93  
    NOT Output, 92  
    NOT, vii, 92-93  
    OR, 79, 91-93, 98, 103-104, 181

Long-enough PCB trace, 135

Lorentz, 3, 31

LOW output, 59, 68-69, 87, 90, 221

Low trip-point accuracy, 115-116

LOW voltage, 26, 50, 98, 131-132

LOW, 7-8, 14, 26, 42-43, 45, 50, 55, 57-60, 66, 68-69, 73-74, 80-81, 86-87, 90, 93, 98, 102, 110, 115-116, 131-132, 152-156, 165-167, 170, 173, 177-179, 181-182, 188, 190-191, 199, 219, 221-222

Lower ON resistances, 95

Lower right leg of the Wheatstone bridge, 59

low-frequency response of the first-order rc filters, 164

low-power hall-effect, 178

## M

machine tools, ix, 151, 197-199, 217

magnet,

    conditioner – an instrument, 224  
    conditioners the ability, 193  
    conditioners, ix, 193-194  
    material, 119, 153-154, 161, 191, 207,

- 219, 221, 224
- null-point sensing, vii, 110-111, 113
- magnetic,
  - BOP, 108, 220, 225
  - domains, 206, 226
  - field intensity magnetic flux, 224
  - fields come from magnetic fields, ix, 203
  - fields these applications all, 187
  - flux density RIN, 38
  - flux density, 38, 83, 117, 122, 141, 158, 166-167, 190, 202, 207, 220, 222, 224-227
  - instrumentation, ix, 190-191, 193, 195, 215
  - linearity, 38
  - materials, 205
  - null-points, 111
  - sensors, xii-xiii, 28, 107, 133, 135, 148, 187, 190, 231
  - simulation software, ix, 199-201, 215-216
  - magnetic targets, viii, 153
  - view film, 193
  - magnetics, 118, 123-126, 129, 187, 203-206, 208, 210, 214, 232
- magnetism, 232
- magnetizer, 224
- magnetizers and magnet conditioners, 193
- magnetizers, ix, 193-194
- magnetizing force, 206-208, 223-224
- magnets, 74, 107, 110-112, 115-118, 121-122, 124-125, 127, 153-156, 162, 170, 179, 191, 193, 200, 205, 207, 210, 213, 219, 222-226
- magnet-to-sensor, 109-110, 154
- magnitude detection schemes, 158
- magnitude of the hall effect, xi
- major instabilities, 150
- make Hall-effect transducers, 7, 13
- make ICs, 220
- make NPN transistors, 22
- make reasonably sensitive Hall-effect transducers, 23
- manual, 57, 148-149, 197, 231
- manufacturers of LDOs, 105
- manufacturers of linear Hall-effect devices, 71
- manufacturers, 20-21, 23, 53, 65, 71, 74-75, 78, 104-105, 126-127, 143-144, 147, 178, 188, 192
- mass production each layer, 17
- material carrier concentration, 8
- material's B-H, 221
- material's BHmax, 208
- maximum BOP, 123, 128
- maximum energy product, 208, 224
- maximum off-state output voltage, 81
- maximum product of b, 208
- maximum service temperature – the maximum temperature, 221, 224
- maxwell – cgs unit of magnetic flux, 224
- Maxwell's equations, 135-136
- measuring AC, 137
- mechanical tolerance Hall-effect sensor IC manufacturers, 126
- mechanical Tools One aspect of magnetic sensor development, 195-196
- mechanical tools, ix, 195-197
- Melexis, 21, 25, 32, 61, 63-64, 166-167, 173, 178, 180-184, 212
- metalization, 23
- metallurgy of soft magnetic materials, 232
- metals, v, 1-2, 5-10, 173-174, 220
- methods of creating magnetic null-points, 111
- Meyer, 231
- MGOe, 208, 210
- microcontrollers, 80, 102-104
- micrometers, ix, 197
- Micronas, 64, 182, 212
- Microphotograph of an IMC Hall-effect transducer, 32
- micropower hall-effect devices, 178
- micropower switches, viii, 177, 179
- millivolt-level output signals, 9
- minimal Hall-effect, 35
- minimum, 65, 85, 115-116, 123, 126-129,

144, 152, 160-161, 164, 166-167, 181, 227  
 mini-networks, vii, 102-103  
 MKS unit, 219, 224, 227  
 model for computer simulation, vi, 38-39  
 modern Hall-effect, 60, 71, 78  
 modern power MOSFETs, 96  
 monolithic Hall-effect ICs, xii  
 monolithic IC, 62  
 MOSFET, 80, 95-96  
 Motorola, 103  
 MTBF, 184-185  
 multiple outputs, 188  
 multiple turns there, 144  
 multiple turns, viii, 144, 148-149  
 multitude of available bop, 86  
 Mu-Metal – A high-permeability magnetic alloy, 225

## N

N data lines, 98  
 N+, 6, 9-10, 22-23, 98, 145, 149, 195, 213, 220  
 narrow PCB trace, 135  
 N-channel MOSFET, 80, 95  
 NdFeB, 74, 117-118, 225  
 neodymium-iron-boron, 225  
 new CMOS Hall angular position sensor, 231  
 newer linear Hall-effect sensors offer user-adjustable, 83-84  
 newer linear Hall-effect, 65, 83-84  
 noise, v-vi, 11, 14-16, 24, 48, 50-51, 67-68, 71, 79-80, 85, 91, 104, 156-157, 180-182, 225  
     Differential gain, 48  
     In addition, 15, 50  
     model of amplifier, 51  
 nonuniformity, 170  
 north magnetic pole, 76-77  
 north-pole switches, 78  
 novel aspect of the IMC, 31  
 NPN, 22, 80, 220  
     bipolar transistor, 80

open-collector output, 80  
 N-type, 8-10, 21-22  
     material, 8, 21-22  
     semiconductor, 8  
     silicon, 9-10, 21  
 N-type,

## O

Oersted, 206, 215, 220, 224-225  
 OFF,  
     LED driver, 94  
     region, 110  
     state, 76-77, 81, 128  
     states, 76, 79, 81, 128-129  
     switch, 122, 146, 166-167, 178, 220  
 off-center current causes leakage flux, 141  
 OFF-ON transition, 113  
 offset and gain adjustment, vi, 71-72, 83-85, 118  
 offset error – a type of measurement error, 225  
 offset of the Hall, 67-68  
 offset of the Hall-effect transducer, 57  
 off-the-shelf Hall-effect ICs, 126  
 Ohm's Law, 225  
 Ohmic offset, v, 11-14, 16-17, 24, 26, 31, 57-60  
 old-style bipolar Hall sensor, 66  
 ON,  
     close, 109  
     LED Driver, 94  
     output, 12-15, 59, 65, 73, 75-76, 79, 81, 90, 93, 98, 113, 183, 221  
     region, 110, 226  
     resistance, 27-28, 95  
     state output voltage, 81  
     state, 76, 79, 81, 89, 96, 179  
     switch, 87, 98, 122-123, 146, 156, 177-179, 220, 228  
 On/Off, 75-76, 79, 81, 89, 100, 112, 117-118, 128-129, 146, 178, 184, 221  
 on-state,

- field, 122-123
- flux density, 123
- flux field, 123
- op-amp voltage gain, 149
- open-collector, 80-81, 88, 90, 182
- open-loop, 225
- operational amplifier, 225
- optical bench, ix, 195-196
- OR output open collector outputs, 93
- ordinary PCB plated-through, 135
- oscilloscope, viii, 80-81, 90, 188-189
- output,
  - characteristics, vi, 67-68, 146
  - drivers, vi, 80
  - of a digital Hall-effect, 96
  - of a Hall-effect, xii, 66-67
  - of a linear Hall-effect, 67-68, 83
  - of a typical Hall-effect switch, 88
  - of the Hall, 90
  - of the linear Hall-effect, 86
  - offset voltage – A DAC, 73
  - off-state leakage, 81
  - ON, 76
  - pull-up resistor, 88
  - resistances, 14
  - saturation voltages, 65
  - signal of just VH, 29
  - state of the Hall-effect sensor, 178
  - switches HIGH, 87
  - thresholding, vii, 83, 85-87
  - triad, 180
  - voltage, 100-101

## P

- P type, 10
- packaging of most Hall-effect, 111-112
- paddlewheel type, 155
- pair of,
  - different colored LEDs, 192
  - digital Hall-effect, 173
- parallel wiring structure, 29
- parameter, 48, 75, 81, 208, 227

- part of standard IC fabrication processes, 9
- particular Hall IC, 129
- particular MOSFET, 95
- PC, 191
- PCB, 134-136, 139
  - substrate, 135-136
  - surface, 135-136
  - traces, 134-135
  - PCB-based, 135-136
- P-channel MOS transistors, 220
- peak-hold geartooth, 166
- permalloy – a high-permeability, 225
- permanent,
  - magnet catalog, 231
  - magnet guidelines, 232
  - magnet materials, ix, 143-144, 210, 221, 232
- permeability, 125, 141-145, 203, 206, 225
- phase shift, 70, 154-155
- Philips, 103, 145
- physical layout, 139
- physics of a Hall-effect transducer, 11
- PLDs, 91
- Plug of high concentration N-type, 22
- P-N junctions, 21
- PNP device, 106
- PNP versions, 220
- polarity probe, ix, 192
- pole piece, 231
- pole, 76-78, 107, 110-112, 116, 122, 153-155, 159, 162-163, 171-172, 179-180, 192-193, 203, 205, 208, 222, 225, 227-228, 231
- pole-counts, 154
- polepiece, e-core, 125
- polepiece, sensor-backing, 125
- polepiece, wrap-around, 125
- POP MAX, 128
- POP MIN, 128
- popular interface standards, 191
- positioning of differential transducer, 167
- positive y, 121
- power + brains = smart motor control, viii,

183, 185  
 power devices, viii, 182  
 power management, vii, 103-105  
 power management, vii, 103-105  
 power MOSFET, 95-96  
 power N-channel MOSFET, 95  
 power supplies, 187  
 power supply requirements for digital sensors, vi, 79  
 power supply requirements for linear sensors, vi, 71  
 powered ON, 165, 178  
 power-on recognition – the ability of a geartooth, 226  
 power-on recognition, 157-158, 226  
 practical devices, 4, 10  
 practical transducers, 11  
 previous description of the Hall effect, 7  
 primary feature of a Helmholtz, 195  
 process variation, 27, 56  
 product of B, 208, 224  
 profibus, 102  
 programmable BOP/BRP, 146  
 property of the Hall-effect transducer, 58  
 proximity sensor – a device, 226  
 proximity-sensing techniques, 107  
 P-type,  
   isolation walls, 21  
   material, 8, 21  
   substrate, 21  
 pull-up resistor, vii, 80-81, 88-90, 92-93

## Q

quad cell, v, 27, 29  
 quadrant ii, 223  
 quadrature, 173, 226  
 quantitative examination, v, 2-3  
 quiescent output voltage, 226, 228  
 QVO, 65, 226, 228

## R

RA resistors, 44, 47, 52

RA/RB divider network, 47  
 RacZ, 231  
 rare-earth magnet, 226  
 ratio BY/BX, 121  
 ratiometric,  
   Hall-effect, 67  
   output Hall, 67-68  
 ratiometry, vi, 66-67  
 raw BX, 121  
 Raymond K. Jr., 231  
 red LED, 93-94  
 reference magnets, 226  
 references and bibliography, ix, 231-232  
 relationship of BOP, 78  
 relay ON, 97  
 relays, solenoids, and inductive loads, 96  
 relays, vii, 96-97, 182  
 RESET input of the flip-flop, 76  
 resistance, 11  
   of RA, 57  
   of the Hall transducer, 9  
 resistive current sensing, vii, 131-133  
 response of four-probe, 139  
 response of hall-effect home-position, 114  
 resulting Hall voltage, 7  
 resulting sensor ICs, 75  
 reverse-battery protection, 79  
 RF, 42  
 ring magnet, 114-116, 153-157, 171-172, 179, 226  
 rise, 4, 54, 67, 81, 90, 98  
 RMS, 16, 71  
   noise measurements, 71  
   voltmeter, 71  
 Robison Electronics, 146, 217  
 Rogowski Coil, 137  
 Rogowski, 137  
 rotary position sensing, vii, 32-33, 118-119, 121  
 rotary table, ix, 195-197  
 RPM, 173-174, 189

**S**

- Samarium-Cobalt,
  - a rare-earth compound, 226
  - magnet, 159-160
- saturation, 38, 65, 81, 95, 100-101, 106, 121, 144, 146, 194, 200, 208, 223, 226
  - magnetic, 226
  - voltage, 81, 95, 100-101
- sauber, 232
- schematic representation of power-cycled Hall, 178
- schematic top, 17
- schematic view of a Hall-effect-based float-level, 114
- Schott, 231
- SCRs, 193-194
- self-demagnetization, 208, 226
- semiconductor, 227
  - sensors, 231-232
  - from, 7
- sense resistor RS, 47
- sensing of flux, 232
- sensitive axis of the Hall, 109
- sensitive hall transducers, 8
- sensitive symmetric latch-type Hall ICs, 110
- sensitivity, v, viii, 5, 7, 9-14, 16-17, 19-20, 23-24, 26, 30-33, 37-41, 65-69, 72, 83-84, 87-88, 106, 115-116, 119, 121, 134-135, 139-140, 143-147, 160, 162-163, 167-168, 191, 194, 202, 227
  - ohmic, v, 11
  - temperature, v, 11-12, 14, 121
  - of a given Hall transducer, 5
  - of a Hall transducer, 7
  - of a Hall-effect transducer, 11-12
  - of a toroidal Hall-effect, 146-147
  - the degree of response, 227
- sensor, viii, xiii, 11-14, 16, 20-21, 24-26, 30-31, 35-36, 38, 41, 57-58, 62-77, 79-81, 83-84, 86-93, 95-96, 98-104, 107-129, 131-171, 173-175, 177-185, 187-192, 194-202, 219-228, 231-233
  - having dual hall IC, 231
  - IC manufacturers, 126-127
  - IC, 67-68
  - ICs, 21, 30, 65-67, 71-72, 75, 103, 107, 117-118, 126-127, 166-167, 170-171, 173-174, 191
  - OFF, 93, 95, 110, 162, 164, 226
  - ON, 20-21, 73-74, 90, 93, 95, 128, 138, 146, 164, 166, 174-175, 225
  - status output voltage, 100
  - maximum BOP, 123
  - minimum BRP, 123
- sensor-backing polepiece, 125
- Sentron AG, 32
- serial,
  - data out, 99
  - shift-register, 99
- serialization, vii, 98-99
- service temperature, 210, 221, 224
- SET input, 76
- setting,
  - BOP, 86
  - RF, 42
- sharp tools, 187
- shift, 31, 70, 87, 99, 154-155
- Shinjuku-ku, 211
- SI (the international system of units), 7, 227
- side of the Hall transducer, 4
- signal correction, 119
- silicon Hall-effect,
  - sensor IC, 25
  - transducer, v, 9-10, 33, 61
- silicon, v, xi-xii, 7-10, 20-25, 27-28, 30-31, 33, 61, 147, 173-174, 184-185, 220, 227
  - silicon ICs, 21
- similar wiring schemes, 29
- simple,
  - AC-coupled scheme, 165-166
  - circuit-level models, 36
  - continuous position sensors can, 115-116
  - Hall-effect transducers, xii
  - sensor network, 102

- SPICE model, 40
- single,
  - D-type flip-flop, 172
  - Hall-effect transducer element, 158
  - point/dynamic threshold •, 159
  - point/fixed threshold •, 159
  - point sensing, viii, 159, 163, 167-168
  - point/dynamic-threshold schemes, 163
- slide-by,
  - a proximity-sensing mode, 227
  - actuation mode, 109
  - sensing another common, 109
  - sensing, vii, 109
- Slope dV/dB, 65
- small,
  - differential Hall output voltage riding, 43
  - Helmholtz, 194-195
  - portable optical benches, 195-196
  - regions of an IC, 28
  - size of Hall-effect, xii
- SmCo, 117-118
- SMD, 227
- Smithsonian,
  - Institute Physical Tables, xi
  - Institution, 231
  - Physical Tables, 231
- Soclof, 231-232
- soft ferrites, 222
- software, magnetic simulation, ix, 199-201, 215-216
- SOIC face, 32-33
- solderless breadboard, 190
- solenoids, vii, 96-97, 182
- some permanent magnet materials, 210
- some thoughts on designing proximity sensors, 126
- south magnetic pole, 76-77
- spatial size, 153
- specialty magnetic materials, 214
- specific BOP, 86
- speed,
  - and direction sensing, 171
  - and timing sensors, 151
  - sensing, viii, 151-152, 170-171
  - sensor, 151-153, 155-157, 162-163, 169-171, 179, 227
- SPI, 103
  - developed, 103
  - functionality, 103
- SPICE (simulation program with integrated circuit emphasis), 37-41
  - input file, 41
  - language, 39
  - view of the world, 38
  - SPICE-compatible circuit, 38
- sputtering, 18-19, 31-32
- standard,
  - IC packaging, xii
  - logic devices, vii, 90-91
  - logic IC, 91
  - specifications, 232
  - three-wire type of hall switch, 180
- state of the D input, 172
- static threshold, 158-159
- Stauth, 232
- stepped magnetic field, 174
- structure of epitaxial resistor, 22
- subsequent circuitry, 151-152, 160
- suitable rectifier diodes, 98
- supplier list, ix, 211-217
- surface of the IC, 28, 30
- surface-mount device, 89, 227
- surface-mount IC packages, xii
- switch, 59, 78, 146
  - OFF, 166-167
  - ON, 87, 98, 122-123, 146, 156, 177-179, 220, 228
  - switches and latches, vi-vii, 62, 75, 86, 88, 221
- switches, vi-viii, xi, 59, 62, 71, 75, 78, 86-88, 122-125, 146, 155-156, 161-162, 177, 179-182, 221
- switching,
  - network, 60, 63-64

power, 96, 105, 177-178  
 current levels, 177  
 switchpoint stability, vi, 78  
 switch-type digital Hall, 108  
 symbol H, 206  
 symmetric bias circuit, 43  
 system diagram of feedback, 150  
 systems, xi, 10, 16, 20, 71, 73, 79, 84, 102,  
 105-106, 109-110, 112-113, 131-132, 148-  
 149, 151-152, 154, 165, 167-168, 173-174,  
 181-182, 188-189, 199-200, 202, 217, 222

## T

targets, viii, 62, 131, 152-153, 155-156, 160,  
 162-163, 166-167, 173-174, 177, 189, 195-  
 198, 221  
 Technisches Messen, 231  
 technology advantages drawbacks hall, 152  
 tempco – *see temperature coefficient*, 227  
 temperature coefficient,  
   the fraction, 227  
   of ohmic offset like sensitivity, 14  
   of resistance, 15  
   of sensitivity, 12  
 temperature of the packaged IC, 28  
 temperature range, vi, xii, 15, 66, 71-72, 128,  
 156, 210  
   operating, 128  
 temperature stability, 12-13, 48, 54, 162, 210  
 temperature stable proximity sensor, 232  
 temperature-compensated amplifier, 54  
 temperature-induced variations, 78  
 terms of the B-H, 208  
 Tesla, 227  
 testing ICs, 66, 194-195  
 Texas Instruments, 105  
 the Hall effect in semiconductors, 7  
 the pull-up resistor, 88  
 the quad cell, 27  
 the transducer, xi-xii, 4-5, 9-10, 12-17, 19-21,  
 23-32, 35-38, 41-48, 50, 52, 54, 56-64, 74,  
 111-112, 118-119, 121, 144, 148-149, 158-  
 160, 163-164, 166-168, 173-174, 178-179,  
 222, 227  
 thin-film,  
   Hall-effect transducer, 17  
   processing sequence, 19  
   processing techniques, 19-20  
   thin-film transducers, v, 17, 19, 42  
 thoughts on designing proximity sensors, vii,  
 126-127, 129  
 three-op-amp differential amplifiers, 52  
 three-wire Hall-effect switch, 180  
 threshold, 62, 75-76, 78, 86-87, 146, 158-159,  
 163-165, 169-170, 178, 181-183, 223  
 through-hole  $\frac{1}{4}$ w resistor, 89  
 tilting, 170  
 time hall, xi, 2  
 timing sensors, viii, 151-152, 154-156, 158,  
 160, 162, 164, 166, 168, 170, 172, 174  
   timing sensor, 167-168, 227  
 tools, mechanical, ix, 195-197  
 toroid, vii-viii, 140-150, 219, 227  
   a donut-shaped flux concentrator, 227  
   material selection and issues, viii, 143  
   slotted, vii, 141-142, 144  
   magnetic gain, 149  
 toroidal current sensors, vii, 140-141, 217  
 traditional Hall-effect transducer, 30, 31  
 transducer,  
   bulk, 16  
   device, 228  
   gain AH, 149  
   geometry, v, 26  
   interfacing, vi, 35-36, 38, 40, 42, 44, 46,  
   48, 50, 52, 54, 56, 58, 60  
   placement, 162  
 TRIACs, 193-194  
 TTL (transistor-transistor logic), 228  
   input, 90  
   logic input, 90  
   TTL, 80, 90, 181, 228  
 turn OFF, 224  
 turn ON, 78, 96, 98, 146, 162, 179, 224-225,



- 228
  - TUV, 135-136
  - two Hall-effect transducers, 158, 166-167
  - two of the simpler, 204
  - two of the wires, 43-44
  - two simple circuits, 94-95
  - two terminal multiplexable sensor, 232
  - two-wire, viii, 180-182, 228
    - Hall-effect switches, 180, 182
    - interface – an electrical interface, 228
    - switches transmitting data signals, 180
    - switches, viii, 180-182
  - typical,
    - auto-nulling Hall IC, 63
    - DC brushless fan, 183
    - digital devices, vi, 81
    - Hall-effect-based, 126
    - leakage paths, 135-136
    - linear devices, vi, 74
    - magnetic responses, 159
  - typical noise performance of various operational amplifiers, 51
  - typical organization of a linear architecture
    - linear Hall IC, 62
  - typical red LED, 93-94
  - typical values, 82
- U**
- UL, 135-136
  - unloaded digital Hall-effect sensor, 80-81
  - USA Linacre House, iv
  - use of,
    - Alnico, 118
    - CMOS technology, 63-64
    - DSP, 166-167
    - Hall-effect digital switch, 153
  - user I/O ports, 39
- V**
- value of H, 223
  - vane, vii-viii, 122-126, 155-157, 228
    - switch flux map, 123
    - switch magnetic architectures, 124
    - switch operation, 122
    - switch, vii-viii, 122-125, 155
  - variations on the basic Hall-effect transducer, v, 29-31
  - variety of LEDs, 93-94
  - various digital Hall-effect, 82
  - various fixtures, 195-196
  - vast array of Hall-effect, 25
  - vector notation, 203
  - vertical Hall-effect transducer, 30-31
  - very inexpensive handheld DMMs, 188-189
  - vicinity of the Hall-effect transducer, 163
  - view film, ix, 193
  - views of thin-film Hall-effect transducer, 17
  - voltage, vii, 1-5, 7, 9, 12-15, 21-22, 24, 26-27, 29, 31, 36-38, 40-51, 54, 57-60, 62, 65-68, 71-74, 78-81, 83-85, 87-91, 93-98, 100-101, 103-106, 131-133, 135-137, 149, 151-152, 180-182, 187-188, 191, 193-194, 222, 225-226, 228, 231
    - bias circuits, 42
    - regulation, vii, 103-105
    - power management, vii, 103-105
    - voltage-mode biasing, vi, 41
    - voltage-mode Hall-effect, 41
  - voltmeters, viii, 188
    - and DMMs, 188
  - volts, 9, 11-12, 43, 46, 65, 73, 79, 84, 96-98, 140, 194, 220, 222
- W**
- Wheatstone Bridge, 58-59
  - where magnetic fields come from, 203
  - whole IC, 22
  - width of the,
    - ON region, 110
    - PCB trace, 135
  - wired,
    - AND, 93
    - OR Output, 93
    - OR, vii, 93

wiring reduction, 102

schemes, 98

World War II, 188-189

wrap-around pole piece, 125

## **X**

X direction, 116

X field, 31-32

## **Z**

Z-axis, 31-32

Zero-flux,

intercept, 65

output voltage, 66-67, 228

Z-field components, 32