MSDS Name: UNI-GRAB Adhesive Revision Date: January 1, 2006

Page Number: 1 of 4

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: UNI-GRAB Insulation Adhesive

CAS Number: none

HMIS Hazard Rating: Health: 1 Fire: 1 Reactivity: 0

Company Identification: McGill AirSeal LLC

2400 Fairwood Avenue Columbus, Ohio 43207

Contact: McGill AirSeal LLC

Telephone: (800) 624-5535 (614) 443-5520

Fax: (614) 542-2620 Chemtrec (24 hour): (800) 424-9300 Chemtrec International: (703) 527-3887

Product Class: polymer dispersed in water

Product Use: adhesive
Product Code: 005898
Division: McGill AirSeal

SECTION 2 – COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Ingredients CAS Number Percent

ethylene glycol 107-21-1 5.64

OSHA PELs and ACGIH TLVs are listed in Section 8 where applicable.

SECTION 3 – HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:

Material is a white paste that is slippery in the wet state.

ROUTES OF ENTRY:

Inhalation: yes
Ingestion: yes
Skin: no
Eye: yes
INHALATION:

Vapors may be irritating to the eyes, nose, throat and lungs.

INGESTION:

Ingestion is not a probable route of exposure. Harmful if swallowed.

SKIN:

Prolonged or repeated skin contact can cause irritation.

EYE:

Mildly irritating to eyes.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Preexisting skin and respiratory conditions.

CARCINOGENICITY:

IARC: no NTP: no OSHA: no

REPRODUCTIVE TOXICITY:

None anticipated based on product formula. Ethylene glycol may cause birth defects based on tests with laboratory animals.

TARGET ORGANS:

Prolonged or repeated overexposure may cause eye, skin, respiratory system, central nervous system, peripheral nervous system, liver and kidney damage.

MSDS Name: UNI-GRAB Adhesive Revision Date: January 1, 2006

Page Number: 2 of 4

SECTION 4 - FIRST AID MEASURES

INHALATION:

Remove to fresh air. If difficulty persists, seek medical attention.

INGESTION:

Call poison control center immediately. Follow their specific instruction. Do not induce vomiting.

SKIN:

Wash with soap and water. Contact physician if irritation develops or persists.

EYE:

Hold eyelids apart and flush with plenty of water for at least 15 minutes. Seek medical attention.

SECTION 5 - FIRE-FIGHTING MEASURES

Flammability Class (OSHA): IIIB Flash Point: > 200°F Setaflash

Explosive Range: Not applicable

EXTINGUISHING MEDIA:

Use alcohol foam, carbon dioxide, water spray, or ABC dry chemical when fighting fires involving this product.

HAZARDOUS COMBUSTION PRODUCTS:

Incomplete combustion can yield low molecular weight hydrocarbons and carbon monoxide.

FIRE FIGHTING MEASURES:

Wear a NIOSH approved self-contained breathing apparatus. Wear appropriate personal protective equipment.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP:

Spread absorbent over material and scrape up material/absorbent and place in an approved container. If product has dried, scrape up and place in an approved container.

EMERGENCY MEASURES:

None required.

SECTION 7 - HANDLING AND STORAGE

HANDLING:

Wash thoroughly after handling. Avoid prolonged or repeated contact with skin. Do not take internally. Close container after each use. Keep away from children.

STORAGE:

Keep away from food and drinking water. Store in a cool, dry place.

PRECAUTIONARY STATEMENT:

Keep out of the reach of children.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL OSHA PEL ethylene glycol 100.00 mg/M3 Not established Not established Not established

ENGINEERING CONTROLS:

Use local exhaust as needed to maintain occupational exposure limits.

OTHER:

Facilities storing or utilizing any chemical should be equipped with an eyewash facility and a safety shower.

RESPIRATORY PROTECTION:

Respiratory protection is not expected to be necessary under normal use. Follow requirements for respiratory protection in OSHA 1910.134.

MSDS Name: UNI-GRAB Adhesive Revision Date: January 1, 2006

Page Number: 3 of 4

EYE PROTECTION:

Chemical splash goggles (ANSI Z87.1 or approved equivalent).

SKIN PROTECTION:

Where skin contact can occur, wear impervious gloves.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form: liquid
Appearance/Color: white
Odor: faint odor
Solubility (in water): miscible
pH Value: 4.5
Boiling range/Point: 212°F

Evaporation Rate: slower than n-Butyl Acetate

 % Volatile:
 25.0 %

 Specific Gravity:
 1.13

 VOC:
 1.6 g/l

SECTION 10 – STABILITY AND REACTIVITY

Stability: This product is stable.

Hazardous polymerization: Hazardous polymerization will not occur.

CONDITIONS TO AVOID:

Strong acids and strong bases

INCOMPATIBILITY:

Strong oxidizing agents, acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS:

Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

Ethylene glycol can irritate the eyes and skin. Prolonged overexposure via inhalation can cause pulmonary edema plus liver and kidney damage. The central nervous system may be affected exhibiting dizziness, weakness, nausea and headache. Brain damage has resulted in humans from swallowing lethal or near lethal amounts of ethylene glycol. Ethylene glycol causes birth defects in experimental animals. Tests for carcinogenicity in experimental animals are negative.

SECTION 12 – ECOLOGICAL INFORMATION

This formulation has not been tested for environmental effects.

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Disposal of this product must comply with all applicable federal, state, and local regulations.

CONTAINER DISPOSAL

Disposal of this container should comply with all applicable federal, state, and local regulations.

SECTION 14 – TRANSPORT INFORMATION

UN Number: None

UN Pack Group: Not applicable UN Class: Nonhazardous ICAO/IATA Class: Nonhazardous IMDG Class: Nonhazardous Shipping Name: Nonhazardous

MSDS Name: UNI-GRAB Adhesive Revision Date: January 1, 2006

Page Number: 4 of 4

Packaging may not be approved for shipping by air. Please contact McGill Airseal for further information.

SECTION 15 – REGULATORY INFORMATION

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the

Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Chemical Name CAS Number Percent ethylene glycol 107-21-1 5.64

TSCA (Toxic Substances Control Act Inventory):

All components of this product are listed on the TSCA inventory except as exempted.

PENNSYLVANIA:

Hazardous components required to be listed at 1% or more:

ethylene glycol; 1,2-ethanediol; 107-21-1

Non-hazardous components required to be listed at 3% or more:

dipropylene glycol dibenzoate 27138-21-4, chlorinated alpha-olefin 68527-02-6, water 7732-18-5, polyvinyl acetate emulsion 24980-61-8

NEW JERSEY:

dipropylene glycol dibenzoate 27138-21-4, chlorinated alpha-olefin 68527-02-6, ethylene glycol 107-21-1, water 7732-18-5, polyvinyl acetate emulsion 24980-61-8

SECTION 16 – OTHER INFORMATION

DISCLAIMER:

While the information and recommendations set forth herein are believed to be accurate as of the data hereof, McGill AirSeal LLC makes no warranty, express or implied, with respect thereto and disclaims all liability from reliance thereon.