

JUnit Workbook(2012)

Links:

- <http://qtp.selenium.com/selenium-tutorial/junit-selenium-training/>

JUNIT

Annotations

@Rule

- Used to declare variables that JUnit can use internally for its tracking and reporting of test progress/errors

@BeforeClass (Static)

- Ran before the first @Test in the class
- Ran before the @Before annotation

@AfterClass (Static)

- The last annotation ran by JUnit in the class

@Before

- Ran before each @Test

@After

- Ran after each @Test

@Ignore

- used with @Test to skip the test

@Test

- Declare a test that JUnit will run
- method name must have 'test'

@Parameters

Handling Assertions

- Create class variable
- Create a Try/Catch block around evaluations
- Use 'Throwable' data type
- Use .addError() to accumulate 'Failures'

Example

```
@Rule //JUNIT Rule
public ErrorCollector errCollector = new ErrorCollector();
..
..
    @Test
    ..
```

```

..
try {
    Assert.assertEquals(expected_total_friends,
actual_total_friends);
} catch (Throwable t) { //Throwable data type
    System.out.println("Error encountered 100..101");
    // java code reports the error
    errCollector.addError(t);
}
System.out.println("B");
..
..

```

Parameterizing

creating data driven tests

method of data storage doesn't matter, Parameterization is done via:

- @Parameters uses Collection<Object[]>() ← this is a 2D Array
- @Test uses objects row-by-row: [1][*], [2][*], [3][*]

Example

```

@Parameters
public static Collection<Object[]> data(){
    //subclass Collection is in superclass ArrayList is subclass
    //Collection a = new ArrayList();
    //a.add("aa");
    //rows - number of times to run the test
    //cols - number of parameters to pass to test
    Object[][] data = new Object[2][3];
    // 1st row
    data[0][0]="testuser1";
    data[0][1]="pass1";
    data[0][2]=7898;
    // 2st row
    data[1][0]="testuser2";
    data[1][1]="pass2";
    data[1][2]=78999;
    //returning a list instead of an array
    return Arrays.asList(data);
}


```

Test Listeners

Custom Runners


Apache Ant

Ant is used for running a test suite via command line and outputting results in XML with HTML pages to review test data results



Installation & Config

- Download Links and Reference
 - <http://ant.apache.org/bindownload.cgi>
 - <http://ant.apache.org/manual/>
- Install
 - Copy to C:\apache-ant-1.8.4\
 - Environment
 - PATH: "C:\apache-ant-1.8.4\bin"
 - ANT_HOME var: C:\apache-ant-1.8.4\



- Run 'ant' and check for errors

Error Message on tools.jar

```
C:\Users\SiloSix>ant
Unable to locate tools.jar. Expected to find it in C:\Program
Files\Java\jre6\lib\tools.jar
Buildfile: build.xml does not exist!
Build failed
```

- Get Tools.jar
 - C:\Program Files\Java\jdk1.6.0_33\lib\tools.jar
 - C:\Program Files\Java\jre6\lib\tools.jar

```
C:\Users\SiloSix>ant
Buildfile: build.xml does not exist!
Build failed
```

build.xml

- Resides at project root
- Ant searches for in the java project
- Gives parameters for ant
- Environment vars are \${} not ()
- All Directories must be present prior to compile/run

Example includes for test classes

```
<!--include name="**/*TestCase*.class /for all files with TestCase-->
<include name="testcases/FirstTestCase.class" />
<include name="testcases/SecondTestCase.class" />
<include name="testcases/ParameterizedTestCase.class" />
<include name="testcases/UnderstandingAssertions.class" />
```

Error on Ant Run (Compile OK)

Errors while applying transformations: Fatal error

My guess is that the problem is caused by the mismatching XSLT version supported by Ant JUnit plugin (which contains XSLT files that are XSLT 1.0, as you correctly noted) and XSLT processor

(supporting XSLT version 2.0). My guess #2 is that you have the newer XSLT processor (like Saxon) somewhere in classpath so that it's loaded before some other XSLT processor (like Xalan which implements XSLT v1.0). For further troubleshooting I would suggest [\[url=http://www.google.com/search?q=junitreport+\"Errors+while+applying+transformations:+Fatal+error+during+transformation\"&btnG=Search\]](http://www.google.com/search?q=junitreport+\) googling it out[[url](#)].

```
D:\Java\Workspace\Module8_Junit_Ant>ant run
Buildfile: D:\Java\Workspace\Module8_Junit_Ant\build.xml

run:
[junit] Running testcases.FirstTestCase
[junit] Tests run: 3, Failures: 0, Errors: 0, Time elapsed: 0.501 sec
[junit] Running testcases.ParameterizedTestCase
[junit] Tests run: 2, Failures: 0, Errors: 0, Time elapsed: 0.485 sec
[junit] Running testcases.SecondTestCase
[junit] Tests run: 3, Failures: 0, Errors: 0, Time elapsed: 0.434 sec
[junit] Running testcases.UnderstandingAssertions
[junit] Tests run: 2, Failures: 3, Errors: 0, Time elapsed: 0.488 sec
[junit] Test testcases.UnderstandingAssertions FAILED
[junitreport] Processing D:\Java\Workspace\reports\TESTS-TestSuites.xml to
C:\Users\SiloSix\AppData\
Local\Temp\null987575801
[junitreport] Loading stylesheet jar:file:/C:/apache-ant-1.8.4/lib/ant-junit.jar!
/org/apache/tools/a
nt/taskdefs/optional/junit/xsl/junit-frames.xsl
[junitreport] jar:file:/C:/apache-ant-1.8.4/lib/ant-junit.jar!/org/apache/tools/
ant/taskdefs/optiona
l/junit/xsl/junit-frames.xsl:6: Warning! Running an XSLT 1.0 stylesheet with an
XSLT 2.0 processor
[junitreport] jar:file:/C:/apache-ant-1.8.4/lib/ant-junit.jar!/org/apache/tools/
ant/taskdefs/optiona
l/junit/xsl/junit-frames.xsl:38: Fatal Error! Unknown extension instruction
[junitreport] Failed to process D:\Java\Workspace\reports\TESTS-TestSuites.xml

BUILD FAILED
D:\Java\Workspace\Module8_Junit_Ant\build.xml:112: Errors while applying
transformations: Fatal error
r during transformation
```

Total time: 10 seconds

Compile/Clean/Run

```
D:\Eclipse\Java\Module8_Junit_Ant>ant clean
D:\Eclipse\Java\Module8_Junit_Ant>ant compile
D:\Eclipse\Java\Module8_Junit_Ant>ant run
```

Creating Ant Batchfile

```
D:\
cd D:\Eclipse\Java\Module8_Junit_Ant
ant clean compile run
```

Home

Packages

[testcases](#)

Classes

[FirstTestCase](#)

[ParameterizedTest](#)

[SecondTestCase](#)

[UnderstandingAsse](#)

Unit Test Results.

Designed for use with [JUnit](#) and [Ant](#).

Summary

Tests	Failures	Errors	Success rate	Time
10	3	0	70.00%	2.656

Note: *failures* are anticipated and checked for with assertions while *errors* are unanticipated.

Packages

Name	Tests	Errors	Failures	Time(s)	Time Stamp	Host
testcases	10	0	3	2.656	2012-08-07T14:49:12	Silo9

TestNG

- <http://testng.org/doc/download.html>
- <http://search.maven.org/#search|ga|1|a%3A%22testng%22>

Appendices

JUnit Test Example 1(Simple)

Test Suite Runner Class (Simple)

```
package testcases;

import org.junit.runner.RunWith;
import org.junit.runners.Suite;
import org.junit.runners.Suite.SuiteClasses;
```

```
@RunWith(Suite.class)
@SuiteClasses({
    FirstTestCase.class,
    SecondTestCase.class
})

public class MyTestSuiteRunner {

}
```

Test Case Example 1 (Simple)

```
package testcases;

import org.junit.After;
import org.junit.AfterClass;
import org.junit.Before;
import org.junit.BeforeClass;
import org.junit.Test;

public class SecondTestCase {

    //@Test
    //@Ignore
    //@Before
    //@After
    //@BeforeClass
    //@AfterClass

    @BeforeClass // must be static
    public static void beforeClass(){
        System.out.println("*****Beginning*****");
    }
    @Before
    public void beforeTestCase(){
        //open browser - selenium
        System.out.println("Opening the browser");
    }

    @Test
    public void sendEmailTest(){
        System.out.println("Testing Sending Email");
    }

    @Test
    public void sendMessageTest(){
```

```
        System.out.println("Testing Sending Message");
    }

    @After
    public void afterTestCase() {
        System.out.println("Closing the browser");
    }

    @AfterClass //must be static
    public static void afterClass() {
        System.out.println("*****Ending*****");
    }
}
```

JUnit Test Example 2

MyTestSuiteRunner.java

```
package testcases;

import org.junit.runner.RunWith;
import org.junit.runners.Suite;
import org.junit.runners.Suite.SuiteClasses;

@RunWith(Suite.class)
@SuiteClasses({
    UnderstandingAssertions.class,
    FirstTestCase.class,
    SecondTestCase.class
})

public class MyTestSuiteRunner {

}
```

FirstTestCase.java

```
package testcases;

import org.junit.After;
import org.junit.AfterClass;
import org.junit.Before;
import org.junit.BeforeClass;
import org.junit.Test;

public class FirstTestCase {
```



```

@BeforeClass
public static void beforeThisTest(){
    System.out.println("Test Class 01 Starting-----");
}

@Test // test case
public void loginTest(){
    // selenium code
    System.out.println("1-logging in user");
}

@Test
public void registerTest(){
    System.out.println("2-Registering a user");
}

@Test
public void dataBaseTest(){
    System.out.println("3-Testing the database");
}

@AfterClass
public static void afterThisTest(){
    System.out.println("Test Class 01 Ending-----");
}
}

```

SecondTestCase.java

```

package testcases;

import org.junit.After;
import org.junit.AfterClass;
import org.junit.Assume;
import org.junit.Before;
import org.junit.BeforeClass;
import org.junit.Test;

public class SecondTestCase {

    //@Test
    //@Ignore
    //@Before
    //@After
    //@BeforeClass

```

```
//@AfterClass

// Function that JUnit won't run automatically
// Must be called within @Tests
public static boolean checkLogin(){
    return true;
    // true - if login is the success
}

@BeforeClass // must be static
public static void beforeClass(){
    System.out.println("Test Class 02 Starting-----");

    // false - skip all tests in this class
    // JUnit monitors this boolean for executing the rest of the tests.
    Assume.assumeTrue(checkLogin());
}

@AfterClass //must be static
public static void afterClass(){
    System.out.println("Test Class 02 Ending-----");
}

@Before
public void beforeTestCase(){
    //open browser - selenium
    System.out.println("Opening the browser");
}

@After
public void afterTestCase(){
    System.out.println("Closing the browser");
}

// TEST CASES*****

@Test
public void sendEmailTest(){
    System.out.println("1-Testing Sending Email");
}

@Test
public void getMessageTest(){
    // Assume.assumeTrue(false); use to break out of a @Test
    System.out.println("2-Testing Sending Message");
}

@Test
```

```

    public void sendMessageTest() {
        System.out.println("3-Testing Receiving Message");
    }

}

```

ParameterizedTestCase.java

```
package testcases;
```

```

import java.util.ArrayList;
import java.util.Arrays;
import java.util.Collection;

```

```

import org.junit.Test;
import org.junit.runner.RunWith;
import org.junit.runners.Parameterized;
import org.junit.runners.Parameterized.Parameters;

```

//1 step

```

@RunWith(Parameterized.class)
public class ParameterizedTestCase {

```

//2 step

```

    //declare parameters at global level
    public String username;
    public String password;
    public int pin;

```

//3 step

```

    //constructor
    public ParameterizedTestCase(
        String username,
        String password,
        int pin
    ){
        this.username = username;
        this.password = password;
        this.pin = pin;
    }

```

//4 step

```

    @Parameters
    public static Collection<Object[]> data(){
        //subclass Collection is in superclass ArrayList is subclass
        //Collection a = new ArrayList();
        //a.add("aa");
    }

```

```

//rows - number of times to run the test
//cols - number of parameters to pass to test
Object[][] data = new Object[2][3];
// 1st row
data[0][0]="testuser1";
data[0][1]="pass1";
data[0][2]=7898;
// 2st row
data[1][0]="testuser2";
data[1][1]="pass2";
data[1][2]=78999;
//returning a list instead of an array
return Arrays.asList(data);
}

```

```

@Test
public void testRegister(){
    //selenium
    System.out.println("testing Registration -- " + username + " -- " + password + " -- " + pin);
}

}

```

UnderstandingAssertions.java

```

package testcases;

import junit.framework.Assert;

import org.junit.Rule;
import org.junit.Test;
import org.junit.rules.ErrorCollector;

public class UnderstandingAssertions {

    @Rule //JUNIT Rule
    public ErrorCollector errCollector = new ErrorCollector();

    @Test
    public void testFriendlistFacebook(){
        int actual_total_friends =100; //selenium picks up this value from page
        int expected_total_friends=101; //from XLS file
        /*
        if (actual_total_friends == expected_total_friends) {

```

```

        System.out.println("Pass");
    } else {
        System.out.println("Fail");
        // report error, but need assert for JUnit to pick up failure
    }
*/

System.out.println("A");
Assert.assertEquals(expected_total_friends, actual_total_friends);
//JUnit will pick up @Test failure
// not executed due to Assert...
System.out.println("B");
}

@Test
public void testFriendlistFacebook2(){
    int actual_total_friends =100; //selenium picks up this value from page
    int expected_total_friends=101; //from XLS file
/*    if (actual_total_friends == expected_total_friends) {
        System.out.println("Pass");
    } else {
        System.out.println("Fail");
        // report error, but need assert for JUnit to pick up failure
    }
*/

    System.out.println("A");
    // try catch will catch error
    // But JUnit won't see the failure
    try {
        Assert.assertEquals(expected_total_friends, actual_total_friends);
    } catch (Throwable t) { //Throwable data type
        System.out.println("Error encountered 100..101");
        // java code reports the error
        errCollector.addError(t);
    }
    System.out.println("B");
    try {
        Assert.assertEquals("A", "B");
    } catch (Throwable t) {
        System.out.println("Error encountered AB");
        errCollector.addError(t);
    }
    try {
        Assert.assertEquals("A", "A");
    } catch (Throwable t) {
        System.out.println("Error encountered AA");
        errCollector.addError(t);
    }
    //assert won't trigger on true

```

```

        Assert.assertTrue("error msg", true);
        Assert.assertTrue("error msg", 6>3);
    }
}

```

Apache ANT Buildfile (build.xml)

```

<?xml version="1.0" encoding="iso-8859-1"?>
<!DOCTYPE project [
]>
<project name="Module_Junit_Ant" default="useage" basedir=".">
    <!-- ===== Initialize Properties ===== -->
    <description>
        Apache Ant build.xml file for Selenium tests
    </description>
    <!-- set global properties for this build -->
    <property name="ws.home" value="${basedir}" />
    <property name="ws.jars" value="D:/jars" />
    <!-- when compile the programs.. send .classes to /build -->
    <property name="test.dest" value="${ws.home}/build" />
    <!-- where .java files reside -->
    <property name="test.src" value="${ws.home}/src" />
    <!-- Reports directory -->
    <property name="test.reportsDir" value="D:/Eclipse/Java/reports" />
    <!-- property name="env.ANT_HOME" value="C:/apache-ant-1.8.4/bin"/-->

    <path id="testcase.path">
        <pathelement location="${test.dest}" />
        <fileset dir="${ws.jars}">
            <include name="*.jar" />
        </fileset>
    </path>

    <!-- target name="start-selenium-server">
        <java jar="${ws.home}/lib/selenium-server.jar"/>
    </target-->

    <target name="setClassPath" unless="test.classpath">
        <path id="classpath_jars">
            <fileset dir="${ws.jars}" includes="*.jar" />
        </path>
        <pathconvert pathsep=":" property="test.classpath" refid="classpath_jars" />
    </target>

    <target name="init" depends="setClassPath">
        <tstamp>

```

```

    <format property="start.time" pattern="MM/dd/yyyy hh:mm aa" />
  </tstamp>
  <condition property="ANT" value="${env.ANT_HOME}/bin/ant.bat"
else="${env.ANT_HOME}/bin/ant">
    <os family="windows" />
  </condition>
  <taskdef name="testng" classpath="${test.classpath}"
classname="org.testng.TestNGAntTask" />
</target>
<!-- all -->
<target name="all"></target>

<!-- clean -->
<target name="clean">
  <delete dir="${test.dest}" />
</target>

<!-- compile -->
<target name="compile" depends="init, clean">
  <!-- delete dir"", even empty directories -->
  <delete includeemptydirs="true" quiet="true">
    <!-- include="**/*" means all files and subdirs -->
    <fileset dir="${test.dest}" includes="**/*" />
  </delete>
  <echo message="making directory..." />
  <!-- where to put the .class compiled files -->
  <mkdir dir="${test.dest}" />
  <echo message="classpath-----: ${test.classpath}" />
  <echo message="compiling..." />
  <javac debug="true" destdir="${test.dest}" srcdir="${test.src}"
target="1.5" classpath="${test.classpath}"></javac>
</target>

<!-- build -->
<target name="build" depends="init"></target>
<target name="usage">
  <echo>
    ant run will execute the test
  </echo>
</target>

<path id="test.c">
  <fileset dir="${ws.jars}" includes="*.jar" />
</path>
<!-- Executes all the tests "run" -->
<target name="run">
  <!-- delete dir"", even empty directories -->
  <delete includeemptydirs="true" quiet="true">
    <!-- include="**/*" means all files and subdirs -->

```

```

    <fileset dir="${test.reportsDir}" includes="**/*" />
  </delete>
  <java jar="${ws.jars}" fork="true" spawn="true" />
  <junit fork="yes" haltonfailure="no" printsummary="yes">
    <classpath refid="testcase.path" />
    <!-- classpath ="${test.classpath}"/> -->

<!-- 1-Run test in the fileset -->

    <batchtest todir="${test.reportsDir}" fork="true">
      <fileset dir="${test.dest}">
        <!--include name="testcases/FirstTest.class" /-->
        <!--include name="testcases/SecondTest.class"/-->
        <include name="testcases/FirstTestCase.class" />
        <include name="testcases/SecondTestCase.class" />
        <include name="testcases/ParameterizedTestCase.class" />
        <include name="testcases/UnderstandingAssertions.class" />
        <!-- exclude name="**/AbstractSeleneseTestCase.class"/ -->
      </fileset>
    </batchtest>
    <formatter type="xml" />
    <classpath refid="testcase.path" />
  </junit>
<!-- Send JUNIT reports to this directory -->
  <junitreport todir="${test.reportsDir}">
    <fileset dir="${test.reportsDir}">
      <include name="TEST-*.xml" />
    </fileset>
    <report todir="${test.reportsDir}" />
  </junitreport>
</target>
</project>

```

Apache Ant Compile/Clean

D:\Eclipse\Java\Module8_Junit_Ant>ant clean

Buildfile: D:\Eclipse\Java\Module8_Junit_Ant\build.xml

clean:

[delete] Deleting directory D:\Eclipse\Java\Module8_Junit_Ant\build

BUILD SUCCESSFUL

Total time: 1 second

D:\Eclipse\Java\Module8_Junit_Ant>ant compile

Buildfile: D:\Eclipse\Java\Module8_Junit_Ant\build.xml


```
setClassPath:

init:

clean:

compile:
    [echo] making directory...
    [mkdir] Created dir: D:\Eclipse\Java\Module8_Junit_Ant\build
    [echo] classpath-----: D:\jars\commons-io-2.4.jar:D:\jars\jdom-2.0.2.jar:D:
\jars\junit-4.11.jar:D:\jars\jxl.jar:D:\jars\selenium-server-standalone-2.25.0.j
ar:D:\jars\testng-6.7.jar:D:\jars\tools.jar
    [echo] compiling...
    [javac] D:\Eclipse\Java\Module8_Junit_Ant\build.xml:55: warning: 'includeant
runtime' was not set, defaulting to build.sysclasspath=last; set to false for re
peatable builds
    [javac] Compiling 5 source files to D:\Eclipse\Java\Module8_Junit_Ant\build

BUILD SUCCESSFUL
Total time: 6 seconds
```

Run

- C:\Eclipse\Project>ant run

```
D:\Eclipse\Java\Module8_Junit_Ant>ant run
Buildfile: D:\Eclipse\Java\Module8_Junit_Ant\build.xml
```

```
run:
    [junit] Running testcases.FirstTestCase
    [junit] Tests run: 3, Failures: 0, Errors: 0, Time elapsed: 0.659 sec
    [junit] Running testcases.ParameterizedTestCase
    [junit] Tests run: 2, Failures: 0, Errors: 0, Time elapsed: 0.684 sec
    [junit] Running testcases.SecondTestCase
    [junit] Tests run: 3, Failures: 0, Errors: 0, Time elapsed: 0.637 sec
    [junit] Running testcases.UnderstandingAssertions
    [junit] Tests run: 2, Failures: 3, Errors: 0, Time elapsed: 0.676 sec
    [junit] Test testcases.UnderstandingAssertions FAILED
[junitreport] Processing D:\Eclipse\Java\reports\TESTS-TestSuites.xml to C:\User
s\SiloSix\AppData\Local\Temp\null276535517
[junitreport] Loading stylesheet jar:file:/C:/apache-ant-1.8.4/lib/ant-junit.jar
!/org/apache/tools/ant/taskdefs/optional/junit/xsl/junit-frames.xsl
[junitreport] Transform time: 2927ms
[junitreport] Deleting: C:\Users\SiloSix\AppData\Local\Temp\null276535517

BUILD SUCCESSFUL
Total time: 15 seconds
```

[Home](#)[Packages](#)[testcases](#)[Classes](#)[FirstTestCase](#)[ParameterizedTest](#)[SecondTestCase](#)[UnderstandingAsse](#)

Unit Test Results.

Designed for use with [JUnit](#) and [Ant](#).

Summary

Tests	Failures	Errors	Success rate	Time
10	3	0	70.00%	2.656

Note: *failures* are anticipated and checked for with assertions while *errors* are unanticipated.

Packages

Name	Tests	Errors	Failures	Time(s)	Time Stamp	Host
testcases	10	0	3	2.656	2012-08-07T14:49:12	Silo9

Properties of testcases.FirstTestCase

Close

Name	Value
ant.core.lib	C:\apache-ant-1.8.4\lib\ant.jar
ant.file	D:\Eclipse\Java\Module8_Junit_Ant\build.xml
ant.file.Module_Junit_Ant	D:\Eclipse\Java\Module8_Junit_Ant\build.xml
ant.file.type	file
ant.file.type.Module_Junit_Ant	file
ant.home	C:\apache-ant-1.8.4\bin\..
ant.java.version	1.6
ant.library.dir	C:\apache-ant-1.8.4\lib
ant.project.default-target	useage
ant.project.invoked-targets	run
ant.project.name	Module_Junit_Ant
ant.version	Apache Ant(TM) version 1.8.4 compiled on May 22 2012
awt.toolkit	sun.awt.windows.WToolkit
basedir	D:\Eclipse\Java\Module8_Junit_Ant
file.encoding	Cp1252
file.encoding.pkg	sun.io
file.separator	\
java.awt.graphicsenv	sun.awt.Win32GraphicsEnvironment
java.awt.printerjob	sun.awt.windows.WPrinterJob

java.class.path	D:\Eclipse\Java\Module8_Junit_Ant\build;D:\jars\commons-io-2.4.jar;D:\jars\jdom-2.0.2.jar;D:\jars\junit-4.11.jar;D:\jars\jxl.jar;D:\jars\selenium-server-standalone-2.25.0.jar;D:\jars\testng-6.7.jar;D:\jars\tools.jar;D:\Eclipse\Java\Module8_Junit_Ant;C:\Program Files (x86)\QuickTime\QTSystem\QTJava.zip;C:\apache-ant-1.8.4\lib\ant-launcher.jar;C:\apache-ant-1.8.4\lib\ant.jar;C:\apache-ant-1.8.4\lib\ant-junit.jar;C:\apache-ant-1.8.4\lib\ant-junit4.jar
java.class.version	50.0
java.endorsed.dirs	C:\Program Files\Java\jre6\lib\endorsed
java.ext.dirs	C:\Program Files\Java\jre6\lib\ext;C:\Windows\Sun\Java\lib\ext
java.home	C:\Program Files\Java\jre6
java.io.tmpdir	C:\Users\SiloSix\AppData\Local\Temp\
java.library.path	C:\Program Files\Java\jre6\bin;C:\Windows\Sun\Java\bin;C:\Windows\system32;C:\Windows;C:\Windows\system32;C:\Windows;C:\Windows\System32\Wbem;C:\Windows\System32\WindowsPowerShell\v1.0\;C:\Program Files (x86)\ATI Technologies\ATI.ACE\Core-Static;C:\Program Files (x86)\Common Files\Acronis\SnapAPI;C:\Program Files (x86)\Microsoft SQL Server\100\Tools\Binn\;C:\Program Files\Microsoft SQL Server\100\Tools\Binn\;C:\Program Files\Microsoft SQL Server\100\DTS\Binn\;C:\Program Files (x86)\QuickTime\QTSystem\;C:\Program Files (x86)\Android\android-sdk\tools;C:\Program Files (x86)\Android\android-sdk\platform-tools;C:\Program Files (x86)\Java\jre6\bin;C:\Program Files (x86)\Java\jre6\bin\client;D:\Python27;C:\Program Files\TortoiseSVN\bin;C:\Program Files (x86)\Mozilla Firefox;C:\Program Files\Java\jdk1.6.0_33\bin;C:\apache-ant-1.8.4\bin;;.
java.runtime.name	Java(TM) SE Runtime Environment
java.runtime.version	1.6.0_33-b03
java.specification.name	Java Platform API Specification
java.specification.vendor	Sun Microsystems Inc.
java.specification.version	1.6
java.vendor	Sun Microsystems Inc.
java.vendor.url	http://java.sun.com/
java.vendor.url.bug	http://java.sun.com/cgi-bin/bugreport.cgi
java.version	1.6.0_33
java.vm.info	mixed mode
java.vm.name	Java HotSpot(TM) 64-Bit Server VM
java.vm.specification.name	Java Virtual Machine Specification
java.vm.specification.vendor	Sun Microsystems Inc.
java.vm.specification.version	1.0
java.vm.vendor	Sun Microsystems Inc.
java.vm.version	20.8-b03
line.separator	
os.arch	amd64

os.name	Windows 7
os.version	6.1
path.separator	;
sun.arch.data.model	64
sun.boot.class.path	C:\Program Files\Java\jre6\lib\resources.jar;C:\Program Files\Java\jre6\lib\rt.jar;C:\Program Files\Java\jre6\lib\sunrsasign.jar;C:\Program Files\Java\jre6\lib\jsse.jar;C:\Program Files\Java\jre6\lib\jce.jar;C:\Program Files\Java\jre6\lib\charsets.jar;C:\Program Files\Java\jre6\lib\modules\jdk.boot.jar;C:\Program Files\Java\jre6\classes
sun.boot.library.path	C:\Program Files\Java\jre6\bin
sun.cpu.endian	little
sun.cpu.isalist	amd64
sun.desktop	windows
sun.io.unicode.encoding	UnicodeLittle
sun.java.command	org.apache.tools.ant.taskdefs.optional.junit.JUnit4TestRunner testcases.FirstTestCase filtertrace=true haltOnError=false haltOnFailure=false formatter=org.apache.tools.ant.taskdefs.optional.junit.SummaryJUnitResultFormatter showoutput=false outputtoformatters=true logfailedtests=true logtestlistenerevents=false formatter=org.apache.tools.ant.taskdefs.optional.junit.XMLJUnitResultFormatter,D:\Eclipse\Java\reports\TEST-testcases.FirstTestCase.xml crashfile=D:\Eclipse\Java\Module8_Junit_Ant\junitvmwatcher1328204574902432774.properties propsfile=D:\Eclipse\Java\Module8_Junit_Ant\junit7241907459533418942.properties
sun.java.launcher	SUN_STANDARD
sun.jnu.encoding	Cp1252
sun.management.compiler	HotSpot 64-Bit Tiered Compilers
sun.os.patch.level	Service Pack 1
test.dest	D:\Eclipse\Java\Module8_Junit_Ant/build
test.reportsDir	D:\Eclipse\Java\reports
test.src	D:\Eclipse\Java\Module8_Junit_Ant/src
user.country	US
user.dir	D:\Eclipse\Java\Module8_Junit_Ant
user.home	C:\Users\SiloSix
user.language	en
user.name	SiloSix
user.timezone	
user.variant	
ws.home	D:\Eclipse\Java\Module8_Junit_Ant
ws.jars	D:/jars

