

Tags

Tags mark a commit you want to find again, a release, a submission snapshot, or a known-good point for bisect

Lightweight vs annotated

- A lightweight tag is simply a name pointing at a commit, quick for local milestones
- An annotated tag stores a message, tagger, and date, better for releases you share
- Use `tag` to list names, `show` to inspect one

Browser lab

Digital Design and Verification Platform

HomeTools

Home / Tools / Tags

INTERACTIVE TOOL

Tags (light vs annotated)

Create **lightweight** pointers and **annotated** release tags on a fixed chip history — compare `git tag` vs `git tag -a -m`.

Starter example: Annotated release v0.1.0 on the wire-alu commit. Tip of main is the merge — tag v0.2.0 as annotated when you ship mul.

Load starter example

Challenges 0 / 22 cleared

Quiz: light: A lightweight tag is mainly a? Answer: pointer or name

Answer

Show hintCheckNextIdle

Quiz: lightQuiz: annotatedQuiz: -aStarter v0.1Annotate v0.2Lightweight tipNeed -mDup refused

Show annotatedQuiz: pushPush tagsDelete tagQuiz: show lightStarter countBoth kindsQuiz: semver

Tag old commitQuiz: movePrefer annotatedLight no taggerQuiz: -mShip v0.2

Two kinds of tags

Lightweight

git tag name — a name that points at a commit. No message, no tagger object.

Annotated

git tag -a name -m "..." — a real object: tagger, date, message. Prefer for releases.

Commits

Create / inspect

Tags lab starter

Real Git practice

```
wsl - module88-git-tags-lab/examples/tags

# Track A - real Unix
# real shell session (Track A)

# practice repo: /tmp/git-tag-tdMaFc

$ git init

$ echo "v1" > notes.md

$ git add notes.md

$ git commit -m "Add notes"

$ git tag v1.0

$ git tag
v1.0

$ git show v1.0
commit a19c84eff80fe8e4fda0731aac4963ae15b0aba9
Author: Demo <demo@local>
Date:   Mon Jul 20 14:21:38 2026 +0800

    Add notes

diff --git a/notes.md b/notes.md
new file mode 100644
index 0000000..626799f
--- /dev/null
+++ b/notes.md
@@ -0,0 +1 @@
+v1

$ git tag -a v1.0.0 -m "Release 1.0"

$ git show v1.0.0
tag v1.0.0
Tagger: Demo <demo@local>
Date:   Mon Jul 20 14:21:38 2026 +0800

Release 1.0

commit a19c84eff80fe8e4fda0731aac4963ae15b0aba9
Author: Demo <demo@local>
Date:   Mon Jul 20 14:21:38 2026 +0800

    Add notes

diff --git a/notes.md b/notes.md
new file mode 100644
index 0000000..626799f
--- /dev/null
+++ b/notes.md
@@ -0,0 +1 @@
+v1
```

Real shell — lightweight and annotated tags

Real Git practice — try these

```
# git init — create a new repository here  
git init
```

```
# echo ... > notes.md — create and commit a tracked file  
echo "v1" > notes.md
```

```
git add notes.md
```

```
git commit -m "Add notes"
```

```
# git tag v1.0 — lightweight tag on this commit  
git tag v1.0
```

```
# git tag — list tag names  
git tag
```

Pitfalls to watch

- Do not reuse a tag name for a different commit without deleting the old one first
- Do not assume push sends tags, use push with tags or push the tag name explicitly
- Prefer annotated tags for anything you publish
- And remember

Your turn

- Complete the checklist for at least one track, preferably both
- In the browser
- On real Git, tag, list, and show in your practice tree
- When you are ready, take the short quiz, then continue to the next module on branch naming