

Submission reproducibility

Before you push or zip a lab, ask: can a grader reproduce your result from a clean checkout?

Clean, root, log, push

- Run status and confirm build artifacts and logs are gitignored, not accidentally staged
- Remove local secrets and scratch files graders should never see
- Run demo or test scripts from the repository root so relative paths match the README
- Capture stdout and stderr with tee into run dot log so reviewers see what you saw
- Then push and verify on the host that only the right files and commits appear

Browser lab

Digital Design and Verification Platform

Home / Tools / Submit repro

HomeTools

INTERACTIVE TOOL

Submission reproducibility

Ship a **clean tree**, run scripts from the **repo root**, and **capture logs** so graders can replay your result.

Starter example: Lab repo with source plus junk (build/, notes.tmp), a local .env, and no run.log yet. Clean, run from root, capture the log.

Load starter example

Challenges 0 / 22 cleared

Quiz: where: Run project scripts from? Answer: repo root

Answer

Show hint

Check

Next

Idle

Quiz: where

Quiz: secrets

Quiz: capture

Quiz: junk

See dirty

At root

Wrong cwd fails

Clean junk

Drop .env

Run from root

Capture log

Status after clean

Quiz: paths

Tee needs root

Example stays

Check not ready

Full ready

Quiz: log file

Check ready OK

Quiz: repro

Sources kept

End to end

Core ideas

1. Clean tree → 2. Scripts from root → 3. Capture log → 4. Ready

Clean tree

No junk, no secrets — graders unzip what you meant to send.

Root + logs

Run scripts/... from repo root; save stdout to run.log.

Submission reproducibility lab starter

learn_git — submission repro

Real Git practice

```
wsl - module20-submission-repro/examples/submission

# Track A - real Unix
# real shell session (Track A)
# practice sandbox: /tmp/git-sr-Qo2bFU

$ git status
## main ... origin/main

$ cat .gitignore
build/
logs/
*.log
.env

$ bash scripts/run_demo.sh
demo ok

$ bash scripts/run_demo.sh 2>&1 | tee run.log
demo ok

$ tail run.log
demo ok

$ git log --oneline -3
c3c91a7 init lab sources

$ git push origin main
```

Real shell — clean tree, run from root, capture log

Real Git practice — try these

```
# git status — see tracked vs ignored files before submit  
git status
```

```
# cat .gitignore — confirm build/, logs/, and .env are excluded  
cat .gitignore
```

```
# bash scripts/run_demo.sh — run the demo from repo root  
bash scripts/run_demo.sh
```

```
# bash scripts/run_demo.sh 2>&1 | tee run.log — capture stdout and  
stderr  
bash scripts/run_demo.sh 2>&1 | tee run.log
```

```
# tail run.log — verify the log captured success output  
tail run.log
```

Pitfalls to watch

- Running scripts from a subdirectory breaks relative paths, check `pwd` first
- Never commit env files with real tokens; copy from env example instead
- A dirty tree with surprise untracked files means you might zip or push the wrong snapshot
- Capture the log only after a successful root run
- And remember

Your turn

- Complete the checklist for at least one track, preferably both
- In the browser, load the starter and get to ready with a clean tree and run dot log
- On real Git, practice status, root run, and log capture before push
- Pull request