

Regression triage

Nightly noise without buckets wastes the morning

Fail, flake, new, env

- Fail means reproducible design, VIP, or scoreboard breakage, own and fix
- Flake means intermittent or seed-sensitive, quarantine and stabilize, do not bury
- New means first appearance this run, escalate; do not assume known
- Env means license, disk, tool, or farm crash, infra, not RTL

Browser lab

Digital Design and Verification Platform

HomeTools

Home / Tools / Regression triage board

INTERACTIVE TOOL

Regression triage board

Document-aid literacy: sort regression results into **fail**, **flake**, **new**, and **env** buckets.

Starter: three fails already triaged — board CLEAN.

Starter example: uart_parity→fail, spi_timeout→flake, i2c_nack→new — board CLEAN.

Load starter example

Challenges 0 / 22 cleared

Quiz: fail: The fail bucket is for...

☐ reproducible DUT / VIP / scoreboard failures to own and fix

☐ any license-server timeout

☐ passing tests only

☐ Makefile PHONY targets

Show hint

Check

Next

Idle

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

Core ideas

fail

Reproducible DUT / VIP / checker break.

flake

Intermittent — quarantine, don't ignore.

new

First-seen this night — escalate early.

CLEAN

Zero open rows — triage complete.

Lab

SCENARIO

Lab starter

Planning docs practice

- Take three fictional nightly lines and assign fail
- Mark which one you would debug first and why
- Optional: note which seed-tag fields you would demand on the flake

Pitfalls to watch

- Do not mark everything flake to clear the board
- Do not treat env red as a DUT bug
- Do not ignore new fails because the night was busy
- And do not close triage without an owner on real fails

Your turn

- Complete the checklist for at least one track, preferably both
- Bucket a small board to clean, then take the quiz and continue to verification metrics