



Token Saver

Local proxy for Cursor and Claude Code. Strips bulky context before it hits the model APIs – fewer tokens, same workflow.

DASHBOARD

<http://127.0.0.1:8081/>

OPTIONAL URL

<http://tokensaver.local/>

PROXY

127.0.0.1:8080

OPS BOARD

<http://127.0.0.1:8081/v2>

Quick start

macOS

1. Double-click **start-mac.command** – installs deps and starts the proxy.
2. Double-click **Install to Applications.app** (or **install-to-applications.command**).
3. Open Token Saver → complete the setup wizard (optional: **Don't show this again**).
4. Dock click focuses the existing dashboard tab (or opens a new one). **Quit** stops the proxy.

Windows

1. Double-click **start-windows.bat** – installs deps and starts the proxy.
2. Open **<http://127.0.0.1:8081/>** – same setup wizard as macOS.
3. Prefer **reverse** mode for Claude Code and Cursor OpenAI BYOK (no CA install).
4. Use `.venv\Scripts\python.exe` for all commands – not a global Python.

Always run aiproxy with the project venv Python: `.venv/bin/python` (macOS) or `.venv\Scripts\python.exe` (Windows).

1. Install (once)

OS	Easiest	Manual
macOS	<code>start-mac.command</code>	<code>python3 -m venv .venv</code> then <code>pip install -r requirements.txt</code> and <code>-e .</code>
Windows	<code>start-windows.bat</code>	<code>python -m venv .venv</code> then the same pip steps via <code>.venv\Scripts\python.exe</code>

```
# Snippets
.venv/bin/python -m aioproxy --print-cursor-settings
.venv/bin/python -m aioproxy --print-claude-settings

# Windows
.\.venv\Scripts\python.exe -m aioproxy --print-cursor-settings
```

macOS Dock app

```
./install-to-applications.command
open -a "Token Saver"
```

- First launch → setup wizard unless **Don't show this again** was saved (`SKIP_SETUP=1`)
- Dock click while open → focus existing dashboard tab, else open a new tab
- Prefs: `.aioproxy_runtime.env` · Logs: `~/Library/Logs/TokenSaver/proxy.log`
- Re-run the installer after moving the repo · Dashboard **Setup** reopens the wizard anytime

2. Modes

Mode	Best for	CA?
mitm	Cursor default models (HTTPS intercept)	Yes
reverse	Cursor BYOK and Claude Code (JSON strip)	No
openai	Cursor OpenAI Base URL / BYOK only	No
anthropic	Claude Code via ANTHROPIC_BASE_URL	No

Pick: Cursor without BYOK → mitm. Claude / Cursor BYOK → reverse / anthropic / openai. On Windows, prefer reverse unless you need MITM.

```
# Dry-run first (logs savings; does not change bodies)
.venv/bin/python -m aioproxy --dry-run
.\.venv\Scripts\python.exe -m aioproxy --dry-run
```

3. Connect Cursor

MITM — macOS

```
.venv/bin/python -m aioproxy --mode mitm --dry-run

sudo security add-trusted-cert -d -r trustRoot \
  -k /Library/Keychains/System.keychain \
  ~/.mitmproxy/mitmproxy-ca-cert.pem
```

Cursor `settings.json` :

```
{
  "http.proxy": "http://127.0.0.1:8080",
  "http.proxySupport": "override",
  "http.proxyStrictSSL": false,
  "cursor.general.disableHttp2": true
}
```

```
export NODE_EXTRA_CA_CERTS="$HOME/.mitmproxy/mitmproxy-ca-cert.pem"
open -a Cursor    # after Cmd+Q quit
```

OpenAI BYOK — Mac or Windows (recommended on Windows)

```
.venv/bin/python -m aiproxy --mode openai --dry-run
# Cursor → Settings → Models → OpenAI Base URL:
# http://127.0.0.1:8080/v1
# No CA. Leave http.proxy unset.
```

Windows MITM (optional)

1. Start with `--mode mitm; trust %USERPROFILE%\mitmproxy\mitmproxy-ca-cert.cer` in Trusted Root.
2. Same Cursor `http.proxy` settings as above.
3. Relaunch Cursor with `NODE_EXTRA_CA_CERTS` set to the `.pem` path.

4. Connect Claude Code

```
# Terminal 1
.venv/bin/python -m aiproxy --mode anthropic --dry-run

# Terminal 2 (macOS / Linux)
export ANTHROPIC_BASE_URL="http://127.0.0.1:8080"
claude

# Terminal 2 (Windows PowerShell)
$env:ANTHROPIC_BASE_URL = "http://127.0.0.1:8080"
claude
```

Persist in `~/.claude/settings.json` (Windows: `%USERPROFILE%\claude\settings.json`):

```
{
  "env": { "ANTHROPIC_BASE_URL": "http://127.0.0.1:8080" }
}
```

Not covered: claude.ai in the browser, Claude Desktop.

5. Memorable URL (optional)

```
# macOS
cd /path/to/ai-token-saver
sudo "$(pwd)/.venv/bin/python" -m aiproxy --install-hostname

# Windows (Admin PowerShell)
cd C:\path\to\ai-token-saver
& "$(Get-Location)\.venv\Scripts\python.exe" -m aiproxy --install-hostname
```

Adds hosts entry for `tokensaver.local` and a small port-80 forwarder to the dashboard.

6. Verify & strip rules

Check	Expected
Dashboard	<code>http://127.0.0.1:8081/ loads</code>
Chat	Requested counters rise
Strip	Saved > 0 (or dry-run log notes)
logs/	*.meta.json when bodies change

Rollout: dry-run → tune `config.yaml` `strip:` → restart without `--dry-run`.

Rule	Idea
<code>max_messages</code>	Keep last N turns (+ system)
<code>max_chars_*</code>	Cap huge file dumps
<code>dedupe_file_blocks</code>	Collapse duplicate path/code blocks
<code>max_tool_result_chars</code>	Truncate old tool output
<code>drop_reasoning_parts</code>	Drop thinking blobs
<code>compress_system</code>	Shrink oversized system prompts

7. Ports & files

What	Where
Proxy	127.0.0.1:8080
Dashboard	127.0.0.1:8081
Config	config.yaml
Launcher prefs	.aiproxy_runtime.env / .aiproxy_session.env (SKIP_SETUP)
Stats	logs/stats.json
mitmproxy CA	~/.mitmproxy/... (Windows: %USERPROFILE%\.mitmproxy\)
macOS app logs	~/Library/Logs/TokenSaver/proxy.log