



Introduction to Computer Graphics with WebGL

Ed Angel

Professor Emeritus of Computer Science

Founding Director, Arts, Research,
Technology and Science Laboratory

University of New Mexico



The University of New Mexico

Input and Interaction

Ed Angel

Professor Emeritus of Computer Science,
University of New Mexico



Objectives

- Introduce the basic input devices
 - Physical Devices
 - Logical Devices
 - Input Modes
- Event-driven input
- Introduce double buffering for smooth animations
- Programming event input with WebGL



Project Sketchpad

- Ivan Sutherland (MIT 1963) established the basic interactive paradigm that characterizes interactive computer graphics:
 - User sees an *object* on the display
 - User points to (*picks*) the object with an input device (light pen, mouse, trackball)
 - Object changes (moves, rotates, morphs)
 - Repeat



Graphical Input

- Devices can be described either by
 - Physical properties
 - Mouse
 - Keyboard
 - Trackball
 - Logical Properties
 - What is returned to program via API
 - A position
 - An object identifier
- Modes
 - How and when input is obtained
 - Request or event




The University of New Mexico


Physical Devices




mouse




trackball




light pen



data tablet



joy stick



space ball



Incremental (Relative) Devices

- Devices such as the data tablet return a position directly to the operating system
- Devices such as the mouse, trackball, and joy stick return incremental inputs (or velocities) to the operating system
 - Must integrate these inputs to obtain an absolute position
 - Rotation of cylinders in mouse
 - Roll of trackball
 - Difficult to obtain absolute position
 - Can get variable sensitivity



Logical Devices

- Consider the C and C++ code
 - C++: `cin >> x;`
 - C: `scanf ("%d", &x);`
- What is the input device?
 - Can't tell from the code
 - Could be keyboard, file, output from another program
- The code provides *logical input*
 - A number (an `int`) is returned to the program regardless of the physical device




Graphical Logical Devices

- Graphical input is more varied than input to standard programs which is usually numbers, characters, or bits
- Two older APIs (GKS, PHIGS) defined six types of logical input
 - **Locator**: return a position
 - **Pick**: return ID of an object
 - **Keyboard**: return strings of characters
 - **Stroke**: return array of positions
 - **Valuator**: return floating point number
 - **Choice**: return one of n items



X Window Input

- The X Window System introduced a client-server model for a network of workstations
 - **Client:** OpenGL program
 - **Graphics Server:** bitmap display with a pointing device and a keyboard






Input Modes

- Input devices contain a *trigger* which can be used to send a signal to the operating system
 - Button on mouse
 - Pressing or releasing a key
- When triggered, input devices return information (their *measure*) to the system
 - Mouse returns position information
 - Keyboard returns ASCII code



Request Mode


- Input provided to program only when user triggers the device
- Typical of keyboard input
 - Can erase (backspace), edit, correct until enter (return) key (the trigger) is depressed





Event Mode

- Most systems have more than one input device, each of which can be triggered at an arbitrary time by a user
- Each trigger generates an *event* whose measure is put in an *event queue* which can be examined by the user program





Event Types

- Window: resize, expose, iconify
- Mouse: click one or more buttons
- Motion: move mouse
- Keyboard: press or release a key
- Idle: nonevent
 - Define what should be done if no other event is in queue



Introduction to Computer Graphics with WebGL

Ed Angel

Professor Emeritus of Computer Science

Founding Director, Arts, Research,
Technology and Science Laboratory

University of New Mexico



The University of New Mexico

Animation

Ed Angel

Professor Emeritus of Computer Science,
University of New Mexico




Callbacks

- Programming interface for event-driven input uses *callback functions* or *event listeners*
 - Define a callback for each event the graphics system recognizes
 - Browsers enters an event loop and responds to those events for which it has callbacks registered
 - The callback function is executed when the event occurs



Execution in a Browser





Execution in a Browser

- Start with HTML file
 - Describes the page
 - May contain the shaders
 - Loads files
- Files are loaded asynchronously and JS code is executed
- Then what?
- Browser is in an event loop and waits for an event




onload Event

- What happens with our JS file containing the graphics part of our application?
 - All the “action” is within functions such as `init()` and `render()`
 - Consequently these functions are never executed and we see nothing
- Solution: use the onload window event to initiate execution of the `init` function
 - onload event occurs when all files read
 - `window.onload = init;`



Rotating Square

- Consider the four points



Animate display by rerendering with different values of θ



The University of New Mexico

Simple but Slow Method

```
for(var theta = 0.0; theta < thetaMax; theta += dtheta; {  
  
    vertices[0] = vec2(Math.sin(theta), Math.cos.(theta));  
    vertices[1] = vec2(Math.sin(theta), -Math.cos.(theta));  
    vertices[2] = vec2(-Math.sin(theta), -Math.cos.(theta));  
    vertices[3] = vec2(-Math.sin(theta), Math.cos.(theta));  
  
    gl.bufferSubData(.....  
  
    render();  
}
```



Better Way

- Send original vertices to vertex shader
- Send θ to shader as a uniform variable
- Compute vertices in vertex shader
- Render recursively
- Code in [03/rotatingSquare1.html](#) and [03/rotatingSquare1.js](#)



Render Function

```
var thetaLoc = gl.getUniformLocation(program, "uTheta");  
\\ binds the thetaLoc JS variable to the uTheta uniform variable of  
the shaders  
function render()  
{ gl.clear(gl.COLOR_BUFFER_BIT);  
  theta += 0.1;  
  gl.uniform1f(thetaLoc, theta);  
  \\ transfers the value of theta to thetaLoc (uTheta), thus updating the  
  shader value  
  gl.drawArrays(gl.TRIANGLE_STRIP, 0, 4);  
  render();  
  \\ recursively calling itself for a continuous animation loop  
}
```




Vertex Shader

```
#version 300 es
in vec4 aPosition;
uniform float uTheta;
void main()
{
    float s = sin(uTheta);
    float c = cos(uTheta);
    gl_Position.x = -s*aPosition.y + c*aPosition.x;
    gl_Position.y =  s*aPosition.x + c*aPosition.y;
    gl_Position.z = 0.0;
    gl_Position.w = 1.0;
}
```



Double Buffering

- Although we are rendering the square, it always into a buffer that is not displayed
- Browser uses double buffering
 - Always display front buffer
 - Rendering into back buffer
 - Need a buffer swap
- Prevents display of a partial rendering



Triggering a Buffer Swap

- Browsers refresh the display at ~60 Hz
 - redisplay of front buffer
 - not a buffer swap
- Trigger a buffer swap through an event
- Two options for rotating square
 - Interval timer
 - requestAnimationFrame



Interval Timer

- Executes a function after a specified number of milliseconds
 - Also generates a buffer swap
- `setTimeout(renderFunc, interval);`
- Note an interval of 0 generates buffer swaps as fast as possible



requestAnimationFrame

```
function render {  
    gl.clear(gl.COLOR_BUFFER_BIT);  
    theta += 0.1;  
    gl.uniform1f(thetaLoc, theta);  
    gl.drawArrays(gl.TRIANGLE_STRIP, 0, 4);  
    requestAnimationFrame(render);  
    \\ requestAnimationFrame asks the browser to  
    \\ generate the next frame (executing the render  
    \\ function), as soon as possible  
}
```



Add an Interval

```
function render()
{
    gl.clear(gl.COLOR_BUFFER_BIT);
    theta += 0.1;
    gl.uniform1f(thetaLoc, theta);
    gl.drawArrays(gl.TRIANGLE_STRIP, 0, 4);
    setTimeout(
        function(){ requestAnimationFrame(render); },
        100 ); \\delay in milliseconds, the animation request
              \\ is generated only after a 100ms delay
}
```



Introduction to Computer Graphics with WebGL

Ed Angel

Professor Emeritus of Computer Science

Founding Director, Arts, Research,
Technology and Science Laboratory

University of New Mexico



The University of New Mexico

Working with Callbacks

Ed Angel

Professor Emeritus of Computer Science

University of New Mexico



Objectives

- Learn to build interactive programs using event listeners
 - Buttons
 - Menus
 - Mouse
 - Keyboard
 - Reshape
- Code in [03/rotatingSquare2.html](#) and `03/rotatingSquare2.js`



Adding a Button

- Let's add a button to control the rotation direction for our rotating cube
- In the render function we can use a var direction which is true or false to add or subtract a constant to the angle

```
var direction = true; // global initialization
```

```
// inside the render() function
```

```
theta += (direction ? 0.1 : -0.1);
```



The Button

- In the HTML file
`<button id="Direction">Change Rotation Direction</button>`
 - Uses HTML `button` tag
 - `id` gives an identifier we can use in JS file
 - Text “Change Rotation Direction” displayed in button
- Clicking on button generates a `click` event
- Note we are using default style and could use CSS or jQuery to get a prettier button



Button Event Listener

- We still need to define the listener
 - no listener and the event occurs but is ignored
- Two forms for event listener in JS file

```
var myButton = document.getElementById("Direction");  
  
myButton.addEventListener("click", function() {  
    direction = !direction;  
});
```

```
document.getElementById("Direction").onclick =  
function() { direction = !direction; };
```



onclick Variants

```
myButton.addEventListener("click", function() {  
  if (event.button == 0) { direction = !direction; }  
});
```

```
myButton.addEventListener("click", function() {  
  if (event.shiftKey == 0) { direction = !direction; }  
});
```

```
<button onclick="direction = !direction"></button>
```



Controlling Rotation Speed

```
var delay = 100;
function render()
{
    gl.clear(gl.COLOR_BUFFER_BIT);
    theta += (direction ? 0.1 : -0.1);
    gl.uniform1f(thetaLoc, theta);
    gl.drawArrays(gl.TRIANGLE_STRIP, 0, 4);
    setTimeout( function ()
                    { requestAnimationFrame(render); },
                delay );
}
```



Menus

- Use the HTML **select** element
- Each entry in the menu is an **option** element with an integer **value** returned by click event

```
<select id="Controls" size="3">  
<option value="0">Toggle Rotation Direction</option>  
<option value="1">Spin Faster</option>  
<option value="2">Spin Slower</option>  
</select>
```



Menu Listener

```
document.getElementById("Controls" ).onclick =  
function(event)  
{  
    switch(event.target.index)  
    {  
        case 0: direction = !direction; break;  
        case 1: delay /= 2.0; break;  
        case 2: delay *= 2.0; break;  
    }  
};
```




Using keydown Event

```
window.onkeydown = function(event)
{
    var key = String.fromCharCode(event.keyCode);
    switch(key)
    {
        case '1': direction = !direction; break;
        case '2': delay /= 2.0; break;
        case '3': delay *= 2.0; break;
    }
};
```



The University of New Mexico

SLIDE DELETED



Slider Element

- Puts slider on page
 - Give it an **id**entifier
 - Give it **minimum** and **maximum** values
 - Give it a step **size** needed to generate an event
 - Give it an initial **value**
- Use **div** tag to put below canvas

```
<div>  
speed 0% <input id="slider" type="range"  
  min="0" max="100" step="10" value="50" />  
100% </div>
```



The University of New Mexico

onchange Event Listener

Code in [03/rotatingSquare3.html](#) and 03/rotatingSquare3.js

Event listener in JavaScript:

```
document.getElementById("slider").onchange =  
    function(event) { speed = 100 - event.target.value; };
```



Introduction to Computer Graphics with WebGL

Ed Angel

Professor Emeritus of Computer Science

Founding Director, Arts, Research,
Technology and Science Laboratory

University of New Mexico



The University of New Mexico

Position Input

Ed Angel

Professor Emeritus of Computer Science

University of New Mexico




Objectives

- Learn to use the mouse to give locations
 - Must convert from position on canvas to position in application
- Respond to window events such as reshapes triggered by the mouse



The University of New Mexico

Window Coordinates





Window to Clip Coordinates

$$(0, h) \rightarrow (-1, -1)$$

$$(w, 0) \rightarrow (1, 1)$$

$$x = -1 + \frac{2 * x_w}{w}$$

$$y = -1 + \frac{2 * (h - y_w)}{h}$$



Returning Position from Click Event

Canvas specified in HTML file of size `canvas.width` x `canvas.height`. Returned window coordinates are `event.clientX` and `event.clientY`

```
// add a vertex to GPU for each click
canvas.addEventListener("mousedown", function(event)
{
    gl.bindBuffer( gl.ARRAY_BUFFER, vBuffer );
    var t = vec2(2*event.clientX/canvas.width-1,
                2*(canvas.height-event.clientY)/canvas.height-1);
    gl.bufferSubData(gl.ARRAY_BUFFER, 8*index, flatten(t));
    gl.bindBuffer(gl.ARRAY_BUFFER, cBuffer);
    t = vec4(colors[(index)%7]);
    gl.bufferSubData(gl.ARRAY_BUFFER, 16*index, flatten(t));
    index++;
} );
```



The University of New Mexico

CAD-like Examples

<http://interactivecomputergraphics.com/Code/03/square.html>: puts a colored square at location of each mouse click

[triangle.html](http://interactivecomputergraphics.com/Code/03/triangle.html): first three mouse clicks define first triangle of triangle strip. Each succeeding mouse clicks adds a new triangle at end of strip

[cad1.html](http://interactivecomputergraphics.com/Code/03/cad1.html): draw a rectangle for each two successive mouse clicks

[cad2.html](http://interactivecomputergraphics.com/Code/03/cad2.html): draws arbitrary polygons



Window Events

- Events can be generated by actions that affect the canvas window
 - moving or exposing a window
 - resizing a window
 - opening a window
 - iconifying/deiconifying a window a window
- Note that events generated by other application that use the canvas can affect the WebGL canvas
 - There are default callbacks for some of these events



Reshape Events

- Suppose we use the mouse to change the size of our canvas
- Must redraw the contents
- Options
 - Display the same objects but change size
 - Display more or fewer objects at the same size
- Almost always want to keep proportions



onresize Event

- Returns size of new canvas is available through `window.innerHeight` and `window.innerWidth`
- Use `innerHeight` and `innerWidth` to change `canvas.height` and `canvas.width`
- Example (next slide): maintaining a square display



Keeping Square Proportions

```
window.onresize = function() {  
    var min = innerWidth;  
    if (innerHeight < min) {  
        min = innerHeight;  
    }  
    if (min < canvas.width || min < canvas.height) {  
        gl.viewport(0, canvas.height-min, min, min);  
    }  
};
```



Introduction to Computer Graphics with WebGL

Ed Angel

Professor Emeritus of Computer Science

Founding Director, Arts, Research,
Technology and Science Laboratory

University of New Mexico



The University of New Mexico

Picking

Ed Angel

Professor Emeritus of Computer Science

University of New Mexico



Objectives

- How do we identify objects on the display
- Overview three methods
 - selection
 - using an off-screen buffer and color
 - bounding boxes



Why is Picking Difficult?

The University of New Mexico

-
- Given a point in the canvas how do map this point back to an object?
 - Lack of uniqueness
 - Forward nature of pipeline
 - Take into account difficulty of getting an exact position with a pointing device



Selection

- Supported by fixed function OpenGL pipeline
- Each primitive is given an id by the application indicating to which object it belongs
- As the scene is rendered, the id's of primitives that render near the mouse are put in a hit list
- Examine the hit list after the rendering



Selection

- Implement by creating a window that corresponds to small area around mouse
 - We can track whether or not a primitive renders to this window
 - Do not want to display this rendering
 - Render off-screen to an extra color buffer or user back buffer and don't do a swap
- Requires a rendering which puts depths into hit record
- Possible to implement with WebGL



Picking with Color


- We can use `gl.readPixels` to get the color at any location in window
- Idea is to use color to identify object but
 - Multiple objects can have the same color
 - A shaded object will display many colors
- Solution: assign a unique color to each object and render off-screen
 - Use `gl.readPixels` to get color at mouse location
 - Use a table to map this color to an object



The University of New Mexico

Picking with Bounding Boxes

- Both previous methods require an extra rendering each time we do a pick
- Alternative is to use a table of (axis-aligned) bounding boxes
- Map mouse location to object through table





Introduction to Computer Graphics with WebGL

Ed Angel

Professor Emeritus of Computer Science

Founding Director, Arts, Research,
Technology and Science Laboratory

University of New Mexico



The University of New Mexico

Geometry

Ed Angel

Professor Emeritus of Computer Science
University of New Mexico



Objectives

- Introduce the elements of geometry
 - Scalars
 - Vectors
 - Points
- Develop mathematical operations among them in a coordinate-free manner
- Define basic primitives
 - Line segments
 - Polygons



Basic Elements

- Geometry is the study of the relationships among objects in an n -dimensional space
 - In computer graphics, we are interested in objects that exist in three dimensions
- Want a minimum set of primitives from which we can build more sophisticated objects
- We will need three basic elements
 - Scalars
 - Vectors
 - Points



Coordinate-Free Geometry

- When we learned simple geometry, most of us started with a Cartesian approach
 - Points were at locations in space $\mathbf{p}=(x,y,z)$
 - We derived results by algebraic manipulations involving these coordinates
- This approach was nonphysical
 - Physically, points exist regardless of the location of an arbitrary coordinate system
 - Most geometric results are independent of the coordinate system
 - Example Euclidean geometry: two triangles are identical if two corresponding sides and the angle between them are identical




Scalars

-
- Need three basic elements in geometry
 - Scalars, Vectors, Points
 - Scalars can be defined as members of sets which can be combined by two operations (addition and multiplication) obeying some fundamental axioms (associativity, commutivity, inverses)
 - Examples include the real and complex number systems under the ordinary rules with which we are familiar
 - Scalars alone have no geometric properties




Vectors

- Physical definition: a vector is a quantity with two attributes
 - Direction
 - Magnitude
- Examples include
 - Force
 - Velocity
 - Directed line segments
 - Most important example for graphics
 - Can map to other types



Vector Operations

- Every vector has an inverse
 - Same magnitude but points in opposite direction
- Every vector can be multiplied by a scalar
- There is a zero vector
 - Zero magnitude, undefined orientation
- The sum of any two vectors is a vector
 - Use head-to-tail axiom





Linear Vector Spaces


- Mathematical system for manipulating vectors
- Operations
 - Scalar-vector multiplication $u = \alpha v$
 - Vector-vector addition: $w = u + v$
- Expressions such as
$$v = u + 2w - 3r$$

Make sense in a vector space



Vectors Lack Position

- These vectors are identical
 - Same length and magnitude




- Vectors spaces insufficient for geometry
 - Need points



Points

- Location in space
- Operations allowed between points and vectors
 - Point-point subtraction yields a vector
 - Equivalent to point-vector addition



$$v = P - Q$$

$$P = v + Q$$




Affine Spaces

- Point + a vector space
- Operations
 - Vector-vector addition
 - Scalar-vector multiplication
 - Point-vector addition
 - Scalar-scalar operations
- For any point define
 - $1 \cdot P = P$
 - $0 \cdot P = \mathbf{0}$ (zero vector)



Lines

- Consider all points of the form
 - $P(\alpha) = P_0 + \alpha \mathbf{d}$
 - Set of all points that pass through P_0 in the direction of the vector \mathbf{d}





Parametric Form

- This form is known as the parametric form of the line
 - More robust and general than other forms
 - Extends to curves and surfaces
- Two-dimensional forms
 - Explicit: $y = mx + h$
 - Implicit: $ax + by + c = 0$
 - Parametric:
$$x(\alpha) = \alpha x_0 + (1-\alpha)x_1$$
$$y(\alpha) = \alpha y_0 + (1-\alpha)y_1$$




Rays and Line Segments

- If $\alpha \geq 0$, then $P(\alpha)$ is the *ray* leaving P_0 in the direction \mathbf{d}

If we use two points to define \mathbf{v} , then

$$\begin{aligned} P(\alpha) &= Q + \alpha (R - Q) = Q + \alpha \mathbf{v} \\ &= \alpha R + (1 - \alpha)Q \end{aligned}$$


For $0 \leq \alpha \leq 1$ we get all the points on the *line segment* joining R and Q






Convexity

- An object is *convex* iff for any two points in the object all points on the line segment between these points are also in the object



convex



not convex



Affine Sums

- Consider the “sum”

$$P = \alpha_1 P_1 + \alpha_2 P_2 + \dots + \alpha_n P_n$$

Can show by induction that this sum makes sense iff

$$\alpha_1 + \alpha_2 + \dots + \alpha_n = 1$$


in which case we have the *affine sum* of the points P_1, P_2, \dots, P_n

- If, in addition, $\alpha_i \geq 0$, we have the *convex hull* of P_1, P_2, \dots, P_n



Convex Hull

- Smallest convex object containing P_1, P_2, \dots, P_n
- Formed by “shrink wrapping” points






Curves and Surfaces

- Curves are one parameter entities of the form $P(\alpha)$ where the function is nonlinear
- Surfaces are formed from two-parameter functions $P(\alpha, \beta)$
 - Linear functions give planes and polygons



$P(\alpha)$




$P(\alpha, \beta)$




Planes

- A plane can be defined by a point and two vectors or by three points




$$P(\alpha, \beta) = R + \alpha u + \beta v$$



$$P(\alpha, \beta) = R + \alpha(Q - R) + \beta(P - R)$$



Triangles



for $0 \leq \alpha, \beta \leq 1$, we get all points in triangle



Barycentric Coordinates

Triangle is convex so any point inside can be represented as an affine sum

$$P(\alpha_1, \alpha_2, \alpha_3) = \alpha_1 P + \alpha_2 Q + \alpha_3 R$$

where

$$\alpha_1 + \alpha_2 + \alpha_3 = 1$$

$$\alpha_i \geq 0$$

The representation is called the **barycentric coordinate** representation of P



Normals

- In three dimensional spaces, every plane has a vector n perpendicular or orthogonal to it called the **normal vector**
- From the two-point vector form $P(\alpha, \beta) = P + \alpha u + \beta v$, we know we can use the cross product to find $n = u \times v$ and the equivalent form $(P(\alpha, \beta) - P) \cdot n = 0$

