

# Your Classifier is Secretly an Energy Based Model and You Should Treat it Like One

January 29, 2020

What is an Energy Based Model (EBM)?

# What is an Energy Based Model (EBM)?

Any pdf  $p_{\theta}(x)$  can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

# What is an Energy Based Model (EBM)?

Any pdf  $p_{\theta}(\mathbf{x})$  can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

where  $Z_{\theta}$  is a normalizing constant:

$$Z_{\theta} = \int_{\mathbf{x}} \exp(-E_{\theta}(\mathbf{x})) d\mathbf{x}$$

# What is an Energy Based Model (EBM)?

Any pdf  $p_{\theta}(\mathbf{x})$  can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

where  $Z_{\theta}$  is a normalizing constant:

$$Z_{\theta} = \int_{\mathbf{x}} \exp(-E_{\theta}(\mathbf{x})) d\mathbf{x}$$

- This parametrization allows us to forget about  $p_{\theta}(\mathbf{x})$  and work with  $E_{\theta}(\mathbf{x})$

# What is an Energy Based Model (EBM)?

Any pdf  $p_{\theta}(\mathbf{x})$  can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

where  $Z_{\theta}$  is a normalizing constant:

$$Z_{\theta} = \int_{\mathbf{x}} \exp(-E_{\theta}(\mathbf{x})) d\mathbf{x}$$

- ▶ This parametrization allows us to forget about  $p_{\theta}(\mathbf{x})$  and work with  $E_{\theta}(\mathbf{x})$
- ▶ Function  $E_{\theta}(\mathbf{x})$  is an *energy function* (hence the name — EBM)

# What is an Energy Based Model (EBM)?

Any pdf  $p_{\theta}(\mathbf{x})$  can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

where  $Z_{\theta}$  is a normalizing constant:

$$Z_{\theta} = \int_{\mathbf{x}} \exp(-E_{\theta}(\mathbf{x})) d\mathbf{x}$$

- ▶ This parametrization allows us to forget about  $p_{\theta}(\mathbf{x})$  and work with  $E_{\theta}(\mathbf{x})$
- ▶ Function  $E_{\theta}(\mathbf{x})$  is an *energy function* (hence the name — EBM)
- ▶ Energy functions are *easier* to work with: you do not have any restrictions on  $E_{\theta}(\mathbf{x})$  ( $p_{\theta}(\mathbf{x})$  is nonnegative and integrates to 1).

# What is an Energy Based Model (EBM)?

Any pdf  $p_{\theta}(x)$  can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

where  $Z_{\theta}$  is a normalizing constant:

$$Z_{\theta} = \int_{\mathbf{x}} \exp(-E_{\theta}(\mathbf{x})) d\mathbf{x}$$

- ▶ This parametrization allows us to forget about  $p_{\theta}(x)$  and work with  $E_{\theta}(x)$
- ▶ Function  $E_{\theta}(x)$  is an *energy function* (hence the name — EBM)
- ▶ Energy functions are *easier* to work with: you do not have any restrictions on  $E_{\theta}(x)$  ( $p_{\theta}(x)$  is nonnegative and integrates to 1).
- ▶ Energy functions are *harder* to work with:  $Z_{\theta}$  is hard or impossible to compute, so we can't optimize EBM for  $\theta$



# How to train EBM

## How to train EBM

- ▶ We perform standard MLE: maximize  $\log p_{\theta}(x_i)$  at our points  $x_i$ .

## How to train EBMs

- ▶ We perform standard MLE: maximize  $\log p_{\theta}(x_i)$  at our points  $x_i$ .
- ▶ By optimizing  $\log p_{\theta}(x)$  we also optimize  $E_{\theta}(x)$ .

# How to train EBMs

- ▶ We perform standard MLE: maximize  $\log p_\theta(x_i)$  at our points  $x_i$ .
- ▶ By optimizing  $\log p_\theta(x)$  we also optimize  $E_\theta(x)$ .
- ▶ We can't compute  $\log p_\theta(x)$ , but we can (approximately) compute its log-derivative via:

$$\frac{\partial \log p_\theta(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_\theta(\mathbf{x}')} \left[ \frac{\partial E_\theta(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_\theta(\mathbf{x})}{\partial \theta} \quad (2)$$

# How to train EBMs

- ▶ We perform standard MLE: maximize  $\log p_\theta(x_i)$  at our points  $x_i$ .
- ▶ By optimizing  $\log p_\theta(x)$  we also optimize  $E_\theta(x)$ .
- ▶ We can't compute  $\log p_\theta(x)$ , but we can (approximately) compute its log-derivative via:

$$\frac{\partial \log p_\theta(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_\theta(\mathbf{x}')} \left[ \frac{\partial E_\theta(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_\theta(\mathbf{x})}{\partial \theta} \quad (2)$$

- ▶ Proof: follows directly from the definition.

# How to train EBMs

- ▶ We perform standard MLE: maximize  $\log p_\theta(x_i)$  at our points  $x_i$ .
- ▶ By optimizing  $\log p_\theta(x)$  we also optimize  $E_\theta(x)$ .
- ▶ We can't compute  $\log p_\theta(x)$ , but we can (approximately) compute its log-derivative via:

$$\frac{\partial \log p_\theta(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_\theta(\mathbf{x}')} \left[ \frac{\partial E_\theta(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_\theta(\mathbf{x})}{\partial \theta} \quad (2)$$

- ▶ Proof: follows directly from the definition.
- ▶ But a new problem arises: how to compute expectation?

# How to train EBMs

- ▶ We perform standard MLE: maximize  $\log p_\theta(x_i)$  at our points  $x_i$ .
- ▶ By optimizing  $\log p_\theta(x)$  we also optimize  $E_\theta(x)$ .
- ▶ We can't compute  $\log p_\theta(x)$ , but we can (approximately) compute its log-derivative via:

$$\frac{\partial \log p_\theta(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_\theta(\mathbf{x}')} \left[ \frac{\partial E_\theta(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_\theta(\mathbf{x})}{\partial \theta} \quad (2)$$

- ▶ Proof: follows directly from the definition.
- ▶ But a new problem arises: how to compute expectation?
- ▶ Answer: we can't do that directly, so let's use SGLD sampling.

# Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:



# Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:

- ▶ Imagine we have a “magic” function  $p_{\theta}(x)$  that takes an input  $x$  and tells us its density.

# Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:

- ▶ Imagine we have a “magic” function  $p_{\theta}(x)$  that takes an input  $x$  and tells us its density.
- ▶ Unfortunately, we cannot sample new  $x$ -s from it directly, i.e.  $p_{\theta}(x)$  does not support such operations.

# Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:

- ▶ Imagine we have a “magic” function  $p_\theta(x)$  that takes an input  $x$  and tells us its density.
- ▶ Unfortunately, we cannot sample new  $x$ -s from it directly, i.e.  $p_\theta(x)$  does not support such operations.
- ▶ But we really want to sample from it! What should we do?

# Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:

- ▶ Imagine we have a “magic” function  $p_{\theta}(x)$  that takes an input  $x$  and tells us its density.
- ▶ Unfortunately, we cannot sample new  $x$ -s from it directly, i.e.  $p_{\theta}(x)$  does not support such operations.
- ▶ But we really want to sample from it! What should we do?
- ▶ SGLD is a method to sample from such functions.

# Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in short:

# Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in short:

1. Start from any random point  $x_0$ .

# Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in short:

1. Start from any random point  $x_0$ .
2. Compute the gradient of  $\nabla \log p_\theta(x_0)$ .

# Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in short:

1. Start from any random point  $x_0$ .
2. Compute the gradient of  $\nabla \log p_\theta(x_0)$ .
3. Perform a small step in that direction.



# Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in short:

1. Start from any random point  $x_0$ .
2. Compute the gradient of  $\nabla \log p_\theta(x_0)$ .
3. Perform a small step in that direction.
4. Add a little bit of noise.

# Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in short:

1. Start from any random point  $x_0$ .
2. Compute the gradient of  $\nabla \log p_\theta(x_0)$ .
3. Perform a small step in that direction.
4. Add a little bit of noise.
5. Obtain  $x_{t+1}$ .

# Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in short:

1. Start from any random point  $x_0$ .
2. Compute the gradient of  $\nabla \log p_\theta(x_0)$ .
3. Perform a small step in that direction.
4. Add a little bit of noise.
5. Obtain  $x_{t+1}$ .

In other words, run the following recurrence a lot of times:

$$\mathbf{x}_0 \sim p_0(\mathbf{x}), \quad \mathbf{x}_{i+1} = \mathbf{x}_i - \frac{\alpha}{2} \frac{\partial E_\theta(\mathbf{x}_i)}{\partial \mathbf{x}_i} + \epsilon, \quad \epsilon \sim \mathcal{N}(0, \alpha) \quad (3)$$

# Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in short:

1. Start from any random point  $x_0$ .
2. Compute the gradient of  $\nabla \log p_\theta(x_0)$ .
3. Perform a small step in that direction.
4. Add a little bit of noise.
5. Obtain  $x_{t+1}$ .

In other words, run the following recurrence a lot of times:

$$\mathbf{x}_0 \sim p_0(\mathbf{x}), \quad \mathbf{x}_{i+1} = \mathbf{x}_i - \frac{\alpha}{2} \frac{\partial E_\theta(\mathbf{x}_i)}{\partial \mathbf{x}_i} + \epsilon, \quad \epsilon \sim \mathcal{N}(0, \alpha) \quad (3)$$

Justification: if your model and your choice of  $\alpha$  are “good” (in some sense), then after infinite amount of steps your samples will be “good” (in some sense).

Ok, how to treat a classifier as an EBM?

## Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as  $E_{\theta}(x)$

## Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as  $E_\theta(x)$
- ▶ Let  $f_\theta(x)$  be our neural network.

## Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as  $E_{\theta}(x)$
- ▶ Let  $f_{\theta}(x)$  be our neural network.
- ▶ Let  $f_{\theta}(x)[y]$  be the  $y$ -th logit (i.e. logit value for class  $y$ ).



## Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as  $E_{\theta}(x)$
- ▶ Let  $f_{\theta}(x)$  be our neural network.
- ▶ Let  $f_{\theta}(x)[y]$  be the  $y$ -th logit (i.e. logit value for class  $y$ ).
- ▶ Let our examples be  $s = (x, y)$

## Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as  $E_\theta(x)$
- ▶ Let  $f_\theta(x)$  be our neural network.
- ▶ Let  $f_\theta(x)[y]$  be the  $y$ -th logit (i.e. logit value for class  $y$ ).
- ▶ Let our examples be  $s = (x, y)$
- ▶ We define energy  $E_\theta(s) = E_\theta(x, y) = -f_\theta(x)[y]$ .

## Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as  $E_\theta(\mathbf{x})$
- ▶ Let  $f_\theta(\mathbf{x})$  be our neural network.
- ▶ Let  $f_\theta(\mathbf{x})[y]$  be the  $y$ -th logit (i.e. logit value for class  $y$ ).
- ▶ Let our examples be  $s = (\mathbf{x}, y)$
- ▶ We define energy  $E_\theta(s) = E_\theta(\mathbf{x}, y) = -f_\theta(\mathbf{x})[y]$ .
- ▶ Using  $E_\theta(\mathbf{x}, y)$  we can define  $p_\theta(\mathbf{x})$ :

$$p_\theta(\mathbf{x}) = \sum_y p_\theta(\mathbf{x}, y) = \frac{1}{Z_\theta} \sum_y \exp(f_\theta(\mathbf{x})[y]) \quad (4)$$

## Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as  $E_\theta(\mathbf{x})$
- ▶ Let  $f_\theta(\mathbf{x})$  be our neural network.
- ▶ Let  $f_\theta(\mathbf{x})[y]$  be the  $y$ -th logit (i.e. logit value for class  $y$ ).
- ▶ Let our examples be  $s = (\mathbf{x}, y)$
- ▶ We define energy  $E_\theta(s) = E_\theta(\mathbf{x}, y) = -f_\theta(\mathbf{x})[y]$ .
- ▶ Using  $E_\theta(\mathbf{x}, y)$  we can define  $p_\theta(\mathbf{x})$ :

$$p_\theta(\mathbf{x}) = \sum_y p_\theta(\mathbf{x}, y) = \frac{1}{Z_\theta} \sum_y \exp(f_\theta(\mathbf{x})[y]) \quad (4)$$

- ▶ Using  $p_\theta(\mathbf{x})$  we can define  $E_\theta(\mathbf{x})$ :

$$E_\theta(\mathbf{x}) = -\log \sum_y \exp(f_\theta(\mathbf{x})[y]) \quad (5)$$

## Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as  $E_\theta(\mathbf{x})$
- ▶ Let  $f_\theta(\mathbf{x})$  be our neural network.
- ▶ Let  $f_\theta(\mathbf{x})[y]$  be the  $y$ -th logit (i.e. logit value for class  $y$ ).
- ▶ Let our examples be  $s = (\mathbf{x}, y)$
- ▶ We define energy  $E_\theta(s) = E_\theta(\mathbf{x}, y) = -f_\theta(\mathbf{x})[y]$ .
- ▶ Using  $E_\theta(\mathbf{x}, y)$  we can define  $p_\theta(\mathbf{x})$ :

$$p_\theta(\mathbf{x}) = \sum_y p_\theta(\mathbf{x}, y) = \frac{1}{Z_\theta} \sum_y \exp(f_\theta(\mathbf{x})[y]) \quad (4)$$

- ▶ Using  $p_\theta(\mathbf{x})$  we can define  $E_\theta(\mathbf{x})$ :

$$E_\theta(\mathbf{x}) = -\log \sum_y \exp(f_\theta(\mathbf{x})[y]) \quad (5)$$

- ▶ Higher the logits — lower the energy of  $\mathbf{x}$ .

## Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as  $E_{\theta}(x)$
- ▶ Let  $f_{\theta}(x)$  be our neural network.
- ▶ Let  $f_{\theta}(x)[y]$  be the  $y$ -th logit (i.e. logit value for class  $y$ ).
- ▶ Let our examples be  $s = (x, y)$
- ▶ We define energy  $E_{\theta}(s) = E_{\theta}(x, y) = -f_{\theta}(x)[y]$ .
- ▶ Using  $E_{\theta}(x, y)$  we can define  $p_{\theta}(x)$ :

$$p_{\theta}(\mathbf{x}) = \sum_y p_{\theta}(\mathbf{x}, y) = \frac{1}{Z_{\theta}} \sum_y \exp(f_{\theta}(\mathbf{x})[y]) \quad (4)$$

- ▶ Using  $p_{\theta}(x)$  we can define  $E_{\theta}(x)$ :

$$E_{\theta}(\mathbf{x}) = -\log \sum_y \exp(f_{\theta}(\mathbf{x})[y]) \quad (5)$$

- ▶ Higher the logits — lower the energy of  $x$ .
- ▶ Our final loss looks like:

$$\mathcal{L}(x) = \log p(x, y) = \underbrace{\log p(y|x)}_{\text{classification loss}} + \underbrace{\log p(x)}_{\text{generative loss}} \quad (6)$$

## Results and discussion

## Results and discussion

- ▶ Disclaimer: results are really good.



## Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:

## Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
  - ▶ has good classification accuracy

## Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
  - ▶ has good classification accuracy
  - ▶ has good IS/FID scores (i.e. has good samples)

# Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
  - ▶ has good classification accuracy
  - ▶ has good IS/FID scores (i.e. has good samples)
  - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)

# Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
  - ▶ has good classification accuracy
  - ▶ has good IS/FID scores (i.e. has good samples)
  - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
  - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)

# Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
  - ▶ has good classification accuracy
  - ▶ has good IS/FID scores (i.e. has good samples)
  - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
  - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)
  - ▶ is robust to adversarial attacks

# Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
  - ▶ has good classification accuracy
  - ▶ has good IS/FID scores (i.e. has good samples)
  - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
  - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)
  - ▶ is robust to adversarial attacks
  - ▶ ...and all of these at the same time!

# Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
  - ▶ has good classification accuracy
  - ▶ has good IS/FID scores (i.e. has good samples)
  - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
  - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)
  - ▶ is robust to adversarial attacks
  - ▶ ...and all of these at the same time!
- ▶ A huge limitation is that because of SGLD the training is unstable and the model is hard to scale.



# Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
  - ▶ has good classification accuracy
  - ▶ has good IS/FID scores (i.e. has good samples)
  - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
  - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)
  - ▶ is robust to adversarial attacks
  - ▶ ...and all of these at the same time!
- ▶ A huge limitation is that because of SGLD the training is unstable and the model is hard to scale.
- ▶ A big limitation: we cannot compute the loss value!!!

# Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
  - ▶ has good classification accuracy
  - ▶ has good IS/FID scores (i.e. has good samples)
  - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
  - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)
  - ▶ is robust to adversarial attacks
  - ▶ ...and all of these at the same time!
- ▶ A huge limitation is that because of SGLD the training is unstable and the model is hard to scale.
- ▶ A big limitation: we cannot compute the loss value!!!
- ▶ An approach was coined Joint Energy based Model (JEM) since we model  $(x, y)$  simultaneously.