

XLNet: Generalized Autoregressive Pretraining for Language Understanding¹

June 21, 2019



¹XLNet: Generalized Autoregressive Pretraining for Language Understanding by Yang et al.



What problems³ BERT has?

²That's why we also predict non-mask tokens during pretraining.

³besides obesity



What problems³ BERT has?

1. It predicts MASK tokens independently, i.e. $p(\tilde{\mathbf{x}}|\hat{\mathbf{x}}) = \prod_{i=1}^T p(\tilde{x}_i|\hat{\mathbf{x}})$, where $\tilde{\mathbf{x}}, \hat{\mathbf{x}}$ are masked and unmasked subsequences of \mathbf{x} . It's a big deal, because in reality:

$$p(\text{New, York}|\hat{\mathbf{x}}) = p(\text{New}|\hat{\mathbf{x}}) \cdot p(\text{York}|\text{New}, \hat{\mathbf{x}}) \neq p(\text{New}|\hat{\mathbf{x}}) \cdot p(\text{York}|\hat{\mathbf{x}})$$

²That's why we also predict non-mask tokens during pretraining.

³besides obesity



What problems³ BERT has?

1. It predicts MASK tokens independently, i.e. $p(\tilde{\mathbf{x}}|\hat{\mathbf{x}}) = \prod_{i=1}^T p(\tilde{x}_i|\hat{\mathbf{x}})$, where $\tilde{\mathbf{x}}, \hat{\mathbf{x}}$ are masked and unmasked subsequences of \mathbf{x} . It's a big deal, because in reality:

$$p(\text{New, York}|\hat{\mathbf{x}}) = p(\text{New}|\hat{\mathbf{x}}) \cdot p(\text{York}|\text{New}, \hat{\mathbf{x}}) \neq p(\text{New}|\hat{\mathbf{x}}) \cdot p(\text{York}|\hat{\mathbf{x}})$$

2. In test time we do not have MASK tokens, which is train-test discrepancy!²

²That's why we also predict non-mask tokens during pretraining.

³besides obesity



What problems³ BERT has?

1. It predicts MASK tokens independently, i.e. $p(\tilde{\mathbf{x}}|\hat{\mathbf{x}}) = \prod_{i=1}^T p(\tilde{x}_i|\hat{\mathbf{x}})$, where $\tilde{\mathbf{x}}, \hat{\mathbf{x}}$ are masked and unmasked subsequences of \mathbf{x} . It's a big deal, because in reality:

$$p(\text{New, York}|\hat{\mathbf{x}}) = p(\text{New}|\hat{\mathbf{x}}) \cdot p(\text{York}|\text{New}, \hat{\mathbf{x}}) \neq p(\text{New}|\hat{\mathbf{x}}) \cdot p(\text{York}|\hat{\mathbf{x}})$$

2. In test time we do not have MASK tokens, which is train-test discrepancy!²
3. Using large contexts is very costly $O(n^2)$.

²That's why we also predict non-mask tokens during pretraining.

³besides obesity



What problems language models have?

⁴or bidirectionally with simple concatenation, like ELMO



What problems language models have?

- ▶ We can train them either forward or backward⁴

⁴or bidirectionally with simple concatenation, like ELMO



What problems language models have?

- ▶ We can train them either forward or backward⁴
- ▶ \implies model is not trained to use the whole context

⁴or bidirectionally with simple concatenation, like ELMO



What problems language models have?

- ▶ We can train them either forward or backward⁴
- ▶ \implies model is not trained to use the whole context
- ▶ \implies it's bad, because such an information is very useful for some tasks

⁴or bidirectionally with simple concatenation, like ELMO



XLNet to the rescue



XLNet to the rescue

- ▶ Let \mathcal{Z}_T be a set of all possible permutations of a sequence of length T (so it has $T!$ elements).



XLNet to the rescue

- ▶ Let \mathcal{Z}_T be a set of all possible permutations of a sequence of length T (so it has $T!$ elements).
- ▶ Note that we can decompose $p(\mathbf{x})$ via chain rule in an arbitrary order:

$$\begin{aligned} p(\mathbf{x}) &= p(x_1, x_2, x_3) \\ &= p(x_1)p(x_2|x_1)p(x_3|x_1, x_2) \\ &= p(x_2)p(x_3|x_2)p(x_1|x_2, x_3) \\ &= \dots \end{aligned}$$



XLNet to the rescue

- ▶ Let \mathcal{Z}_T be a set of all possible permutations of a sequence of length T (so it has $T!$ elements).
- ▶ Note that we can decompose $p(\mathbf{x})$ via chain rule in an arbitrary order:

$$\begin{aligned} p(\mathbf{x}) &= p(x_1, x_2, x_3) \\ &= p(x_1)p(x_2|x_1)p(x_3|x_1, x_2) \\ &= p(x_2)p(x_3|x_2)p(x_1|x_2, x_3) \\ &= \dots \end{aligned}$$

- ▶ Which order is the best for our task? Forward? Backward?



XLNet to the rescue

- ▶ Let \mathcal{Z}_T be a set of all possible permutations of a sequence of length T (so it has $T!$ elements).
- ▶ Note that we can decompose $p(\mathbf{x})$ via chain rule in an arbitrary order:

$$\begin{aligned} p(\mathbf{x}) &= p(x_1, x_2, x_3) \\ &= p(x_1)p(x_2|x_1)p(x_3|x_1, x_2) \\ &= p(x_2)p(x_3|x_2)p(x_1|x_2, x_3) \\ &= \dots \end{aligned}$$

- ▶ Which order is the best for our task? Forward? Backward?
- ▶ All of them:

$$\mathcal{L}_{\text{XLNet}}(\theta) = - \mathbb{E}_{\mathbf{z} \sim \mathcal{Z}_T} [\log p_{\theta}(\mathbf{x})] = - \mathbb{E}_{\mathbf{z} \sim \mathcal{Z}_T} \left[\sum_{t=1}^T \log p_{\theta}(x_{z_t} | \mathbf{x}_{\mathbf{z}_{<t}}) \right]$$



XLNet to the rescue

- ▶ Let \mathcal{Z}_T be a set of all possible permutations of a sequence of length T (so it has $T!$ elements).
- ▶ Note that we can decompose $p(\mathbf{x})$ via chain rule in an arbitrary order:

$$\begin{aligned} p(\mathbf{x}) &= p(x_1, x_2, x_3) \\ &= p(x_1)p(x_2|x_1)p(x_3|x_1, x_2) \\ &= p(x_2)p(x_3|x_2)p(x_1|x_2, x_3) \\ &= \dots \end{aligned}$$

- ▶ Which order is the best for our task? Forward? Backward?
- ▶ All of them:

$$\mathcal{L}_{\text{XLNet}}(\theta) = - \mathbb{E}_{\mathbf{z} \sim \mathcal{Z}_T} [\log p_{\theta}(\mathbf{x})] = - \mathbb{E}_{\mathbf{z} \sim \mathcal{Z}_T} \left[\sum_{t=1}^T \log p_{\theta}(x_{z_t} | \mathbf{x}_{\mathbf{z}_{<t}}) \right]$$

- ▶ Is this an upper bound for a true loss? Yes:

$$\mathbb{E}_{\mathbf{z}} [\log p(\mathbf{x}|\mathbf{z})] \leq \log \mathbb{E}_{\mathbf{z}} [p(\mathbf{x}|\mathbf{z})] = \log p(\mathbf{x})$$



How does it look like in practice (1/3)?



How does it look like in practice (1/3)?

- ▶ It's straight-forward how to decode the sequence in the required order z : just use proper masks



How does it look like in practice (1/3)?

- It's straight-forward how to decode the sequence in the required order z : just use proper masks




Figure: Example of prediction token x_3 for different permutation orders z .



How does it look like in practice (2/3)?



How does it look like in practice (2/3)?

- ▶ But we cannot predict “next” token like we do in language models!



How does it look like in practice (2/3)?

- ▶ But we cannot predict “next” token like we do in language models!
- ▶ Because we have many possible permutations, the same hidden state will be used to predict different tokens:

$$\left. \begin{array}{l} \mathbf{z}^{(1)} = (3, 4, 2, 1, 5) \\ \mathbf{z}^{(2)} = (3, 4, 2, 5, 1) \end{array} \right\} \Rightarrow \begin{cases} p(x_1 = s | x_3, x_4, x_2) = \frac{\exp(e(x)^\top h_\theta(\mathbf{x}_{z < t}))}{\sum_{x'} \exp(e(x')^\top h_\theta(\mathbf{x}_{z < t}))} \\ p(x_5 = s | x_3, x_4, x_2) = \frac{\exp(e(x)^\top h_\theta(\mathbf{x}_{z < t}))}{\sum_{x'} \exp(e(x')^\top h_\theta(\mathbf{x}_{z < t}))} \end{cases}$$



How does it look like in practice (2/3)?

- ▶ But we cannot predict “next” token like we do in language models!
- ▶ Because we have many possible permutations, the same hidden state will be used to predict different tokens:

$$\left. \begin{array}{l} \mathbf{z}^{(1)} = (3, 4, 2, 1, 5) \\ \mathbf{z}^{(2)} = (3, 4, 2, 5, 1) \end{array} \right\} \Rightarrow \begin{cases} p(x_1 = s | x_3, x_4, x_2) = \frac{\exp(e(x)^\top h_\theta(\mathbf{x}_{z < t}))}{\sum_{x'} \exp(e(x')^\top h_\theta(\mathbf{x}_{z < t}))} \\ p(x_5 = s | x_3, x_4, x_2) = \frac{\exp(e(x)^\top h_\theta(\mathbf{x}_{z < t}))}{\sum_{x'} \exp(e(x')^\top h_\theta(\mathbf{x}_{z < t}))} \end{cases}$$

- ▶ Solution?



How does it look like in practice (2/3)?

- ▶ But we cannot predict “next” token like we do in language models!
- ▶ Because we have many possible permutations, the same hidden state will be used to predict different tokens:

$$\left. \begin{array}{l} \mathbf{z}^{(1)} = (3, 4, 2, 1, 5) \\ \mathbf{z}^{(2)} = (3, 4, 2, 5, 1) \end{array} \right\} \Rightarrow \begin{cases} p(x_1 = s | x_3, x_4, x_2) = \frac{\exp(e(x)^\top h_\theta(\mathbf{x}_{z < t}))}{\sum_{x'} \exp(e(x')^\top h_\theta(\mathbf{x}_{z < t}))} \\ p(x_5 = s | x_3, x_4, x_2) = \frac{\exp(e(x)^\top h_\theta(\mathbf{x}_{z < t}))}{\sum_{x'} \exp(e(x')^\top h_\theta(\mathbf{x}_{z < t}))} \end{cases}$$

- ▶ Solution? Predict token from additional [MASK] embedding.



How does it look like in practice (3/3)?




Figure: Two-stream self-attention (copy pasted for intensive hand waving).



Training details



Training details

- ▶ For each sentence in a batch take a random permutation $\mathbf{z} \in \mathcal{Z}_T$ for decoding.



Training details

- ▶ For each sentence in a batch take a random permutation $\mathbf{z} \in \mathcal{Z}_T$ for decoding.
- ▶ Initialize [MASK] tokens with trained embeddings.



Training details

- ▶ For each sentence in a batch take a random permutation $\mathbf{z} \in \mathcal{Z}_T$ for decoding.
- ▶ Initialize [MASK] tokens with trained embeddings.
- ▶ Use forward/backward pass for each half of the batch (explained later).



Training details

- ▶ For each sentence in a batch take a random permutation $\mathbf{z} \in \mathcal{Z}_T$ for decoding.
- ▶ Initialize [MASK] tokens with trained embeddings.
- ▶ Use forward/backward pass for each half of the batch (explained later).
- ▶ Mask around 15% of tokens (because otherwise it will be hard to train).



Training details

- ▶ For each sentence in a batch take a random permutation $\mathbf{z} \in \mathcal{Z}_T$ for decoding.
- ▶ Initialize [MASK] tokens with trained embeddings.
- ▶ Use forward/backward pass for each half of the batch (explained later).
- ▶ Mask around 15% of tokens (because otherwise it will be hard to train).
- ▶ We use [A, SEP, B, SEP, CLS] like in BERT.



Training details

- ▶ For each sentence in a batch take a random permutation $\mathbf{z} \in \mathcal{Z}_T$ for decoding.
- ▶ Initialize [MASK] tokens with trained embeddings.
- ▶ Use forward/backward pass for each half of the batch (explained later).
- ▶ Mask around 15% of tokens (because otherwise it will be hard to train).
- ▶ We use [A, SEP, B, SEP, CLS] like in BERT.
- ▶ We use relative segment encoding: $a_{ij}^{\text{final}} = a_{ij} + (\mathbf{q}_i + \mathbf{b})^\top \mathbf{s}_{ij}$, where \mathbf{q}_i is our query, \mathbf{b} is a learned head-specific vector, $\mathbf{s}_{ij} = \mathbf{s}_-$ or \mathbf{s}_+ if i is in the same context as j or not.



Relative positional encoding

(from Transformer-XL)



Relative positional encoding

(from Transformer-XL)

- ▶ Key idea: make information about position be dependent only on relative positions between objects, regardless where they are placed in the sequence
- ▶ Why do we need this?



Relative positional encoding

(from Transformer-XL)

- ▶ Key idea: make information about position be dependent only on relative positions between objects, regardless where they are placed in the sequence
- ▶ Why do we need this? To attend on memory without much trouble (memory usually has the same positional embeddings).



Relative positional encoding

(from Transformer-XL)

- ▶ Key idea: make information about position be dependent only on relative positions between objects, regardless where they are placed in the sequence
- ▶ Why do we need this? To attend on memory without much trouble (memory usually has the same positional embeddings).
- ▶ Imagine we have hidden states $\mathbf{e}_i, \mathbf{e}_j$. We add positional embeddings to them: $\mathbf{h}_i = \mathbf{e}_i + \mathbf{p}_i$ and $\mathbf{h}_j = \mathbf{e}_j + \mathbf{p}_j$



Relative positional encoding

(from Transformer-XL)

- ▶ Key idea: make information about position be dependent only on relative positions between objects, regardless where they are placed in the sequence
- ▶ Why do we need this? To attend on memory without much trouble (memory usually has the same positional embeddings).
- ▶ Imagine we have hidden states $\mathbf{e}_i, \mathbf{e}_j$. We add positional embeddings to them: $\mathbf{h}_i = \mathbf{e}_i + \mathbf{p}_i$ and $\mathbf{h}_j = \mathbf{e}_j + \mathbf{p}_j$

Then normal attention of \mathbf{h}_i on \mathbf{h}_j is computed as

$$\begin{aligned}\text{Attn}(\mathbf{h}_i, \mathbf{h}_j) &= \langle W_q \mathbf{h}_i, W_k \mathbf{h}_j \rangle = \langle W_q(\mathbf{e}_i + \mathbf{p}_i), W_k(\mathbf{e}_j + \mathbf{p}_j) \rangle \\ &= \mathbf{e}_i^\top W_q^\top W_k \mathbf{e}_j + \mathbf{e}_i^\top W_q^\top W_k \mathbf{p}_j + \mathbf{p}_i^\top W_q^\top W_k \mathbf{e}_j + \mathbf{p}_i^\top W_q^\top W_k \mathbf{p}_j\end{aligned}$$

Relative positional encoding just changes attention mechanism to:

$$\text{Attn}^{\text{rel}}(\mathbf{h}_i, \mathbf{h}_j) = \mathbf{e}_i^\top W_q^\top W_k^e \mathbf{e}_j + \mathbf{e}_i^\top W_q^\top W_k^r \mathbf{p}_{i-j} + \mathbf{u}^\top W_k^e \mathbf{e}_j + \mathbf{v}^\top W_k^r \mathbf{p}_{i-j}$$



Adding memory (aka “recurrence mechanism”)

(from Transformer-XL)

- ▶ When we have really large sequence, we can process it segment by segment
- ▶ When previous segment is processed, put it into cache and attend as embeddings like we do in machine translation



Quiz time!

⁵And authors said that the model still underfit after 500K steps (but performance on downstream tasks didn't improve)



Quiz time!

- ▶ How many TPUs v3 were used?

⁵And authors said that the model still underfit after 500K steps (but performance on downstream tasks didn't improve)



Quiz time!

- ▶ How many TPUs v3 were used? — 512

⁵And authors said that the model still underfit after 500K steps (but performance on downstream tasks didn't improve)



Quiz time!

- ▶ How many TPUs v3 were used? — 512
- ▶ How long did the thing trained?

⁵And authors said that the model still underfit after 500K steps (but performance on downstream tasks didn't improve)



Quiz time!

- ▶ How many TPUs v3 were used? — 512
- ▶ How long did the thing trained? — 2.5 days⁵

⁵And authors said that the model still underfit after 500K steps (but performance on downstream tasks didn't improve)



Quiz time!

- ▶ How many TPUs v3 were used? — 512
- ▶ How long did the thing trained? — 2.5 days⁵
- ▶ What was the batch size?

⁵And authors said that the model still underfit after 500K steps (but performance on downstream tasks didn't improve)



Quiz time!

- ▶ How many TPUs v3 were used? — 512
- ▶ How long did the thing trained? — 2.5 days⁵
- ▶ What was the batch size? — 2048

⁵And authors said that the model still underfit after 500K steps (but performance on downstream tasks didn't improve)



Quiz time!

- ▶ How many TPUs v3 were used? — 512
- ▶ How long did the thing trained? — 2.5 days⁵
- ▶ What was the batch size? — 2048
- ▶ What optimizer did they use?

⁵And authors said that the model still underfit after 500K steps (but performance on downstream tasks didn't improve)



Quiz time!

- ▶ How many TPUs v3 were used? — 512
- ▶ How long did the thing trained? — 2.5 days⁵
- ▶ What was the batch size? — 2048
- ▶ What optimizer did they use? — Adam

⁵And authors said that the model still underfit after 500K steps (but performance on downstream tasks didn't improve)



TODO

I didn't have enough time to copy-paste tables from scores and ablation study, so let's open the paper and see them manually.



Things I didn't get

- ▶ Span-based prediction?

