

Your Classifier is Secretly an Energy Based Model and You Should Treat it Like One¹

January 30, 2020

¹Will Grathwohl et al., ICLR 2020

What is an Energy Based Model (EBM)?

What is an Energy Based Model (EBM)?

Any pdf $p_{\theta}(x)$ can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

What is an Energy Based Model (EBM)?

Any pdf $p_{\theta}(\mathbf{x})$ can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

where Z_{θ} is a normalizing constant:

$$Z_{\theta} = \int_{\mathbf{x}} \exp(-E_{\theta}(\mathbf{x})) d\mathbf{x}$$

What is an Energy Based Model (EBM)?

Any pdf $p_{\theta}(\mathbf{x})$ can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

where Z_{θ} is a normalizing constant:

$$Z_{\theta} = \int_{\mathbf{x}} \exp(-E_{\theta}(\mathbf{x})) d\mathbf{x}$$

- This parametrization allows us to forget about $p_{\theta}(\mathbf{x})$ and work with $E_{\theta}(\mathbf{x})$

What is an Energy Based Model (EBM)?

Any pdf $p_{\theta}(x)$ can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

where Z_{θ} is a normalizing constant:

$$Z_{\theta} = \int_{\mathbf{x}} \exp(-E_{\theta}(\mathbf{x})) d\mathbf{x}$$

- ▶ This parametrization allows us to forget about $p_{\theta}(x)$ and work with $E_{\theta}(x)$
- ▶ Function $E_{\theta}(x)$ is an *energy function* (hence the name — EBM)

What is an Energy Based Model (EBM)?

Any pdf $p_{\theta}(\mathbf{x})$ can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

where Z_{θ} is a normalizing constant:

$$Z_{\theta} = \int_{\mathbf{x}} \exp(-E_{\theta}(\mathbf{x})) d\mathbf{x}$$

- ▶ This parametrization allows us to forget about $p_{\theta}(\mathbf{x})$ and work with $E_{\theta}(\mathbf{x})$
- ▶ Function $E_{\theta}(\mathbf{x})$ is an *energy function* (hence the name — EBM)
- ▶ Energy functions are *easier* to work with: you do not have any restrictions on $E_{\theta}(\mathbf{x})$ ($p_{\theta}(\mathbf{x})$ is nonnegative and integrates to 1).

What is an Energy Based Model (EBM)?

Any pdf $p_{\theta}(x)$ can be written down as:

$$p_{\theta}(\mathbf{x}) = \frac{\exp(-E_{\theta}(\mathbf{x}))}{Z_{\theta}} \quad (1)$$

where Z_{θ} is a normalizing constant:

$$Z_{\theta} = \int_{\mathbf{x}} \exp(-E_{\theta}(\mathbf{x})) d\mathbf{x}$$

- ▶ This parametrization allows us to forget about $p_{\theta}(x)$ and work with $E_{\theta}(x)$
- ▶ Function $E_{\theta}(x)$ is an *energy function* (hence the name — EBM)
- ▶ Energy functions are *easier* to work with: you do not have any restrictions on $E_{\theta}(x)$ ($p_{\theta}(x)$ is nonnegative and integrates to 1).
- ▶ Energy functions are *harder* to work with: Z_{θ} is hard or impossible to compute, so we can't optimize EBM for θ

How to train EBM

How to train EBMs

- ▶ We perform standard MLE: maximize $\log p_{\theta}(x_i)$ at our points x_i .

How to train EBMs

- ▶ We perform standard MLE: maximize $\log p_{\theta}(x_i)$ at our points x_i .
- ▶ By optimizing $\log p_{\theta}(x)$ we also optimize $E_{\theta}(x)$.

How to train EBMs

- ▶ We perform standard MLE: maximize $\log p_\theta(x_i)$ at our points x_i .
- ▶ By optimizing $\log p_\theta(x)$ we also optimize $E_\theta(x)$.
- ▶ We can't compute $\log p_\theta(x)$, but we can (approximately) compute its log-derivative via:

$$\frac{\partial \log p_\theta(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_\theta(\mathbf{x}')} \left[\frac{\partial E_\theta(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_\theta(\mathbf{x})}{\partial \theta} \quad (2)$$

How to train EBMs

- ▶ We perform standard MLE: maximize $\log p_\theta(x_i)$ at our points x_i .
- ▶ By optimizing $\log p_\theta(x)$ we also optimize $E_\theta(x)$.
- ▶ We can't compute $\log p_\theta(x)$, but we can (approximately) compute its log-derivative via:

$$\frac{\partial \log p_\theta(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_\theta(\mathbf{x}')} \left[\frac{\partial E_\theta(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_\theta(\mathbf{x})}{\partial \theta} \quad (2)$$

- ▶ Proof: follows directly from the definition.

How to train EBMs

- ▶ We perform standard MLE: maximize $\log p_\theta(x_i)$ at our points x_i .
- ▶ By optimizing $\log p_\theta(x)$ we also optimize $E_\theta(x)$.
- ▶ We can't compute $\log p_\theta(x)$, but we can (approximately) compute its log-derivative via:

$$\frac{\partial \log p_\theta(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_\theta(\mathbf{x}')} \left[\frac{\partial E_\theta(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_\theta(\mathbf{x})}{\partial \theta} \quad (2)$$

- ▶ Proof: follows directly from the definition.
- ▶ But a new problem arises: how to compute expectation?

How to train EBMs

- ▶ We perform standard MLE: maximize $\log p_\theta(x_i)$ at our points x_i .
- ▶ By optimizing $\log p_\theta(x)$ we also optimize $E_\theta(x)$.
- ▶ We can't compute $\log p_\theta(x)$, but we can (approximately) compute its log-derivative via:

$$\frac{\partial \log p_\theta(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_\theta(\mathbf{x}')} \left[\frac{\partial E_\theta(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_\theta(\mathbf{x})}{\partial \theta} \quad (2)$$

- ▶ Proof: follows directly from the definition.
- ▶ But a new problem arises: how to compute expectation?
- ▶ Answer: we can't do that directly, so let's use SGLD sampling.

Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:

Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:

- ▶ Imagine we have a “magic” function $p_\theta(x)$ that takes an input x and tells us its density.

Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:

- ▶ Imagine we have a “magic” function $p_{\theta}(x)$ that takes an input x and tells us its density.
- ▶ Unfortunately, we cannot sample new x -s from it directly, i.e. $p_{\theta}(x)$ does not support such operations.

Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:

- ▶ Imagine we have a “magic” function $p_{\theta}(x)$ that takes an input x and tells us its density.
- ▶ Unfortunately, we cannot sample new x -s from it directly, i.e. $p_{\theta}(x)$ does not support such operations.
- ▶ But we really want to sample from it! What should we do?

Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:

- ▶ Imagine we have a “magic” function $p_{\theta}(x)$ that takes an input x and tells us its density.
- ▶ Unfortunately, we cannot sample new x -s from it directly, i.e. $p_{\theta}(x)$ does not support such operations.
- ▶ But we really want to sample from it! What should we do?
- ▶ SGLD is a method to sample from such functions.

Stochastic Gradient Langevin Dynamics (SGLD)

Motivation:

- ▶ Imagine we have a “magic” function $p_{\theta}(x)$ that takes an input x and tells us its density.
- ▶ Unfortunately, we cannot sample new x -s from it directly, i.e. $p_{\theta}(x)$ does not support such operations.
- ▶ But we really want to sample from it! What should we do?
- ▶ SGLD is a method to sample from such functions.
- ▶ What is cool about SGLD is that it allows to use *unnormalized* density $\tilde{p}(x)$ (a very important property in our case!).

Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in a (very) few words:

Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in a (very) few words:

1. Start from any random point x_0 .

Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in a (very) few words:

1. Start from any random point x_0 .
2. Compute the gradient of $\nabla \log p_\theta(x_0)$.

Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in a (very) few words:

1. Start from any random point x_0 .
2. Compute the gradient of $\nabla \log p_\theta(x_0)$.
3. Perform a small step in that direction.

Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in a (very) few words:

1. Start from any random point x_0 .
2. Compute the gradient of $\nabla \log p_\theta(x_0)$.
3. Perform a small step in that direction.
4. Add a little bit of noise.

Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in a (very) few words:

1. Start from any random point x_0 .
2. Compute the gradient of $\nabla \log p_\theta(x_0)$.
3. Perform a small step in that direction.
4. Add a little bit of noise.
5. Obtain x_{t+1} . Accept it if:

$$\frac{p(x_t|x_{t+1})p(x_t)}{p(x_{t+1}|x_t)p(x_{t+1})} < u, u \sim \mathcal{U}[0, 1] \quad (3)$$

Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in a (very) few words:

1. Start from any random point \mathbf{x}_0 .
2. Compute the gradient of $\nabla \log p_\theta(\mathbf{x}_0)$.
3. Perform a small step in that direction.
4. Add a little bit of noise.
5. Obtain \mathbf{x}_{t+1} . Accept it if:

$$\frac{p(\mathbf{x}_t | \mathbf{x}_{t+1}) p(\mathbf{x}_t)}{p(\mathbf{x}_{t+1} | \mathbf{x}_t) p(\mathbf{x}_{t+1})} < u, u \sim \mathcal{U}[0, 1] \quad (3)$$

In other words, run the following recurrence a lot of times:

$$\mathbf{x}_0 \sim p_0(\mathbf{x}), \quad \mathbf{x}_{i+1} = \mathbf{x}_i - \frac{\alpha}{2} \frac{\partial E_\theta(\mathbf{x}_i)}{\partial \mathbf{x}_i} + \epsilon, \quad \epsilon \sim \mathcal{N}(0, \alpha) \quad (4)$$

Stochastic Gradient Langevin Dynamics (SGLD)

SGLD in a (very) few words:

1. Start from any random point x_0 .
2. Compute the gradient of $\nabla \log p_\theta(x_0)$.
3. Perform a small step in that direction.
4. Add a little bit of noise.
5. Obtain x_{t+1} . Accept it if:

$$\frac{p(x_t|x_{t+1})p(x_t)}{p(x_{t+1}|x_t)p(x_{t+1})} < u, u \sim \mathcal{U}[0, 1] \quad (3)$$

In other words, run the following recurrence a lot of times:

$$\mathbf{x}_0 \sim p_0(\mathbf{x}), \quad \mathbf{x}_{i+1} = \mathbf{x}_i - \frac{\alpha}{2} \frac{\partial E_\theta(\mathbf{x}_i)}{\partial \mathbf{x}_i} + \epsilon, \quad \epsilon \sim \mathcal{N}(0, \alpha) \quad (4)$$

Justification: if your model and your choice of α are “good” (in some sense), then after infinite amount of steps your samples will be “good” (in some sense).

Ok, how to treat a classifier as an EBM?

Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as $E_{\theta}(x)$

Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as $E_\theta(x)$
- ▶ Let $f_\theta(x)$ be our neural network.

Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as $E_\theta(x)$
- ▶ Let $f_\theta(x)$ be our neural network.
- ▶ Let $f_\theta(x)[y]$ be the y -th logit (i.e. logit value for class y).

Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as $E_{\theta}(x)$
- ▶ Let $f_{\theta}(x)$ be our neural network.
- ▶ Let $f_{\theta}(x)[y]$ be the y -th logit (i.e. logit value for class y).
- ▶ Let our examples be $s = (x, y)$

Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as $E_\theta(x)$
- ▶ Let $f_\theta(x)$ be our neural network.
- ▶ Let $f_\theta(x)[y]$ be the y -th logit (i.e. logit value for class y).
- ▶ Let our examples be $s = (x, y)$
- ▶ We define energy $E_\theta(s) = E_\theta(x, y) = -f_\theta(x)[y]$.

Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as $E_\theta(\mathbf{x})$
- ▶ Let $f_\theta(\mathbf{x})$ be our neural network.
- ▶ Let $f_\theta(\mathbf{x})[y]$ be the y -th logit (i.e. logit value for class y).
- ▶ Let our examples be $s = (\mathbf{x}, y)$
- ▶ We define energy $E_\theta(s) = E_\theta(\mathbf{x}, y) = -f_\theta(\mathbf{x})[y]$.
- ▶ Using $E_\theta(\mathbf{x}, y)$ we can define $p_\theta(\mathbf{x})$:

$$p_\theta(\mathbf{x}) = \sum_y p_\theta(\mathbf{x}, y) = \frac{1}{Z_\theta} \sum_y \exp(f_\theta(\mathbf{x})[y]) \quad (5)$$

Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as $E_\theta(\mathbf{x})$
- ▶ Let $f_\theta(\mathbf{x})$ be our neural network.
- ▶ Let $f_\theta(\mathbf{x})[y]$ be the y -th logit (i.e. logit value for class y).
- ▶ Let our examples be $s = (\mathbf{x}, y)$
- ▶ We define energy $E_\theta(s) = E_\theta(\mathbf{x}, y) = -f_\theta(\mathbf{x})[y]$.
- ▶ Using $E_\theta(\mathbf{x}, y)$ we can define $p_\theta(\mathbf{x})$:

$$p_\theta(\mathbf{x}) = \sum_y p_\theta(\mathbf{x}, y) = \frac{1}{Z_\theta} \sum_y \exp(f_\theta(\mathbf{x})[y]) \quad (5)$$

- ▶ Using $p_\theta(\mathbf{x})$ we can define $E_\theta(\mathbf{x})$:

$$E_\theta(\mathbf{x}) = -\log \sum_y \exp(f_\theta(\mathbf{x})[y]) \quad (6)$$

Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as $E_\theta(\mathbf{x})$
- ▶ Let $f_\theta(\mathbf{x})$ be our neural network.
- ▶ Let $f_\theta(\mathbf{x})[y]$ be the y -th logit (i.e. logit value for class y).
- ▶ Let our examples be $s = (\mathbf{x}, y)$
- ▶ We define energy $E_\theta(s) = E_\theta(\mathbf{x}, y) = -f_\theta(\mathbf{x})[y]$.
- ▶ Using $E_\theta(\mathbf{x}, y)$ we can define $p_\theta(\mathbf{x})$:

$$p_\theta(\mathbf{x}) = \sum_y p_\theta(\mathbf{x}, y) = \frac{1}{Z_\theta} \sum_y \exp(f_\theta(\mathbf{x})[y]) \quad (5)$$

- ▶ Using $p_\theta(\mathbf{x})$ we can define $E_\theta(\mathbf{x})$:

$$E_\theta(\mathbf{x}) = -\log \sum_y \exp(f_\theta(\mathbf{x})[y]) \quad (6)$$

- ▶ Higher the logits — lower the energy of \mathbf{x} .

Ok, how to treat a classifier as an EBM?

- ▶ Remember that *any* function can be used as $E_{\theta}(x)$
- ▶ Let $f_{\theta}(x)$ be our neural network.
- ▶ Let $f_{\theta}(x)[y]$ be the y -th logit (i.e. logit value for class y).
- ▶ Let our examples be $s = (x, y)$
- ▶ We define energy $E_{\theta}(s) = E_{\theta}(x, y) = -f_{\theta}(x)[y]$.
- ▶ Using $E_{\theta}(x, y)$ we can define $p_{\theta}(x)$:

$$p_{\theta}(\mathbf{x}) = \sum_y p_{\theta}(\mathbf{x}, y) = \frac{1}{Z_{\theta}} \sum_y \exp(f_{\theta}(\mathbf{x})[y]) \quad (5)$$

- ▶ Using $p_{\theta}(x)$ we can define $E_{\theta}(x)$:

$$E_{\theta}(\mathbf{x}) = -\log \sum_y \exp(f_{\theta}(\mathbf{x})[y]) \quad (6)$$

- ▶ Higher the logits — lower the energy of x .
- ▶ Our final loss looks like:

$$\mathcal{L}(x) = \log p(x, y) = \underbrace{\log p(y|x)}_{\text{classification loss}} + \underbrace{\log p(x)}_{\text{generative loss}} \quad (7)$$

Is JEM using adversarial training?!

Is JEM using adversarial training?!

- Let's take a closer look to the gradient of the part of the loss:

$$\frac{\partial \log p_{\theta}(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_{\theta}(\mathbf{x}')} \left[\frac{\partial E_{\theta}(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_{\theta}(\mathbf{x})}{\partial \theta} \quad (8)$$

Is JEM using adversarial training?!

- ▶ Let's take a closer look to the gradient of the part of the loss:

$$\frac{\partial \log p_{\theta}(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_{\theta}(\mathbf{x}')} \left[\frac{\partial E_{\theta}(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_{\theta}(\mathbf{x})}{\partial \theta} \quad (8)$$

- ▶ If we use a single sample to approximate expectation and compute the gradient across the dataset our gradient we'll look like:

$$\frac{\partial \log p_{\theta}(\mathbf{X})}{\partial \theta} \approx \frac{1}{n} \sum_{i=1}^n \left(\frac{\partial E_{\theta}(\mathbf{x}^{\text{fake}})}{\partial \theta} - \frac{\partial E_{\theta}(\mathbf{x}^{\text{real}})}{\partial \theta} \right) \quad (9)$$

Is JEM using adversarial training?!

- ▶ Let's take a closer look to the gradient of the part of the loss:

$$\frac{\partial \log p_{\theta}(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_{\theta}(\mathbf{x}')} \left[\frac{\partial E_{\theta}(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_{\theta}(\mathbf{x})}{\partial \theta} \quad (8)$$

- ▶ If we use a single sample to approximate expectation and compute the gradient across the dataset our gradient we'll look like:

$$\frac{\partial \log p_{\theta}(\mathbf{X})}{\partial \theta} \approx \frac{1}{n} \sum_{i=1}^n \left(\frac{\partial E_{\theta}(\mathbf{x}^{\text{fake}})}{\partial \theta} - \frac{\partial E_{\theta}(\mathbf{x}^{\text{real}})}{\partial \theta} \right) \quad (9)$$

- ▶ And this gradient looks very similar to the gradient of the following loss:

$$\mathcal{L}(\theta) = \mathbb{E}_{p_{\theta}(x)} [E_{\theta}(x)] - \mathbb{E}_{p_{\text{data}}(x)} [E_{\theta}(x)] \quad (10)$$

Is JEM using adversarial training?!

- ▶ Let's take a closer look to the gradient of the part of the loss:

$$\frac{\partial \log p_{\theta}(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_{\theta}(\mathbf{x}')} \left[\frac{\partial E_{\theta}(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_{\theta}(\mathbf{x})}{\partial \theta} \quad (8)$$

- ▶ If we use a single sample to approximate expectation and compute the gradient across the dataset our gradient we'll look like:

$$\frac{\partial \log p_{\theta}(\mathbf{X})}{\partial \theta} \approx \frac{1}{n} \sum_{i=1}^n \left(\frac{\partial E_{\theta}(\mathbf{x}^{\text{fake}})}{\partial \theta} - \frac{\partial E_{\theta}(\mathbf{x}^{\text{real}})}{\partial \theta} \right) \quad (9)$$

- ▶ And this gradient looks very similar to the gradient of the following loss:

$$\mathcal{L}(\theta) = \mathbb{E}_{p_{\theta}(x)} [E_{\theta}(x)] - \mathbb{E}_{p_{\text{data}}(x)} [E_{\theta}(x)] \quad (10)$$

- ▶ Which is a discriminator loss!

Is JEM using adversarial training?!

- ▶ Let's take a closer look to the gradient of the part of the loss:

$$\frac{\partial \log p_{\theta}(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_{\theta}(\mathbf{x}')} \left[\frac{\partial E_{\theta}(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_{\theta}(\mathbf{x})}{\partial \theta} \quad (8)$$

- ▶ If we use a single sample to approximate expectation and compute the gradient across the dataset our gradient we'll look like:

$$\frac{\partial \log p_{\theta}(\mathbf{X})}{\partial \theta} \approx \frac{1}{n} \sum_{i=1}^n \left(\frac{\partial E_{\theta}(\mathbf{x}^{\text{fake}})}{\partial \theta} - \frac{\partial E_{\theta}(\mathbf{x}^{\text{real}})}{\partial \theta} \right) \quad (9)$$

- ▶ And this gradient looks very similar to the gradient of the following loss:

$$\mathcal{L}(\theta) = \mathbb{E}_{p_{\theta}(x)} [E_{\theta}(x)] - \mathbb{E}_{p_{\text{data}}(x)} [E_{\theta}(x)] \quad (10)$$

- ▶ Which is a discriminator loss!
- ▶ Reformulation of GANs via EBM is not new.

Is JEM using adversarial training?!

- ▶ Let's take a closer look to the gradient of the part of the loss:

$$\frac{\partial \log p_{\theta}(\mathbf{x})}{\partial \theta} = \mathbb{E}_{p_{\theta}(\mathbf{x}')} \left[\frac{\partial E_{\theta}(\mathbf{x}')}{\partial \theta} \right] - \frac{\partial E_{\theta}(\mathbf{x})}{\partial \theta} \quad (8)$$

- ▶ If we use a single sample to approximate expectation and compute the gradient across the dataset our gradient we'll look like:

$$\frac{\partial \log p_{\theta}(\mathbf{X})}{\partial \theta} \approx \frac{1}{n} \sum_{i=1}^n \left(\frac{\partial E_{\theta}(\mathbf{x}^{\text{fake}})}{\partial \theta} - \frac{\partial E_{\theta}(\mathbf{x}^{\text{real}})}{\partial \theta} \right) \quad (9)$$

- ▶ And this gradient looks very similar to the gradient of the following loss:

$$\mathcal{L}(\theta) = \mathbb{E}_{p_{\theta}(x)} [E_{\theta}(x)] - \mathbb{E}_{p_{\text{data}}(x)} [E_{\theta}(x)] \quad (10)$$

- ▶ Which is a discriminator loss!
- ▶ Reformulation of GANs via EBM is not new.
- ▶ The key novelty of the paper is that we can do that “inside” the classifier.

Results and discussion

Results and discussion

- ▶ Disclaimer: results are really good.

Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:

Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
 - ▶ has good classification accuracy

Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
 - ▶ has good classification accuracy
 - ▶ has good IS/FID scores (i.e. has good samples)

Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
 - ▶ has good classification accuracy
 - ▶ has good IS/FID scores (i.e. has good samples)
 - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)

Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
 - ▶ has good classification accuracy
 - ▶ has good IS/FID scores (i.e. has good samples)
 - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
 - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)

Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
 - ▶ has good classification accuracy
 - ▶ has good IS/FID scores (i.e. has good samples)
 - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
 - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)
 - ▶ is robust to adversarial attacks

Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
 - ▶ has good classification accuracy
 - ▶ has good IS/FID scores (i.e. has good samples)
 - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
 - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)
 - ▶ is robust to adversarial attacks
 - ▶ ...and all of these at the same time!

Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
 - ▶ has good classification accuracy
 - ▶ has good IS/FID scores (i.e. has good samples)
 - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
 - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)
 - ▶ is robust to adversarial attacks
 - ▶ ...and all of these at the same time!
- ▶ A huge limitation: SGLD makes both the training unstable and the model hard to scale.

Results and discussion

- ▶ Disclaimer: results are really good.
- ▶ Authors built a model on SVHN/CIFAR10/CIFAR100 which:
 - ▶ has good classification accuracy
 - ▶ has good IS/FID scores (i.e. has good samples)
 - ▶ has much better calibrated predictions (i.e. is not overconfident unlike traditional classifiers)
 - ▶ has good out-of-distribution predictions (i.e. detecting when we feed OOD-samples into it)
 - ▶ is robust to adversarial attacks
 - ▶ ...and all of these at the same time!
- ▶ A huge limitation: SGLD makes both the training unstable and the model hard to scale.
- ▶ An approach was coined Joint Energy based Model (JEM) since we model (x, y) simultaneously.