

# Linux, day 15



# LAB: PKill



# Assignment

- Write a shell script to start 15x "*sleep 120*".
- Use "*pkill*" to kill all of them in one go.

# LAB: Swap space

# Preparations

- We made extra disk devices for Fedora a while back.
  - If you still have those, unused, use one of those.
  - If they are in use, make a new device of 100MB.
- The next slide assumes `"/dev/sdc"`.
  - Adjust for your situation!

# Checking and expanding swap

- Make the (new) device into swap space.
  - Use "*mkswap*" and "*swapon*".
  - Verify swap space with "*free*" before and after.
  - Add the swap device to "*/etc/fstab*" and reboot.
- After the lab, remove from fstab again,
  - And remove with "*swapoff*".

# LAB: System performance



# Installing sar

- Install the "*sysstat*" package.
- Check where the "*sa1*" and "*sa2*" scrips were added.
  - You will need the path, to add into *cron*.
  - So far I've seen:
    - */usr/lib/sa/, /usr/lib/sysstat/, /usr/lib64/sa/*



# Checking sar cronjobs

- Check */etc/cron.d*.
  - Are there config files for "*sysstat*"?
  - Any other job files that have "*sa1*"?
- **If these cron-jobs exist, skip the next slide.**

# Manually creating cron jobs

- Edit the "root" crontab (*sudo crontab -e*).
  - Add *sa1* and *sa2*. For example (check the path):

```
# Collect measurements at 10-minute intervals
*/10 * * * * /usr/lib/sysstat/sa1

# Create daily reports and purge old files
0 0 * * * /usr/lib/sysstat/sa2 -A
```

# Manual testing

- Run *sa1* a few times, manually.
- Run *sa2* once.
- Go to `"/var/log/sa/"` (Fedora). Check the files there.
  - On Ubuntu the path is `"/var/log/sysstat"`.
  - You should at least have one report.

# Querying reports

- Query the "sar" file, for example (check the name).

```
# sar -u -f /var/log/sa/sa03
```

```
# sar -r -f /var/log/sa/sa03
```

```
# sar -d -f /var/log/sa/sa03
```

# LAB: Storage issues



# Assignment 1: Isof

- Can you find:
  - Which processes currently access "*system.journal*"?
  - Which processes use files from "*/etc/*"?
  - Which files and resources are used by "*sshd*"?
- Can you spot port 22?

# Assignment 2: iostat

- Choose one of your throw-away disk devices.
  - Like `"/dev/sdc"` that was used for swap space.
- Open two terminals.
  - In one keep a running `"iostat /dev/sdc 1"`
  - In the other we will try a few `"dd"` tests.

# Assignment 2: iostat

- The following need "*root*" (use *sudo* or *su*).
- Compare speed, throughput and iostat activity.

```
# dd if=/dev/urandom of=/dev/sdc bs=1M count=50  
  
# dd if=/dev/urandom of=/dev/sdc bs=1024 count=50000
```

- Is there a difference? If so, why?



# LAB: Network issues



# Assignment 1

- Start a *netcat* listener on port 8080.
- Use *netcat* in a second shell to connect to port 8080.
  - Type a bit of text. Does it arrive?
- Try a file transfer with netcat ([example here](#)).

# Assignment 2

- Let's see how you can connect to `www.google.com`.
  - Compare "*getent hosts*" and "*nslookup*".
  - Can you ping the host?
  - Do a *traceroute*. Can you see where you leave ITVitae?
  - What does "*mtr --report www.google.com*" tell you?

# Assignment 3

- Start a web server on your VM.
- Start a *netcat* listener on port 3389.
- Run an *nmap* scan from your other VM.
  - What services do you find?
  - Can you access both services?
  - Are there any firewalls in the way?

# LAB: Extra work, DVWA



# Introduction


- *D\*mn Vulnerable Web App*
  - A learning tool for InfoSec students.
  - A highly vulnerable web application to exploit.
- Vulnhub has plenty more like these.
  - But we're going for a challenge.

# What we'll do

- Normally DVWA runs on one host / VM.
- We will use one *Vagrantfile* to define **two** VMs.
  - In a shared network segment, with fixed IPs.
  - One will run MariaDB (MySQL),
  - The other Apache and the web app.



# The end result





# Don't worry!

- Take things step by step! Don't get flustered. :)
- Remember!
  - Disable the auto-update of vbox guest additions.
  - If Vagrant provisioning fails, no need to rebuild.
  - You can re-run "*vagrant provision*".
  - If you're blocked, open the firewall.

# Resources

- *"015-Vagrantfile-start-here"* is your **starting point**.
  - Yes, there is also *"015-Vagrantfile-spoilers"*.
  - There's even [a walkthrough video I made!](#)
- [The DVWA Github page](#) has setup guides and wiki.
- MySQL / MariaDB have [a getting-started guide](#).

# Step 1: Vagrant + software

- Adjust the example configuration:
  - Run generic/centos7
  - First make sure networking works.
- The "mysql" VM should install MariaDB (MySQL).

# Step 1: Vagrant + software

- The "www" VM should install Apache.
  - The DVWA Github page lists all required packages.
  - Don't forget the port forward for 80.

# Step 2: Basic networking

- Boot both VMs and login to both.
- Can you confirm that they can communicate?
  - Can you connect between the hosts with *netcat*?
  - Can you connect to the SSH daemon?
    - Logins DO NOT need to work!
- If it doesn't work, let's troubleshoot!

# Step 3: MySQL basic checks

- On the database host, verify that MySQL was installed.
  - Or MariaDB of course... depending on your distro.
- Make sure the DB software starts (also at reboot).
  - Can you connect to the database?
  - Check the [MySQL getting-started guide](#).

# Step 4: Setup MySQL database

- Follow [the DVWA database setup instructions](#).
  - Login: *mysql -u root -h localhost dvwa*
- You will need to create:
  - A database
  - A user (don't use "*@localhost*", use "*@'%'*")
  - Access privileges for the user.

# Step 5: Testing MySQL

- Can you login to the DB with the new account?
  - On "mysql": *mysql -u dvwa -p -h localhost dvwa*
  - From "www": *mysql -u dvwa -p -h mysql dvwa*
- If the first fails, we troubleshoot MySQL.
- If the second fails, let's check networking!



# Step 6: Apache setup

- Make sure that Apache (httpd) starts at boot.
- After starting, can you pull <http://localhost> with curl?
  - Can you also access the page from your host OS?
    - <http://localhost:8080>
    - If not, did you set up the port forward?
  - And from mysql? <http://www/>

# Step 7: DVWA install

- Clone the DVWA Git repo to *"/var/www/html/"*.
- Edit *"/var/www/html/config/config.php"*.
  - Follow the setup guide on Github.
  - At least you should setup the DB connection info.

# Step 8: DVWA setup

- Continue the setup guide on Github.
  - <http://www/setup.php>
  - There are more instructions of things to fix.
  - At the bottom, click the "Reset database" button.
- THIS WILL BE BLOCKED... by SELinux. Fix that! 🤔💕

# Closing



# Homework

- Reading:
  - Chapter 6, review
  - Chapter 22, entirely
  - Chapter 23, review
  - Chapter 24, entirely

# Homework

- Go over the objectives document.
  - Use a marker, a pen, or whatever you like.
  - Cross off anything you really understand.
- This makes it clear which topics you need to repeat.

# Homework

- Go do:
  - Get DVWA up and running on two VMs.
  - The lab describes all the steps needed.
  - You can first try each step separately or manually.

# Reference materials





# Resources

- [Linux load averages, solving the mystery](#)
- [Troubleshooting high load averages](#)
- [System Activity Reporter \(sar\)](#)
- [Quick sar explanation](#)
- [IOPing tutorial](#)
- In-depth: [redis.io performance improvements](#)

# Resources

- [File transfer with netcat](#)
- [Netcat shells, bind and reverse](#)
- [Netcat cheatsheet](#)
- [CloudFlare: what is MTR?](#)
- [Linux ate my RAM!](#)
- Deepdive: [Interpreting iostat output](#)