Lesson 4

Material

https://github.com/unixfile/learning-python-2026

Today

- Reading and writing files
- Sets and set operations
- Dictionaries

1 Reading from a file

```
f = open("foo.txt")
content = f.read()
f.close()
type(content)  # str
```

2 Reading lines

```
f = open("bar.txt")
lines = f.readlines()
f.close()
type(lines)  # list
```

3 Iterating over lines

```
f = open("baz.txt")
for line in f:
    print(line, end="")
f.close()
```

- Each line keeps its `\n`, so `end=""` avoids blank lines in between

4 Writing to a file

```
f = open("file.txt", "w")
f.write("Travel far, ")
f.write("meet yourself.\n")
f.close()
```

5 Appending to a file

```
f = open("file.txt", "a")
f.write("Appending...\n")
f.close()
```

6 Opening with scope

```
with open("file.txt", "r") as f:
    data = f.read()
```

- File is closed automatically at end of block

7 Sets

```
In : my_set = {3, 7, 'gamma', 'echo'}
In : type(my_set)
Out: set
```

- A set is an unordered collection of **unique** elements
- Sets are mutable

8 Set idiosyncrasies

```
In : fruits = {'banan', 'banan', 'melon', 'kiwi'}
In : fruits
Out: {'banan', 'melon', 'kiwi'}
```

- Duplicates are silently removed
- Elements have no guaranteed order, so indexing is not possible

```
In : fruits[0]
...
TypeError: 'set' object is not subscriptable
```

9 Adding and removing

```
In : countries = {'Brasilien', 'Chile'}

In : countries.add('Bolivia')
In : countries
Out: {'Brasilien', 'Chile', 'Bolivia'}

In : countries.update({'Brasilien', 'Paraguay'})
In : countries
Out: {'Brasilien', 'Chile', 'Bolivia', 'Paraguay'}

In : countries.remove('Sverige')   # KeyError if missing
In : countries.discard('Sverige')  # silent no-op if missi
```

10 Set operations

```
In : low = {1, 2, 3, 4}
In : high = {3, 4, 5, 6}

In : low | high   # union
Out: {1, 2, 3, 4, 5, 6}

In : low & high   # intersection
Out: {3, 4}

In : low ^ high   # symmetric difference
Out: {1, 2, 5, 6}

In : low - high   # difference
Out: {1, 2}
```

11 Dictionaries

```
In : fruit_colors = {
   :     'äpple':   'grön',
   :     'banan':   'gul',
   :     'vindruva': 'lila',
   : }
In : type(fruit_colors)
Out: dict
```

- A dictionary stores key-value pairs
- Dictionaries are mutable and ordered (since Python 3.7)

12 Accessing values

```
In : fruit_colors['banan']
Out: 'gul'

In : fruit_colors['citron']                    # KeyError!
In : fruit_colors.get('citron')                # None, no crash
In : fruit_colors.get('citron', 'okänd')
Out: 'okänd'
```

- `[]` raises `KeyError` when the key is missing
- `.get()` returns `None` (or a default) instead
- `None` is Python's value for "nothing here"

13 Looping over dictionaries

```
for fruit in fruit_colors:
    print(fruit)
# äpple
# banan
# vindruva

for color in fruit_colors.values():
    print(color)
# grön
# gul
# lila

for fruit, color in fruit_colors.items():
    print(f"{fruit}: {color}")
# äpple: grön
# banan: gul
# vindruva: lila
```

14 Modifying dictionaries

```
In : fruit_colors['äpple'] = 'röd'    # update existing
In : fruit_colors['mango'] = 'orange' # add new key

In : fruit_colors.pop('banan')
Out: 'gul'

In : fruit_colors.update({'kiwi': 'grön', 'äpple': 'grön'})
```

15 Nested dictionaries

```
In : betyg = {
   :      'Alice': {'Matte': 85, 'Kemi': 92},
   :      'Bob':   {'Matte': 78, 'Kemi': 88},
   : }

In : betyg['Alice']['Matte']
Out: 85

In : betyg['Bob']['Engelska'] = 87
```