HyperKAN: Verified Symbolic Rewrite Search with Scoped Actions and Frontier Shaping

Marcel
Independent Researcher

Abstract

We study learned heuristics for formally verified symbolic rewrite search in algebraic reasoning. Our starting point is a global-action benchmark in which a model predicts one of six whole-expression SymPy rewrites (`expand`, `factor`, `cancel`, `apart`, `together`, `trigsimp`) toward an exact target form, and a search loop verifies success by executing those rewrites symbolically. On this benchmark, a Static KAN head outperforms an MLP baseline, while an initial goal-conditioned HyperKAN underperforms and only becomes competitive after reducing hypernetwork capacity. Exact graph mining of the benchmark reveals a deeper issue: whole-expression rewrite semantics make composition shallow, so apparent difficulty collapses under global transformations.

To address this, we introduce a scoped-action benchmark in which actions are pairs of the form (u, o), where u is a deterministic subtree location and o is one of the original rewrite families. Guided scoped datasets validate that the end-to-end pipeline is trainable, but only a structural held-out-family probe produces real compositional pressure. On this probe, both Static KAN and recovered HyperKAN solve seen families but fail completely on a held-out mixed composition family by default, revealing a root-action collapse failure mode. A simple inference-side localization bias substantially rescues HyperKAN, and a frontier-aware reranker improves held-out mixed-family beam solve rate further, indicating that early hidden-branch access is a key mechanism for compositional success. A deeper depth-7 expansion then exposes a clear failure boundary: the moderate-depth rescue does not carry over cleanly to deeper compositions. Additional bounded diagnostics show that learned frontier supervision and a frontier-head-only RL controller do not internalize this deeper transfer behavior.

These results support four conclusions. First, benchmark semantics and action granularity dominate apparent reasoning difficulty in verified symbolic search. Second, supervised validation loss is an unreliable proxy for search performance. Third, moderate compositional gains can be obtained through inference-time frontier shaping, but current training objectives do not internalize that behavior. Fourth, the current mechanism has a measurable depth boundary rather than scaling smoothly with chain length.

1 Introduction

A recurring failure mode in neural-symbolic reasoning is to confuse cosmetic algebraic complexity with actual multi-step reasoning depth. Expressions can look complicated while remaining one rewrite away from a target under a sufficiently strong global action vocabulary. For this reason, benchmark design is inseparable from model evaluation: if the rewrite graph is shallow, apparent reasoning gains may be artifacts of local ranking rather than evidence of long-horizon symbolic control.

This paper studies that problem in a deliberately formal setting. We train policy/value models for symbolic rewrite search where every state transition is executed by SymPy and every final success condition is exactly verifiable. The original benchmark uses a small global action space consisting of

six whole-expression SymPy rewrites. Within that setting, a Static KAN policy head outperforms an MLP baseline, while an initial goal-conditioned HyperKAN underperforms. After reducing hypernetwork capacity, HyperKAN nearly matches Static KAN on the shallow global benchmark, but detailed analysis shows that supervised validation loss and verified search performance diverge sharply.

At that point, the project becomes a benchmark-design problem as much as a modeling problem. Exact graph mining shows that global whole-expression rewrites admit isolated depth-2 and depth-3 ladders but do not yield robust depth-4+ compositional families at useful density. This motivates a benchmark redesign around scoped actions: instead of predicting only which rewrite to apply, the model predicts where in the expression to apply it.

The scoped reformulation immediately validates the pipeline, but the first guided datasets are too templated to separate models. The first meaningful benchmark is a structural held-out-family probe: models train on three single-block families and are evaluated on a mixed composition family never seen in training. This probe is non-saturated and exposes a concrete failure mode: both Static KAN and recovered HyperKAN collapse to root-level whole-expression actions instead of selecting local subgoals. Inference-time localization and frontier shaping partially rescue HyperKAN on this moderate-depth probe, but a deeper depth-7 expansion shows that the rescue has a clear boundary.

The paper makes four contributions:

1. A verified symbolic rewrite benchmark analysis showing that global whole-expression semantics produce shallow composition even when isolated ladders exist.
2. A scoped-action benchmark formulation with deterministic subtree sites and grouped `Add` slices that makes compositional failures visible.
3. A structural held-out-family probe demonstrating that compositional generalization can fail completely despite success on seen families.
4. A mechanism study showing that inference-time frontier shaping can rescue moderate-depth compositional performance by increasing early hidden-branch access, while current training-time fixes, learned frontier supervision, and a bounded frontier-head-only RL controller fail to internalize that behavior for deeper transfer.

The intended claim is deliberately modest. This is a benchmark-and-mechanism paper, not a claim that HyperKAN universally dominates MLP or Static KAN, and not a claim that symbolic reasoning has been solved. The benchmark is intentionally controlled so that action granularity, search, and model inductive bias can be studied under exact symbolic verification.

2 Related Work

This work sits at the intersection of symbolic computation, neural-guided formal search, and benchmark design for compositional reasoning. On the symbolic side, SymPy provides the executable rewrite substrate and exact target-form verification used throughout our experiments [1]. On the neural-guided search side, our setting is closer in spirit to learned heuristic guidance for formal reasoning than to pure one-step classification: the phenomenon of interest is how model scores interact with search frontier management under exact symbolic execution [2, 3]. On the architecture side, KANs provide a structured spline-based alternative to dense policy heads, while HyperKAN asks whether goal-conditioned spline routing yields a useful inductive bias for symbolic rewrite control [4]. Finally, our emphasis on benchmark semantics is aligned with work arguing that the structure of a benchmark can dominate the difficulty it appears to measure [5, 6].



Figure 1: Verified symbolic rewrite search loop. The model scores actions and progress, but every transition is executed symbolically and every success condition is exactly checked.

Our contribution differs from these lines in two ways. First, we show that whole-expression rewrite semantics can make a formally verified algebra benchmark compositionally shallow even when local ladders exist. Second, we expose a concrete search-control failure mode — root-collapse — on a scoped held-out-family probe, then analyze both the rescue mechanism and its failure boundary.

3 Problem Setting

We study goal-directed symbolic rewriting under exact verification. Each example consists of a current symbolic state S, an exact target form G, and a search procedure that executes candidate rewrites and checks whether the target has been reached. The model predicts actions conditioned on (S, G). During inference, the model is embedded inside a beam-search loop. Search expands candidate states by applying model-scored actions, SymPy executes the corresponding rewrite, and exact matching against the target form determines success.

The crucial design choice is the action semantics.

3.1 Global actions

The original benchmark uses six whole-expression actions:

$$\mathcal{O} = \{\texttt{expand}, \texttt{factor}, \texttt{cancel}, \texttt{apart}, \texttt{together}, \texttt{trigsimp}\}.$$

These actions are expressive and easy to verify, but they act globally. A single rewrite can often collapse multiple latent subproblems at once.

3.2 Scoped actions

The scoped benchmark keeps the same operator families but changes the granularity of control. Actions are represented as

$$a = (u, o),$$

where u is a deterministic site identifier and $o \in \mathcal{O}$ is one of the rewrite types above. The scoped site model includes subtree path sites such as `expr@root`, `expr@1`, `numerator@1`, and `denominator@1`, plus grouped `Add` slices such as `add_slice@root[0:2]`. This changes the task from predicting only what rewrite to apply to predicting both where and what.

4 Notation, Models, and Inference

Let the current symbolic state be S and the exact target form be G. A rewrite environment defines transitions

$$S' = T_a(S),$$

where a is a discrete action and T_a is the corresponding SymPy rewrite when valid. Invalid transitions are discarded by the search procedure.

For each example we observe a pair (S, G) and one of two supervision types: a set of shortest valid next actions $A^\star(S, G)$, or a guided single-path next action $a^\star(S, G)$. We define the shortest-path distance to goal under the benchmark semantics as

$$d(S, G) = \min_{\substack{k \geq 0,\ a_1, \ldots, a_k \\ T_{a_k} \circ \cdots \circ T_{a_1}(S) = G}} k,$$

when a valid path exists within the search horizon.

All models share a structural tokenizer over symbolic expressions and a common encoder backbone. The current state and goal are encoded as

$$z_S = E(S), \qquad z_G = E(G),$$

and fused into

$$h = [z_S; z_G; z_S - z_G; z_S \odot z_G],$$

where $\odot$ is elementwise multiplication and $[\cdot;\cdot]$ denotes concatenation. A value head predicts the distance-to-goal estimate $\hat{d} = v(h)$. The policy head differs by model family.

MLP baseline. The MLP policy head maps h directly to action logits with a small dense network.

Static KAN. The Static KAN head replaces a dense mapping with spline-based edge functions. Abstractly, each output logit is built from sums of one-dimensional nonlinear edge functions over hidden coordinates:

$$y_j = \sum_i \phi_{ij}(x_i),$$

where each ϕ_{ij} is represented by a learned spline or a mixture over spline templates.

HyperKAN. HyperKAN is a goal-conditioned KAN in which a hypernetwork modulates the policy head using the goal embedding. Let $H(\cdot)$ denote the hypernetwork. It maps the goal representation to modulation parameters $m = H(z_G)$. For an edge function represented as a mixture over K templates,

$$\phi_{ij}(x_i \mid z_G) = \sum_{k=1}^{K} \alpha_{ij,k}(z_G)\, \psi_{ij,k}(x_i),$$

where the coefficients $\alpha_{ij,k}(z_G)$ are produced by the hypernetwork and $\psi_{ij,k}$ are learned template functions.

In a later factorized site/op variant, flat action logits are decomposed as

$$\ell(u, o) = \ell_{\text{site}}(u) + \ell_{\text{op}}(o),$$

with auxiliary site and operator losses added during training. This variant improves seen-family efficiency but does not solve the held-out mixed family.



Figure 2: Policy-head comparison. The models share the same state/goal encoder and value head; the policy head changes from dense logits to static spline edge functions to goal-conditioned spline mixtures.

Training combines an action loss and a value loss. For multi-label shortest-action supervision we use a binary cross-entropy style action loss over the valid shortest set $A^\star(S, G)$:

$$\mathcal{L}_{\text{act}} = \sum_{a \in \mathcal{A}} \text{BCE}(p_\theta(a \mid S, G), y_a)\,, \qquad y_a = \mathbf{1}[a \in A^\star(S, G)].$$

For guided single-path scoped datasets, the target is a one-hot action $a^\star(S, G)$. Distance-to-goal is trained with a Huber regression loss $\mathcal{L}_{\text{val}} = \text{Huber}(\hat{d}, d(S, G))$. The total loss is

$$\mathcal{L} = \mathcal{L}_{\text{act}} + \lambda_{\text{val}} \mathcal{L}_{\text{val}} + \mathcal{L}_{\text{aux}},$$

where $\mathcal{L}_{\text{aux}}$ is zero for the base models and contains optional auxiliary terms in ablation branches, such as site/op supervision, root-avoidance penalties, or frontier-label losses.

At inference time, the model is embedded inside beam search. For a partial path $\pi_t = (a_1, \ldots, a_t)$ producing states $S_0, \ldots, S_t$, the shaped search score is

$$\text{score}(\pi_t) = \sum_{\tau=1}^{t} \left[\log p_\theta(a_\tau \mid S_{\tau-1}, G) + \beta_v\, \hat{v}(S_\tau, G) + b_{\text{root}}(a_\tau, S_{\tau-1}) + b_{\text{frontier}}(S_\tau, \tau)\right].$$

Here b_{root} is an optional penalty on root-level whole-expression actions and b_{frontier} is an optional early-frontier bonus or reranking term. Beam search is therefore not an afterthought in this paper; the interaction between model scores and frontier management is the phenomenon under study.

5 Global Benchmark

The original verified benchmark contains 274 non-terminal test problems. Beam search uses width 4 and a maximum of 8 steps. Table 1 reports the main global-action result.

A reduced-capacity HyperKAN (`hyper_hidden_dim = 64`) narrows the gap to Static KAN. However, search-temperature calibration does not close the remaining gap, and longer training does not reliably help: verified search can regress even when supervised validation loss continues improving. Thus the global benchmark supports two strong conclusions. First, Static KAN is better than MLP on the shallow verified benchmark. Second, supervised validation loss is not a reliable proxy for search performance. The benchmark does *not* support broad claims about compositional reasoning because it is too shallow.



Figure 3: Static versus goal-conditioned spline mixtures on the same test examples. Static KAN uses fixed template weights by construction. HyperKAN routing changes with the goal, showing that goal-conditioned spline modulation is active even though it does not automatically translate into better verified search.

Table 1: Global-action benchmark results. Depth-2 is saturated for all models; depth-3 is the only real discriminator.

Model	Beam solves	Solve rate	Depth-3 solves
MLP	147/274	53.6%	0/127
Static KAN	163/274	59.5%	16/127
HyperKAN (initial)	148/274	54.0%	1/127
HyperKAN (recovered)	162/274	59.1%	15/127



Figure 4: Historical global-action benchmark plot. Static KAN is strongest overall, while the initial HyperKAN underperforms on depth-3 examples.

6 Why Global Actions Fail as a Compositional Benchmark

We replaced heuristic dataset generation with exact graph mining over typed symbolic families. The graph analysis shows that `block_a_trig_merge_expand` yields a verified depth-3 ladder and `block_b_cancel_expand` yields a verified depth-2 ladder. However, naive additive composition under global whole-expression rewrites does not produce robust depth-4+ families at useful density.

The failure is structural. Global rewrites often simplify multiple latent subproblems at once, collapsing what should be additive depth. Scoped actions are therefore not a cosmetic redesign; they are the benchmark change required to make compositional structure visible at all.

7 Scoped Benchmark Development

The first scoped datasets were guided plumbing checks. A smoke dataset uses 24 guided trajectories from a depth-4 family and both Static KAN and HyperKAN solve 16/16 non-terminal test examples. A medium version scales the same family to 200 trajectories and both models solve 48/48 examples. A diverse guided split adds four action-order families and 400 guided trajectories, but both models still solve 400/400 examples under greedy and beam search.

These results validate the scoped data path, model heads, training loop, checkpointing, and scoped beam evaluation. They also show that guided action-order variation is too templated to test compositional generalization by solve rate. This matters because it motivates the later structural probe: the paper is not claiming that every scoped reformulation creates a meaningful reasoning benchmark, only that scoped actions make it possible to construct one.

8 Structural Scoped Probe

The first non-saturated scoped benchmark replaces action-order variation with structurally different algebraic families:

- `trig_merge`: `trigsimp` → `together` → `expand`,
- `hidden_cancel`: numerator `factor` → `cancel` → `expand`,
- `apart_normalize`: denominator `factor` → `apart`,
- `mixed_trig_hidden`: composition of a trig block and a hidden-factor block.

Train/validation use the first three families. Test consists only of `mixed_trig_hidden`. After search-based checkpoint selection, both Static KAN and recovered HyperKAN score 0/60 on the held-out mixed family by default, while seen-family performance remains strong. This benchmark is non-saturated and exposes a real held-out composition gap.

8.1 Failure mode: root-collapse

Targeted failure analysis reveals root-action collapse. Static KAN assigns top-1 first action `expr@root::together` on every mixed-family test row. HyperKAN assigns top-1 first action `expr@root::expand` on every mixed-family test row. Default greedy rollouts remain global and never switch into local blockwise behavior. The problem is therefore not simply insufficient beam width; the learned policies fail to localize onto independent subproblems inside a composed expression.

Table 2: Held-out `mixed_trig_hidden` structural-probe results. The frontier reranker is the best moderate-depth result but remains an inference-side intervention.

Condition	Validation beam-4	Greedy	Beam-4
Static KAN default	—	0/60	0/60
Static KAN + root penalty 2.0	—	0/60	0/60
Recovered HyperKAN default	16/16	0/60	0/60
Recovered HyperKAN + root penalty 2.0	16/16	24/60	36/60
Recovered HyperKAN + root penalty 2.0 + frontier reranker	14/16	36/60	48/60

8.2 Inference-time rescue and mechanism

A simple inference-time penalty on root actions has very different effects on the two models. Static KAN remains at 0/60 under root penalty 2.0. Recovered HyperKAN rises to 24/60 greedy and 36/60 beam. This establishes that recovered HyperKAN contains useful compositional signal that default inference does not surface.

The rescue is not explained by first-step localization alone. Under root penalty 2.0, the top-1 action changes on all 60 mixed-family rows, but solved and unsolved beam rows still share the same penalized top-1 action: `expr@0::trigsimp`. What separates solved from unsolved rows is the early frontier: solved beam rows reach the hidden block and `expr@2::cancel` within the first three actions in all 36 solved cases, while only 12 of the 24 unsolved rows do so. Thus the rescue comes from early hidden-branch access, not merely from choosing a better first local site.

Straightforward training-time fixes do not internalize this behavior. A small `expr@root` avoidance loss does not improve default compositional generalization and weakens the stronger inference-only rescue. A factorized site/op HyperKAN head improves seen-family efficiency but still yields 0/60 on the held-out mixed family and preserves the same root-action bias.

8.3 Early-frontier reranker

The strongest positive result comes from making the mechanism explicit. We add a frontier-aware inference adjustment that rewards early access to the hidden branch while keeping the root penalty. Table 2 summarizes the moderate-depth structural-probe result.

An earlier hidden-action bonus reduced beam expansions but did not improve solve count and hurt seen-family validation. The later frontier-state reranker improves solve count at moderate depth. This should not be read as a fully internalized learned solution. It is an inference-side intervention that changes the early frontier enough for hidden-branch states to survive beam pruning.



(a) Solved by all models (easy depth-2 case).



(b) Solved only by Static KAN under the shallow global benchmark.



(c) Failed by all models. The explored graph is broad but does not reach the exact target.

Figure 5: Representative verified rewrite trajectories from the global benchmark. Green paths show successful beam trajectories; gray edges indicate explored dead branches. These examples illustrate why exact target form and search frontier management matter even at shallow depth.

9 Depth-7 Expansion: A Clear Failure Boundary

To test whether the moderate-depth rescue scales, we add a deeper held-out family, `mixed_trig_hidden_apart`, built from three structural blocks with a guided chain of length 7:

$$\begin{aligned}\texttt{expr@1::trigsimp} &\to \texttt{add_slice@root[1:3]::together} \to \texttt{expr@2::expand}\\ &\to \texttt{numerator@3::factor} \to \texttt{expr@3::cancel}\\ &\to \texttt{denominator@1::factor} \to \texttt{expr@1::apart}.\end{aligned}$$

The depth-expansion probe contains 48 trajectories, 228 rows, 84 non-terminal held-out test attempts, and 14 scoped actions.

All 18 solved beam cases under the successful conditions are the same one-action path, `expr@1::apart`. Table 4 gives the distance-slice failure analysis.

The reranker reaches a hidden site early on 10/84 rows, but reaches hidden cancel within the first 3 actions on 0/84 rows. It reshapes part of the frontier without converting that into deeper hidden-branch solves. This depth-7 probe is therefore a genuine failure boundary. The moderate-depth rescue is real, but it does not carry over cleanly to deeper compositions.

10 Internalization Diagnostics: Learned Frontier and RL

The moderate-depth rescue invites an obvious question: can the useful inference-side frontier signal be internalized? We tested this with two bounded diagnostics. First, we added explicit frontier-positive supervision to both recovered HyperKAN and Static KAN. Second, we fine-tuned only a frontier head with a REINFORCE-style objective on top of a frozen recovered HyperKAN checkpoint. These experiments were intentionally bounded and should be read as diagnostics, not as replacement headline results.

In-family depth-7 frontier labels are learnable, but the in-family split saturates too quickly to be informative about transfer. We therefore evaluated on the first 12 non-terminal held-out `mixed_trig_hidden_apart` attempts. Table 5 shows that learned frontier scoring does not rescue the harder transfer slice for either model family. The only nonzero result is a single shallow 1/12 solve for Static KAN under the heuristic reranker.

We also tested a frontier-head-only RL controller on top of the recovered HyperKAN transfer setup, freezing the base model and fine-tuning only the frontier head with a REINFORCE-style reward equal to verified solve minus a small expansion penalty. The RL plumbing ran cleanly, but rollout solve rate stayed flat during training, and evaluation slightly worsened expansions relative to the supervised frontier head (Table 6).

These diagnostics sharpen the interpretation of the depth-7 boundary. The frontier signal is learnable, but simply supervising or fine-tuning a frontier score head on top of the current base policy is not sufficient to recover deeper transfer.

11 Limitations and Reproducibility

This work has several important limitations. First, the strongest scoped results still rely on guided single-path labels or guided accepted families rather than fully strict composed shortest-action recovery at dataset scale. Second, the successful rescues are inference-side interventions. They provide mechanism insight, but they are not yet clean end-to-end learned solutions. Third, the benchmark remains highly structured. Although the structural probe is stronger than the guided

Table 3: Depth-7 held-out expansion results for recovered HyperKAN. The frontier reranker no longer improves solve rate over the root-penalty baseline.

Condition	Greedy	Beam-4	Mean beam expansions
Default	0/84	0/84	171.23
Root penalty 2.0	0/84	18/84	144.67
Root penalty 2.0 + frontier reranker	0/84	18/84	150.18

Table 4: Distance-slice analysis for the depth-7 held-out family. The partial rescue does not traverse the deeper chain.

Condition	$d = 1$	$d = 2$	$d = 3$	$d = 4$	$d = 5$	$d = 6$	$d = 7$
Root penalty 2.0	9/12	0/12	9/12	0/12	0/12	0/12	0/12
Root penalty 2.0 + frontier reranker	9/12	0/12	9/12	0/12	0/12	0/12	0/12

smoke and medium datasets, it is still a controlled symbolic setting rather than a broad theorem-proving benchmark. Fourth, the depth-7 expansion shows that the current rescue mechanism has a limited regime of validity.

The public repository includes dataset builders, training configurations, evaluation scripts, checkpoint-selection utilities, and the figure-generation code used in this paper. Reproduction instructions are given from repository root rather than a machine-specific path. The core paper story is therefore reproducible from the released code and artifacts, even though the repository also contains ongoing exploratory branches and diagnostics.

12 Conclusion

The main lesson of this project is that symbolic benchmark semantics and action granularity matter as much as model class. Whole-expression rewrite actions create shallow composition even when local ladders exist, while scoped actions expose real compositional failure modes. On this scoped benchmark, default policies collapse to root-level actions on held-out mixed compositions. A localization-aware inference bias rescues recovered HyperKAN, and a frontier-aware reranker improves held-out moderate-depth compositional performance further, showing that early hidden-branch access is a key mechanism. However, this rescue fails to scale cleanly to a deeper depth-7 family, marking a clear current limit of the approach. Additional bounded diagnostics show that neither learned frontier supervision nor a frontier-head-only RL controller closes that deeper transfer gap.

The result is therefore not a claim that HyperKAN is universally superior, nor that symbolic reasoning has been solved. It is a more precise claim: learned heuristics for verified symbolic rewrite search are highly sensitive to action granularity, search-time frontier shaping, and benchmark depth, and moderate compositional gains can be obtained and analyzed mechanistically before a clear failure boundary emerges.

Table 5: Bounded depth-7 transfer diagnostic on the first 12 non-terminal held-out attempts. Frontier labels are learnable, but learned frontier scores do not rescue transfer.

Model	Condition	Solves	Mean expansions
Recovered HyperKAN	Default	0/12	257.17
	Root penalty 2.0	0/12	312.17
	Root penalty + heuristic frontier reranker	0/12	317.33
	Learned frontier 0.05	0/12	260.42
	Learned frontier 0.1	0/12	258.42
	Learned frontier 0.25	0/12	278.58
	Root penalty + learned frontier 0.1	0/12	316.67
Static KAN	Default	0/12	296.83
	Root penalty 2.0	0/12	327.75
	Root penalty + heuristic frontier reranker	1/12	314.08
	Learned frontier 0.05	0/12	306.50
	Learned frontier 0.1	0/12	305.92
	Learned frontier 0.25	0/12	293.67
	Root penalty + learned frontier 0.1	0/12	324.42

Table 6: Bounded RL frontier-controller diagnostic on the same 12-attempt transfer slice. Fine-tuning only the frontier head does not rescue transfer.

Condition	Solves	Mean expansions
Supervised learned frontier 0.1	0/12	258.42
RL frontier 0.1	0/12	264.17
Root penalty + supervised learned frontier 0.1	0/12	316.67
Root penalty + RL frontier 0.1	0/12	319.00

A Current Best Results Summary

B Representative Public Figures

References

[1] Aaron Meurer, Christopher P. Smith, Mateusz Paprocki, Ondřej Čertík, Sergey B. Kirpichev, Matthew Rocklin, Štěpánka Kumar, Sergiu Ivanov, Jason K. Moore, Sartaj Singh, Thilina Rathnayake, Sean Vig, Brian E. Granger, Richard P. Muller, Francesco Bonazzi, Harsh Gupta, Shivam Vats, Fredrik Johansson, Fabian Pedregosa, Matthew J. Curry, Andy R. Terrel, Štěpán M. Roučka, Ashutosh Saboo, Isuru Fernando, Sumith Kulal, Robert Cimrman, and Anthony Scopatz. SymPy: symbolic computing in Python. *PeerJ Computer Science*, 3:e103, 2017.

[2] Sarah Loos, Gabriel Irving, Christian Szegedy, and Cezary Kaliszyk. Deep network guided proof search. In *LPAR-21*, 2017.

[3] Stanislas Polu and Ilya Sutskever. Generative language modeling for automated theorem proving. *arXiv preprint arXiv:2009.03393*, 2020.

[4] Ziming Liu, Yifu Wang, Sachin Vaidya, Fabian R. Chale, and Max Tegmark. KAN: Kolmogorov-Arnold Networks. *arXiv preprint arXiv:2404.19756*, 2024.



Figure 6: Main empirical arc. Global actions provide a verified but shallow starting point; scoped structural probes expose a held-out mixed-family gap; frontier shaping rescues moderate-depth performance; the depth-7 expansion marks the current failure boundary.

Setting	Best condition	Outcome
Global benchmark	Static KAN	163/274 (59.5%)
Moderate-depth mixed-family scoped benchmark	Recovered HyperKAN + root penalty 2.0 + frontier reranker	48/60 beam, 36/60 greedy
Moderate-depth mechanism	Early hidden-branch access	all 36 solved beam rows reach hidden cancel within 3 actions
Depth-7 scoped expansion	Recovered HyperKAN + root penalty 2.0	18/84 beam

[5] François Chollet. On the measure of intelligence. *arXiv preprint arXiv:1911.01547*, 2019.

[6] Trieu H. Trinh, Yuhuai Wu, Quoc Le, He He, and Thang Luong. Solving Olympiad geometry without human demonstrations. *Nature*, 625:476–482, 2024.



Figure 7: Solve rate by motif family on the shallow global benchmark. The hardest family, `rat_three_partial_trig_to_expanded`, is unsolved by all models.



Figure 8: Greedy versus beam on the shallow global benchmark. Beam rescue is largest for Static KAN and nearly absent for the initial HyperKAN.



Figure 9: Same current state, different goals: HyperKAN routing changes with the target, confirming that the goal-conditioned spline mechanism is active rather than dormant.