Operators in MongoDB

What will be covered

- Operators in Mongodb
- Sorting data.

Opreators in MongoDB

OBJECT™ TECHNOLOGIES

- Comparison operators are used to compare two expressions and fetch data (documents) from the MongoDB database (collections) based on their usage in filters.
- Various comparison operators in MongoDB are as follows
  - $eq – Equal To
  - $ne – Not Equal To (!=)
  - $gt – Greater Than (>)
  - $gte – Greater Than Equal To (>=)
  - $lt – Less Than (<)
  - $lte – Less Than Equal To (<=)
  - $in – In (Available in)
  - $nin – Not In (Not available in)

Opreators in MongoDB

OBJECT™ TECHNOLOGIES

Operator	Description
$eq	Matches values that are equal to the value specified in the query
$ne	Matches all values that are not equal to the value specified in the query.
$gt	Matches values that are greater than the value specified in the query.
$gte	Matches values that are greater than or equal to the value specified in the query.
$lt	Matches values that are less than the value specified in the query.
$lte	Matches values that are less than or equal to the value specified in the query.
$in	Matches any of the values that exist in an array specified in the query.
$nin	Matches values that do not exist in an array specified in the query.

Examples

Query::

Display all movies with rating = 3.

Solution::

```
>db.movie.find({rating:3});
```

Query::

Display all movies with rating = 3 and price=200.

Solution::

```
>db.movie.find({rating:3,price=200});
```


www.object.co.in

Query::

Display all movies with price>200 and <400

Solution::

```
>db.movie.find({price:{$gt:200,$lt:400});
```

Query::

Display all movies with price=200 or price =540 or price=400.

(in used in Oracle)

Solution::

```
>db.movie.find({price:{$in:[200,540,400]}});
```

- not in (nin)

Query::

Display all movies whose price is not equal to 400,540 or 350. **Solution::**

```
>db.movie.find({price:{$nin:[350,540,400]}));
```

Query::

Display all movies with rating=4 or price > 300.

Solution::

consider,

```
{rating:4},price:{$gt:300}
$or:[{},{},{}]
```

so,

```
>db.movie.find({$or:[{rating:4},{price:{$gt:30}}]});
```


www.object.co.in

- not operator

Query::

Display all movies not in range 200 and 400

Solution::

consider query for in...

```
>db.movie.find({price:{$gt:200,$lt:400}});
```

converting above query using not in...

```
>db.movie.find({price:{$not:{$gt:200,$lt:400}}});
```


www.object.co.in

- mod operator

Query::

Display all movies whose rating is even.

Solution::

```
>db.movie.find({rating:{$mod:[2,0]}});
```

Query::

Display all movies whose rating is odd.

Solution::

```
>db.movie.find({rating:{$mod:[2,1]}});
```

- Simple query

Query::

Display all movies of Amitabh.

Solution::

```
>db.movie.find({actor:'Amitabh'}{$gt:200,$lt:400}});
```

Sorting Data

- Sorting data in ascending order.

Query::

Display all movies of Amitabh.

Solution::

>db.movie.find({actor:'Amitabh'});

- Sorting data in ascending order.

Query::

Display all movies of Amitabh sorted in the order of namein ascending order.

Solution::

>db.movie.find({actor:'Amitabh'}).sort({name:1});

Descending order.

>db.movie.find({actor:'Amitabh'}).sort({name:-1});

www.object.co.in