



Dealing with REST API

1. Using fetch API for get request
2. Using fetch API for post request
3. Other methods of REST API
4. Example of Axios library

1. Using fetch for get request

- fetch API provides a global `fetch()` method that provides an easy, logical way to fetch resources asynchronously across the network.
- Basic syntax:
 - `fetch(url, [options])` which return a promise object.
 - options for configuring request by specifying additional information
- Javascript promises
 - Promise is an object that represents the completion (or failure) of an asynchronous operation in future.
 - Promise object has a property `then` which accepts 2 callback functions for success and failure.
- Example

2. Using fetch for post request

- The `fetch()` function accepts a second argument, an options object, which allows you to customize the request.
- The important(frequently required) options that can be specified in the second argument are:
 - `method`: e.g., GET, POST, PUT, DELETE.
 - `headers`: Sets custom headers for the request.
 - `body`: Sets the request body (used for methods like POST and PUT).
- It returns a promise object which allows to access response object returned from server

- REST APIs enable to develop web application having all possible CRUD (create, retrieve, update, delete) operations.
- GET and POST are the most popular methods of REST API.
 - GET: to retrieve resource and not to modify
 - POST: create a new resource
 - PUT: update existing resource
 - DELETE: delete resources
 - PATCH: partially updates an existing resource
- Less common methods
 - HEAD
 - OPTIONS
 - TRACE
 - CONNECT

4. Example of Axios library

- Axios is a very popular JavaScript library
- Axios can be installed using npm: `npm install axios`
- Axios library is easier to use than `fetch()` function because it has got some advantages.
- Using get request:
`axios.get(url, [config])`
- Using post request
`axios.post(url, data, [config])`