



Dynamic HTML

1. Events
2. Event handlers
3. Generating dynamic content
4. JS Popup Boxes

- Events are actions or occurrences that happen within a web page or application.
- They can be triggered by user interactions (like clicks, key presses, or mouse movements),
- Different categories of events are:
 - Mouse events
 - Keyboard events
 - Form events
 - Window events

- Event handler is usually a JavaScript function which the programmer creates that runs when the event fires.
- It is event listener which performs some actions when event gets fired.
- Event listener attributes:
 - They are used to assign an event handler to an event associated with an HTML element.
 - Event handlers typically have names that begin with on
 - Example:
`<input type="button" value="Save" onclick="alert('button clicked')" />`

- Attaching event handler
 - Element's event handler properties (like onclick) can be used for assigning event handler function.
 - `addEventListener()` function can be used for the same

- Create a HTML page and decide the event to be handled on a particular element.
- Define javascript function that performs the required action to be executed for a given event.
- Use the event attribute for attaching the javascript function.

- JavaScript has three kinds of popup boxes:
 - **Alert box:** for displaying information message
 - **Confirm box:** For getting confirmation in terms of yes or no
 - **Prompt box:** for accepting some input
- If JavaScript is disabled in a user's browser, it is not possible to use JavaScript to create a popup box directly.
- In general, it's not recommended to use popup boxes in modern web development