



HTML DOM using jQuery

1. Get or Set contents or values
2. Add or remove elements
3. Modifying CSS
4. Traversing nodes

- Few jQuery methods can be used to either assign or read some values of a selected element.
- Function with no argument, is referred as getter, with a value as an argument, it's referred as setter.
- Such methods are:
 - `text()`: gets or sets the combined text contents of the selected elements
 - `html()`: gets or sets the HTML contents of the selected elements
 - `attr()`: gets or sets the HTML value of the specified attribute of the selected element
 - `val()`: gets or sets the value of input, select or textarea in the HTML form

- Adding content within the selected element
 - Element that is inserted becomes the first child or last child of the selected element.
 - i. **prepend()**: inserts content at the beginning of selected element
 - ii. **append()**: inserts content at the end of selected element
- Adding content before or after(adjacent) the selected element
 - Newly added element and selected element become siblings of each other
 - i. **before()**: inserts content before the selected element
 - i. **after()**: inserts content after the selected element

- Adding parent to the selected element
 - Selected element becomes child of the wrapped element
 - i. **wrap()**: wrap the selected elements by newly inserted element
- Removing element or content
 - Allow to remove existing HTML elements or contents from the document.
 - i. **remove()**: removes selected element with content
 - ii. **empty()**: removes content of selected element
 - iii. **unwrap()**: removes parent of selected element
- Removing attributes
 - removes an attribute from the selected elements.
 - i. **removeAttr()**: removes specified attribute of selected element

- Getting or setting CSS properties
 - `css()` method is used to get and set CSS properties
- Setting multiple CSS properties
 - multiple CSS properties on the matched elements using a single jQuery method `css()`
- Adding CSS class
 - `addClass()` method to add a CSS class to the matched HTML element(s)
- Removing CSS class
 - `removeClass()` method can remove a single class, multiple classes, or all classes at once from the selected elements.
- Toggling CSS class
 - `toggleClass()` method add or remove one or more classes from the selected elements

- Traversing allows you to move up, down, and sideways through the DOM tree to find and interact with specific elements.
- The methods used for traversing are categorized into moving to children, moving to parent and moving to siblings
- Traversing down the tree
 - `children()`: used to get the direct children of the selected element.
 - `find()`: used to get the descendant elements based on certain criteria
- Traversing up the tree
 - `parent()`: used to get the direct parent
 - `parents()`: used to get the ancestors of the selected element till the root.
 - `parentsUntil()`: returns all ancestor elements until the given criteria

- Traversing sideways in the tree
 - `siblings()`: used to get the sibling elements of the selected element.
 - `prev()`: used to get the immediately preceding sibling
 - `prevAll()`: used to get all preceding siblings
 - `prevUntil()`: to get all the preceding siblings up to the specified selector
 - `next()`: used to get the immediately following sibling
 - `nextAll()`: used to get all following(next) siblings
 - `nextUntil()`: used to get all the following siblings up to the specified selector