







NOTE: 1."L X" OR "LUMEX"

PAR	RT NUMBER	SSF-LXH240GGD	REV		
REV	E.C.N. NU	IMBER AND REVISION COMMEN	TS	DATE	
A CHG'D LEAD LENGTHS.					
B CHG'D LEAD LENGTHS.					
С	CHG'D HOLDER BOTTOM & SAFE OP. SPECS.				
D	UPDATED SPECS.				
П	CHG'D STAND-OFF TO 4 FOOD CONSTR.				
F E.C.N. #10100					
G	E.C.N. #101	04		2.6.96	
H E.C.N. #10BRDR. & REDRAWN.					
I ECN-Lumex201700040					

ELECTRO-OPTICAL CHARACTERISTIC TA=25°C

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND	
PEAK WAELENGHT	-	565	-	nm	If=20mA	
FORWARD VOLTAGE	-	2.2	2.6	Vf	If=20mA	
REVERSE VOLTAGE	-	-	5	Vr	Ir=100uA	
LUMINOUS INTENSITY	-	40	-	mcd	If=20mA	
VIEWING ANGLE		60	-	2x theta1/2	-	
EMITTED COLOR	GREEN					
EPOXY LENS FINISH	GREEN DIFFUSED					

ABSOLUTE MAXIMUM RATINGS TA=25℃

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
FORWARD CURRENT	25	mA
POWER DISIPATION	105	mW
STORAGE TEMPERATURE	-40 TO +85	°C
OPERATING TEMPERATURE	-40 TO +85	°C
SOLDERING TEMP.	3 SEC. MAX @ 260	°C

^{*} t<10us

^{** 2.00}mm FROM BODY

ITEM NO. PARTS		QTY.	DESCRIPTION	
1	SSH-LXH240 HOLDER	1	BLACK NYLON 94V-0	
2	SSL-LX3044GD LED	2	-	

UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.x=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MINI= DECIMAL PRECISION MAX. = 0.00 (±0.000)



425 N. GARY AVE. CAROL STREAM, IL 60188 PHONE: 800-278-5666 FAX: 630-315-2150 WEB: WWW.LUMEX.COM 9.65(L)*4.32(W)*10.77(H)mm, T-3mm RIGHT ANGLE FAULT INDICATOR LED, DUAL 565nm GREEN LEDS, GREEN DIFFUSED.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION

CONTINENT INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE: 2017.08.01 DRAWN BY: C.C.

PAGE: 1 OF 1 CHKD BY: G.Y.

SCALE: NTF APRVD BY: E.C.

UNIT: mm [INCH]