

LogLogistic

Parametrisation

The LogLogistic distribution has cumulative distribution function

$$F(y) = \frac{1}{1 + (y/\beta)^{-\alpha}}$$

where

$\alpha > 0$ is the shape parameter.

$\beta > 0$ is the scale parameter.

Link-function

The parameter β is linked to the linear predictor as:

$$\beta = \exp(\eta)$$

Hyperparameters

The α parameter is represented as

$$\theta = \log \alpha$$

and the prior is defined on θ .

Specification

- family = `loglogistic`
- Required arguments: y (to be given in a format by using `inla.surv()` function)

Hyperparameter spesification and default values

hyper

theta

hyperid 80001
name log alpha
short.name alpha
initial 1
fixed FALSE
prior loggamma
param 25 25
to.theta function(x) log(x)
from.theta function(x) exp(x)

survival TRUE

discrete FALSE

link default log

pdf loglogistic

Example

In the following example we estimate the parameters in a simulated case

```
rloglogistic = function(n, beta, alpha = 1)
{
  p = runif(n)
  return (beta* (((1-p)/p)^(-1/alpha)))
}

n = 1000
alpha = 2
x = runif(n)
eta = 1+x
beta = exp(eta)
y = rloglogistic(n, beta = beta, alpha = alpha)
event = rep(1,n)
data = list(y=y, event=event, x=x)
formula=inla.surv(y,event) ~ x
r=inla(formula, family ="loglogistic", data=data, verbose=T)
```

Notes

- Loglogistic model can be used for right censored, left censored, interval censored data.
- A general frame work to represent time is given by `inla.surv`
- If the observed times y are large/huge, then this can cause numerical overflow in the likelihood routines giving error messages like

```
file: smtp-taucs.c  hgid: 891deb69ae0c  date: Tue Nov 09 22:34:28 2010 +0100
Function: GMRFLib_build_sparse_matrix_TAUCS(), Line: 611, Thread: 0
Variable evaluates to NAN/INF. This does not make sense. Abort...
```

If you encounter this problem, try to scale the observatios, `time = time / max(time)` or similar, before running `inla()`.